

cases	doc_1		doc_2		decision	id
	authors	<ul style="list-style-type: none">Yue HeChen ChenJing ZhangJuhua LiuFengxiang HeChaoyue WangBo Du	authors	<ul style="list-style-type: none">Yue HeChen ChenJing ZhangJuhua LiuFengxiang HeChaoyue WangBo Du	DUPLICATES	29
	title	Visual Semantics Allow for Textual Reasoning Better in Scene Text Recognition	title	Visual Semantics Allow for Textual Reasoning Better in Scene Text Recognition		
	publication_date	2021-12-24 02:43:42+00:00	publication_date	2021-12-24 00:00:00		
	source	SupportedSources.ARXIV	source	SupportedSources.INTERNET_ARCHIVE		
	journal	None	journal			
	volume		volume			
	doi		doi			
	urls	<ul style="list-style-type: none">http://arxiv.org/pdf/2112.12916v1http://arxiv.org/abs/2112.12916v1http://arxiv.org/pdf/2112.12916v1	urls	<ul style="list-style-type: none">https://web.archive.org/web/20220105103329/https://arxiv.org/pdf/2112.12916v1.pdf		
	id	id8715457885182187645	id	id433245745519123933		
	abstract	Existing Scene Text Recognition (STR) methods typically use a language model to optimize the joint probability of the 1D character sequence predicted by a visual recognition (VR) model, which ignore the 2D spatial context of visual semantics within and between character instances, making them not generalize well to arbitrary shape scene text. To address this issue, we make the first attempt to perform textual reasoning based on visual semantics in this paper. Technically, given the character segmentation maps predicted by a VR model, we construct a subgraph for each instance, where nodes represent the pixels in it and edges are added between nodes based on their spatial similarity. Then, these subgraphs are sequentially connected by their root nodes and merged into a complete graph. Based on this graph, we devise a graph convolutional network for textual reasoning (GTR) by supervising it with a cross-entropy loss. GTR can be easily plugged in representative STR models to improve their performance owing to better textual reasoning. Specifically, we construct our model, namely S-GTR, by paralleling GTR to the language model in a segmentation-based STR baseline, which can effectively exploit the visual-linguistic complementarity via mutual learning. S-GTR sets new state-of-the-art on six challenging STR benchmarks and generalizes well to multi-linguistic datasets. Code is available at https://github.com/adeline-cs/GTR .	abstract	Existing Scene Text Recognition (STR) methods typically use a language model to optimize the joint probability of the 1D character sequence predicted by a visual recognition (VR) model, which ignore the 2D spatial context of visual semantics within and between character instances, making them not generalize well to arbitrary shape scene text. To address this issue, we make the first attempt to perform textual reasoning based on visual semantics in this paper. Technically, given the character segmentation maps predicted by a VR model, we construct a subgraph for each instance, where nodes represent the pixels in it and edges are added between nodes based on their spatial similarity. Then, these subgraphs are sequentially connected by their root nodes and merged into a complete graph. Based on this graph, we devise a graph convolutional network for textual reasoning (GTR) by supervising it with a cross-entropy loss. GTR can be easily plugged in representative STR models to improve their performance owing to better textual reasoning. Specifically, we construct our model, namely S-GTR, by paralleling GTR to the language model in a segmentation-based STR baseline, which can effectively exploit the visual-linguistic complementarity via mutual learning. S-GTR sets new state-of-the-art on six challenging STR benchmarks and generalizes well to multi-linguistic datasets. Code is available at https://github.com/adeline-cs/GTR .		
	versions		versions			