

	doc_1		doc_2		decision	id
cases	authors	<ul style="list-style-type: none"><li>• V. Ivanov</li><li>• A. Sadovykh</li><li>• A. Naumchev</li><li>• A. Bagnato</li><li>• K. Yakovlev</li></ul>	authors	<ul style="list-style-type: none"><li>• Vladimir Ivanov</li><li>• Andrey Sadovykh</li><li>• Alexandr Naumchev</li><li>• Alessandra Bagnato</li><li>• Kirill Yakovlev</li></ul>	DUPLICATES	114
	title	Extracting Software Requirements from Unstructured Documents	title	Extracting Software Requirements from Unstructured Documents		
	publication_date	2022-02-04 00:00:00	publication_date	2022-02-04 00:00:00		
	source	SupportedSources.SEMANTIC_SCHOLAR	source	SupportedSources.INTERNET_ARCHIVE		
	journal		journal			
	volume		volume			
	doi	10.1007/978-3-031-15168-2_2	doi			
	urls	<ul style="list-style-type: none"><li>• https://www.semanticscholar.org/paper/a6e77c9890b90035986f202c14901de68a23e986</li></ul>	urls	<ul style="list-style-type: none"><li>• https://web.archive.org/web/20220208155525/https://arxiv.org/pdf/2202.02135v1.pdf</li></ul>		
	id	id6350016892214582653	id	id3556725635840589375		
	abstract	None	abstract	Requirements identification in textual documents or extraction is a tedious and error prone task that many researchers suggest automating. We manually annotated the PURE dataset and thus created a new one containing both requirements and non-requirements. Using this dataset, we fine-tuned the BERT model and compare the results with several baselines such as fastText and ELMo. In order to evaluate the model on semantically more complex documents we compare the PURE dataset results with experiments on Request For Information (RFI) documents. The RFIs often include software requirements, but in a less standardized way. The fine-tuned BERT showed promising results on PURE dataset on the binary sentence classification task. Comparing with previous and recent studies dealing with constrained inputs, our approach demonstrates high performance in terms of precision and recall metrics, while being agnostic to the unstructured textual input.		
	versions					
			versions			