

cases	doc_1		doc_2		decision	id
					NOT DUPLICATES	385
	authors	<ul style="list-style-type: none">Haochen TanWei ShaoHan WuKe YangLinqi Song	authors	<ul style="list-style-type: none">Haochen TanWei ShaoHan WuKe YangLinqi Song		
	title	A Sentence is Worth 128 Pseudo Tokens: A Semantic-Aware Contrastive Learning Framework for Sentence Embeddings	title	A Sentence is Worth 128 Pseudo Tokens: A Semantic-Aware Contrastive Learning Framework for Sentence Embeddings		
	publication_date	2022-03-11 00:00:00	publication_date	2022-03-11 00:00:00		
	source	SupportedSources.OPENALEX	source	SupportedSources.INTERNET_ARCHIVE		
	journal		journal			
	volume		volume			
	doi	None	doi			
	urls	<ul style="list-style-type: none">https://openalex.org/W4226186836	urls	<ul style="list-style-type: none">https://web.archive.org/web/20220315003228/https://arxiv.org/pdf/2203.05877v1.pdf		
	id	id2628709532708716661	id	id-6081150094875659401		
	abstract		abstract	Contrastive learning has shown great potential in unsupervised sentence embedding tasks, e.g., SimCSE. However, We find that these existing solutions are heavily affected by superficial features like the length of sentences or syntactic structures. In this paper, we propose a semantics-aware contrastive learning framework for sentence embeddings, termed Pseudo-Token BERT (PT-BERT), which is able to exploit the pseudo-token space (i.e., latent semantic space) representation of a sentence while eliminating the impact of superficial features such as sentence length and syntax. Specifically, we introduce an additional pseudo token embedding layer independent of the BERT encoder to map each sentence into a sequence of pseudo tokens in a fixed length. Leveraging these pseudo sequences, we are able to construct same-length positive and negative pairs based on the attention mechanism to perform contrastive learning. In addition, we utilize both the gradient-updating and momentum-updating encoders to encode instances while dynamically maintaining an additional queue to store the representation of sentence embeddings, enhancing the encoder's learning performance for negative examples. Experiments show that our model outperforms the state-of-the-art baselines on six standard semantic textual similarity (STS) tasks. Furthermore, experiments on alignments and uniformity losses, as well as hard examples with different sentence lengths and syntax, consistently verify the effectiveness of our method.		
	versions		versions			