

cases	doc_1		doc_2				decision	id
							DUPLICATES	139
	authors	<ul style="list-style-type: none">Shreyas PadhyZachary NadoJie RenJeremiah Zhe LiuJasper SnoekBalaji Lakshminarayanan	authors	<ul style="list-style-type: none">Shreyas PadhyZachary NadoJie RenJeremiah LiuJasper SnoekBalaji Lakshminarayanan				
	title	Revisiting One-vs-All Classifiers for Predictive Uncertainty and Out-of-Distribution Detection in Neural Networks	title	Revisiting One-vs-All Classifiers for Predictive Uncertainty and Out-of-Distribution Detection in Neural Networks				
	publication_date	2020-07-10 00:00:00	publication_date	2020-07-10 00:00:00				
	source	SupportedSources.OPENALEX	source	SupportedSources.INTERNET_ARCHIVE				
	journal	arXiv (Cornell University)	journal					
	volume		volume					
	doi	None	doi					
	urls	<ul style="list-style-type: none">https://openalex.org/W3041775211	urls	<ul style="list-style-type: none">https://web.archive.org/web/20200721104909/https://arxiv.org/pdf/2007.05134v1.pdf				
	id	id5324055575912532880	id	id-5464527606838449503				
	abstract		abstract	Accurate estimation of predictive uncertainty in modern neural networks is critical to achieve well calibrated predictions and detect out-of-distribution (OOD) inputs. The most promising approaches have been predominantly focused on improving model uncertainty (e.g. deep ensembles and Bayesian neural networks) and post-processing techniques for OOD detection (e.g. ODIN and Mahalanobis distance). However, there has been relatively little investigation into how the parametrization of the probabilities in discriminative classifiers affects the uncertainty estimates, and the dominant method, softmax cross-entropy, results in misleadingly high confidences on OOD data and under covariate shift. We investigate alternative ways of formulating probabilities using (1) a one-vs-all formulation to capture the notion of "none of the above", and (2) a distance-based logit representation to encode uncertainty as a function of distance to the training manifold. We show that one-vs-all formulations can improve calibration on image classification tasks, while matching the predictive performance of softmax without incurring any additional training or test-time complexity.				
	versions							
		versions						