

cases	doc_1		doc_2		decision	id
	authors	<ul style="list-style-type: none">Deshui MiaoJiaqi ZhangWenbo XieJian SongXin LiLijuan JiaNing Guo	authors	<ul style="list-style-type: none">Deshui Miao and Jiaqi Zhang and Wenbo Xie and Jian Song and Xin Li and Lijuan Jia and Ning Guo	DUPLICATES	236
	title	Simple Contrastive Representation Adversarial Learning for NLP Tasks	title	Simple Contrastive Representation Adversarial Learning for NLP Tasks		
	publication_date	2021-11-26 00:00:00	publication_date	2021-12-02 00:00:00		
	source	SupportedSources.SEMANTIC_SCHOLAR	source	SupportedSources.INTERNET_ARCHIVE		
	journal	ArXiv	journal			
	volume	abs/2111.13301	volume			
	doi		doi			
	urls	<ul style="list-style-type: none">https://www.semanticscholar.org/paper/023719b69c1722e35ad4d06e2efe130f630334f0	urls	<ul style="list-style-type: none">https://web.archive.org/web/20211204035232/https://arxiv.org/pdf/2111.13301v2.pdf		
	id	id-3793469978650143194	id	id7363458507224468358		
	abstract	Self-supervised learning approach like contrastive learning is attached great attention in natural language processing. It uses pairs of training data augmentations to build a classification task for an encoder with well representation ability. However, the construction of learning pairs over contrastive learning is much harder in NLP tasks. Previous works generate word-level changes to form pairs, but small transforms may cause notable changes in the meaning of sentences as the discrete and sparse nature of natural language. In this paper, adversarial training is performed to generate challenging and harder learning adversarial examples over the embedding space of NLP as learning pairs. Using contrastive learning improves the generalization ability of adversarial training because contrastive loss can uniform the sample distribution. And at the same time, adversarial training also enhances the robustness of contrastive learning. Two novel frameworks, supervised contrastive adversarial learning (SCAL) and unsupervised SCAL (USCAL), are proposed, which yield learning pairs by utilizing the adversarial training for contrastive learning. The label-based loss of supervised tasks is exploited to generate adversarial examples while unsupervised tasks bring contrastive loss. To validate the effectiveness of the proposed framework, we employ it to Transformer-based models for natural language understanding, sentence semantic textual similarity, and adversarial learning tasks. Experimental results on GLUE benchmark tasks show that our fine-tuned supervised method outperforms BERTbase over 1.75%. We also evaluate our unsupervised method on semantic textual similarity (STS) tasks, and our method gets 77.29% with BERTbase . The robustness of our approach conducts state-of-the-art results under multiple adversarial datasets on	abstract	Self-supervised learning approach like contrastive learning is attached great attention in natural language processing. It uses pairs of training data augmentations to build a classification task for an encoder with well representation ability. However, the construction of learning pairs over contrastive learning is much harder in NLP tasks. Previous works generate word-level changes to form pairs, but small transforms may cause notable changes on the meaning of sentences as the discrete and sparse nature of natural language. In this paper, adversarial training is performed to generate challenging and harder learning adversarial examples over the embedding space of NLP as learning pairs. Using contrastive learning improves the generalization ability of adversarial training because contrastive loss can uniform the sample distribution. And at the same time, adversarial training also enhances the robustness of contrastive learning. Two novel frameworks, supervised contrastive adversarial learning (SCAL) and unsupervised SCAL (USCAL), are proposed, which yields learning pairs by utilizing the adversarial training for contrastive learning. The label-based loss of supervised tasks is exploited to generate adversarial examples while unsupervised tasks bring contrastive loss. To validate the effectiveness of the proposed framework, we employ it to Transformer-based models for natural language understanding, sentence semantic textual similarity and adversarial learning tasks. Experimental results on GLUE benchmark tasks show that our fine-tuned supervised method outperforms BERT_base over 1.75%. We also evaluate our unsupervised method on semantic textual similarity (STS) tasks, and our method gets 77.29% with BERT_base. The robustness of our approach conducts state-of-the-art results under multiple adversarial datasets on NLI tasks.		
	versions		versions			