

cases	doc_1		doc_2		decision	id
					DUPLICATES	214
	authors	<ul style="list-style-type: none">Kevin LunaKatherine KlymkoJohannes Blaschke	authors	<ul style="list-style-type: none">Kevin LunaK. KlymkoJohannes Blaschke		
	title	Accelerating GMRES with Deep Learning in Real-Time.	title	Accelerating GMRES with Deep Learning in Real-Time		
	publication_date	2021-03-19 00:00:00	publication_date	2021-03-19 00:00:00		
	source	SupportedSources.OPENALEX	source	SupportedSources.SEMANTIC_SCHOLAR		
	journal	arXiv (Cornell University)	journal	ArXiv		
	volume		volume	abs/2103.10975		
	doi	None	doi			
	urls	<ul style="list-style-type: none">https://openalex.org/W3136298896	urls	<ul style="list-style-type: none">https://www.semanticscholar.org/paper/22209ae3cb6c6a0ca33a58b2375d58b903428514		
	id	id1770712446202720729	id	id-169794819884136897		
	abstract		abstract	GMRES is a powerful numerical solver used to find solutions to extremely large systems of linear equations. These systems of equations appear in many applications in science and engineering. Here we demonstrate a real-time machine learning algorithm that can be used to accelerate the time-to-solution for GMRES. Our framework is novel in that it integrates the deep learning algorithm in an in situ fashion: the AI-accelerator gradually learns how to optimizes the time to solution without requiring user input (such as a pre-trained data set). We describe how our algorithm collects data and optimizes GMRES. We demonstrate our algorithm by implementing an accelerated (MLGMRES) solver in Python. We then use MLGMRES to accelerate a solver for the Poisson equation – a class of linear problems that appears in may applications. Informed by the properties of formal solutions to the Poisson equation, we test the performance of different neural networks. Our key takeaway is that networks which are capable of learning non-local relationships perform well, without needing to be scaled with the input problem size, making them good candidates for the extremely large problems encountered in high-performance computing. For the inputs studied, our method provides a roughly 2 ^Å — acceleration.		
	versions		versions			