	doc_1		doc_2	
authors	 Jianmo Ni Gustavo Hern'andez 'Abrego Noah Constant Ji Ma Keith B. Hall Daniel Matthew Cer Yinfei Yang 	authors	Gustavo HernÃ;ndez Ãbrego Yinfei Yang Daniel Cer Keith B. Hall Ji Ma Noah Constant Jianmo Ni Sentence-T5: Scalable Sentence Encoders from Pre-trained Text-to-Text Models	
			tion date 2021-08-19 00:00:00	
title	Schence-13. Scalable Schience Encoders from Fig-trained Text-to-Text Models		SupportedSources.PAPERS WITH CODE	
	tte 2021-08-19 00:00:00	source iournal	Supported Sources: Fit Etcs_WIII_CODE	
source	SupportedSources.SEMANTIC_SCHOLAR	volume		
journal volume	ArXiv	doi		
cases doi	10.18653/v1/2022.findings-acl.146		https://arxiv.org/pdf/2108.08877v3.pdf	DUPLICATES 245
urls	• https://www.semanticscholar.org/paper/dbe87b171bfb789e1d22a047aeeee69105e6fd02	urls	 https://github.com/google-research/t5x_retrieval https://aclanthology.org/2022.findings-acl.146.pdf 	
id	id-8907498693760694982	id	id-8808029539496120860	
abstract	We provide the first exploration of sentence embeddings from text-to-text transformers (T5) including the effects of scaling up sentence encoders to 11B parameters. Sentence embeddings are broadly useful for language processing tasks. While T5 achieves impressive performance on language tasks, it is unclear how to produce sentence embeddings from encoder-decoder models. We investigate three methods to construct Sentence-T5 (ST5) models: two utilize only the T5 encoder and one using the full T5 encoder-decoder. We establish a new sentence representation transfer benchmark, SentGLUE, which extends the SentEval toolkit to nine tasks from the GLUE benchmark. Our encoder-only models outperform the previous best models on both SentEval and SentGLUE transfer tasks, including semantic textual similarity (STS). Scaling up ST5 from millions to billions of parameters shown to consistently improve performance. Finally, our encoder-decoder method achieves a new state-of-the-art on STS when using sentence embeddings.	abstract	We provide the first exploration of sentence embeddings from text-to-text transformers (T5). Sentence embeddings are broadly useful for language processing tasks. While T5 achieves impressive performance on language tasks cast as sequence-to-sequence mapping problems, it is unclear how to produce sentence embeddings from encoder-decoder models. We investigate three methods for extracting T5 sentence embeddings: two utilize only the T5 encoder and one uses the full T5 encoder-decoder model. To support our investigation, we establish a new sentence representation transfer benchmark, SentGLUE, which extends the SentEval toolkit to nine tasks from the GLUE benchmark. Our encoder-only models outperforms Sentence-BERT and SimCSE sentence embeddings on both SentEval and SentGLUE transfer tasks, including semantic textual similarity (STS). Scaling up T5 from millions to billions of parameters is found to produce consistent further improvements. Finally, our encoder-decoder method achieves a new state-of-the-art on STS when using sentence embeddings. Our models are released at https://tfhub.dev/google/collections/sentence-t5/1.	
		versions	1 0 0	