

cases	doc_1		doc_2		decision	id
					DUPLICATES	366
	authors	<ul style="list-style-type: none">Lingfei WuI. E. YenKun XuFangli XuAvinash BalakrishnanPin-Yu ChenPradeep RavikumarM. Witbrock	authors	<ul style="list-style-type: none">Lingfei WuIan E. H. YenKun XuFangli XuAvinash BalakrishnanPin-Yu ChenPradeep RavikumarMichael J. Witbrock		
	title	Word Mover’s Embedding: From Word2Vec to Document Embedding	title	Word Mover's Embedding: From Word2Vec to Document Embedding		
	publication_date	2018-10-26 00:00:00	publication_date	2018-10-30 19:43:17+00:00		
	source	SupportedSources.SEMANTIC_SCHOLAR	source	SupportedSources.ARXIV		
	journal	ArXiv	journal	None		
	volume	abs/1811.01713	volume			
	doi	10.18653/v1/D18-1482	doi			
	urls	<ul style="list-style-type: none">https://www.semanticscholar.org/paper/ef56afa4cefb90e263b1434dd3ca650904f54c6e	urls	<ul style="list-style-type: none">http://arxiv.org/pdf/1811.01713v1http://arxiv.org/abs/1811.01713v1http://arxiv.org/pdf/1811.01713v1		
	id	id-8103817222637774579	id	id861658142524851966		
	abstract	While the celebrated Word2Vec technique yields semantically rich representations for individual words, there has been relatively less success in extending to generate unsupervised sentences or documents embeddings. Recent work has demonstrated that a distance measure between documents called Word Mover’s Distance (WMD) that aligns semantically similar words, yields unprecedented KNN classification accuracy. However, WMD is expensive to compute, and it is hard to extend its use beyond a KNN classifier. In this paper, we propose the Word Mover’s Embedding (WME), a novel approach to building an unsupervised document (sentence) embedding from pre-trained word embeddings. In our experiments on 9 benchmark text classification datasets and 22 textual similarity tasks, the proposed technique consistently matches or outperforms state-of-the-art techniques, with significantly higher accuracy on problems of short length.	abstract	While the celebrated Word2Vec technique yields semantically rich representations for individual words, there has been relatively less success in extending to generate unsupervised sentences or documents embeddings. Recent work has demonstrated that a distance measure between documents called \emph{Word Mover's Distance} (WMD) that aligns semantically similar words, yields unprecedented KNN classification accuracy. However, WMD is expensive to compute, and it is hard to extend its use beyond a KNN classifier. In this paper, we propose the \emph{Word Mover's Embedding } (WME), a novel approach to building an unsupervised document (sentence) embedding from pre-trained word embeddings. In our experiments on 9 benchmark text classification datasets and 22 textual similarity tasks, the proposed technique consistently matches or outperforms state-of-the-art techniques, with significantly higher accuracy on problems of short length.		
	versions		versions			