

cases	doc_1		doc_2		decision	id
	authors	<ul style="list-style-type: none">Lulu ZhangTao LuoYaoyu ZhangZ. XuZheng Ma	authors	<ul style="list-style-type: none">Lulu ZhangTao LuoYaoyu ZhangWeinan EZhi-Qin John XuZheng Ma	DUPLICATES	224
	title	MOD-Net: A Machine Learning Approach via Model-Operator-Data Network for Solving PDEs	title	MOD-Net: A Machine Learning Approach via Model-Operator-Data Network for Solving PDEs		
	publication_date	2021-07-08 00:00:00	publication_date	2021-12-28 00:00:00		
	source	SupportedSources.SEMANTIC_SCHOLAR	source	SupportedSources.INTERNET_ARCHIVE		
	journal	ArXiv	journal			
	volume	abs/2107.03673	volume			
	doi	10.4208/cicp.OA-2021-0257	doi			
	urls	<ul style="list-style-type: none">https://www.semanticscholar.org/paper/d0954fc407403a403b5755f9aca38d2a6110b465	urls	<ul style="list-style-type: none">https://web.archive.org/web/20220105214338/https://arxiv.org/pdf/2107.03673v2.pdf		
	id	id-260616992357392007	id	id6932344208928904025		
	abstract	. In this paper, we propose a a machine learning approach via model-operator-data network (MOD-Net) for solving PDEs. A MOD-Net is driven by a model to solve PDEs based on operator representation with regularization from data. For linear PDEs, we use a DNN to parameterize the Green’s function and obtain the neural operator to approximate the solution according to the Green’s method. To train the DNN, the empirical risk consists of the mean squared loss with the least square formulation or the variational formulation of the governing equation and boundary conditions. For complicated problems, the empirical risk also includes a few labels, which are computed on coarse grid points with cheap computation cost and significantly improves the model accuracy. Intuitively, the labeled dataset works as a regularization in addition to the model constraints. The MOD-Net solves a family of PDEs rather than a specific one and is much more efficient than original neural operator because few expensive labels are required. We numerically show MOD-Net is very efficient in solving Poisson equation and one-dimensional radiative transfer equation. For nonlinear PDEs, the nonlinear MOD-Net can be similarly used as an ansatz for solving nonlinear PDEs, exemplified by solving several nonlinear PDE problems, such as the Burgers equation. subject classifications : 35C15; 35J05; 35Q20; 35Q49; 45K05	abstract	In this paper, we propose a a machine learning approach via model-operator-data network (MOD-Net) for solving PDEs. A MOD-Net is driven by a model to solve PDEs based on operator representation with regularization from data. For linear PDEs, we use a DNN to parameterize the Green's function and obtain the neural operator to approximate the solution according to the Green's method. To train the DNN, the empirical risk consists of the mean squared loss with the least square formulation or the variational formulation of the governing equation and boundary conditions. For complicated problems, the empirical risk also includes a few labels, which are computed on coarse grid points with cheap computation cost and significantly improves the model accuracy. Intuitively, the labeled dataset works as a regularization in addition to the model constraints. The MOD-Net solves a family of PDEs rather than a specific one and is much more efficient than original neural operator because few expensive labels are required. We numerically show MOD-Net is very efficient in solving Poisson equation and one-dimensional radiative transfer equation. For nonlinear PDEs, the nonlinear MOD-Net can be similarly used as an ansatz for solving nonlinear PDEs, exemplified by solving several nonlinear PDE problems, such as the Burgers equation.		
	versions		versions			