

ZyXEL

ADSL Router

AMG1001-T10A

- Status
- Quick Start
- Interface Setup
 - Internet
 - LAN
- Advanced Setup
- Access Management
- Maintenance
- Help

ATM VC

Virtual Circuit : PVC0

Status : ☒ Activated ☐ Deactivated

VPI : 8 (range: 0~255)

VCI : 35 (range: 32~65535)

QoS

ATM QoS : UBR

PCR : 0 cells/second

SCR : 0 cells/second

MBS : 0 cells

Encapsulation

ISP : ☐ Dynamic IP Address

☒ Static IP Address

☐ PPPoA/PPPoE

☐ Bridge Mode

Static IP

Encapsulation : 1483 Routed IP VC-Mux

Static IP Address : 193.152.59.10

IP Subnet Mask : 255.255.255.252

Gateway : 193.152.59.9

NAT : Enable

Default Route : ☐ Yes ☒ No

TCP MTU Option : TCP MTU(0:default) 0 bytes

Dynamic Route : RIP1 Direction Both

Multicast : Disabled

ZyXEL

ADSL Router

AMG1001-T10A

- Status
 - Device Info
 - System Log
 - Statistics
- Quick Start
- Interface Setup
 - Internet
 - LAN
- Advanced Setup
- Access Management
- Maintenance
- Help

Device Information

LAN

Firmware Version : V1.00(AAJL.0)C0
MAC Address : e8:37:7a:96:83:56

WAN

IP Address : 192.168.1.1
Subnet Mask : 255.255.255.0
DHCP Server : Disabled

ADSL

Virtual Circuit :
Status : Connected
Connection Type : Static IP
IP Address : 193.152.59.10
Subnet Mask : 255.255.255.252
Default Gateway : 0.0.0.0
DNS Server : 0.0.0.0
NAT : Enabled

ADSL Firmware Version : FwVer:3.22.2.0_A60394 HwVer:T14F7_12.0
Line State : Showtime
Modulation : G.DMT
Annex Mode : ANNEX_A

	Downstream	Upstream	
SNR Margin :	17.0	18.0	db
Line Attenuation :	58.5	27.0	db
Data Rate :	1504	320	kbps