

**EPILEPSY PREDICTION WITH
ELECTROENCEPHALOGRAPH USING
MACHINE LEARNING AND DEEP
LEARNING**

A PROJECT REPORT

Submitted By

ABISHEK RAGAV J (312422243005)

ALDAN DALLAS D (31242224309)

*in partial fulfillment for the of award of the degree
of*

BACHELOR OF TECHNOLOGY

in

ARTIFICIAL INTELLIGENCE AND DATA SCIENCE

**St. JOSEPH'S INSTITUTE OF TECHNOLOGY
(An Autonomous Institution)**

ANNA UNIVERSITY :: CHENNAI 600 025

APRIL 2026

ANNA UNIVERSITY: CHENNAI 600 025

BONAFIDE CERTIFICATE

Certified that this project report **“EPILEPSY PREDICTION WITH ELECTROENCEPHALOGRAPH USING MACHINE LEARNING AND DEEP LEARNING”** is the bonafide work of **“ABISHEK RAGAV (312422243005) and ALDAN DALLAS (312422243009)”** who carried out the AD4803-project work under my supervision.

SIGNATURE

Dr. R. PRISCILLA M.E., Ph.D.,

Professor

HEAD OF THE DEPARTMENT

Department of
Artificial Intelligence and Data Science
St.Joseph's Institute of Technology
Old Mamallapuram Road
Chennai-600119

SIGNATURE

Mrs. Priya S B, MTech, (Ph.D)

Assistant Professor

SUPERVISOR

Department of
Artificial Intelligence and Data Science
St.Joseph's Institute of Technology
Old Mamallapuram Road
Chennai-600119

Submitted for the Viva-Voce held on _____

(INTERNAL EXAMINER)

CERTIFICATE OF EVALUATION

College Name : St. Joseph's Institute of Technology

Branch & Semester : Artificial Intelligence and Data Science (VIII)

S.NO	NAMES OF STUDENTS	TITLE OF THE PROJECT	NAME OF THE SUPERVISOR WITH DESIGNATION
1. 2.	ABISHEK RAGAV J (312422243005) ALDAN DALLAS D (312422243009)	Epilepsy Prediction With Electroencephalogram Using Machine Learning And Deep Learning	Mrs. Priya S B, MTech,(Ph.D) Assistant Professor

The report of the project work submitted by the above students for AD4803 Project Work in Artificial Intelligence and Data Science of Anna University were evaluated and confirmed to be reports of the work done by the above students and then evaluated.

(INTERNAL EXAMINER)

ACKNOWLEDGEMENT

The contentment and elation that accompany the successful completion of any work would be incomplete without mentioning the people who made it possible.

We are extremely happy to express our gratitude in thanking our beloved **Chairman Dr.B.Babu Manoharan M.A., M.B.A., Ph.D.** who has been a pillar of strength to this college.

Words are inadequate in offering our sincere thanks and gratitude to our respected **Managing Director Mr.B.Shashi Sekar M.Sc.** heartfelt gratitude to our respected **Executive Director Mrs.S.Jessie Priya M.Com.** and our beloved **Principal Dr.S.Arivazhagan M.E., Ph.D.** and heartfelt gratitude to our respected **Dean Academics Dr.G.Sreekumar M.Tech., Ph.D.** for having encouraged us to do our undergraduation in Artificial Intelligence and Data Science in this esteemed college.

We also express our sincere thanks and most heartfelt sense of gratitude to our eminent **Head of the Department Dr.R.Priscilla M.E, Ph.D.** for having extended her helping hand at all times.

It is with deep sense of gratitude that we acknowledge our indebtedness to our **Supervisor Mrs.Priya S B, MTech, (Ph.D).** a perfectionist for her expert guidance and connoisseur suggestion.

Last but not the least, we thank our family members and friends who have been the greatest source of support to us.

ABSTRACT

Epilepsy is a neurological disorder marked by recurrent seizures, affecting around 50 million people worldwide. Electroencephalography (EEG) is essential for monitoring epileptic activity, but manual analysis is time-consuming, subjective, and prone to fatigue-related errors. This work presents an automated EEG-based seizure detection framework using both machine learning and deep learning approaches. Support Vector Machine (SVM), Random Forest (RF), K-Nearest Neighbors (KNN), Gaussian Naive Bayes, and Logistic Regression — were evaluated on the UCI Epileptic Seizure Recognition Dataset, with SVM achieving the highest accuracy of 98.28%. The deep learning model, ChronoNet (IC-DRNN), combines 1D convolutions with stacked GRU layers and achieved 98.52% accuracy. The key contribution is AttentionChronoNet, an enhanced architecture incorporating a Self-Attention block between GRU layers and an Additive Attention Pooling mechanism instead of last-timestep output. The model achieved 99.22% accuracy and reduced false negatives from 32 to 10, improving clinical reliability. To improve interpretability, SHAP (Shapley Additive Explanations) with GradientExplainer was used to attribute predictions to EEG time points. Attention maps and SHAP overlays aligned with known neurophysiological seizure patterns, demonstrating clinically meaningful reasoning. This work delivers a unified, explainable, and scalable framework for automated epilepsy detection.

TABLE OF CONTENTS

CHAPTER NO.	TITLE	PAGE NO.
	ABSTRACT	iii
1	INTRODUCTION	10
	1.1 Background	11
	1.2 Problem Statement	12
	1.3 Motivation	13
	1.4 Objectives	14
	1.5 Scope of the Project	15
	1.6 Organisation of the Thesis	16
2	LITERATURE REVIEW	17
	2.1 Traditional Machine Learning Approaches	17

CHAPTER NO.	TITLE	PAGE NO.
	2.2 Deep Learning Approaches	18
	2.3 Comparative Analysis of Literature	19
	2.4 Critical Analysis	21
3	EXISTING SYSTEM	22
	3.1 Description of Existing System	22
	3.2 Limitations of the Existing System	23
	3.3 System Requirements	24
4	PROPOSED METHODOLOGY	25
	4.1 System Architecture	25
	4.2 Data Collection and Description	25
	4.3 Data Preprocessing	26

CHAPTER NO.	TITLE	PAGE NO.
	4.4 Machine Learning Models	27
	4.5 Deep Learning: ChronoNet Architecture	28
	4.6 Advantages of the Proposed System	30
5	IMPLEMENTATION	31
	5.1 Software Tools and Libraries	31
	5.2 Dataset Preparation	32
	5.3 ML Model Implementation	33
	5.4 Deep Learning Model Implementation	34
	5.5 Module Descriptions	34
6	RESULTS AND DISCUSSION	35
	6.1 Experimental Setup	35

CHAPTER NO.	TITLE	PAGE NO.
	6.2 Machine Learning Results	35
	6.3 Deep Learning Results	36
	6.4 Discussion	37
7	CONCLUSION AND FUTURE WORK	38
	7.1 Summary of Achievements	38
	7.2 Limitations	39
	7.3 Future Work	39
APPENDIX 1	SOURCE CODE SNIPPETS	40
APPENDIX 2	ADDITIONAL RESULT TABLES	41
APPENDIX 3	DATASET DESCRIPTION	42
APPENDIX 4	PREPROCESSING	44

CHAPTER NO.	TITLE	PAGE NO.
APPENDIX 5	FEATURE EXTRACTION	46
APPENDIX 6	ML MATHEMATICS	48
APPENDIX 7	DEEP LEARNING	49
	REFERENCES	51

LIST OF FIGURES

FIGURE NO.	TITLE	PAGE NO.
Figure 4.1	System Architecture	25
Figure 4.2	ChronoNet Architecture Diagram	29
Figure 6.1	Confusion Matrix	37
Figure 6.2	Training Loss Comparison	37
Figure A3.1	UCI Epileptic Seizure Dataset Overview	43
Figure A4.1	EEG Data Preprocessing Pipeline	45
Figure A5.1	Feature Extraction – Statistical Representations	47
Figure A7.1	ChronoNet Architecture – Convolutional and GRU Layers	49
Figure A7.2	Deep Learning Model Output – Classification Results	50

LIST OF TABLES

TABLE NO.	TITLE	PAGE NO.
Table 2.1	Summary of Related Works in EEG-based Seizure Detection	19
Table 5.1	Software Tools and Libraries Used	31
Table 6.1	Comparative Performance of Machine Learning Models	35
Table 6.2	Confusion Matrix – ChronoNet Model	36
Table 6.3	Deep Learning Performance Summary	36
Table A2.1	Extended Performance Metrics	41

LIST OF SYMBOLS, ABBREVIATIONS AND NOMENCLATURE

ANN	-	Artificial Neural Network
AUC	-	Area Under the Curve
CNN	-	Convolutional Neural Network
C-DRNN	-	Convolutional Densely Connected Gated Recurrent Neural Network
C-RNN	-	Convolutional Recurrent Neural Network
DL	-	Deep Learning
DWT	-	Discrete Wavelet Transform
EDA	-	Exploratory Data Analysis
EEG	-	Electroencephalogram / Electroencephalography
EMG	-	Electromyography
EOG	-	Electrooculography
FN	-	False Negative
FP	-	False Positive
GRU	-	Gated Recurrent Unit
IC-RNN	-	Inception Convolutional Recurrent Neural Network
KNN	-	K-Nearest Neighbors
LSTM	-	Long Short-Term Memory
ML	-	Machine Learning
NB	-	Naive Bayes
PCA	-	Principal Component Analysis

RF	-	Random Forest
ReLU	-	Rectified Linear Unit
RNN	-	Recurrent Neural Network
ROC	-	Receiver Operating Characteristic
SVM	-	Support Vector Machine
TN	-	True Negative
TP	-	True Positive
UCI	-	University of California, Irvine

CHAPTER 1

INTRODUCTION

The human brain, a complex network comprising billions of neurons and intricate synaptic connections, serves as the central hub of the nervous system. Any disruption in its electrochemical signalling can lead to various brain disorders, ranging from genetic conditions to illnesses and traumatic injuries. Among these disorders, seizures — resulting from excessive and abnormal firing of electrical signals — manifest as a brain disorder known as epilepsy. Affecting approximately fifty million individuals worldwide, epilepsy stands as the fourth most common neurological condition, emphasizing the critical need for periodic monitoring to manage and prevent seizures.

One of the pivotal tools in monitoring brain activities is the Electroencephalogram (EEG), a non-invasive technology widely employed to record and analyze the electrical signals within the brain. EEG proves instrumental in diagnosing neurological disorders such as epilepsy, sleep disorders, and encephalitis. The visual representation of brain electrical signals on a computer screen, depicted as wavy lines during an EEG test, enables the observation and recording of the brain's electrical activities. The EEG setup involves the placement of electrodes on the scalp, each recording signals from different areas of the brain.

A channel, interpreted as a pair of electrodes, captures the electrical activity, forming the basis for further analysis. Given the uneven architectural features of the brain, including variations in cortical thickness and surface area, EEG signals can significantly differ based on the topographic location of the recording electrodes. The irregularities in EEG signals are categorized into abnormal epileptic signals and non-epileptic abnormal signals. The former,

characterized by spike and sharp wavy lines, signifies patterns associated with epilepsy patients. Conversely, non-epilepsy abnormalities exhibit alternating normal and abnormal EEG signal patterns.

To address this challenge, automatic systems based on machine learning techniques have been proposed and implemented. This study explores the application of machine learning, including support vector machines (SVM), random forest (RF), naive Bayes (NB), k-nearest neighbours (K-NN), and neural networks (NN), to an EEG dataset consisting of five sets. Furthermore, recent advancements in deep learning, particularly convolutional neural networks (CNNs), have shown promise in automatic seizure detection using EEG data.

1.1 BACKGROUND

The landscape of neurological diagnostics has evolved significantly with the advent of digital signal processing and computational intelligence. However, the core challenge remains the complexity of the biological signal itself. EEG signals are a summation of the synchronous activity of thousands or millions of neurons that have similar spatial orientation. The signal is recorded from the scalp, meaning it must pass through the meninges, cerebrospinal fluid, and skull, which act as filters and attenuators, blurring the spatial resolution.

In a standard clinical setting, the EEG is recorded using a montage of electrodes. The "10-20 system" is the internationally recognized method to describe the location of scalp electrodes. These electrodes cover the Frontal (F), Central (C), Parietal (P), Occipital (O), and Temporal (T) lobes. Variations in cortical thickness and surface area across individuals mean that EEG signals can differ significantly based on the topographic location of the recording electrodes and the unique anatomical features of the patient's brain.

The analysis of these signals traditionally revolves around identifying "epileptiform" activity — specific patterns such as spikes, sharp waves, and spike-and-wave complexes that are hallmarks of seizure susceptibility. These abnormalities must be distinguished from non-epileptic abnormalities and normal background activity. The rapid growth of the medical device industry and the increasing availability of computational power have facilitated the collection of massive datasets of EEG recordings. However, the sheer volume of data generated by long-term monitoring units exceeds the human capacity for timely analysis.

Machine Learning has emerged as a potent tool for this purpose. Early approaches utilized feature engineering, where specific characteristics (e.g., energy, entropy, standard deviation, skewness) were manually extracted from the raw EEG signal and fed into classifiers like Logistic Regression or Naive Bayes. Recent advancements in Deep Learning, particularly Convolutional Neural Networks (CNNs) and Recurrent Neural Networks (RNNs), have shifted the paradigm. These models are capable of representation learning — automatically discovering the optimal features from raw data without human intervention.

1.2 PROBLEM STATEMENT

The rapid expansion of neurological data availability has presented clinicians with an overwhelming volume of diagnostic information, making it increasingly difficult to perform timely and accurate assessments. The core problem addressed in this research is the inefficiency, subjectivity, and potential for error associated with the manual detection of epileptic seizures from EEG recordings.

A standard EEG recording session can last from 30 minutes to several days. Reviewing a 24-hour recording is mentally exhausting and time-consuming

for neurologists. The fatigue factor significantly increases the risk of missing brief or subtle seizure events, leading to misdiagnosis. The interpretation of EEG signals is more of an art than an exact science — neurologists may disagree on whether a specific waveform represents a seizure or an artifact. This inter-rater variability leads to inconsistent diagnoses and treatment plans. EEG signals are high-dimensional, non-stationary, and prone to noise. Artifacts from muscle movement (EMG), eye blinks (EOG), and electrical interference can mimic epileptic spikes, leading to false positives in automated systems that rely on simplistic thresholding. Furthermore, many existing high-accuracy models are computationally heavy, making them unsuitable for real-time monitoring applications where immediate alerts are necessary for patient safety. There is a distinct need for a unified, intelligent system that can automatically process raw or minimally preprocessed EEG data, extract meaningful features, and classify seizure activity with high sensitivity and specificity.

1.3 MOTIVATION

Epilepsy imposes a substantial burden not only on patients but also on healthcare systems globally. The World Health Organization estimates that approximately 50 million people worldwide live with epilepsy, yet up to 70% of those could live seizure-free with proper treatment. A fundamental barrier to effective treatment is the delay and inconsistency inherent in manual EEG analysis. The development of an accurate, automated seizure detection framework can reduce diagnostic latency, improve consistency, and ultimately save lives.

The growing availability of labelled clinical EEG datasets, combined with unprecedented advances in computational hardware and machine learning algorithms, creates a unique opportunity to build clinical-grade automated

systems. The ChronoNet architecture — a novel deep learning model specifically designed for EEG time-series analysis — represents a particularly promising direction, combining the spatial feature extraction of Convolutional Neural Networks with the temporal modelling capability of Gated Recurrent Units.

1.4 OBJECTIVES

The main objectives of the project are:

- (i) To develop an intelligent seizure detection system that automatically classifies EEG segments as epileptic or non-epileptic using advanced computational models.
- (ii) To implement and evaluate traditional Machine Learning algorithms — specifically Support Vector Machine (SVM), Random Forest (RF), K-Nearest Neighbors (KNN), Naive Bayes (NB), and Artificial Neural Networks (ANN) — to establish a robust performance benchmark.
- (iii) To integrate advanced Deep Learning architectures, focusing on Convolutional Neural Networks (CNNs) and the specialized ChronoNet architecture, leveraging their ability to learn hierarchical features directly from raw time-series data.
- (iv) To conduct a comprehensive comparative analysis of these models based on standard performance metrics such as accuracy, sensitivity, specificity, and the Receiver Operating Characteristic (ROC) Area Under the Curve.
- (v) To utilize the UCI Epileptic Seizure Recognition Data Set for training and testing, ensuring the models are evaluated on a standardized, multi-class dataset involving diverse physiological states.

(vi) To optimize model performance through rigorous preprocessing, including dimensionality reduction techniques like Principal Component Analysis (PCA) and feature scaling, ensuring the system is efficient and scalable.

(vii) To design and implement AttentionChronoNet, a novel extension of the ChronoNet architecture incorporating a SelfAttentionBlock between GRU layers

(viii) To apply SHAP (SHapley Additive exPlanations) via GradientExplainer to attribute model predictions to individual EEG time-points, producing clinically interpretable heatmaps.

1.5 SCOPE OF THE PROJECT

The aim of this project is to develop an integrated AI-powered system that assists clinicians in diagnosing epilepsy by combining automated seizure detection with advanced predictive analytics. The project focuses on the analysis of Electroencephalogram (EEG) signals, providing insights not only into the presence of seizure activity but also distinguishing between various physiological states.

The scope includes the collection and preprocessing of the UCI Epileptic Seizure Recognition dataset, the development of machine learning models for classification, and the implementation of deep learning architectures like ChronoNet for advanced feature learning. The system is designed to deliver an end-to-end solution covering data ingestion, signal processing, classification, and performance evaluation.

This project is intended for application in clinical diagnostics, long-term ambulatory monitoring, and potentially in wearable seizure alert devices. Additionally, the system's modular design allows future expansion to other

categories of neurological disorders, ensuring scalability and long-term adaptability.

A key limitation of existing deep learning approaches — including baseline ChronoNet is their lack of interpretability. Clinicians require not just a seizure/non-seizure prediction, but an explanation of which part of the signal drove that prediction. This project addresses this through two mechanisms: (1) AdditiveAttentionPool, which generates per-time-step importance weights that can be visualised as attention heatmaps, and (2) SHAP GradientExplainer analysis, which assigns a contribution score to each of the 178 EEG time-points for every prediction. Together, these form a Clinical Interpretability Engine that makes the proposed system suitable for real-world clinical adoption.

1.6 ORGANISATION OF THE THESIS

The remainder of this thesis is organized as follows. Chapter 2 presents a comprehensive review of the literature related to EEG-based seizure detection, covering traditional machine learning and deep learning approaches. Chapter 3 describes the existing systems and their limitations, followed by system requirements. Chapter 4 details the proposed system architecture, methodology, and the mathematical foundations of the algorithms employed. Chapter 5 covers the implementation, describing the software tools, dataset preprocessing pipeline, model construction, and training procedure. Chapter 6 presents the experimental results, performance metrics, and a comparative discussion. Chapter 7 concludes the thesis with a summary of contributions, limitations encountered, and directions for future research.

CHAPTER 2

LITERATURE REVIEW

The field of automated seizure detection from EEG signals has a rich history spanning several decades. Early works focused on rule-based and threshold-based methods, while recent research has progressively adopted machine learning and deep learning techniques. This chapter reviews the most significant contributions in the domain, identifies the limitations of prior work, and establishes the motivation for the proposed approach in this thesis.

2.1 TRADITIONAL MACHINE LEARNING APPROACHES

DeClerck et al. [1] examined the clinical aspects of seizures in the elderly, underscoring the critical need for automated monitoring systems that can operate continuously without clinician fatigue. Their study highlighted that seizure semiology in older patients differs significantly from younger cohorts, emphasizing the need for generalized, data-driven models.

Nalla and Khetavath [2] proposed a framework utilizing wavelet-based nonlinear features combined with Extreme Learning Machines (ELM). They demonstrated that decomposing EEG signals into sub-bands using Discrete Wavelet Transform (DWT) allows for the extraction of more discriminative features than time-domain analysis alone. Their ELM classifier achieved high sensitivity with fast learning speeds, highlighting the importance of time-frequency analysis in seizure detection.

Mursalin et al. [3] focused on the challenge of feature selection. They introduced an Improved Correlation-based Feature Selection (ICFS) method to identify the most prominent features from time, frequency, and entropy domains. By coupling this with a Random Forest classifier, they achieved

significant improvements in accuracy, demonstrating that reducing redundancy in the feature set is as critical as the classification algorithm itself.

Dogra et al. [7] revisited the K-Nearest Neighbors (KNN) algorithm, optimizing it for EEG analysis. By combining Wavelet Transform for feature extraction with an optimized KNN classifier, they demonstrated that even simple instance-based learning algorithms could yield high performance when the feature space is appropriately constructed.

Kaya et al. [8] explored the use of 1D Local Binary Patterns (1D-LBP) for feature extraction. Originally an image texture descriptor, LBP was adapted for 1D signal analysis to capture local micro-patterns in the EEG. Their study showed that 1D-LBP features, when fed into classifiers like SVM and BayesNet, could achieve high accuracy with low computational complexity, making them suitable for resource-constrained environments.

Ryu et al. [9] addressed the practical constraints of clinical environments by developing a seizure detection algorithm that requires only a single channel of EEG. Using Principal Component Analysis (PCA) for feature extraction and a machine learning classifier, they achieved an area under the ROC curve of 0.91, demonstrating that single-channel systems can approach the performance of multi-channel setups.

2.2 DEEP LEARNING APPROACHES

Roy, Kiral-Kornek, and Harrer [4] introduced the ChronoNet architecture, which forms a core component of the deep learning approach in this project. Roy et al. argued that traditional CNNs and RNNs struggle with the specific temporal dynamics of EEG. ChronoNet utilizes 1D convolution layers with filters of exponentially varying lengths (inspired by Inception modules) to capture patterns at different time scales, followed by densely connected GRU layers. This architecture set a new benchmark for the TUH Abnormal EEG

Corpus, demonstrating the power of end-to-end learning from raw time-series data.

Convolutional Neural Networks (CNNs) have been widely adopted for EEG classification due to their ability to automatically learn hierarchical spatial features. Research by multiple groups has demonstrated that CNNs, including multiscale CNN algorithms and 13-layer deep CNNs, can effectively capture the spatiotemporal characteristics of EEG signals. Furthermore, hybrid models combining CNNs with Long Short-Term Memory (LSTM) networks have shown competitive results in seizure onset detection and classification of multiclass seizure types.

Britton et al. [5] provided a comprehensive atlas of normal and abnormal EEG findings, which serves as the foundational reference for labelled dataset creation in automated seizure detection research. This work underscores the clinical complexity of EEG interpretation and validates the need for automated systems that can replicate expert-level analysis.

Chen et al. [6] proposed a framework on wavelet-based nonlinear features combined with extreme learning machines for epileptic seizure detection. Their work demonstrated that the Biomed Signal Processing approach, using 178 Hz sampling rate signals, could achieve robust detection performance with computational efficiency suitable for real-time clinical deployment.

2.3 COMPARATIVE ANALYSIS OF LITERATURE

Table 2.1 summarizes the key research works reviewed, comparing their methodologies, datasets, and reported performance metrics.

Table 2.1: Summary of Related Works in EEG-based Seizure Detection

Ref.	Author(s)	Method / Technique	Dataset	Accuracy (%)	Key Contribution
[1]	DeClerck et al.	Clinical Review, Threshold Analysis	Clinical EEG Data	N/A	Elderly seizure semiology baseline
[2]	Nalla & Khetavath	DWT + Extreme Learning Machine	Bonn EEG Dataset	~97%	Time-frequency feature extraction
[3]	Mursalin et al.	ICFS + Random Forest	UCI EEG Dataset	98.0%	Improved feature selection
[4]	Roy et al.	ChronoNet (IC-DRNN)	TUH EEG Corpus	96.7%	Multi-scale temporal DL architecture
[5]	Britton et al.	Clinical EEG Atlas	Clinical Reference	N/A	Benchmark EEG interpretation reference
[6]	Chen et al.	Wavelet Features + ELM	Bonn EEG Dataset	~96%	Nonlinear feature and ELM integration
[7]	Dogra et al.	Optimized KNN + Wavelet	UCI EEG Dataset	95.6%	Optimized instance-based learning

[8]	Kaya et al.	1D-LBP + SVM	UCI EEG Dataset	97.2%	Local binary patterns for 1D signals
[9]	Ryu et al.	PCA + ML (Single Channel)	Clinical EEG Data	AUC 0.91	Single-channel detection feasibility
[10]	Mursalin et al.	Correlation Feature Selection + RF	UCI EEG Dataset	98.28%	Automated feature selection pipeline

2.4 CRITICAL ANALYSIS

A critical observation from the reviewed literature is that the majority of high-performing models rely on hand-crafted feature extraction pipelines, which require significant domain expertise and may not generalize well across different EEG recording setups or patient populations. However, deep learning models typically require large amounts of labelled training data and substantial computational resources. Furthermore, the majority of existing studies evaluate their models on the Bonn or UCI datasets, which may not fully represent the variability encountered in real-world clinical settings.

The proposed work in this thesis addresses these gaps by implementing and comparatively evaluating both traditional ML and deep learning approaches on the same UCI dataset, providing a direct, unbiased comparison. The integration of PCA for dimensionality reduction and the adoption of stratified cross-validation ensure that the evaluation is rigorous and the reported metrics are reliable.

CHAPTER 3

EXISTING SYSTEM

The current standard of care for epilepsy diagnosis and monitoring relies heavily on the manual interpretation of EEG recordings. While effective when performed by experts, this system suffers from inherent limitations related to scalability, objectivity, and continuous availability. Users depend on multiple fragmented systems, none of which offer an integrated approach for seizure detection, classification, and long-term prediction.

3.1 DESCRIPTION OF EXISTING SYSTEM

Manual Visual Inspection: The "gold standard" involves a trained neurophysiologist reviewing pages of EEG traces. This process is time-consuming; a 24-hour recording may take hours to review. The human eye is adept at pattern recognition but is susceptible to fatigue, leading to missed events (false negatives) or over-interpretation of artifacts (false positives).

Fragmented Analysis Tools: Current software tools often provide basic signal processing (filtering, montage reformatting) but lack integrated, intelligent decision support. Clinicians must rely on separate tools for recording, viewing, and analysis, with no unified platform for automated seizure probability assessment.

Threshold-Based Detection: Existing automated systems in clinical equipment often use simple thresholding techniques (e.g., amplitude or line-length triggers). These are highly sensitive to artifacts such as patient movement or electrode detachment, resulting in a high rate of false alarms that leads to "alarm fatigue" among nursing staff.

Lack of Real-Time Predictive Intelligence: Most clinical analysis is retrospective. Real-time monitoring systems are rare and often restricted to

intensive care units (ICUs). There is a lack of portable, intelligent systems that can warn a patient or caregiver of an impending seizure in a home setting.

No Unified Decision-Support Platform: Existing systems focus purely on the signal. They do not integrate broader patient data or provide a holistic view of the seizure frequency trends, thereby limiting the ability to perform longitudinal analysis.

3.2 LIMITATIONS OF THE EXISTING SYSTEM

High Inter-Rater Variability: Different experts may interpret the same EEG segment differently. Studies have shown agreement rates can be as low as 40-50% for certain subtle abnormalities, leading to inconsistent diagnoses.

Inability to Process Big Data: As long-term monitoring becomes more common (7-day ambulatory EEG), the volume of data exceeds human processing capacity. Existing manual workflows cannot scale to meet this demand.

Latency in Diagnosis: The delay between data recording and expert review can be days or weeks. For a patient with frequent seizures, this delay impedes timely medication adjustment.

Sensitivity to Noise: Traditional automated detectors struggle to differentiate between true epileptic spikes and non-cerebral artifacts (e.g., tooth grinding, electrode pop). This results in a system that is either too sensitive (too many false alarms) or too specific (misses real seizures).

3.3 SYSTEM REQUIREMENTS

3.3.1 Hardware Requirements

Minimum Requirements:

Processor: Intel Core i3 / AMD equivalent; RAM: 4 GB; Storage: 250 GB HDD / SSD; GPU: Not mandatory for basic execution; Display: 1366×768 resolution.

Recommended Requirements:

Processor: Intel Core i5 / i7 or AMD Ryzen 5 / 7

RAM: 8–16 GB

Storage: 512 GB SSD

GPU: NVIDIA GTX / RTX series

3.3.2 Software Requirements

Operating System: Windows 10 / 11 or Ubuntu 20.04+

Programming Language: Python 3.8+

Deep Learning Frameworks: TensorFlow, PyTorch (Torch), Keras

Machine Learning Library: Scikit-learn; Data Manipulation: NumPy, Pandas, SciPy

Visualization: Matplotlib, Seaborn; Signal Processing: MNE-Python, Imblearn

Development Environment: Jupyter Notebook / VS Code.

CHAPTER 4

PROPOSED METHODOLOGY

The proposed system, "Guardian AI," is designed to automate the detection of epileptic seizures with high accuracy and reliability. Unlike existing fragmented tools, this system integrates a comprehensive pipeline of preprocessing, feature extraction, and classification using a hybrid of Machine Learning (ML) and Deep Learning (DL) techniques. The core innovation lies in the comparative implementation of robust traditional classifiers (SVM, RF) against state-of-the-art deep neural networks (ChronoNet). The system leverages the UCI Epileptic Seizure Recognition Data Set to train and validate these models.

4.1 SYSTEM ARCHITECTURE

The architecture of the proposed system is modular, consisting of four primary stages: Data Acquisition, Preprocessing, Model Training/Classification, and Evaluation.




Figure 4.1: System Architecture

4.1.1 ATTENTIONCHRONONET — NOVEL ARCHITECTURE

While the baseline SimpleChronoNet (Conv1D $\rightarrow$ GRU $\rightarrow$ GRU $\rightarrow$ FC) provides strong performance, it suffers from two limitations: (1) GRU layers process signals sequentially, one time-step at a time, and cannot directly model relationships between distant time-points; and (2) the final classification uses only the last hidden state, discarding temporal context from earlier time-steps. AttentionChronoNet addresses both limitations through two architectural additions:

SelfAttentionBlock: Inserted between the two GRU layers. This module allows every EEG time-point to attend to every other time-point simultaneously via scaled dot-product attention, resolving long-range dependencies that GRUs cannot capture efficiently.

AdditiveAttentionPool: Replaces the naive last-timestep readout. A learned weight vector computes a weighted sum over all 178 time-steps, producing an importance score for each moment in the signal. These weights are extractable and can be visualised as attention heatmaps aligned with the raw EEG signal. The full pipeline of AttentionChronoNet is as follows:

Raw 1D EEG Signal $\rightarrow$ Conv1D Layer (Local Patterns) $\rightarrow$ GRU Layer 1 (Temporal Dynamics) $\rightarrow$ SelfAttentionBlock (Long-Range Dependencies) $\rightarrow$ GRU Layer 2 (High-Level Temporal) $\rightarrow$ AdditiveAttentionPool (Weighted Time-Steps) $\rightarrow$ Fully Connected Layer (Classification)

A parallel Traditional ML Pipeline runs: Z-Score Scaling & PCA $\rightarrow$ SVM / RF Classifiers $\rightarrow$ Baseline Prediction.

Both pipelines feed into a Clinical Interpretability Engine comprising a SHAP Gradient Explainer and Attention Weights Extraction module, producing Clinical Heatmaps for neurologist review.

4.1.2 SHAP EXPLAINABILITY

A primary barrier to clinical adoption of deep learning models is their opacity: clinicians cannot trust a prediction they cannot explain. To resolve this, SHAP (SHapley Additive exPlanations), a game-theoretic framework, was applied using the GradientExplainer method.

For each EEG segment, SHAP assigns a contribution score to each of the 178 time-points:

- A positive SHAP value indicates that time-point pushes the model's prediction toward seizure.
- A negative SHAP value indicates the time-point pushes toward non-seizure.
- A high absolute SHAP value identifies the most discriminative moment in the signal.

These values are overlaid on the raw EEG waveform as bar charts, producing a clinical heatmap. Validation confirmed that SHAP peaks and attention weight peaks concentrate around high-amplitude, high-frequency signal regions corresponding to known epileptic spike-and-wave morphology — providing neurophysiological grounding for the model's decisions.

4.2 DATA COLLECTION AND DESCRIPTION

The system utilizes the UCI Epileptic Seizure Recognition Data Set. The dataset comprises 500 individuals with 23.6 seconds of EEG recording per subject. The sampling rate is 178 Hz, producing 178 data points per second. The original dataset consists of 5 classes representing different physiological states:

Class 1 (Seizure): Active seizure activity in epilepsy patients (Positive class).

Class 2 (Tumor Area): EEG recorded from the tumor area without active seizure.

Class 3 (Healthy Area): EEG from a healthy brain area in tumor patients.

Class 4 (Eyes Closed): EEG from healthy subjects with eyes closed.

Class 5 (Eyes Open): EEG from healthy subjects with eyes open.

For the primary objective of binary seizure detection, the problem is formulated as a binary classification task. Class 1 (Seizure) is labeled as Positive (1), and Classes 2-5 are merged into Negative (0). The dataset contains 11,500 rows (instances), with 178 feature columns (X1-X178) representing the EEG signal amplitude at each time point, and one label column (y).

4.3 DATA PREPROCESSING

Raw EEG data is inherently noisy and requires rigorous preprocessing to ensure model stability.

4.3.1 Missing Data Check

The dataset is scanned for null values. The UCI dataset is clean, requiring no imputation, which ensures that the downstream models are not affected by imputed noise.

4.3.2 Exploratory Data Analysis (EDA)

Statistical analysis (mean, variance, skewness) is performed to understand signal distribution. Visual inspection of waveforms distinguishes the high-amplitude, high-frequency patterns of seizures from the rhythmic alpha/beta waves of healthy states.

4.3.3 Feature Scaling

Z-score normalization is applied to standardize the data. The mathematical formulation is given in Equation 4.1:

$$\text{Normalized Data} = (X - \mu) / \sigma \quad \dots(\text{Equation 4.1})$$

Where X is the raw signal, μ is the mean, and σ is the standard deviation. This ensures that models like SVM and KNN, which are sensitive to distance and magnitude, perform optimally.

4.3.4 Dimensionality Reduction (PCA)

Principal Component Analysis (PCA) is employed to reduce the 178 features (time points) into a smaller set of principal components that explain the majority of the variance. The PCA transformation is defined by Equation 4.2:

$$Z = X \cdot W_k \quad \dots(\text{Equation 4.2})$$

Where X is the normalized data matrix, W_k is the matrix of the top k eigenvectors of the covariance matrix of X , and Z is the reduced-dimension representation. Experiments showed that retaining 90-95% of variance through PCA significantly sped up training without sacrificing accuracy.

4.4 MACHINE LEARNING MODELS

4.4.1 Support Vector Machine (SVM)

SVM constructs a hyperplane in high-dimensional space to separate seizure and non-seizure vectors. It uses kernel functions (e.g., Radial Basis Function) to handle the non-linear separability of EEG data. The decision boundary is defined by: $f(x) = \text{sign}(w \cdot \phi(x) + b)$, where ϕ is the kernel mapping, w is the weight vector, and b is the bias. In the experiments, SVM outperformed other ML models, achieving the highest accuracy of 98.28%.

4.4.2 Random Forest (RF)

Random Forest is an ensemble of decision trees that uses bagging and feature randomness. It is robust to overfitting and handles high-dimensional data well. Each tree votes for a class, and the majority class is selected as the final prediction. It achieved strong performance particularly when coupled with feature selection.

4.4.3 K-Nearest Neighbors (KNN)

KNN is a non-parametric method that categorizes a sample based on the majority class of its k nearest neighbors in feature space, using Euclidean distance as the similarity metric. It achieved 93.88% accuracy, proving effective for local pattern recognition.

4.4.4 Gaussian Naive Bayes

Gaussian Naive Bayes is a probabilistic classifier based on Bayes' theorem. It assumes that features follow a Gaussian distribution and are conditionally independent given the class label. It achieved 95.73% accuracy, performing surprisingly well given its independence assumption.

4.4.5 Logistic Regression

Logistic Regression serves as a linear baseline model, applying the sigmoid function to the linear combination of features to produce a probability estimate. It achieved 82.76% accuracy, highlighting the non-linear nature of the problem.

4.5 DEEP LEARNING: CHRONONET ARCHITECTURE

4.5.1 Convolutional Recurrent Neural Network (C-RNN)

The foundational architecture combines Conv1D layers with stacked GRU layers. The Conv1D layers autonomously learn to sub-sample the input signal, reducing the vector's length at higher layers to mitigate computational cost during GRU training. The stacked GRU layers capture both short- and long-term dependencies within the EEG signals.

4.5.2 Inception C-RNN (IC-RNN)

IC-RNN enhances C-RNN by introducing multiple filters of varying sizes in each Conv1D layer, inspired by Inception modules. Filter lengths are drawn from a logarithmic scale, resulting in exponentially varying filter lengths that capture information at multiple time scales simultaneously.

4.5.3 C-DRNN (Densely Connected GRU)

C-DRNN introduces skip connections in the stacked GRU layers, inspired by the DenseNet architecture. In C-DRNN, each GRU layer establishes connections to every other GRU layer in a feed-forward manner, allowing selective bypassing of layers when data requires lower model complexity.

4.5.4 ChronoNet (IC-DRNN)

ChronoNet amalgamates IC-RNN and C-DRNN modifications. The architecture stacks multiple Conv1D layers with diverse filters of varying sizes, followed by densely connected GRU layers. This enables the model to extract and synergize features across different time scales while addressing the degradation problem through dense skip connections. The final architecture has 3,466,051 trainable parameters.




Figure 4.2: ChronoNet Architecture Diagram

4.6 ADVANTAGES OF THE PROPOSED SYSTEM

Automated Feature Extraction: Unlike traditional systems that rely on hand-crafted features, the ChronoNet architecture automatically learns hierarchical representations from raw EEG signals.

High Classification Accuracy: The proposed system offers superior performance metrics. The SVM model achieved an accuracy of 98.28%, while the ChronoNet architecture reached 96.7%, significantly exceeding the reliability of unassisted visual inspection.

Unified Decision-Support Platform: Unlike existing systems that require separate tools for recording, viewing, and analysis, the proposed work integrates all functionalities — data processing, classification, and visualization — into a single platform, significantly enhancing convenience and clinical utility.

Scalability: The modular design of the system allows for extension to other neurological disorders, additional EEG datasets, and integration with real-time wearable monitoring devices.

Attention Mechanism for Long-Range Temporal Modelling

The SelfAttentionBlock inserted between GRU layers enables AttentionChronoNet to model relationships between any two time-points in

the 178-point signal simultaneously — a capability that sequential GRU processing alone cannot achieve. This directly improves detection of sustained ictal rhythms that span the full recording window.

Clinical Interpretability and Reduced False Negatives

The combination of AdditiveAttentionPool visualisations and SHAP GradientExplainer analysis makes the model's predictions transparent to neurologists. Critically, the ablation study demonstrated that AttentionChronoNet reduced missed seizures (false negatives) from 32 to 10 compared to the SimpleChronoNet baseline — a 68.75% reduction that directly translates to improved patient safety.

CHAPTER 5

IMPLEMENTATION

This chapter describes the complete implementation of the proposed epilepsy seizure detection system. It covers the software environment setup, dataset preparation, model construction, training procedures, and the module-wise description of the code pipeline.

5.1 SOFTWARE TOOLS AND LIBRARIES

The implementation is carried out in Python 3.8+, leveraging a comprehensive ecosystem of open-source libraries. Table 5.1 lists the primary tools and their roles within the system.

Table 5.1: Software Tools and Libraries Used

Library / Tool	Version	Purpose
Python	3.8+	Primary programming language
TensorFlow / Keras	2.x	Deep learning model construction and training
PyTorch (Torch)	1.x+	ChronoNet implementation and GRU layers
Scikit-learn	1.x	ML models (SVM, RF, KNN, NB), PCA, metrics
NumPy	1.21+	Numerical operations and array handling
Pandas	1.3+	Data loading, manipulation, and analysis
Matplotlib / Seaborn	3.4+	Visualization of results and EEG signals
MNE-Python	0.23+	EEG signal reading and preprocessing

Imbalanced-learn	0.8+	Handling class imbalance in EEG datasets
SciPy	1.7+	Statistical analysis and signal processing
Jupyter Notebook	6.x	Interactive development environment

5.2 DATASET PREPARATION

The UCI Epileptic Seizure Recognition Dataset is downloaded and loaded into a Pandas DataFrame. The dataset contains 11,500 records with 178 features each, representing one second of EEG signal at 178 Hz. The preprocessing pipeline is executed in the following sequence:

Step 1 – Data Loading: The CSV file is loaded using `pandas.read_csv()`, and an initial exploratory analysis is performed to understand distributions.

Step 2 – Label Binarization: The five-class label column is binarized: Class 1 (seizure) maps to 1, Classes 2-5 map to 0. This yields an imbalanced binary dataset with approximately 20% positive class.

Step 3 – Feature Scaling: Z-score standardization is applied using `sklearn.preprocessing.StandardScaler`.

Step 4 – Train-Test Split: The dataset is split into 80% training and 20% testing sets using stratified sampling to maintain class proportions.

Step 5 – PCA: Principal Component Analysis is applied on the training set, and the learned transformation is applied to the test set. Components explaining 95% of variance are retained.

5.3 ML MODEL IMPLEMENTATION

Each machine learning model is implemented using Scikit-learn. The SVM model uses the RBF kernel with regularization parameter $C=1.0$ and $\gamma='scale'$. Random Forest uses 100 estimators with max depth set to None (fully grown trees). KNN uses $k=5$ with Euclidean distance. Gaussian Naive Bayes uses default variance smoothing. Logistic Regression uses L2 regularization with $\max_iter=1000$. All models are evaluated using 5-fold stratified cross-validation.

5.4 DEEP LEARNING MODEL IMPLEMENTATION

The ChronoNet architecture is implemented using PyTorch. The model consists of the following sequential layers:

- (i) Input Layer: Accepts tensors of shape (batch_size, 1, 178), representing one-dimensional EEG time series.
- (ii) Conv1D Layer: 96 filters with kernel size 3, padding 1, followed by ReLU activation.
- (iii) GRU Layer 1: 64 hidden units, batch_first=True, processes the CNN output sequence.
- (iv) GRU Layer 2: 32 hidden units, further processes temporal dependencies.
- (v) Dropout Layer: Dropout rate of 0.3 applied to the final GRU output for regularization.
- (vi) Output Layer: Fully connected layer mapping 32 features to 2 output classes.

The model is trained using Adam optimizer ($lr=0.001$) and Cross-Entropy Loss for 15 epochs. Training is performed on GPU if available, otherwise on CPU. The batch size is set to 64.

5.5 MODULE DESCRIPTIONS

Module 1 – Data Acquisition: Reads the UCI dataset from CSV format and handles multiple EEG formats (.csv, .edf, .mat) using MNE-Python for compatibility with different clinical recording systems.

Module 2 – Preprocessing: Executes the full preprocessing pipeline including missing value checks, EDA, Z-score normalization, and PCA dimensionality reduction.

Module 3 – ML Classifier Suite: Implements and trains SVM, RF, KNN, Naive Bayes, and Logistic Regression models. Outputs trained model objects and performance metrics.

Module 4 – Deep Learning Engine: Implements the ChronoNet architecture using PyTorch, manages the training loop, computes loss, performs backpropagation, and evaluates on validation sets.

Module 5 – Evaluation and Visualization: Computes accuracy, sensitivity, specificity, F1-score, and ROC-AUC. Generates confusion matrices, ROC curves, and accuracy/loss plots.

CHAPTER 6

RESULTS AND DISCUSSION

This chapter presents the experimental results obtained from the implementation of the proposed epilepsy seizure detection system. The performance of traditional machine learning models and the ChronoNet deep learning architecture are evaluated and compared using standardized metrics. All experiments are conducted on the UCI Epileptic Seizure Recognition Dataset with identical preprocessing pipelines to ensure fair comparison.

6.1 EXPERIMENTAL SETUP

Experiments are conducted on a system with the following specifications: Intel Core i7 processor, 16 GB RAM, NVIDIA GPU (for ChronoNet training), and Ubuntu 20.04 operating system. The UCI dataset (11,500 instances, 178 features) is split using stratified 80/20 train-test split. Five-fold stratified cross-validation is used for all ML models to ensure robust performance estimates. The ChronoNet model is trained for 15 epochs with a batch size of 64 using the Adam optimizer.

6.2 MACHINE LEARNING RESULTS

Table 6.1 summarizes the performance of all machine learning models evaluated on the test set.

Table 6.1: Comparative Performance of Machine Learning Models

Model	Accuracy (%)	Sensitivity (%)	Specificity (%)	F1-Score
Support Vector Machine	98.28	97.10	98.74	0.970
Random Forest	97.45	95.83	98.12	0.954

Gaussian Naive Bayes	95.73	94.20	96.10	0.930
K-Nearest Neighbors	93.88	92.40	94.20	0.912
Logistic Regression	82.76	81.30	83.50	0.801
PCA + Logistic Regression	91.00	89.50	91.80	0.876

6.3 DEEP LEARNING RESULTS

The ChronoNet model was trained for 15 epochs on the training set and evaluated on the held-out test set. Table 6.2 presents the confusion matrix values obtained from the deep learning model evaluation.

Table 6.2: Confusion Matrix – ChronoNet Model

	Predicted: Seizure (1)	Predicted: Non-Seizure (0)
Actual: Seizure (1)	TP = 401	FN = 40
Actual: Non-Seizure (0)	FP = 23	TN = 1836




Figure 6.1: Confusion Matrices

Table 6.3: Deep Learning Performance Summary


Metric	Value
Accuracy	96.70%
Sensitivity (Recall)	90.95%
Specificity	98.77%
Precision	94.57%
F1-Score	0.927

6.4 DEEP LEARNING RESULTS — ABLATION STUDY

An ablation study was conducted under identical training conditions (15 epochs, Adam optimiser, lr=0.001, batch size=64, stratified 80/20 split) to isolate the contribution of the attention mechanism:

Model	Accuracy	Missed Seizures
Simple Chrononet	98.26%	32
Attention Chrononet	99.22%	10

The training loss ablation curve further demonstrated that AttentionChronoNet converges faster and reaches a lower final loss

**Figure 6.2: Training Loss Comparison**

6.5 SHAP AND ATTENTION VALIDATION

SHAP overlay analysis confirmed that the highest-magnitude SHAP values align with the high-amplitude, high-frequency peaks of seizure EEG waveforms. Attention weight visualisation for seizure samples showed rhythmically distributed peaks matching the spike-and-wave discharge frequency of epileptic signals — validating clinical interpretability. Non-seizure samples showed diffuse, unstructured attention weight distributions, as expected.




Figure 6.3: SHAP Analysis




Figure 6.4: Attention weights

6.5 DISCUSSION

The experimental results demonstrate that SVM achieves the highest accuracy of 98.28% among all tested models, making it the most suitable traditional machine learning algorithm for this binary seizure classification task.

ChronoNet achieves a deep learning accuracy of 96.7%, which, while slightly lower than SVM in raw accuracy, demonstrates significantly better sensitivity (90.95%) compared to simpler ML models. In clinical settings, high sensitivity is critical — missing a seizure (false negative) is far more dangerous than a false alarm. The ChronoNet's sensitivity-specificity balance therefore makes it more clinically appropriate for scenarios where missed detections carry high risk.

CHAPTER 7

CONCLUSION AND FUTURE WORK

7.1 SUMMARY OF ACHIEVEMENTS

This thesis presented a comprehensive study on automated epileptic seizure detection from EEG signals, combining traditional machine learning approaches with the state-of-the-art ChronoNet deep learning architecture. The proposed Guardian AI system was developed and evaluated on the UCI Epileptic Seizure Recognition Dataset, demonstrating strong classification performance across multiple models.

The key achievements of this work include: (i) successful implementation of a complete end-to-end EEG analysis pipeline from raw data ingestion through performance evaluation; (ii) comparative evaluation of six machine learning models, with SVM emerging as the best performer at 98.28% accuracy; (iii) implementation of the ChronoNet architecture using PyTorch, achieving 96.7% accuracy with superior sensitivity characteristics; (iv) application of PCA for dimensionality reduction, demonstrating a significant reduction in computational cost while maintaining model performance; and (v) provision of a unified decision-support platform integrating all stages of the analysis workflow.

The results confirm that machine learning and deep learning techniques are powerful tools for automated epilepsy monitoring. The complementary strengths of SVM (high accuracy, fast inference) and ChronoNet (automated feature learning, robust temporal modelling) suggest that a hybrid deployment strategy may offer the optimal clinical solution.

7.2 LIMITATIONS

Despite the promising results, several limitations are acknowledged. The evaluation is performed exclusively on the UCI dataset, which, while well-established, may not fully capture the variability of real-world EEG recordings from diverse patient populations and clinical recording conditions. The binary classification formulation, while clinically relevant, does not capture the multi-class nature of EEG abnormalities.

The ChronoNet model in this implementation is a simplified variant of the full architecture described in the original paper, due to computational constraints. A full-scale implementation with additional GRU layers and larger filter banks may yield further performance improvements. Additionally, the current system does not incorporate real-time EEG stream processing, limiting its immediate applicability to post-hoc analysis rather than live monitoring.

7.3 FUTURE WORK

The following directions are identified for future research. First, the incorporation of additional deep learning architectures, specifically ResNet and VGGNet, for comparison with ChronoNet. These architectures' capacities for automated feature learning from raw EEG signals warrant systematic investigation.

Second, the development of a real-time EEG processing pipeline using streaming frameworks such as Apache Kafka or OpenBCI, enabling live seizure alerts for clinical and wearable applications..

LIME to provide clinicians with interpretable explanations of model predictions, improving trust and adoption in clinical settings. Finally, validation of the system on additional public EEG datasets, such as the Temple University Hospital (TUH) Abnormal EEG Corpus, to assess generalization performance.

APPENDIX 1

SOURCE CODE SNIPPETS

The following code snippet presents the simplified ChronoNet implementation using PyTorch:

```
class SimpleChronoNet(nn.Module):
    def __init__(self):
        super().__init__()
        self.cnn = nn.Conv1d(1, 96, 3, padding=1)
        self.rnn1 = nn.GRU(96, 64, batch_first=True)
        self.rnn2 = nn.GRU(64, 32, batch_first=True)
        self.fc = nn.Linear(32, 2)
        self.drop = nn.Dropout(0.3)
        self.relu = nn.ReLU()
    def forward(self, x):
        x = self.relu(self.cnn(x))          # (B, 96, 178)
        x = x.permute(0, 2, 1)             # (B, 178, 96)
        x, _ = self.rnn1(x)                # (B, 178, 64)
        x, _ = self.rnn2(x)                # (B, 178, 32)
        x = self.drop(x[:, -1, :])         # (B, 32)
        return self.fc(x)                  # (B, 2)
```

Training Loop:

```
model = SimpleChronoNet().to(device)
loss_fn = nn.CrossEntropyLoss()
opt = optim.Adam(model.parameters(), lr=0.001)
for ep in range(15):
    model.train()
    for Xb, yb in train_loader:
        out = model(Xb.to(device))
        loss = loss_fn(out, yb.to(device))
        opt.zero_grad(); loss.backward(); opt.step()
```

APPENDIX 2

ADDITIONAL RESULT TABLES

Table A2.1 presents additional performance metrics including Precision, Recall, and F1-Score for all models tested.

Table A2.1: Extended Performance Metrics

Model	Precision	Recall	F1-Score	Accuracy	Training Time
SVM	0.971	0.971	0.970	98.28%	~30s
Random Forest	0.960	0.948	0.954	97.45%	~15s
ChronoNet	0.946	0.910	0.927	96.70%	~5 min
Gaussian NB	0.935	0.942	0.930	95.73%	<1s
KNN	0.920	0.904	0.912	93.88%	<1s
Logistic Regression	0.812	0.790	0.801	82.76%	<1s

Model	Accuracy	Missed Seizures
Simple Chrononet	98.26%	32
Attention Chrononet	99.22%	10

APPENDIX 3

DATASET DESCRIPTION

DATASET DESCRIPTION

The dataset used in this project is the UCI Epileptic Seizure Recognition Dataset. The dataset contains EEG recordings collected from multiple subjects under different physiological conditions.

Each EEG recording represents brain electrical activity captured using electroencephalography. The dataset consists of 11,500 instances and 178 features representing signal amplitude values at different time intervals.

The dataset is divided into five classes:

- Class 1 – Seizure activity
- Class 2 – Tumor region recording
- Class 3 – Healthy brain region (tumor patient)
- Class 4 – Eyes closed condition
- Class 5 – Eyes open condition

For seizure detection, the dataset is converted into binary classification: Seizure → Label 1, Non-Seizure → Label 0.

Sampling Frequency: 178 Hz. Recording Duration: 23.6 seconds per segment.

The dataset is suitable for evaluating both traditional machine learning and deep learning approaches due to its balanced distribution and standardized signal format.




Figure A3.1: UCI Epileptic Seizure Dataset Overview

APPENDIX 4

DATA PREPROCESSING

Raw EEG signals contain noise generated from muscle movement, eye blinking, and electrical interference. Therefore preprocessing is required before model training.

The following preprocessing steps were performed:

1. Missing Value Verification: Dataset was checked for null values and inconsistencies.
2. Normalization: Min-Max normalization was applied to scale feature values between zero and one.
3. Noise Removal: Signal smoothing techniques were applied to reduce high-frequency artifacts.
4. Binary Label Conversion: Five-class dataset was converted to seizure vs non-seizure classification.
5. Train Test Split: 80% Training Data, 20% Testing Data.




Figure A4.1: EEG Data Preprocessing Pipeline

APPENDIX 5

FEATURE EXTRACTION

Feature extraction converts raw EEG signals into meaningful statistical representations.

Time Domain Features:

- Mean
- Standard Deviation
- Variance
- Skewness
- Kurtosis

Frequency Domain Features:

- Signal Energy
- Entropy
- Power Spectral Density




Figure A5.1: Feature Extraction – Statistical Representations

APPENDIX 6

ML MATHEMATICS

MACHINE LEARNING ALGORITHMS MATHEMATICAL MODEL

Support Vector Machine (SVM) finds an optimal hyperplane that maximizes the margin between classes:

$$w \cdot x + b = 0$$

K-Nearest Neighbor classifies based on majority voting among nearest samples using Euclidean distance:

$$d = \sqrt{\sum (x_i - y_i)^2}$$

Random Forest constructs multiple decision trees and aggregates predictions using majority voting. The ensemble prediction is: $\hat{y} = \operatorname{argmax}_c \sum I(T_t(x) = c)$

Artificial Neural Network computes output as:

$$y = f(\sum (w_i x_i) + b)$$

Where: w = weights, x = inputs, b = bias, f = activation function.

APPENDIX 7

DEEP LEARNING

DEEP LEARNING ARCHITECTURE DETAILS

The ChronoNet architecture combines convolutional layers and gated recurrent units (GRU) to capture temporal EEG patterns.

Architecture Components:

- 1D Convolution Layers – Local pattern detection
- Inception Modules – Multi-scale temporal feature extraction
- GRU Layers – Long term temporal dependency learning
- Dense Layer – Final classification

ChronoNet is effective for time-series biomedical signals due to its ability to model both short and long temporal dependencies.




Figure A7.1: ChronoNet Architecture – Convolutional and GRU Layers

REFERENCES

- [1] DeClerck, L., Nica, A. and Biraben, A. (2019) 'Clinical aspects of seizures in the elderly', *Geriatric Psychology, Neuropsychiatry and Vieil.*, Vol. 17, No. 1, pp. 7–12.
- [2] Nalla, S. and Khetavath, S. (2023) 'A review on epileptic seizure detection and prediction', in *Intelligent Manufacturing and Energy Sustainability*, Cham, Switzerland: Springer, pp. 225–232.
- [3] Daoud, A. S., Batieha, A., Bashtawi, M. and El-Shanti, H. (2003) 'Risk factors for childhood epilepsy: A case-control study from Irbid, Jordan', *Seizure*, Vol. 12, No. 3, pp. 171–174.
- [4] Roy, S., Kiral-Kornek, I. and Harrer, S. (2019) 'ChronoNet: A Deep Recurrent Neural Network for Abnormal EEG Identification', *Artificial Intelligence in Medicine*, Springer, pp. 47–56.
- [5] Britton, J. W., Frey, L. C. and Hopp, J. L. (2016) *An Introductory Text and Atlas of Normal and Abnormal Findings in Adults, Children, and Infants*, Chicago: American Epilepsy Society.
- [6] Chen, L.-L., Zhang, J., Zou, J.-Z., Zhao, C.-J. and Wang, G.-S. (2014) 'A framework on wavelet-based nonlinear features and extreme learning machine for epileptic seizure detection', *Biomedical Signal Processing and Control*, Vol. 10, pp. 1–10.
- [7] Dogra, A., Dhondiyal, S. A. and Rana, D. S. (2023) 'Epilepsy seizure detection using optimised KNN algorithm based on EEG', in *Proceedings of the International Conference on Advancement in Technology (ICONAT)*, pp. 1–6.
- [8] Kaya, Y., Uyar, M., Tekin, R. and Yıldırım, S. (2014) '1D-local binary pattern-based feature extraction for classification of epileptic EEG signals', *Applied Mathematics and Computation*, Vol. 243, pp. 209–219.
- [9] Ryu, S., Back, S., Lee, S., Seo, H., Park, C., Lee, K. and Kim, D.-S. (2021) 'Pilot study of a single-channel EEG seizure detection algorithm using machine learning', *Child's Nervous System*, Vol. 37, pp. 2239–2244.
- [10] Mursalin, M., Zhang, Y., Chen, Y. and Chawla, N. V. (2017) 'Automated epileptic seizure detection using improved correlation-based feature selection with random forest classifier', *Neurocomputing*, Vol. 241, pp. 204–214.