

Zsh line editor (zle)											
Builtin widgets, emacs binding, vicmd binding, viins binding; € denotes escape key:											
accept-and-hold	€a			execute-last-named-cmd	€z			redisplay	^R	^R	
accept-and-infer-next-history				execute-name-cmd	€x			redo			
accept-and-menu-complete				expand-cmd-path				reset-prompt			
accept-line	^M	^M	^M	expand-history	€!			reverse-menu-complete			
accept-line-and-down-history	^O			expand-or-complete	^I		^I	run-help	€h		
argument-base				expand-or-complete-prefix				self-insert	...		...
backward-char	^B			expand-word	^X*			self-insert-unmeta	€^M		
backward-delete-char	^H			forward-char			^F	send-break	^G		
backward-delete-word				forward-word	€f			set-mark-command	^@		
backward-kill-line				get-line	€g			spell-word	€s		
backward-kill-word	^W			gosmacs-transpose-chars				set-local-history			
backward-word	€b			history-beginning-search-backward				transpose-chars	^T		
beep				history-beginning-search-forward				transpose-words	€t		
beginning-of-buffer-or-history	€<			history-incremental-search-backward	^R			undefined-key			
beginning-of-history				history-incremental-search-forward	^Xr			undo	^_		
beginning-of-line	^A			history-search-backward	^S			universal-argument	€u		
beginning-of-line-hist				history-search-forward	^Xs			up-case-word		^p	
capitalize-word	€C			infer-next-history	€p			up-history		k	up
clear-screen	^L	^L	^L	insert-last-word	€n			up-line-or-history	^p		
complete-word				kill-buffer	^x^n			up-line-or-search			
copy-prev-word	€^_			kill-line	€_			vi-add-eol		A	
copy-prev-shell-word				kill-region	^X^K			vi-add-next		a	
copy-region-as-kill	€w			kill-whole-line	^K			vi-backward-blank-word		B	
delete-char				list-choices	^U			vi-backward-char		h	^H left
delete-char-or-list	^D			list-expand	€d	^d	^d	vi-backward-delete-char		X	^H
delete-word				magic-space	€Xg	^G	^G	vi-backward-kill-word			^W
describe-key-briefly				menu-complete				vi-backward-word		b	
digit-argument	€0..1..9			menu-expand-or-complete				vi-beginning-of-line			
down-case-word	€l			neg-argument	€-			vi-caps-lock-panic			
down-history		^n		overwrite-mode	^X^O			vi-change		c	
down-line-or-history	^n	j	down	pound-insert				vi-change-eol		C	
down-line-or-search				push-input				vi-change-whole-line		S	
emacs-backward-word				push-line				vi-cmd-mode	^XV		€
emacs-forward-word				push-line-or-edit	€q			vi-delete		d	
end-of-buffer-or-history				quoted-insert				vi-delete-char		x	
end-of-history				quote-line	€'			vi-digit-or-beginning-of-line		0	
end-of-line	^E			quote-region	€"			vi-down-line-or-history		+	
end-of-line-hist				recursive-edit				Builtin widgets cont.:			
end-of-list								vi-end-of-line		\$	
exchange-point-and-mark	^X^X							vi-fetch-history		G	
								vi-find-next-char	^X^F	f	
								vi-find-next-char-skip		t	
								vi-find-prev-char		F	

vi-find-prev-char-skip	T		what-cursor-position	^X=	\Mx, \M-x	Set 8 th bit in character
vi-first-non-blank	^		where-is		\Cx, \C-x	Control character e.g. \C-a
vi-forward-blank-word	W		which-command	€?	^x	Control character e.g. ^a (same as ^A)
vi-forward-blank-word-end	E		yank	^y	^?	Delete
vi-forward-char	l	<i>right</i>	yank-pop	€y	\\	Single backslash
vi-forward-word	w					
vi-forward-word-end	e		Special parameters inside user-defined widgets; † indicates readonly:			
vi-goto-column	€ 	 	BUFFER	Entire editing buffer	emacs	Like Emacs editor
vi-goto-mark		.	BUFFERLINES	Number of screen lines for full buffer	viins	Like Vi editor in insert mode
vi-goto-mark-line		.	†CONTEXT	start, cont, select, vared	vicmd	Like Vi editor in command mode
vi-history-search-backward	/		CURSOR	Index of cursor position into \$BUFFER	.safe	Emergency keymap, not modifiable
vi-history-search-forward	?		CUTBUFFER	Last item to be killed		
vi-indent	>		HISTNO	Currently history line being retrieved	Examples of key binding:	
vi-insert	i		†KEYMAP	Currently selected keymap	bindkey '^xt' gosmacs-transpose-chars	
vi-insert-bol	I		†KEYS	Keys typed to invoke current widget	bindkey '\e[2~' overwrite-mode	
vi-join	^X^J	J	killring	Array of previously killed items, can resize	bindkey -M viins '^u' backward-kill-line	
vi-kill-eol	D		†LASTSEARCH	Last search string in interactive search	bindkey -s '^x^z' '\eqsuspend\n'	
vi-kill-line		^U	†LASTWIDGET	Last widget to be executed	autoload -Uz replace-string	
vi-match-bracket	^X^B%		LBUFFER	Part of buffer left of cursor	zle -N replace-string	
vi-open-line-above	O		MARK	Index of mark position into \$BUFFER	bindkey '\er' replace-string	
vi-open-line-below	o		NUMERIC	Numeric argument passed with widget	zle -N replace-string replace-pattern	
vi-oper-swap-case			†PENDING	Number of bytes still to be read	bindkey '\e%' replace-pattern	
vi-pound-insert			†PREBUFFER	Input already read (no longer being edited)	See man zshcontrib for supplied editing functions such as	
vi-put-after	P		PREDISPLAY	Text to display before editable buffer	replace-string.	
vi-put-before	p		POSTDISPLAY	Text to display after editable buffer		
vi-quoted-insert		^V	RBUFFER	Part of buffer starting from cursor		
vi-repeat-change	.		WIDGET	Name of widget being executed		
vi-repeat-find	;		WIDGETFUNC	Name of function implementing \$WIDGET		
vi-repeat-search	N		WIDGETSTYLE	Implementation style of completion widget		
vi-replace	R		Special characters in bindkey strings:			
vi-replace-chars	r		\a	Bell (alarm)		
vi-rev-repeat-find	,		\b	Backspace		
vi-rev-repeat-search	“		\e, \E	Escape		
vi-set-buffer	m		\f	Form feed		
vi-set-mark	s		\n	Newline		
vi-substitute	~		\r	Carriage return		
vi-swap-case	u		\t	Tab (horizontal)		
vi-undo-change	<		\v	Tab (vertical)		
vi-unindent	-		\nnn	Octal character e.g. \081		
vi-up-line-or-history	-		\xnn	Hexadecimal character eg. \x41		
vi-yank	y					
vi-yank-eol	Y					
vi-yank-whole-line						