

Tareax - API REST

No description provided (generated by Swagger Codegen <https://github.com/swagger-api/swagger-codegen>)

More information: <https://helloverb.com>

Contact Info: hello@helloverb.com

Version: v1

All rights reserved

<http://apache.org/licenses/LICENSE-2.0.html>

Access

Methods

[[Jump to Models](#)]

Table of Contents

[ListaEndpoint](#)

- [PUT /tableros/{tableroId}/listas/{listaId}/configurar](#)
- [PUT /tableros/{tableroId}/listas/{listaId}/prerrequisitos](#)
- [POST /tableros/{tableroId}/listas](#)
- [PUT /tableros/{tableroId}/listas/{listaId}/especial](#)
- [DELETE /tableros/{tableroId}/listas/{listaId}](#)
- [GET /tableros/{tableroId}/listas](#)
- [GET /listas/{listaId}](#)
- [PUT /tableros/{tableroId}/listas/{listaId}/renombrar](#)

[PlantillaEndpoint](#)

- [POST /plantillas](#)
- [GET /plantillas/{plantillaId}](#)
- [GET /plantillas](#)

[TableroEndpoint](#)

- [PUT /tableros/{tableroId}/bloquear](#)
- [PUT /tableros/{tableroId}/configurar](#)
- [POST /tableros](#)
- [DELETE /tableros/{tableroId}/bloquear](#)
- [DELETE /tableros/{tableroId}](#)

- [GET /tableros/{tableroId}/tarjetas](#)
- [GET /tableros/{tableroId}/historial](#)
- [GET /tableros](#)
- [GET /tableros/{tableroId}](#)
- [PUT /tableros/{tableroId}/renombrar](#)

TarjetaEndpoint

- [POST /tableros/{tableroId}/listas/{listaId}/tarjetas/{tarjetaId}/completar](#)
- [PUT /tableros/{tableroId}/listas/{listaId}/tarjetas/{tarjetaId}/checklist/{indice}/completar](#)
- [POST /tableros/{tableroId}/listas/{listaId}/tarjetas](#)
- [PUT /tableros/{tableroId}/listas/{listaId}/tarjetas/{tarjetaId}/editar](#)
- [DELETE /tableros/{tableroId}/listas/{listaId}/tarjetas/{tarjetaId}](#)
- [DELETE /tableros/{tableroId}/listas/{listaId}/tarjetas/{tarjetaId}/etiqueta](#)
- [POST /tableros/{tableroId}/listas/{listaId}/tarjetas/{tarjetaId}/etiqueta](#)
- [PUT /tableros/{tableroId}/listas/{listaId}/tarjetas/{tarjetaId}/etiqueta](#)
- [PUT /tableros/{tableroId}/listas/{listaId}/tarjetas/{tarjetaId}/mover](#)
- [GET /tarjetas/{tarjetaId}](#)
- [GET /listas/{listaId}/tarjetas](#)
- [DELETE /tableros/{tableroId}/listas/{listaId}/tarjetas/{tarjetaId}/checklist/{indice}/completar](#)
- [PUT /tableros/{tableroId}/listas/{listaId}/tarjetas/{tarjetaId}/renombrar](#)

UsuarioEndpoint

- [POST /usuarios/{usuarioId}/login](#)
- [GET /usuarios/validar](#)
- [POST /usuarios/{usuarioId}/verificar](#)

ListaEndpoint

PUT /tableros/{tableroId}/listas/{listaId}/configurar

[Up](#)

(configurarLimite)

Path parameters

tableroId (required)

Path Parameter —

listaId (required)

Path Parameter —

Consumes

This API call consumes the following media types via the Content-Type request header:

- application/json

Request body

body [LimiteRequest](#) (required)

Body Parameter —

Request headers

Return type

Object

Example data

Content-Type: application/json

```
{ }
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- */*

Responses

200

OK [Object](#)

PUT /tableros/{tableroId}/listas/{listaId}/prerrequisitos

[Up](#)

(configurarPrerrequisitos)

Path parameters

tableroId (required)

Path Parameter —

listaId (required)

Path Parameter —

Consumes

This API call consumes the following media types via the Content-Type request header:

- application/json

Request body

body [PrerrequisitoRequest](#) (required)

Body Parameter —

Request headers

Return type

Object

Example data

Content-Type: application/json

```
{ }
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- */*

Responses

200

OK [Object](#)

POST /tableros/{tableroId}/listas

[Up](#)

(crear1)

Path parameters

tableroId (required)

Path Parameter —

Consumes

This API call consumes the following media types via the Content-Type request header:

- application/json

Request body

body [CrearListaRequest](#) (required)

Body Parameter —

Request headers

Return type

Object

Example data

Content-Type: application/json

```
{ }
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- */*

Responses

200

OK [Object](#)

PUT /tableros/{tableroId}/listas/{listaId}/especial

[Up](#)

(definirEspecial)

Path parameters

tableroId (required)

Path Parameter —

listaId (required)

Path Parameter —

Request headers

Return type

Object

Example data

Content-Type: application/json

```
{ }
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- */*

Responses

200

OK [Object](#)

DELETE /tableros/{tableroId}/listas/{listaId}

[Up](#)

(eliminar1)

Path parameters

tableroId (required)

Path Parameter —

listaId (required)

Path Parameter —

Request headers

Return type

Object

Example data

Content-Type: application/json

```
{ }
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- */*

Responses

200

OK [Object](#)

GET /tableros/{tableroId}/listas

[Up](#)

(obtener2)

Path parameters

tableroId (required)

Path Parameter —

Request headers

Return type

Object

Example data

Content-Type: application/json

```
{ }
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- */*

Responses

200

OK [Object](#)

GET /listas/{listaId}

[Up](#)

(obtener3)

Path parameters

listaId (required)

Path Parameter —

Request headers

Return type

Object

Example data

Content-Type: application/json

```
{ }
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- */*

Responses

200

OK [Object](#)

PUT /tableros/{tableroId}/listas/{listaId}/renombrar

[Up](#)

(renombrar2)

Path parameters

tableroId (required)

Path Parameter —

listaId (required)

Path Parameter —

Consumes

This API call consumes the following media types via the Content-Type request header:

- application/json

Request body

body [RenombrarRequest](#) (required)

Body Parameter —

Request headers

Return type

Object

Example data

Content-Type: application/json


```
{ }
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- */*

Responses

200

OK [Object](#)

PlantillaEndpoint

POST /plantillas

[Up](#)

(crear3)

Consumes

This API call consumes the following media types via the Content-Type request header:

- application/json

Request body

body [CrearPlantillaRequest](#) (required)

Body Parameter —

Request headers

Return type

Object

Example data

Content-Type: application/json

```
{ }
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- */*

Responses

200

OK [Object](#)

GET /plantillas/{plantillaId}

[Up](#)

(obtenerPorId1)

Path parameters

plantillaId (required)

Path Parameter —

Request headers

Return type

Object

Example data

Content-Type: application/json

```
{ }
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- */*

Responses

200

OK [Object](#)

GET /plantillas

[Up](#)

(obtenerTodas)

Request headers

Return type

Object

Example data

Content-Type: application/json

```
{ }
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- */*

Responses

200

OK [Object](#)

TableroEndpoint

PUT /tableros/{tableroId}/bloquear

[Up](#)

(bloquear)

Path parameters

tableroId (required)

Path Parameter —

Consumes

This API call consumes the following media types via the Content-Type request header:

- application/json

Request body

body [BloqueoRequest](#) (required)

Body Parameter —

Request headers

Return type

Object

Example data

Content-Type: application/json

```
{ }
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- */*

Responses

200

OK [Object](#)

PUT /tableros/{tableroId}/configurar

[Up](#)

(configurar)

Path parameters

tableroId (required)

Path Parameter —

Consumes

This API call consumes the following media types via the Content-Type request header:

- application/json

Request body

body [LimiteRequest](#) (required)

Body Parameter —

Request headers

Return type

Object

Example data

Content-Type: application/json

```
{ }
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- */*

Responses

200

OK [Object](#)

POST /tableros

[Up](#)

(crear)

Consumes

This API call consumes the following media types via the Content-Type request header:

- application/json

Request body

body [CrearTableroRequest](#) (required)

Body Parameter —

Request headers

Return type

Object

Example data

Content-Type: application/json

```
{ }
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- */*

Responses

200

OK [Object](#)

DELETE /tableros/{tableroId}/bloquear

[Up](#)

(desbloquear)

Path parameters

tableroId (required)

Path Parameter —

Request headers

Return type

Object

Example data

Content-Type: application/json

```
{ }
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- */*

Responses

200

OK [Object](#)

DELETE /tableros/{tableroId}

[Up](#)

(eliminar)

Path parameters

tableroId (required)

Path Parameter —

Request headers

Return type

Object

Example data

Content-Type: application/json

```
{ }
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- */*

Responses

200

OK [Object](#)

GET /tableros/{tableroId}/tarjetas

[Up](#)

(filtrarTarjetas)

Path parameters

tableroId (required)

Path Parameter —

Request headers

Query parameters

body (required)

Query Parameter —

Return type

Object

Example data

Content-Type: application/json

```
{ }
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- */*

Responses

200

OK [Object](#)

GET /tableros/{tableroId}/historial

[Up](#)

(mostrarHistorial)

Path parameters

tableroId (required)

Path Parameter —

Request headers

Query parameters

page (optional)

Query Parameter — default: 1 format: int32

tamano (optional)

Query Parameter — default: 20 format: int32

Return type

Object

Example data

Content-Type: application/json

```
{ }
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- */*

Responses

200

OK [Object](#)

GET /tableros

[Up](#)

(obtener1)

Request headers

Query parameters

url (optional)

Query Parameter —

Return type

Object

Example data

Content-Type: application/json

```
{ }
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- */*

Responses

200

OK [Object](#)

GET /tableros/{tableroId}

[Up](#)

(obtenerPorId)

Path parameters

tableroId (required)

Path Parameter —

Request headers

Return type

Object

Example data

Content-Type: application/json

```
{ }
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- */*

Responses

200

OK [Object](#)

PUT /tableros/{tableroId}/renombrar

[Up](#)

(renombrar)

Path parameters

tableroId (required)

Path Parameter —

Consumes

This API call consumes the following media types via the Content-Type request header:

- application/json

Request body

body [RenombrarRequest](#) (required)

Body Parameter —

Request headers

Return type

Object

Example data

Content-Type: application/json

```
{ }
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- */*

Responses

200

OK [Object](#)

TarjetaEndpoint

POST /tableros/{tableroId}/listas/{listaId}/tarjetas/{tarjetaId}/completar

[Up](#)

(completar)

Path parameters

tableroId (required)

Path Parameter —

listaId (required)

Path Parameter —

tarjetaId (required)

Path Parameter —

Request headers

Return type

Object

Example data

Content-Type: application/json

```
{ }
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- */*

Responses

200

OK [Object](#)

PUT /tableros/{tableroId}/listas/{listaId}/tarjetas/{tarjetaId}/checklist/{indice}/completar

[Up](#)

(completarItem)

Path parameters

tableroId (required)

Path Parameter —

listaId (required)

Path Parameter —

tarjetaId (required)

Path Parameter —

indice (required)

Path Parameter — format: int32

Request headers

Return type

Object

Example data

Content-Type: application/json

```
{ }
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- */*

Responses

200

OK [Object](#)

POST /tableros/{tableroId}/listas/{listaId}/tarjetas

[Up](#)

(crear2)

Path parameters

tableroId (required)

Path Parameter —

listaId (required)

Path Parameter —

Consumes

This API call consumes the following media types via the Content-Type request header:

- application/json

Request body

body [CrearTarjetaRequest](#) (required)

Body Parameter —

Request headers

Return type

Object

Example data

Content-Type: application/json

```
{ }
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- */*

Responses

200

OK [Object](#)

PUT /tableros/{tableroId}/listas/{listaId}/tarjetas/{tarjetaId}/editar

[Up](#)

(editar)

Path parameters

tableroId (required)

Path Parameter —

listaId (required)

Path Parameter —

tarjetaId (required)

Path Parameter —

Consumes

This API call consumes the following media types via the Content-Type request header:

- application/json

Request body

body [EditarTarjetaRequest](#) (required)

Body Parameter —

Request headers

Return type

Object

Example data

Content-Type: application/json

```
{ }
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- */*

Responses

200

OK [Object](#)

DELETE /tableros/{tableroId}/listas/{listaId}/tarjetas/{tarjetaId}

[Up](#)

(eliminar2)

Path parameters

tableroId (required)

Path Parameter —

listaId (required)

Path Parameter —

tarjetaId (required)

Path Parameter —

Request headers

Return type

Object

Example data

Content-Type: application/json

```
{ }
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- */*

Responses

200

OK [Object](#)

DELETE /tableros/{tableroId}/listas/{listaId}/tarjetas/{tarjetaId}/etiqueta

[Up](#)

(eliminarEtiqueta)

Path parameters

tableroId (required)

Path Parameter —

listaId (required)

Path Parameter —

tarjetaId (required)

Path Parameter —

Request headers

Query parameters

nombre (required)

Query Parameter —

color (required)

Query Parameter —

Return type

Object

Example data

Content-Type: application/json

```
{ }
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- */*

Responses

200

OK [Object](#)

POST /tableros/{tableroId}/listas/{listaId}/tarjetas/{tarjetaId}/etiqueta

[Up](#)

(etiquetar)

Path parameters

tableroId (required)

Path Parameter —

listaId (required)

Path Parameter —

tarjetaId (required)

Path Parameter —

Consumes

This API call consumes the following media types via the Content-Type request header:

- application/json

Request body

body [CrearEtiquetaRequest](#) (required)

Body Parameter —

Request headers

Return type

Object

Example data

Content-Type: application/json

```
{ }
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- */*

Responses

200

OK [Object](#)

PUT /tableros/{tableroId}/listas/{listaId}/tarjetas/{tarjetaId}/etiqueta

[Up](#)

(modificarEtiqueta)

Path parameters

tableroId (required)

Path Parameter —

listaId (required)

Path Parameter —

tarjetaId (required)

Path Parameter —

Consumes

This API call consumes the following media types via the Content-Type request header:

- application/json

Request body

body [ModificarEtiquetaRequest](#) (required)

Body Parameter —

Request headers

Return type

Object

Example data

Content-Type: application/json

```
{ }
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- */*

Responses

200

OK [Object](#)

PUT /tableros/{tableroId}/listas/{listaId}/tarjetas/{tarjetaId}/mover

[Up](#)

(mover)

Path parameters

tableroId (required)

Path Parameter —

listaId (required)

Path Parameter —

tarjetaId (required)

Path Parameter —

Consumes

This API call consumes the following media types via the Content-Type request header:

- application/json

Request body

body [MoverTarjetaRequest](#) (required)

Body Parameter —

Request headers

Return type

Object

Example data

Content-Type: application/json

```
{ }
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- */*

Responses

200

OK [Object](#)

GET /tarjetas/{tarjetaId}

[Up](#)

(obtener)

Path parameters

tarjetaId (required)

Path Parameter —

Request headers

Return type

Object

Example data

Content-Type: application/json

```
{ }
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- */*

Responses

200

OK [Object](#)

GET /listas/{listaId}/tarjetas

[Up](#)

(obtenerPorLista)

Path parameters

listaId (required)

Path Parameter —

Request headers

Return type

Object

Example data

Content-Type: application/json

```
{ }
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- */*

Responses

200

OK [Object](#)

DELETE /tableros/{tableroId}/listas/{listaId}/tarjetas/{tarjetaId}/checklist/{indice}/completar

[Up](#)

(pendienteItem)

Path parameters

tableroId (required)

Path Parameter —

listaId (required)

Path Parameter —

tarjetaId (required)

Path Parameter —

indice (required)

Path Parameter — format: int32

Request headers

Return type

Object

Example data

Content-Type: application/json

```
{ }
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- */*

Responses

200

OK [Object](#)

PUT /tableros/{tableroId}/listas/{listaId}/tarjetas/{tarjetaId}/renombrar

[Up](#)

(renombrar1)

Path parameters

tableroId (required)

Path Parameter —

listaId (required)

Path Parameter —

tarjetaId (required)

Path Parameter —

Consumes

This API call consumes the following media types via the Content-Type request header:

- application/json

Request body

body [RenombrarRequest](#) (required)

Body Parameter —

Request headers

Return type

Object

Example data

Content-Type: application/json

```
{ }
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- */*

Responses

200

OK [Object](#)

UsuarioEndpoint

POST /usuarios/{usuarioId}/login

[Up](#)

(login)

Path parameters

usuarioId (required)

Path Parameter —

Responses

200

OK

GET /usuarios/validar

[Up](#)

(validarYRenovar)

Request headers

Return type

Object

Example data

Content-Type: application/json

```
{ }
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- */*

Responses

200

OK [Object](#)

POST /usuarios/{usuarioId}/verificar

[Up](#)

(**verificarToken**)

Path parameters

usuarioId (required)

Path Parameter —

Query parameters

codigo (required)

Query Parameter —

Return type

Object

Example data

Content-Type: application/json

```
{ }
```

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- */*

Responses

200

OK [Object](#)

Models

[Jump to [Methods](#)]

Table of Contents

1. [BloqueoRequest](#)
2. [ContenidoTarjetaCmd](#)
3. [CrearEtiquetaRequest](#)
4. [CrearListaRequest](#)
5. [CrearPlantillaRequest](#)
6. [CrearTableroRequest](#)
7. [CrearTarjetaRequest](#)
8. [EditarTarjetaRequest](#)
9. [FiltradoRequest](#)
10. [LimiteRequest](#)
11. [ListaId](#)
12. [ModificarEtiquetaRequest](#)
13. [MoverTarjetaRequest](#)
14. [Plantilla](#)
15. [PlantillaId](#)
16. [PrerrequisitoRequest](#)
17. [RenombrarRequest](#)
18. [TableroId](#)
19. [UsuarioId](#)

BloqueoRequest

[Up](#)

inicio (optional)

[Date](#) format: date-time

fin (optional)

[Date](#) format: date-time

motivo (optional)

[String](#)

ContenidoTarjetaCmd

[Up](#)

tipoContenido (optional)

[String](#)

Enum:

TAREA

CHECKLIST

descripcionTarea (optional)

[String](#)

itemsChecklist (optional)

[array\[String\]](#)

emailUsuario (optional)

[String](#)

CrearEtiquetaRequest

[Up](#)

nombre (optional)

[String](#)

color (optional)

[String](#)

CrearListaRequest

[Up](#)

nombre (optional)

[String](#)

CrearPlantillaRequest

[Up](#)

yaml (optional)

[String](#)

CrearTableroRequest

[Up](#)

nombre (optional)

[String](#)

email (optional)

[*String*](#)

plantillaId (optional)

[*String*](#)

nombrePlantilla (optional)

[*String*](#)

plantillaCreacion (optional)

[*Plantilla*](#)

CrearTarjetaRequest

[Up](#)

nombre (optional)

[*String*](#)

contenido (optional)

[*ContenidoTarjetaCmd*](#)

EditarTarjetaRequest

[Up](#)

cmd (optional)

[*ContenidoTarjetaCmd*](#)

FiltradoRequest

[Up](#)

nombresEtiquetas (optional)

[*array\[String\]*](#)

modo (optional)

[*String*](#)

Enum:

AND

OR

pagina (optional)

[*Integer*](#) format: int32

tamano (optional)

[*Integer*](#) format: int32

LimiteRequest

[Up](#)

limite (optional)
[*Integer*](#) format: int32

ListaId

[Up](#)

id (optional)
[*String*](#)

ModificarEtiquetaRequest

[Up](#)

nombreOld (optional)
[*String*](#)

colorOld (optional)
[*String*](#)

nombreNuevo (optional)
[*String*](#)

colorNuevo (optional)
[*String*](#)

MoverTarjetaRequest

[Up](#)

destino (optional)
[*String*](#)

Plantilla

[Up](#)

identificador (optional)
[*PlantillaId*](#)

nombre (optional)
[*String*](#)

contenidoYaml (optional)
[*String*](#)

PlantillaId

[Up](#)

id (optional)

[*String*](#)

PrerrequisitoRequest

[Up](#)

prerrequisitos (optional)

[*array\[String\]*](#)

RenombrarRequest

[Up](#)

nuevoNombre (optional)

[*String*](#)

TableroId

[Up](#)

id (optional)

[*String*](#)

UsuarioId

[Up](#)

correo (optional)

[*String*](#)