# LEARN CODING

ale66

github.com/ale66/learn-coding

# 2-DIMENSIONAL LISTS (AND A CRITIQUE)

# SO FAR

While they admit arbitrary members, lists are best understood as iterables of homogeneous values



# NESTED LISTS

Represent multi-dimensional data

The meaning of data and the objective of the code guide the organization in lists and sublists

Example: weekend temperatures in Naples (from Thur. to Sun.)

```
1  my2Dlist = [[18, 22, 20, 26], [26, 27, 28, 21], [18, 16, 21, 20]]
```

as with lists of strings, by simple nesting of indices we can access specific data points

Q: Temperature on the first Thursday of October?

```
1  print(my2Dlist[0][0])
```

Visualise it on Pythontutor

```
1  my2Dlist = [[18, 22, 20, 26], [26, 27, 28, 21], [18, 16, 21, 20]]
```

Q: Average temperature on Thursday in October?

- use an accumulator variable
- go along the list, pick up the first item of each list
- accumulate it
- print the computed average (if it exists: what if it's too early to tell?)

```
accumulator = 0
count = 0

for weekend in my2Dlist:
  accumulator += weekend[0]
  count += 1

if count > 0:
  average_temp_thursday = accumulator / count
else:
  # avoid 0 as it is a valid average temp.
  average_temp_thursday = NaN
```

# Visualise it on Pythontutor

# WORK WITH NESTED LISTS

Textual data sets may also be organized in 2-d lists

```
my_writers = [
                ['Dickens', 1812],
                ['King', 1947],
                ['J.K. Rowling', 1965],
                ['Christie', 1890]
]

for row in my_writers:
        print(row)
```

Here a clear semantic structure remains *latent* within the Python variables

## Print authors only:

```
1  for row in my_writers:
2    print(row[0])
```

## Print authors and they their year of birth?

```
1  for row in my_writers:
2    for element in row:
3        print(element)
```

## Spin it up on Pythontutor

# OBSERVATIONS

To extract the needed data we need to know something about their logical organization: the data structure

- each element is a weekend, starting Thursday

A fixed structure is required for instructions to work:

- each pair is author followed by year

A more flexible data structure is needed

# DICTIONARIES

# THE NON-LIST

An unsorted bag of values, each with its own label, called key.

```
1  my_data = {'author': 'Agatha Christie',
2             'nickname': 'Mary Westmacott',
3             'year_of_birth': 1890
4           }
```



# PROPERTIES

A dictionary is a collection of `key:value` pairs that is

- unordered
- changeable, and
- indexed

**Dictionaries are Python most powerful data structure**

# EXTENSIBILITY

## The more we have, the more we can put

```
my_writers = [
  {'author':'Dickens', 'year_of_birth':1812},
  {'author':'King', 'year_of_birth':1947},
  {'author':'J.K. Rowling', 'year_of_birth':1965},
  {'author':'Agatha Christie', 'nickname':'Mary Westmacott', 'year_of_birth':1890}
]
```

# ACCESSING ITEMS

```python
my_dict = {'author': 'Agatha Christie',
           'nickname': 'Mary Westmacott',
           'year_of_birth': 1890
}

print(my_dict['author'])
```

```python
NOW = 2024

delta = NOW - my_dict['year_of_birth']

print(f{{my_dict['author']} was born {delta} years ago.})
```

# AMENDING VALUES

```
my_dict['year_of_birth'] = 2019

print(my_dict['year_of_birth'])
```

```
#
king = my_writers[1]

print(king['author'])

king['author'] = 'Stephen King'
```

We have more information but `my_writers` is unchanged

# COMBINING INDICES

```
1  my_writers[1]['author'] = 'Stephen King'
2
3  print(my_writers)
4
5  [{'author':'Dickens', 'year_of_birth':1812},
6   {'author':'Stephen King', 'year_of_birth':1947},
7   {'author':'J.K. Rowling', 'year_of_birth':1965},
8   {'author':'Agatha Christie', 'nickname':'Mary Westmacott', 'year_of_birth':1890}]
```

# ITERATION

As the data structure is completely arbitrary, simple indexing (`i=0,1, ...`) does not work anymore.

A lazy iterable, similar to `range`, will serve the `key:value` pairs on request

```
1  # always key first
2  for key, value in my_dict.items():
3    print(key, value)
```

```
1  author Agatha Christie
2  nickname Mary Westmacott
3  year_of_birth 1890
```

# THE `key` AND `value` VARIABLE NAMES


```
1  for key in my_dict.items():
2    print(key)
```

```
1  author
2  nickname
3  year_of_birth
```

```
1  for value in my_dict.items():
2    print(key)
```

```
1  Agatha Christie
2  Mary Westmacott
3  1890
```

# LISTS VS DICTIONARIES




github.com/ale66/learn-coding

# GROW A LIST

```
1  my_list = []
2
3  my_list.append(10)
4
5  my_list.append(20)
6
7  print(alist)
8
9  [10, 20]
```

Direct access is always possible:

```
1  print(my_list[-1])
2
3  20
```

# GROW A DICTIONARY


```
1  my_dict = {}
2
3  my_dict['name'] = 'Tom'
4
5  my_dict['age'] = 35
6
7  print(my_dict)
```

```
1  {'name':'Tom', 'age':35}
```

```
1  print(my_dict['name'])
2
3  Tom
```

Disadvantage: dictionaries are inherently unordered

# ONE KEY, MANY VALUES




```
my_python = {'Student_ID':['S1','S2'],
             'Student_Name':['John', 'Mary']
}
```

# RECAP: COMMON OPERATIONS

```
1  # create an empty dictionary
2  my_dict = {}
3
4  # create a new dict with 3 items
5  my_dict = {'one':1, 'two':2, 'three':3}
6
7  # access an element
8  print(my_dict['two'])
```

## Data updates:

```
1  # add an entry
2  my_dict['four'] = 4
3
4  # change an entry
5  my_dict['one'] = 'uno'
6
7  # count items
8  howmany = len(my_dict)
```

# keys AND values


```
1 # iterate over keys
2 for item in my_dict.keys():
3   print (item)
4
5 # iterate over values
6 for item in my_dict.values():
7   print(item)
```

## Inspect the data structure:

```
1 # list out the keys
2 my_dict.keys()
3
4 # list out the values
5 my_dict.values()
```

# QUIZ!

# Create a dictionary out of the following data:




| | A | B | C |
|---|---|---|---|
| 1 | Name | Age | City |
| 2 | Andrea | 32 | London |
| 3 | Tom | 35 | Brighton |
| 4 | | | |




# Spin up VS Code and create a quick notebook