



Lecture 10: Architecting for the eVoter

Jan Martijn van der Werf, Nishant Saurabh

Imagine the following situation


Build me an 'eVoting system'!

What will you build?

How will you start?

Gather requirements?

System design?




User stories:

- As the organiser, we want to hold referenda, so that we know the opinion of our participant
- As a participant I want to vote anonymously, so that my privacy is respected

Credit: [MIKKO LEMOLA Getty Images](#)




System design





System design




New customer:

- European parliament wants to use it for elections and referenda in the whole of the EU.
- Extra concern: Handle 150 Million voters in one day




Viewpoint catalog



Where do we start?




System design





Many different qualities to look into...





Viewpoints and Quality Attributes



- Put the important QAs on the columns
- For each cell:


What is the importance of the QA on the view?

How influence the view and QA each other?


	Security	Availability	Scalability	Reliability
Context	A	A, H.		
Functional	A B C D	A, H		
Information	E, F			
Concurrency	G.	G.		
Development				
Deployment				
Operational				

Addressing concerns with quality scenarios

Environment




Is this a view?




Functional Architecture.

Annotations: "points of contact" with the different perspectives.



Context


- Use case diagram



Only two real use cases:

- Holding a referendum,
- Casting your ballot for a referendum.

- External Systems Diagram



Only external system: authorization system, like dutch DIGID


A: 150 M voters in 15h is
15M voters per hour is
4,16k voters per second.

Thus, we need an SLA with the Auth service for >4.16k connections per second.

Information views

Scenarios

As overlays on the functional Architecture



A: Casting a ballot:

A: Casting a ballot:

log in, if succeeded,
send referendum details
directly to user.
User then casts vote.

Alternative path:

After ④ the log in failed,
messaged to student.

B Holding a referendum

Result can only be retrieved
After referendum is over!

Decision: The actual ballots are stored inside
VoteManagement, to ensure security.

In the context of: storing ballot information
facing security

We decided to

store the ballot information
inside VoteManagement

And not

store the ballot information
inside ResultManagement


To achieve

reliable referenda, where it is
impossible to view results
while the referendum is running

Accepting

The overhead of calculating the
results after the referendum is
over


Data view





Constraint: Each participant can vote at most once for a referendum.

However this model is potentially unsafe, as relation "casts" stores privacy-sensitive data.




Now, we know when somebody voted ("ballot"), but we do not have a connection with the actual value.

Decision: more complex data model for privacy.


In the context of	storing data
facing	Privacy
We decided to	Use datamodel ①
And not	datamodel ②
To achieve	Anonymity of the voting results
Accepting	the complexity involved to ensure that the data remains consistent (e.g. that #ballot equals #votes).

[Note that another consequence of this decision is restoring faults: what if #ballots \neq #votes]

Process view.



Deployment view



(A) Load balancer decides which node a participant is directed to. This node takes the complete vote-process of that participant.

(B) Referendum populates the load balancer to be able to distribute participants over VoteNodes

(C) Referendum sends a notification which referendum is open

- ③ Referendum sends a notification which referendum is open
Only retrieves data after the deadline of the referendum
- ④ Unknown protocol, to investigate

Implicit decision

In the context of

Facing

We decided to

And not

Accepting

the eVoter application

functionality

Go for a distributed (virtual) server architecture

- "Paper supporting technology
- Blockchain
- ...

that the system cannot be used for elections, as the system does not have any means for trust and reliability (i.e., it does not allow recounts)