

# Práctica: 12-3

Agustín Alejandro Mota Hinojosa

## Inténtelo/Resuélvalo

1. Respuesta: Cuando no se tiene un valor en específico y se quiere insertar un valor por defecto.
2. Respuesta inciso c:

```
insert into copy_f_promotional_menus
(code,name,start_date,end_date,give_away)
values
(120,'New Customer',default,to_date('01-Jun-2005','DD-MM-YYYY'),'cupon del 10% de descuento');
```

3. Respuestas:

- Respuesta inciso b:

```
create table manager_copy_d_cds
as (select * from d_cds);
```

- Respuesta inciso c:

```
insert into copy_d_cds
(cd_number,title,producer,year)
values
(20, 'Hello World Here I Am', 'Middle Earth Records', '1998');
```

- Respuesta inciso d:

```
merge into manager_copy_d_cds c using d_cds o
on (c.cd_number = o.cd_number)
when matched then update
set
    c.title = o.title,
    c.year = o.year
when not matched then insert
values (o.cd_number,o.title,o.producer,o.year);
```

4. Respuesta:

```
insert all
when (salary > 2000) then
into special_sal
values (employee_id,hire_date,salary)
into sal_history
values (employee_id,hire_date,salary)
into mgr_history
values (employee_id,manager_id,salary)
select employee_id,hire_date,salary,manager_id
from employees;
```