

Poool Game: Concurrent Implementation Report

Assignment 01 - PCD Course

Academic Year 2025-2026

Abstract

This report presents a concurrent implementation of the Poool Game, a 2D board game where two players (human and bot) control balls to push smaller balls into holes. The document provides a detailed analysis of concurrency challenges, design architecture, behavioral specifications using Petri Nets, performance evaluation, and formal verification using JPF (Java Path Finder). The concurrent implementation demonstrates significant improvements over a sequential baseline while effectively exploiting available processor cores through multithreading and task-based approaches.

Contents

1	Problem Analysis	3
1.1	Problem Description	3
1.2	Concurrency-Related Challenges	3
1.2.1	Computational Complexity	3
1.2.2	Temporal Constraints	3
1.2.3	Synchronization Requirements	3
1.2.4	Data Races and Race Conditions	4
1.3	Task-based Related Challenges	4
1.3.1	Computational Complexity	4
1.3.2	Temporal Constraints	5
1.3.3	Synchronization Requirements	6
2	Design and Architecture	7
2.1	Architectural Overview for Multithreading	7
2.1.1	Thread Model	7
2.1.2	Parallel Physics Pipeline	9
2.1.3	Synchronization Mechanisms	10
2.1.4	MVC and Multithreading Interaction	11
2.2	Architectural Overview for Task-Based Approach	12
2.2.1	Component Descriptions	12
2.3	Synchronization Strategy	17
2.3.1	Barrier Synchronization via invokeAll()	17
2.3.2	Fine-Grained Ball Locking in Collision Detection	17
2.3.3	ConcurrentHashMap for Shared State	18
2.3.4	Exception Handling and Reliability	18
2.3.5	Memory Visibility and Happens-Before Guarantees	18

3	Behavior Specification: Petri Nets	19
3.1	High-Level Game Flow Net Task-based	19
4	Performance Evaluation	20
4.1	Experimental Setup	20
4.1.1	Test Configurations	20
4.1.2	Performance Metrics	20
4.2	Expected Performance Improvements	20
4.2.1	Sequential Baseline Issues	20
4.2.2	Concurrent Improvements	21
4.2.3	Task-based Improvements	21
5	Formal Verification with JPF	21
5.1	Java Path Finder Integration	21
5.1.1	JPF Configuration	21
5.2	Safety Properties Verified	22
5.2.1	1. Mutual Exclusion (No Data Races)	22
5.2.2	2. Deadlock Freedom	22
5.2.3	3. Liveness (Game Termination)	22
5.3	Race Condition Detection	23
5.3.1	Synchronized Field Accesses	23
5.3.2	Temporal Assertions	23
5.4	Model Checking Results	23
5.4.1	Test Configuration: MainJPF	23

1 Problem Analysis

1.1 Problem Description

The Pool Game is a two-player billiard-like game on a 2D board with the following characteristics:

- **Dynamic Objects:** Multiple balls (typically ranging from 2 to 4500) moving and interacting on the board
- **Physics Simulation:** Elastic collisions, friction forces, and momentum transfer between bodies
- **Players:** Two players (human controlled via keyboard, bot controlled autonomously) with scoring systems
- **Game Objective:** Insert small balls into holes at board corners; winner is determined by score or by eliminating opponent's ball

1.2 Concurrency-Related Challenges

1.2.1 Computational Complexity

- **Collision Detection:**
- **Physics Updates:**
- **Rendering Overhead:**
- **Scalability Issue:** Massive board configurations (4500 balls) demonstrate poor frame rates (< 20 fps)

1.2.2 Temporal Constraints

- Main game loop must maintain consistent frame timing
- Asynchronous user input (keyboard) must be always responsive
- Bot decisions occur independently of frame timing
- Rendering cannot block physics computation indefinitely

1.2.3 Synchronization Requirements

- Game state must remain consistent across multiple concurrent accesses
- Player inputs must be atomically integrated into game state
- Collision detection results determine score updates
- Rendering must not interfere with state modifications

1.2.4 Data Races and Race Conditions

Without proper synchronization, the following race conditions can occur:

- **View Model Corruption:** Concurrent modifications during rendering
- **Score Inconsistency:** Multiple threads incrementing scores non-atomically
- **Ball State Inconsistency:** Position and velocity updated concurrently
- **Collision Detection Errors:** Detecting collisions while positions change

1.3 Task-based Related Challenges

The task-based concurrent implementation using the Executor Framework introduces a different set of challenges compared to the thread-per-entity model. The Pool implementation uses work-stealing task decomposition via `WorkerPool` to parallelize physics updates and collision detection.

1.3.1 Computational Complexity

Task-based parallelism in the Pool implementation must address several complexity-related challenges:

- **Task Granularity Trade-off:**
 - Fine-grained tasks (small chunk size) improve load balancing but increase task creation and scheduling overhead
 - In `WorkerPool`, each task updates balls in range $[i, i + \text{chunkSize})$, where chunk size is computed as $\text{chunkSize} = \max(1, n/k)$ with $k = 2 \cdot \text{numProcessors}$
- **Collision Detection Complexity:**
 - `CollisionTask` must verify all pairs (i, j) with $i < j$ without duplication
 - Naive task decomposition (dividing range $[0, n)$) would create $O(n^2)$ pair computations
 - Current implementation partitions the range $[i_0, i_1)$ and checks each task's range against *all* other balls: $\sum_{i=i_0}^{i_1} (n - i - 1)$ comparisons per task
 - Actual complexity per task is $O((i_1 - i_0) \cdot n)$, not $O((i_1 - i_0)^2)$
- **Memory Bandwidth Saturation:**
 - Task-based approach requires all workers to read shared Ball objects' position/velocity data
 - With k cores simultaneously accessing the same memory region, cache line contention increases
 - `ConcurrentHashMap` operations on `lastTouchedBy` introduce additional memory traffic
- **Synchronization Overhead in Collision Detection:**

```
1   synchronized (first) {  
2       synchronized (second) {  
3           // Atomic collision resolution  
4           Ball.resolveCollision(a, b);  
5       }  
6   }
```

Listing 1: Ordered Lock Acquisition

- Each collision check acquires locks on two Ball objects using `synchronized(first)` then `synchronized(second)`
- Lock ordering (by `System.identityHashCode()`) prevents deadlock but adds comparison overhead
- If two tasks try to resolve the same collision pair with different order, one will block the other

1.3.2 Temporal Constraints

Task-based parallelism introduces timing-related constraints that differ from the thread-per-entity model:

- **Barrier Synchronization Latency:**

- In `WorkerPool`, `PlayerCollisionTask`, `parallelBallUpdate()` and `parallelCollisionDe` use `invokeAll()`, which is a synchronization barrier
- All tasks must complete before control returns to the `GameLoop`
- Frame time = $\max(\text{task duration}) + \text{overhead}$

- **Task Queue Delay:**

- Created tasks are submitted to the `ExecutorService` queue
- If all workers are busy, new tasks wait in queue, delaying their execution
- With a fixed thread pool of size k , tasks may experience queueing delay proportional to queue depth
- This adds non-deterministic latency to each game frame

- **Future.get() Blocking Behavior:**

- The main `GameLoop` thread calls `f.get()` (code in class `WorkerPool`) on all futures from `invokeAll()`
- This is a blocking operation—the `GameLoop` cannot proceed until *all* tasks complete
- Any uncaught exception in a task will be re-thrown at `get()`, potentially crashing the loop

1.3.3 Synchronization Requirements

Task-based parallelism requires careful synchronization to ensure memory consistency and avoid data races:

- **ConcurrentHashMap for lastTouchedBy:**

- Multiple `CollisionTask` instances concurrently update `lastTouchedBy` map via `put()` calls
- Using a non-concurrent map would cause data races
- `ConcurrentHashMap` uses bucket-level locking (segment locking), reducing contention vs. a single global lock
- However, repeated `put()` calls on the same `Ball` key still incur synchronization overhead

- **Read-Write Visibility:**

- After `invokeAll().get()`, all field writes in tasks are visible to the main `GameLoop` (happens-before guarantee)
- The Java Memory Model ensures that synchronization actions (lock acquire/release) create memory barriers
- Without these barriers, updates to `Ball.vel` and `Ball.pos` made by one task might not be visible to the next phase

- **Task Isolation:**

- `BallUpdateTask` accesses `board` (the `Board` object) to query boundary constraints
- This creates a shared dependency: if `Board` is modified during task execution, physics updates may read stale boundary data
- Current implementation assumes `Board` state (bounds, player positions) is immutable during a phase
- If asynchronous modifications occur (e.g., player ball movement), visibility must be explicitly synchronized

- **Exception Handling and Task Failure:**

- If a task throws an unchecked exception, `f.get()` will re-throw it via `ExecutionException`
- The `GameLoop` must handle `InterruptedException` (task thread interrupted) and `ExecutionException` (task computation failed)
- Without proper handling, the entire game loop may crash
- Current implementation in `GameLoop.run()` catches both exceptions and breaks the loop gracefully

2 Design and Architecture

2.1 Architectural Overview for Multithreading

The project is structured following the **Model-View-Controller (MVC)** pattern, with a strict separation of responsibilities across three packages: `pcd.assignment01.model`, `pcd.assignment01.view`, and `pcd.assignment01.controller`.

- **Model:** The model package contains all domain state and physics logic, with no knowledge of rendering or threading policy. The central class is `Board`, which owns the list of `Ball` objects, the two player balls, the board boundaries, the scores, and the game-over flag.

`updatePlayers()`, `resolveBallCollision()`, `resolvePlayerCollisions()`, and `checkHolesAndGameOver()` are the only methods through which the controller modifies the model state.

- **View:** The view package contains `View`, `ViewFrame`, and `ViewModel`. The view never reads directly from `Board`: it reads exclusively from `ViewModel`, a thread-safe snapshot object whose fields are updated by the controller once per tick via `update(Board, int)`. This decoupling ensures that the Swing Event Dispatch Thread (EDT) always paints a consistent, fully-populated snapshot without ever competing with the physics threads for `Board`'s intrinsic lock.

`ViewModel` stores `BallViewInfo` records (position and radius) for all small balls and for each player, the current scores, the FPS counter, and the game-over message. The game-over message is written only once, through `setGameOverMessage(String)`, called by the controller at the end of the game; it is never written during normal tick updates, avoiding a race between physics threads and the EDT.

`RenderSynch` provides a generation counter that lets the update thread block until the EDT has completed the current repaint, preventing frame tearing without busy-waiting.

- **Controller:** The controller package contains `GameController`, `BotController`, `InputHandler`, and `WorkerThread`.

`GameController` is the orchestrator: it owns the update loop thread, the worker pool, both `CyclicBarrier` instances, and the `BotController`. It is the only component that calls physics methods on `Board` in the correct sequential order after the parallel phases have completed.

`BotController` encapsulates the autonomous player (player 2) logic in its own thread, waiting on a private monitor until the game physics signal that the ball is still enough to act.

`InputHandler` translates keyboard events from the EDT into `board.kickPlayer1()` calls, with an early-exit guard on `isGameOver()`. It is registered on the `View` inside `SwingUtilities.invokeLater`, ensuring registration happens on the EDT.

2.1.1 Thread Model

The application runs five categories of threads simultaneously during a game:




Figure 1: High-Level Game Flow Petri Net

1. **Main thread:** bootstraps the model and schedules the Swing initialization on the EDT via `SwingUtilities.invokeLater`. It exits immediately after.
2. **Event Dispatch Thread (EDT):** the standard Swing thread. It handles key events (forwarded by `InputHandler`) and executes repaints triggered by `panel.repaint()`. It never touches `Board` directly: key events call `board.kickPlayer1()`, which is `synchronized`, and repaints read only from `ViewModel`.
3. **UpdateThread:** a single daemon thread owned by `GameController`. It drives the game loop: it advances the physics pipeline each tick, signals `BotController`, copies state into `ViewModel`, and calls `view.render()`. It also participates in both `CyclicBarriers` as the $(N + 1)$ -th party, allowing it to perform the sequential post-barrier phases without additional synchronization.
4. **WorkerThread-0 ... WorkerThread-N:** a pool of $N = \text{availableProcessors}() + 1$ persistent daemon threads, created once at startup and never recreated. Each worker waits on its private `tickMonitor` until `GameController` calls `startTick()`, then executes phase 1 (positions) and phase 2 (ball-ball collisions) before waiting again for the next tick.
5. **BotThread:** a single daemon thread owned by `BotController`. It waits on a private `botMonitor` until `GameController` signals that player 2 is still, then applies a random kick impulse subject to a 2-second cooldown.

All threads except the main thread are daemon threads, so the JVM exits cleanly when the window is closed.

2.1.2 Parallel Physics Pipeline

The physics update for each game tick is divided into five phases, two of which execute in parallel across the worker pool.

1. **Player update (sequential):** Before the parallel work begins, `GameController` calls `board.updatePlayers(dt)`, which advances the positions of the two heavy player balls. This is sequential because (a) there are only two such balls, and (b) the workers' collision phase reads player state indirectly via `resolvePlayerCollisions()`, which runs after the barriers. Keeping player updates sequential avoids any contention.
2. **Position update (parallel):** The list of small balls is divided into N contiguous, disjoint partitions using a balanced split (each partition differs in size by at most one element). Each `WorkerThread` receives its partition and calls `ball.updateState(dt)` on every ball it owns. Because the partitions are disjoint, no two workers write to the same `Ball` object during this phase, and no locking is required.

After finishing, each worker calls `barrierPositions.await()`. The `UpdateThread` also calls `barrierPositions.await()` as the $(N+1)$ -th party. The barrier scatters all threads into phase 2 only once every worker (and the controller) has finished phase 1, guaranteeing that all positions are fully updated before any collision is resolved.

3. **Ball-ball collision resolution (parallel):** Each worker resolves collisions between its own balls and all balls with a higher index in the global `allBalls` list. Formally, worker i owns balls with indices $[start_i, start_i + |partition_i|)$ and processes pairs (a, b) where $idx(a) < idx(b)$. This scheme ensures that each pair is processed exactly once across all workers, eliminating the $O(n^2)$ duplication that would arise from a naive per-worker full scan.

Concurrent access to the same `Ball` object by different workers is possible at partition boundaries. To prevent data races, each worker acquires two **synchronized** locks — one on each ball — before calling `board.resolveBallCollision()`. The locks are always acquired in index order (lower index first), which is the canonical lock-ordering protocol that eliminates the possibility of deadlock: no cycle can form in the lock-dependency graph because the ordering is strict and total.

The index-based ordering also replaces the earlier use of `System.identityHashCode()` as the canonical key, which was unsafe because two distinct objects can share the same identity hash code, breaking the strict total order required for deadlock freedom.

After finishing, each worker calls `barrierCollisions.await()`, and the `UpdateThread` does the same. The barrier guarantees that all ball-ball collisions are fully resolved before the sequential phases begin.

4. **Player collision resolution (sequential):** `GameController` calls `board.resolvePlayerCollisions()`, which is **synchronized** on `Board`. This method resolves collisions between each player and every small ball, and between the two players themselves. It also updates the `lastTouchedBy` map, which records the last

player to touch each small ball and is used for scoring. This phase is sequential because both player objects are shared across all potential pairs, making fine-grained locking impractical.

5. **Hole detection and game-over (sequential):** `GameController` calls `board.checkHolesAndGameOver()`, which is also synchronized on `Board`. It checks whether any ball or player has entered a hole, removes sunk balls from the list, increments scores using `lastTouchedBy`, and sets `isGameOver` if appropriate. This phase is sequential because it mutates the shared `balls` list and the scoring state atomically.

2.1.3 Synchronization Mechanisms

- **CyclicBarrier:** The `CyclicBarrier` (in package `pcd.assignment01.util`) is implemented from scratch using Java's built-in monitor protocol (`synchronized`, `wait()`, `notifyAll()`). It maintains three fields: `parties` (the total number of threads that must call `await()` before the barrier fires), `count` (the number of threads still outstanding), and `generation` (an integer that increments on each firing and is used as the condition variable to distinguish the current cycle from the next one, guarding against spurious wakeups).

When the last thread arrives (`count == 0`), it resets `count` to `parties`, increments `generation`, and calls `notifyAll()`. All waiting threads check `myGeneration == generation` as their loop condition: once the generation advances, they know the barrier has fired and they exit the wait.

The barrier also maintains a `broken` flag. If any waiting thread is interrupted, it sets `broken = true` and calls `notifyAll()`, which causes every other waiting thread to wake up and throw `InterruptedException`. This prevents the pathological scenario where a single interrupted thread leaves `count` permanently non-zero, causing all other threads to block forever. The `broken` flag is cleared when the last thread successfully fires the barrier for the next generation.

Two instances of `CyclicBarrier` are created per game, each with `parties = N + 1` (one per worker plus the `UpdateThread`): `barrierPositions` separates phase 1 from phase 2, and `barrierCollisions` separates phase 2 from the sequential phases 3 and 4.

- **Per-ball locking and deadlock prevention:** During phase 2, each worker acquires `synchronized` locks on two `Ball` objects before calling `Board.resolveBallCollision()`. To prevent deadlock, locks are always acquired in ascending index order (the index of the ball in the shared `allBalls` snapshot). Because this order is a strict total order and is respected by all workers, no circular wait can occur: a thread holding `lock(ball[i])` and waiting for `lock(ball[j])` with $i < j$ will never be blocked by another thread holding `lock(ball[j])` and waiting for `lock(ball[i])`.
- **ConcurrentHashMap for lastTouchedBy:** The `lastTouchedBy` map is accessed from two different contexts: from `WorkerThreads` during phase 2 (to remove entries for colliding balls) and from the `UpdateThread` during phases 3 and 4 under the `Board` lock (to update and query entries). Using a `ConcurrentHashMap` makes individual operations on the map thread-safe without requiring a `synchronized(this)`

block inside `resolveBallCollision()`. This eliminates a potential deadlock that would arise from the lock ordering `synchronized(ball) → synchronized(board)`, which could interleave incorrectly with `synchronized(board)` held by `resolvePlayerCollisions()`.

- **BotController monitor:** The `BotController` uses a private `Object botMonitor` as a condition variable. The `BotThread` waits on this monitor inside a guarded loop that checks both `running` and `board.isPlayer2Still()`. The `UpdateThread` calls `botController.signal()` once per tick; if player 2 is still, `signal()` calls `notifyAll()` on the monitor. The `stop()` method calls `notifyAll()` unconditionally, ensuring the `BotThread` is always unblocked on shutdown regardless of the ball's current velocity.
- **ViewModel snapshot and thread safety:** All public methods of `ViewModel` are `synchronized` on the `ViewModel` instance. The `UpdateThread` calls `update()` once per tick, which replaces the internal collections with fresh copies of the model state. The EDT calls getters (`getBalls()`, `getPlayer1()`, etc.) during repaints. Because `update()` returns deep copies (e.g. `new ArrayList<>(balls)`) and all getters return copies as well, the EDT never holds a reference to an object being mutated by the physics threads.

2.1.4 MVC and Multithreading Interaction

The interaction between the MVC layers in the presence of multiple threads is governed by three invariants:

1. **The Model is only mutated by the controller.** The EDT never calls any mutating method on `Board` except `kickPlayer1()`, which is `synchronized`. The `BotThread` calls only `kickPlayer2()`, also `synchronized`. All physics mutations happen exclusively within the sequential and parallel phases orchestrated by `GameController`.
2. **The View never reads the Model directly.** `ViewFrame` and its inner `VisualiserPanel` read exclusively from `ViewModel`. The snapshot is written once per tick by the `UpdateThread` after all physics phases are complete, so the view always paints a consistent state that reflects a completed tick.
3. **Game-over handling is atomic with respect to rendering.** When `checkHolesAndGameOver()` sets `isGameOver = true`, the `UpdateThread` detects this before calling `viewModel.update()` or `view.render()`. It calls `handleGameOver()`, which writes the winner message to `ViewModel` via `setGameOverMessage()`, and then renders one final frame. This ensures the game-over overlay is shown on a frame that already reflects the final physical state, with no intermediate partially-updated frame visible to the player.

Figure 2 summarises the thread interactions and synchronization points for a single game tick.




Figure 2: Thread interactions and synchronization points during a single game tick.

2.2 Architectural Overview for Task-Based Approach

The task-based concurrent implementation differs fundamentally from the thread-per-entity model. Rather than creating persistent threads for each game component, this approach uses the **Executor Framework** with a fixed-size thread pool to parallelize computation-heavy phases of the game loop. We used **Map-Reduce** algorithms, the architecture implements a Master/Worker pattern where the **GameLoop** acts as the master coordinator. It delegates tasks to a **WorkerPool** abstraction which, knowing the data space topology in advance, splits the workload into smaller, independent chunks (*map phase*). These chunks are then efficiently computed in parallel by the underlying **ExecutorService**.

2.2.1 Component Descriptions

The task-based architecture consists of the following key components:

GameLoop (Master/Orchestrator Thread)

The **GameLoop** extends **Thread** and serves as the main control flow:




Figure 3: UML class diagram

- **Role:** Central orchestrator managing game state, input handling, and task delegation
- **Responsibilities:**
 - Maintains the main game loop (`while !board.isGameOver()`)
 - Manages non-blocking input via `BlockingQueue<V2d> inputQueue`
 - Delegates parallelizable phases to `WorkerPool`
 - Executes sequential phase (player/hole collisions) exclusively
 - Handles rendering synchronization and frame rate
 - Catches `ExecutionException` and `InterruptedException` from worker tasks
- **Key Code Pattern:**

```

1 while (!board.isGameOver()) {
2     V2d impulse = inputQueue.poll(); // Non-blocking input
3
4     // Phase 1: Parallel physics
5     workerPool.parallelBallUpdate(board.getBalls(), elapsed,
6                                   board);
7
8     // Sequential player logic
9     if (board.getPlayer1() != null)
10         board.getPlayer1().updateState(elapsed, board);
11
12     // Phase 2: Parallel collision detection
13     workerPool.parallelCollisionDetection(board.getBalls(),
14                                           board.getLastTouchedBy());

```

```
14
15     // Phase 3: Parallel player updates
16     workerPool.parallelPlayerCollision();
17
18     board.checkHolesAndEndGame();
19
20     // Render
21     viewModel.update(board, fps);
22     view.render();
23 }
```

Listing 2: GameLoop Main Loop Structure

WorkerPool (Task Coordinator Abstraction)

The WorkerPool encapsulates all ExecutorService framework details from the GameLoop:

- **Role:** Hides complexity of task scheduling, execution, and synchronization
- **Internal Structure:**
 - ExecutorService executor: Fixed thread pool with size $k = 2 \times \text{availableProcessors}$
 - Three public methods: parallelBallUpdate(), parallelCollisionDetection(), and parallelPlayerCollision()
 - All use invokeAll() for barrier synchronization
- **Key Guarantee:** The GameLoop does not import java.util.concurrent.*, maintaining clean separation of concerns
- **Exception Propagation:** Exceptions in tasks are bundled into ExecutionException and re-thrown at f.get()

BallUpdateTask (Parallel Worker)

Implements Callable<Void> to update a range of balls' physics state:

- **Input Parameters:**
 - List<Ball> balls: Shared reference to all balls
 - int from, int to: Range $[from, to)$ of balls this task processes
 - long dt: Elapsed time since last frame
 - Board board: Context for boundary constraints
- **Computation:**

```
1 public Void call() {
2     for (int i = from; i < to; i++) {
3         balls.get(i).updateState(dt, board);
4     }
5     return null;
6 }
```

Listing 3: BallUpdateTask Execution

- **Synchronization:** No locks required; each task reads from distinct list indices and modifies only the Ball objects at those indices. The Board's boundary data is assumed immutable during execution.

CollisionTask (Parallel Worker)

Implements `Callable<Void>` to resolve pairwise ball collisions:

- **Input Parameters:**
 - `List<Ball> balls`: Shared reference to all balls
 - `int from, int to`: Range $[from, to)$ of "first" balls in pairs
 - `ConcurrentHashMap<Ball, Integer> lastTouchedBy`: Shared map of ball-to-player touches
- **Pair Enumeration:** For each ball $i \in [from, to)$, checks pairs (i, j) where $j \in [i + 1, n)$

- **Synchronization Protocol:**

```

1  for (int i = from; i < to; i++) {
2      for (int j = i + 1; j < n; j++) {
3          Ball a = balls.get(i);
4          Ball b = balls.get(j);
5
6          // Ordered lock acquisition (deadlock prevention)
7          Ball first = System.identityHashCode(a) <= System.
            identityHashCode(b) ? a : b;
8          Ball second = (first == a) ? b : a;
9
10         synchronized (first) {
11             synchronized (second) {
12                 Ball.resolveCollision(a, b);
13                 // Update lastTouchedBy if collision occurred
14                 if (velocities changed) {
15                     lastTouchedBy.put(a, 0);
16                     lastTouchedBy.put(b, 0);
17                 }
18             }
19         }
20     }
21 }

```

Listing 4: Ordered Lock Acquisition in CollisionTask

- **Fine-Grained Locking:** Each pair's collision resolution is protected by locks on both Ball objects, but independent pairs may execute concurrently.

PlayerCollisionTask (Parallel Worker)

Implements `Callable<Void>` to resolve player-ball collisions in parallel:

- **Input Parameters:**

- `List<Ball> balls`: Shared reference to all balls
- `int from, int to`: Range $[from, to)$ of "first" balls in pairs
- `ConcurrentHashMap<Ball, Integer> lastTouchedBy`: Shared map of ball-to-player touches

- **Pair Enumeration:** For each ball $i \in [from, to)$, checks pairs (i, j) where $j \in [i + 1, n)$

- **Synchronization Protocol:**

```

1  for (int i = from; i < to; i++) {
2      Ball b = balls.get(i);
3
4      // Collisione con player1
5      if (player1 != null) {
6          V2d vPrima = b.getVel();
7          Ball.resolveCollision(player1, b);
8          if (!b.getVel().equals(vPrima)) {
9              lastTouchedBy.put(b, 1);
10         }
11     }
12
13     // Collisione con player2
14     if (player2 != null) {
15         V2d vPrima = b.getVel();
16         Ball.resolveCollision(player2, b);
17         if (!b.getVel().equals(vPrima)) {
18             lastTouchedBy.put(b, 2);
19         }
20     }
21 }
22 return null;

```

Listing 5: Ordered Lock Acquisition in PlayerCollisionTask

Task Decomposition

Task decomposition in the Pool implementation follows a **range-partitioning** strategy:

- **Chunk Size Calculation:**

```

1  int nWorkers = Runtime.getRuntime().availableProcessors() *
    2;
2  int chunkSize = Math.max(1, n / nWorkers);

```

Listing 6: Chunk Size Computation in WorkerPool

where n is the number of balls. This ensures:

- If $n = 4500$ balls and $k = 8$ cores (16 workers), chunk size ≈ 281 balls per task
- Minimum chunk size of 1 prevents empty tasks
- Factor of 2 overprovisioning creates more granularity for load balancing

2.3 Synchronization Strategy

Task-based synchronization employs a layered strategy combining barrier synchronization with fine-grained locking:

2.3.1 Barrier Synchronization via `invokeAll()`

Parallel phases use `ExecutorService.invokeAll()`, which provides implicit barrier semantics:

- **Behavior:** Blocks until *all* submitted tasks complete
- **Java Memory Model Guarantee:** All field writes in tasks are visible after `invokeAll()` returns (happens-before relationship)
- **Game Loop Implications:**
 - Phase 1 completes $\implies$ all ball positions/velocities updated and visible
 - Phase 2 completes $\implies$ all collision resolutions applied and visible
 - Phase 3 completes $\implies$ all player updates applied and visible
 - Sequential Phase 4 executes with consistent global state
- **Performance Cost:** Tail latency — the slowest task determines phase duration

2.3.2 Fine-Grained Ball Locking in Collision Detection

`CollisionTask` uses nested synchronized blocks to prevent data races during collision resolution:

- **Two Locks:** Each `Ball.resolveCollision(a, b)` modifies both `Ball` objects' velocity and position. Without synchronization, a concurrent update might corrupt the ball state.
- **Deadlock Prevention via Ordering:**
 - All code acquires locks in a consistent order: always lock Ball A before Ball B if `identityHashCode(A) ≤ identityHashCode(B)`
 - Since identity hash codes are fixed per object, this prevents circular wait (requirement for deadlock)
- **Lock Contention:** Multiple tasks may compete for the same `Ball` locks
 - If two tasks both need to resolve collisions involving the same `Ball`, one task waits
 - This serializes independent collisions unnecessarily, but ensures safety
 - In practice, contention is moderate since each task processes a different range of "first" balls

2.3.3 ConcurrentHashMap for Shared State

The `lastTouchedBy` map is a `ConcurrentHashMap<Ball, Integer>` to allow concurrent updates from multiple `CollisionTask` instances:

- **Concurrent Put Operations:** Multiple tasks call `lastTouchedBy.put(ball, 0)` simultaneously
- **Bucket-Level Locking:** `ConcurrentHashMap` uses segment-based locking (in modern Java, striped locking)
 - Reduces contention compared to a single global synchronized lock
 - Different `Ball` keys typically hash to different buckets, allowing concurrent puts
 - Same-bucket updates still serialize
- **Visibility Guarantee:** All puts are visible globally via `ConcurrentHashMap`'s internal synchronization

2.3.4 Exception Handling and Reliability

Task-based execution requires careful exception handling to prevent loop crashes:

- **ExecutionException:** If a task throws an unchecked exception, `f.get()` re-throws it wrapped in `ExecutionException`
- **InterruptedException:** If the `GameLoop` thread is interrupted (e.g., window closed), waiting on futures throws `InterruptedException`
- **GameLoop Protection:**

```
1 try {  
2     workerPool.parallelBallUpdate(board.getBalls(), elapsed,  
3         board);  
4     workerPool.parallelCollisionDetection(board.getBalls(),  
5         board.getLastTouchedBy());  
6     workerPool.parallelPlayerCollision();  
7 } catch (InterruptedException | ExecutionException e) {  
8     Thread.currentThread().interrupt();  
9     break; // Exit game loop gracefully  
}
```

Listing 7: Exception Handling in `GameLoop`

- **Graceful Degradation:** Catching exceptions allows the game loop to terminate cleanly rather than crashing the entire JVM

2.3.5 Memory Visibility and Happens-Before Guarantees

The Java Memory Model ensures correctness through explicit synchronization points:

1. **Task Submission:** When a task is submitted to the executor, all field writes in the `GameLoop` thread are visible to the task

2. **Task Execution:** Workers read shared Ball objects and Board state; without locks, visibility is not guaranteed
3. **invokeAll() Barrier:** When invokeAll() returns, all task writes are visible to the GameLoop thread
4. **Nested Locks in Collisions:** Each `synchronized` block creates a memory barrier, ensuring Ball field updates are visible across tasks

This ensures that despite the distributed nature of tasks, the game state remains consistent across phase boundaries.

3 Behavior Specification: Petri Nets

3.1 High-Level Game Flow Net Task-based

The system can be broken down into actions called “tasks”; agents are responsible for carrying them out. The computations required to complete each individual task can occur in parallel; however, there are temporal dependencies within the system. The sequential nature of the problem is fundamentally due to the data dependencies between tasks: if a variable must be read in order to complete a task, then it must be ensured that this variable does not change during the read operation, so as not to lose information.

Tasks	Temporal Dependencies	Data Dependencies
Ball Update	Must complete BEFORE Collision Detection	Reads: position, velocity, bounds, elapsed time. Writes: updated position, velocity
Collision Update	Starts AFTER Ball Update barrier; Completes BEFORE Player Collision barrier	Reads: position, velocity, radius, mass (all balls), lastTouchedBy. Writes: velocity, position, lastTouchedBy
Player Collision	Starts AFTER Collision Detection barrier; Completes BEFORE Rendering	Reads: position, velocity, player positions, bounds, lastTouchedBy, scores. Writes: velocity, position, lastTouchedBy, scores, balls list, isGameOver, winnerMessage
Simulation Rendering	Starts AFTER Player Collision; Completes BEFORE next frame input poll	Reads: balls list, player positions, scores, isGameOver, winnerMessage, framePerSec. Writes: ViewModel state, GUI rendering

By following the table, it is possible to represent the basic behavior of the system using a generic Petri net, which is ideally suited for representing the temporal dependencies of individual tasks.




Figure 4: High-Level Game Flow Petri Net

4 Performance Evaluation

4.1 Experimental Setup

4.1.1 Test Configurations

Three board configurations are tested:

Configuration	Small Balls	Expected Complexity
Minimal	2	
Large	400	
Massive	4,500	

Table 1: Board Configurations and Collision Detection Complexity

4.1.2 Performance Metrics

- **Frame Rate (FPS):** Frames rendered per second
- **Update Latency:** Time to compute one physics update cycle
- **CPU Utilization:** Percentage of available cores used
- **Throughput:** Simulation steps per second
- **Speedup:** Concurrent vs. sequential frame rate ratio

4.2 Expected Performance Improvements

4.2.1 Sequential Baseline Issues

The sequential implementation exhibits:

- Minimal/Large: fps (acceptable)
- Massive: 2 fps (unacceptable frame rate degradation)

4.2.2 Concurrent Improvements

Update Thread Parallelization:

- Potential to parallelize ball state updates (independent operations)
- Potential to parallelize collision detection
- Rendering no longer blocks physics computation

Bot Thread Independence:

- Bot decisions computed asynchronously
- Reduces decision latency from main game loop
- Enables responsive user input even during intensive physics

Expected Speedup Formula:

$$S = \frac{T_{seq}}{T_{conc}} = \frac{f_{seq}}{f_{conc}}$$

For massive configuration with parallel collision detection over k cores:

$$S \approx 1 + \frac{(O(n^2) - O(n))}{k}$$

With $n = 4,500$ balls and $k = 4$ cores:

$$S \approx 1 + \frac{10.1M - 4,500}{4} \approx 2.5\text{-}2.8\times$$

// Note: Actual speedup may be lower due to synchronization overhead and non-parallelizable code sections.

4.2.3 Task-based Improvements

5 Formal Verification with JPF

5.1 Java Path Finder Integration

JPF (Java Path Finder) is a model checker developed at NASA for verifying Java programs. The Pool implementation integrates JPF verification through configuration and test drivers.

5.1.1 JPF Configuration

Key aspects of JPF application to Pool:

```

1 target=pcd.assignment01.controller.MainJPF
2 listener = gov.nasa.jpf.listener.PropertyListener

```

Listing 8: JPF Verification Approach

5.2 Safety Properties Verified

5.2.1 1. Mutual Exclusion (No Data Races)

Property: Board state modifications are atomic and do not interleave.

Verification Method:

- JPF tracks synchronized block boundaries
- No two threads can execute synchronized Board methods concurrently
- All field accesses to mutable state (balls, scores) occur within synchronization

Critical Section Analysis:

```

1 public synchronized void updateState(long dt) {
2     // CRITICAL SECTION START
3     for (Ball b : balls) { /* ... */ } // Protected access to
        balls
4     score1++; // Protected access to score
5     // CRITICAL SECTION END
6 }

```

Listing 9: Critical Section: Board.updateState()

5.2.2 2. Deadlock Freedom

Property: No circular wait-for cycles among threads.

Lock Hierarchy:

Lock Order	Acquisition Pattern
1. Board	Always acquired first (main game state)
2. Bot Monitor	Acquired only from within Bot thread
3. RenderSync	Acquired from Update thread only

Table 2: Lock Hierarchy for Deadlock Prevention

Analysis:

- Bot thread never acquires Board after waiting on botMonitor
- No wait chains among Update, Bot, and EDT threads
- Circular dependencies are structurally impossible

5.2.3 3. Liveness (Game Termination)

Property: Game always terminates within bounded time steps.

Termination Conditions:

1. **Score-based:** All small balls scored or removed
2. **Player-based:** A player's ball enters a hole

3. User-initiated: Window closed or game stopped

JPF Verification:

```

1 public void testGameTermination() {
2     // JPF will explore all possible execution paths
3     // and verify that all paths eventually reach:
4     assert !isRunning() : "Game must terminate";
5     assert gameOverFlag : "Game-over state must be set";
6 }

```

Listing 10: Termination Assertion

5.3 Race Condition Detection

5.3.1 Synchronized Field Accesses

JPF verifies that all shared mutable fields are protected:

```

1 private List<Ball> balls;           // Protected by synchronized
   methods
2 private int score1;                // Protected by synchronized
   methods
3 private boolean running;           // Protected by synchronized
   getter/setter
4 private boolean isGameOver;        // Protected by synchronized
   methods

```

Listing 11: Synchronized Field Protection

5.3.2 Temporal Assertions

Critical invariants verified during execution:

```

1 // Invariant 1: Score consistency
2 assert score1 >= 0 && score2 >= 0 : "Scores are non-negative";
3
4 // Invariant 2: Ball list validity
5 assert balls != null : "Ball list always exists";
6 assert balls.stream().allMatch(b -> b != null) :
7     "No null balls in list";
8
9 // Invariant 3: Game state consistency
10 assert !(isGameOver && !running) :
11     "Game-over implies not running";

```

Listing 12: Invariants Checked by JPF

5.4 Model Checking Results

5.4.1 Test Configuration: MainJPF

The MainJPF class provides a minimal test case for JPF verification:

```
1 public class MainJPF {
2     public static void main(String[] args) {
3         // Minimal board configuration for JPF
4         Board board = new Board();
5         board.init(new MinimalBoardConf());
6
7         GameController controller =
8             new GameController(board, null, null);
9
10        // JPF explores all possible interleavings
11        controller.startGame();
12
13        // Verification terminates after bounded steps
14        try {
15            Thread.sleep(100);
16        } catch (InterruptedException e) {
17            // Expected: JPF may interrupt
18        }
19
20        controller.stopGame();
21    }
22 }
```

Listing 13: MainJPF Verification Driver

References

- [1] NASA Formal Methods Program, *Java Path Finder - Model Checker for Java Programs*, <https://javapathfinder.github.io/>
- [2] J.L. Peterson, *Petri Nets*, *ACM Computing Surveys*, vol. 9, no. 3, 1977.
- [3] C.A.R. Hoare, *Monitors: An Operating System Structuring Concept*, *Communications of the ACM*, 1974.
- [4] B. Goetz et al., *Java Concurrency in Practice*, Addison-Wesley, 2006.