

# Crabsort

## Spike-sorting for small circuit networks


Alec Hoyland Cosmo Guerini

Center for Systems Neuroscience


June 25, 2019

# Spike-sorting primer

Spike-sorting is the process of mapping action potentials to the originating cell.



**Figure:** Intracellular recordings of pyloric cells.



**Figure:** **A** circuit diagram of nerves; **B** connectivity diagram, circles are cells, synapses are lines and dots; **C** extracellular recording of motor nerves.

# How to sort spikes


- 1 Identify spikes from membrane potential waveform (easy)
- 2 Sort spikes using some magic algorithm (hard)

For large networks, spike sorting means:

- 1 Methods: PCA, SVD, stochastic k-means matching of correlograms
- 2 Data: 100s of channels but without a ground truth

For small networks, spike sorting means:

- 1 Methods: dimensionality reduction, machine learning
- 2 Data: few channels with known activity



**Figure:** Spike-sorting using PCA and window filtering by spike-waveform analysis (R. Quian Quiroga).


# Crabsort

# Dimensionality Reduction

Dimensionality reduction is the process of taking high-dimensional data and representing it in a lower dimensional space.

Crabsort allows the user to:

- 1 Dimensionally reduce the data to a 2-dimensional manifold
- 2 Interactively label the data



**Figure:** Using the t-SNE algorithm to reduce a 3-dimensional dataset to a 2-dimensional dataset.

# t-SNE

