Numerical Methods[1]

Alejandro Campos

October 1, 2021

[1]Disclaimer: a large chunk of the work in this document is not original; instead, parts of this document are personal notes obtained from the following books: Lomax, Pulliam, Zing; Larsson, Thomee; Hirsch; Leveque; Blazek; Laney; Moin.

Contents

V Finite Element for PDE's   25

10 Elliptic   26

11 Parabolic   27

12 Hyperbolic   28

A Notes on functional analysis   29

Part I

Introductory Concepts

- Analytical solution u satisfies

$$D(u) = Au - f = 0 \quad \text{in } \Omega, \tag{1}$$

  where A is the differential operator.

- Discrete numerical solution U_j satisfies

$$D_h(U_j^n) = 0 \quad \text{for all } n, j, \tag{2}$$

  where D_h is the discrete operator for D.

- Continuous numerical solution v satisfies

$$D_h v = 0 \quad \text{in } \Omega, \tag{3}$$

  Thus, $v(t_n, x_j) = U_j^n$ for all n, j.

- Local truncation error

$$l_j^{n+1} = u(t_{n+1}, x_j) - U_j^{n+1}, \tag{4}$$

  given that $U_j^n = u(t_n, x_j)$ for all j.

- Global truncation error

$$e_j^{n+1} = u(t_{n+1}, x_j) - U_j^{n+1}, \tag{5}$$

  given that $U_j^0 = u(t_0, x_j)$ for all j.

- Truncation error τ: difference between the discrete and analytical equations when applied to a given continuous function g

$$\tau = D_h g - D g. \tag{6}$$

The truncation error allows us to compute global truncation errors. Also, consider the truncation error for the analytical solution, that is, $\tau = D_h u - D u$. Using equation (1), one obtains that u is also the solution to $D_h u = \tau$. This means that the **analytical solution satisfies the numerical equation but with an additional source term equal to** τ. Conversely, consider the truncation error for the function v, $\tau = D_h v - D v$. Using equation (3), one obtains that v is also a solution to $D v = \tau$. This means that the **numerical solution satisfies the analytical equation but with an additional source term equal to** τ.

- Order of accuracy r defined by $\tau^n = \mathcal{O}(\Delta t^r)$ as $\Delta t \to 0$ for ODE's and $\tau^n = \mathcal{O}(\Delta x^r)$ as $\Delta x \to 0$ for PDE's, where Δt is related to Δx.

Part II

Numerical Solution of ODE's

Chapter 1

List of time integrators

Consider the IVP for $u = u(t)$

$$\frac{du}{dt} = f(t, u) \quad \text{in } (0, \infty) \tag{1.1}$$

with initial condition $u(0) = u^0$. We will discretize time into a set of finite values t^n, and express the numerical solution at a given time t^n as U^n.

1.1 Explicit

- Explicit Euler method (Forward Euler method)

$$u^{n+1} = u^n + \Delta t f(t_n, u^n) \qquad 1^{\text{st}} \text{ O.A.} \tag{1.2}$$

1.2 Implicit

- Implicit Euler (Backward Euler)

$$u^{n+1} = u^n + \Delta t f(t_{n+1}, u^{n+1}) \qquad 1^{\text{st}} \text{ O.A.} \tag{1.3}$$

- Trapezoidal (Crank-Nicholson)

$$u^{n+1} = u^n + \frac{\Delta t}{2}[f(t_n, u^n) + f(t_{n+1}, u^{n+1})] \qquad 2^{\text{nd}} \text{ O.A.} \tag{1.4}$$

- Implicit Midpoint

$$u^{n+1} = u^n + \Delta t f\left(t_{n+1/2}, \frac{1}{2}\left(u^n + u^{n+1}\right)\right) \tag{1.5}$$

1.3 Predictor-Corrector

- Explicit Midpoint (Modified Euler, 2^{nd} order RK)

$$u^{n+1/2} = u^n + \frac{\Delta t}{2}f(t_n, u^n)$$
$$u^{n+1} = u^n + \Delta t f(t_{n+1/2}, u^{n+1/2}) \tag{1.6}$$

- Heun's (Explicit Trapezoidal, Improved Euler)

$$\tilde{u}^{n+1} = u^n + \Delta t f(t_n, u^n)$$
$$u^{n+1} = u^n + \frac{\Delta t}{2}[f(t_n, u^n) + f(t_{n+1}, \tilde{u}^{n+1})] \quad 2^{\text{ nd}} \text{ O.A.} \tag{1.7}$$

1.4 Runge-Kutta

- 4^{th} order Runge-Kutta

$$k_1 = f(t_n, u^n)$$
$$k_2 = f(t_{n+1/2}, u^n + \frac{\Delta t}{2} k_1)$$
$$k_3 = f(t_{n+1/2}, u^n + \frac{\Delta t}{2} k_2)$$
$$k_4 = f(t_n, u^n + \Delta t k_3)$$
$$u^{n+1} = u^n + \frac{\Delta t}{6}(k_1 + 2k_2 + 2k_3 + k_4) \tag{1.8}$$

1.5 Multi-Step

- Leapfrog

- Adams-Bashforth

Chapter 2

Solving non-linear equations

The implicit schemes result in non-linear equations that require some sort of non-linear solver. For this chapter, we'll assume the governing ODE is

$$\frac{du}{dt} = f(u) \qquad \text{in } (0, \infty), \tag{2.1}$$

or, for a system of equations,

$$\frac{d\mathbf{u}}{dt} = \mathbf{f}(\mathbf{u}) \qquad \text{in } (0, \infty). \tag{2.2}$$

2.1 Newton's method

The Euler scheme requires finding u^{n+1} so that the following is satisfied

$$u^{n+1} = u^n + \Delta t f(u^{n+1}). \tag{2.3}$$

That is, we need to find the root of the nonlinear equation

$$g(x) = x - u^n - \Delta t f(x). \tag{2.4}$$

Newton's method finds the root of a non-linear equation $g(x)$ by iterating through m as follows

$$x^{m+1} = x^m - \frac{g(x^m)}{g'(x^m)}. \tag{2.5}$$

Applying Newton's method to eq. (2.4), we have

$$x^{m+1} = x^m - \frac{x^m - u^n - \Delta t f(x^m)}{1 - \Delta t f'(x^m)}, \tag{2.6}$$

The initial value for the non-linear solver is $x^0 = u^n$. Thus, using the above, u^{n+1} is approximated by x^m as $m \to \infty$. Note that this is only one example of what is referred to as a fixed-point iteration. There are other fixed-point-iteration methods that can be used to solve eq. (2.4) that are not Newton's method.

As a side note, let's assume u^{n+1} is approximated sufficiently well by x^1, that is, only one Newton iteration is needed. Then we have

$$u^{n+1} = u^n + \frac{\Delta t f(u^n)}{1 - \Delta t f'(u^n)}, \tag{2.7}$$

which we re-write as

$$\left(\frac{1}{\Delta t} - f'(u^n)\right)\Delta u = f(u^n),\tag{2.8}$$

where $\Delta u = u^{n+1} - u^n$. The above is the approximation that gets used for pseudo-time stepping, so that the Backward Euler scheme can converge to the steady state solution as one iterates through n.

To solve for the root of a system of non-linear equations $\mathbf{g}(\mathbf{x})$, Newton's method is as follows

$$\mathbf{x}^{m+1} = \mathbf{x}^m - \mathbf{J}^{-1}(\mathbf{x}^m)\mathbf{g}(\mathbf{x}^m).\tag{2.9}$$

In the above, $\mathbf{J}^{-1}(\mathbf{x})$ is the inverse of the Jacobian matrix $\mathbf{J}(\mathbf{x})$, which is given by

$$\mathbf{J}(\mathbf{x}) = \frac{\partial \mathbf{g}(\mathbf{x})}{\partial \mathbf{x}} = \begin{pmatrix} \frac{\partial g_1(\mathbf{x})}{\partial x_1} & \frac{\partial g_1(\mathbf{x})}{\partial x_2} & \cdots \\ \frac{\partial g_2(\mathbf{x})}{\partial x_1} & \frac{\partial g_2(\mathbf{x})}{\partial x_2} & \\ \vdots & & \ddots \end{pmatrix}.\tag{2.10}$$

For the backward Euler scheme, the equivalent of eq. (2.6) would be

$$\mathbf{x}^{m+1} = \mathbf{x}^m - \left(\mathbf{I} - \Delta t \left.\frac{\partial \mathbf{f}(\mathbf{x})}{\partial \mathbf{x}}\right|_{\mathbf{x}=\mathbf{x}^m}\right)^{-1}(\mathbf{x}^m - \mathbf{u}^n - \Delta t \mathbf{f}(\mathbf{x}^m)),\tag{2.11}$$

and the equivalent of eq. (2.8) would be

$$\left(\frac{\mathbf{I}}{\Delta t} - \left.\frac{\partial \mathbf{f}(\mathbf{x})}{\partial \mathbf{x}}\right|_{\mathbf{x}=\mathbf{u}^n}\right)\Delta \mathbf{u} = \mathbf{f}(\mathbf{u}^n),\tag{2.12}$$

where $\Delta \mathbf{u} = \mathbf{u}^{n+1} - \mathbf{u}^n$.

Part III

Finite Difference for PDE's

Chapter 3

Finite difference formulas

Forward	Backward	Central	Central (2nd order)
$\partial U_j = \dfrac{U_{j+1} - U_j}{h}$	$\bar{\partial} U_j = \dfrac{U_j - U_{j-1}}{h}$	$\hat{\partial} U_j = \dfrac{U_{j+1} - U_{j-1}}{2h}$	$\partial \bar{\partial} U_j = \dfrac{U_{j+1} - 2U_j + U_{j-1}}{h^2}$

3.1 Fourier analysis

This analysis is based on a test function that is periodic and thus has the following form

$$u(x) = \sum_{n=-\infty}^{n=\infty} \hat{u}_n e^{i\kappa_n x}. \tag{3.1}$$

We are interested in using the different numerical methods to compute the resulting approximate derivatives of the generic mode $e^{i\kappa x}$. We note that one can then combine the approximate derivatives of all the modes to obtain the approximate derivative of our test function u.

The analytically derivative of our generic mode $e^{i\kappa x}$ is $i\kappa e^{i\kappa x}$. We now assume that the approximate derivatives at a point x_j obtained using numerical schemes will be of the form $i\kappa^* e^{i\kappa x_j}$, where κ^* is a modified wave number. The closer κ^* is to κ the higher the accuracy of the numerical scheme. For example, for the central first order scheme

$$\delta U_j = \frac{U_{j+1} - U_{j-1}}{2h} \tag{3.2}$$

we have

$$i\kappa^* e^{i\kappa x_j} = \frac{e^{i\kappa(x_j+h)} - e^{i\kappa(x_j-h)}}{2h} \tag{3.3}$$

which leads to

$$\kappa^* = \frac{\sin \kappa h}{h}. \tag{3.4}$$

For the sixth-order compact scheme

$$\alpha \delta U_{j-1} + \delta U_j + \alpha \delta U_{j+1} = \frac{a}{2h} \left(U_{j+1} - U_{j-1} \right) + \frac{b}{4h} \left(U_{j+2} - U_{j-2} \right) \tag{3.5}$$

we have

$$\alpha i\kappa^* e^{i\kappa(x_j-h)} + i\kappa^* e^{i\kappa x_j} + \alpha i\kappa^* e^{i\kappa(x_j+h)} = \frac{a}{2h} \left[e^{i\kappa(x_j+h)} - e^{i\kappa(x_j-h)} \right] + \frac{b}{2h} \left[e^{i\kappa(x_j+2h)} - e^{i\kappa(x_j-2h)} \right] \tag{3.6}$$

which leads to

$$\kappa^* = \frac{\frac{a}{h}\sin\kappa h + \frac{b}{2h}\sin 2\kappa h}{1 + 2\alpha\cos\kappa h}. \tag{3.7}$$

A spectral method, on the other hand, will explicitly express the derivative of a mode as $i\kappa e^{i\kappa x_j}$, up to the last mode $\kappa = \frac{2\pi}{L}\frac{N}{2}$, and will not be able to capture higher modes. Thus,

$$\kappa^* = \begin{cases} \kappa & \text{for } \frac{2\pi}{L}\left(-\frac{N}{2}+1\right) \le \kappa \le \frac{2\pi}{L}\frac{N}{2} \\ 0 & \text{o.w.} \end{cases} \tag{3.8}$$

Chapter 4

Elliptic

Define the following norm: $|U|_S = \max_{x_j \in S} |U_j|$.

For $Au = -au'' + cu = f$ in $\Omega = (0,1)$, where $a(x) > 0$ and $c(x) \geq 0$, with boundary conditions $u(0) = U_0$ and $u(1) = U_m$, and $A_h = -a_j \partial \bar{\partial} U_j + c_j U_j$:

- **Lemma 4.2**
$$|U|_{\bar{\Omega}} \leq \max\{|U_0|, |U_M|\} + C|A_h U|_\Omega$$

- **Theorem 4.1** The error bound follows,
$$|U - u|_\Omega \leq Ch^2 ||u||_C^4$$

For $Au = -\Delta u = f$ in $\Omega = (0,1) \times (0,1)$, with boundary doncitions $u = 0$ in Γ, and $A_h = -\Delta_h = -\partial_1 \bar{\partial}_1 U_j - \partial_2 \bar{\partial}_2 U_j$:

- **Lemma 4.4**
$$|U|_{\bar{\Omega}} \leq |U|_\Gamma + C|\Delta_h U|_\Omega$$

- **Theorem 4.2** The error bound follows,
$$|U - u|_\Omega \leq Ch^2 ||u||_C^4$$

Chapter 5

Parabolic

For $u_t = u_{xx}$ in $\mathbf{R} \times \mathbf{R}_+$, with initial condition $u(\cdot, 0) = v$ in $\mathbf{R}$.

- Each scheme can be associated with its discrete solution operator E_k, defined in either of the following two ways, where U_j^n is defined only at mesh points, and $u^n(x)$ is the corresponding numerical solution defined over all space,

$$U_j^{n+1} = (E_k U^n)_j = \sum_p a_p U_{j-p}^n$$

$$u^{n+1}(x) = (E_k u^n)(x) = \sum_p a_p u^n(x - x_p)$$

- Repeated application yields $U_j^n = (E_k^n V)_j$ or $u^n(x) = (E_k^n v)(x)$, where V_i and $v(x)$ are the initial conditions, specified at mesh points and over all space, respectively.

- The **stability** of E_k (and hence the associated scheme) is defined by $||U^n||_{l_p} = ||E_k^n V||_{l_p} \leq ||V||_{l_p}$ and $||u^n||_{L_p} = ||E_k^n v||_{L_p} \leq ||v||_{L_p}$.

- The **symbol** or characteristic polynomial of E_k is defined as follows,

$$\tilde{E}(\xi) = \sum_p a_p e^{-ip\xi}.$$

If we make use of the following Fourier series and Fourier transform,

$$\hat{V}(\xi) = h \sum_{j=-\infty}^{\infty} V_j e^{-ij\xi}$$

$$\hat{v}(\xi) = \int_{-\infty}^{\infty} v(x) e^{-ix\xi} dx$$

then we obtain $(E_k V)\hat{}(\xi) = \tilde{E}(\xi)\hat{V}(\xi)$ and $(E_k v)\hat{}(\xi) = \tilde{E}(h\xi)\hat{v}(\xi)$, which for repeated application leads to,

$$(E_k^n V)\hat{}(\xi) = \tilde{E}^n(\xi)\hat{V}(\xi)$$
$$(E_k^n v)\hat{}(\xi) = \tilde{E}^n(h\xi)\hat{v}(\xi).$$

- Using Parseval's theorem one arrives at the **von Neumann's stability condition**, namely, $|\tilde{E}(\xi)| \leq 1|$ for all ξ is sufficient for stability in l_2 and L_2, and necessary for stability in l_∞.

- The **order of accuracy** r is defined by $\tau^n = \mathcal{O}(h^r)$ as $h \to 0$. Since $u^{n+1}(x) = E_k u^n(x) + k\tau^n(x)$, where $u^n(x)$ is now the analytical solution and k is the time step, then the order of accuracy is also obtained from $u^{n+1}(x) - E_k u^n(x) = k\mathcal{O}(h^r)$. This expression for order of accuracy is equivalent to $\tilde{E}(\xi) = e^{-\lambda\xi^2} + \mathcal{O}(|\xi|^{r+2})$, as $\xi \to 0$.

Chapter 6

Hyperbolic

For $u_t = au_x$ in $\mathbf{R} \times \mathbf{R}_+$, with initial condition $u(\cdot, 0) = v$ in $\mathbf{R}$:

- As for parabolic equations, von Neumann's condition $|\tilde{E}(\xi)| \leq 1$ for all ξ is a necessary and sufficient condition for stability in the L_2 norm.

- Order of accuracy is defined in the same manner as for the parabolic case, except that now the symbol of E_k is given by $\tilde{E}(\xi) = e^{ia\lambda\xi} + \mathcal{O}(|\xi|^{r+1})$ as $\xi \to 0$.

- **CFL condition** for stability: a necessary condition for stability is that the domain of dependence of the finite difference scheme at (x, t) contains the domain of dependence of the continuous problem.

- The Friedrichs scheme (first order accurate) follows,

$$(E_k U^n)(x) = 1/2(1 + a\lambda)U^n(x + h) + 1/2(1 - a\lambda)U^n(x - h)$$

- The Lax-Wendroff scheme (second order accurate) follows,

$$(E_k U^n)(x) = 1/2(a^2\lambda^2 + a\lambda)U^n(x + h) + (1 - a^2\lambda^2)U^n(x) + 1/2(a^2\lambda^2 - a\lambda)U^n(x - h)$$

Part IV

Finite Volume for PDE's

Chapter 7

Elliptic

Chapter 8

Parabolic

Chapter 9

Hyperbolic

9.1 One-dimensional case

Consider the hyperbolic equation

$$\frac{\partial u}{\partial t} + \frac{\partial f}{\partial x} = 0, \tag{9.1}$$

where $f = f(u)$ is the flux of u. The finite volume method consists on discretizing the spatial domain into volumes, which we will denote by the index i, and which are defined by $x \in [x_{i-1/2}, x_{i+1/2}]$, where $x_{i-1/2}$ and $x_{i+1/2}$ represent the boundaries of the finite volume i.

We now proceed by averaging the equation over each control volume, that is

$$\frac{1}{\Delta x_i} \int_{x_{i-1/2}}^{x_{1+1/2}} \frac{\partial u}{\partial t} dx + \frac{1}{\Delta x_i} \int_{x_{i-1/2}}^{x_{1+1/2}} \frac{\partial f}{\partial x} dx = 0, \tag{9.2}$$

where $\Delta x_i = x_{i+1/2} - x_{i-1/2}$. Moving the time derivative and using the Divergence theorem, the above becomes

$$\frac{d}{dt} \left(\frac{1}{\Delta x_i} \int_{x_{i-1/2}}^{x_{i+1/2}} u \, dx \right) + \frac{1}{\Delta x_i} (f_{i+1/2} - f_{i-1/2}) = 0, \tag{9.3}$$

where $f_{i\pm1/2}$ is the flux evaluated at $x_{i\pm1/2}$. The spatially-discrete numerical solution then satisfies

$$\frac{dU_i}{dt} + \frac{1}{\Delta x_i} (F_{i+1/2} - F_{i-1/2}) = 0, \tag{9.4}$$

where $U_i = U_i(t)$ is the discrete solution at some specific point within the finite volume, and is used to approximate the average of u. $F_{i\pm1/2}$ are the so-called numerical fluxes.

Godunov Scheme:

$$F_{j+1/2}^n = \begin{cases} \min_{U_j \leq u \leq U_{j+1}} f(u) & \text{for} \quad U_j < U_{j+1} \\ \min_{U_{j+1} \leq u \leq U_j} f(u) & \text{for} \quad U_j > U_{j+1} \end{cases}$$

Lax-Friedrichs:

$$F_{j+1/2}^n = \frac{h}{2k}(U_j - U_{j+1} + \frac{1}{2}(f(U_j) + f(U_{j+1}))$$

9.2 Multi-dimensional case

We follow a similar approach for the multidimensional case. Consider a generic conservation equation

$$\frac{\partial w_i}{\partial t} + \frac{\partial f_{ij}^{(c)}}{\partial x_j} = \frac{\partial f_{ij}^{(v)}}{\partial x_j} + q_i \tag{9.5}$$

where w_i is the vector of conservative variables, $f_{ij}^{(c)}$ the convective flux tensor, $f_{ij}^{(v)}$ the viscous flux tensor, and q_i some heat source.

Averaging the equation over a generic finite volume denoted by the index I, one obtains

$$\frac{d}{dt}\left(\frac{1}{\Omega_I}\int_{\Omega_I} w_i \, dV\right) + \frac{1}{\Omega_I}\int_{\delta\Omega_I} f_i^{(c)} \, dS = \frac{1}{\Omega_I}\int_{\delta\Omega_I} f_i^{(v)} \, dS + \frac{1}{\Omega_I}\int_{\Omega_I} q_i \, dV, \qquad (9.6)$$

where $f_i^{(c)} = f_{ij}^{(c)} n_j$ and $f_i^{(v)} = f_{ij}^{(v)} n_j$ are the vectors of convective and viscous fluxes, respectively. In vector notation, this is written as

$$\frac{d}{dt}\left(\frac{1}{\Omega_I}\int_{\Omega_I} \mathbf{w} \, dV\right) + \frac{1}{\Omega_I}\int_{\delta\Omega_I} \mathbf{f}^{(c)} \, dS = \frac{1}{\Omega_I}\int_{\delta\Omega_I} \mathbf{f}^{(v)} \, dS + \frac{1}{\Omega_I}\int_{\Omega_I} \mathbf{q} \, dV. \qquad (9.7)$$

A specific example is the Navier-Stokes equations, for which we have

$$\mathbf{w} = \begin{bmatrix} \rho \\ \rho u \\ \rho v \\ \rho w \\ \rho E \end{bmatrix} \qquad \mathbf{f}^{(c)} = \begin{bmatrix} \rho(u_j n_j) \\ \rho u(u_j n_j) + p n_1 \\ \rho v(u_j n_j) + p n_2 \\ \rho w(u_j n_j) + p n_3 \\ \rho\left(E + \frac{p}{\rho}\right)(u_j n_j) \end{bmatrix} \qquad \mathbf{f}^{(v)} = \begin{bmatrix} 0 \\ \tau_{1j} n_j \\ \tau_{2j} n_j \\ \tau_{3j} n_j \\ u_i \tau_{ij} n_j + \kappa \frac{\partial T}{\partial x_j} n_j \end{bmatrix} \qquad \mathbf{q} = \begin{bmatrix} 0 \\ \rho g_1 \\ \rho g_2 \\ \rho g_3 \\ \rho u_i g_i \end{bmatrix}. \qquad (9.8)$$

The spatially-discrete numerical solution then satisfies

$$\frac{d\mathbf{W}_I}{dt} + \frac{1}{\Omega_I}\sum_{K \in N(I)} \mathbf{F}_K^{(c)} \Delta S_K = \frac{1}{\Omega_I}\sum_{K \in N(I)} \mathbf{F}_K^{(v)} \Delta S_K + \mathbf{Q}_I \qquad (9.9)$$

where $\mathbf{W}_I = \mathbf{W}_I(t)$ is the numerical solution at some specific point within the finite volume, and is used to approximate the average of the vector $\mathbf{w}$. The faces of the finite volumes are indexed, and the set $N(I)$ consists of the indices of the faces of the finite volume I. The variables $\mathbf{F}_K^{(c)} = \mathbf{F}_K^{(c)}(\mathbf{W}_1, \mathbf{W}_2, \dots)$ and $\mathbf{F}_K^{(v)} = \mathbf{F}_K^{(v)}(\mathbf{W}_1, \mathbf{W}_2, \dots)$ are the numerical fluxes, and ΔS_K the surface area, for face K. The averaged source term $\mathbf{Q}_I = \mathbf{Q}_I(\mathbf{W}_I)$ is approximated as the source vector $\mathbf{q}$ evaluated using $\mathbf{W}_I$. The above is typically rewritten as

$$\frac{d\mathbf{W}_I}{dt} = -\frac{1}{\Omega_I}\mathbf{R}_I, \qquad (9.10)$$

where the residual $\mathbf{R}_I = \mathbf{R}_I(\mathbf{W}_1, \mathbf{W}_2, \dots)$ is given by

$$\mathbf{R}_I = \sum_{K \in N(I)} \mathbf{F}_K^{(c)} \Delta S_K - \sum_{K \in N(I)} \mathbf{F}_K^{(v)} \Delta S_K - \mathbf{Q}_I \, \Omega_I \qquad (9.11)$$

The Jacobian is then

$$\frac{\partial \mathbf{R}_I}{\partial \mathbf{W}_J} = \sum_{K \in N(I)} \frac{\partial \mathbf{F}_K^{(c)}}{\partial \mathbf{W}_J} \Delta S_K - \sum_{K \in N(I)} \frac{\partial \mathbf{F}_K^{(v)}}{\partial \mathbf{W}_J} \Delta S_K - \frac{\partial \mathbf{Q}_I}{\partial \mathbf{W}_J} \Omega_I \qquad (9.12)$$

Note the the Jacobian is only non zero when $J \in M(I)$, where $M(I)$ represents the set of all finite volumes that the numerical fluxes of finite volume I depend on.

9.2.1 An example from turbulence modeling

Consider the SST turbulence model. The two transport equations solved by the model are

$$\frac{\partial \rho k}{\partial t} + \frac{\partial \rho k u_j}{\partial x_j} = P - \beta^* \rho w k + \frac{\partial}{\partial x_j}\left[(\mu + \sigma_k \mu_t)\frac{\partial k}{\partial x_j}\right] \tag{9.13}$$

$$\frac{\partial \rho w}{\partial t} + \frac{\partial \rho w u_j}{\partial x_j} = \frac{\gamma}{\nu_t}P - \beta\rho w^2 + \frac{\partial}{\partial x_j}\left[(\mu + \sigma_w \mu_t)\frac{\partial w}{\partial x_j}\right] + 2(1-F_1)\frac{\rho\sigma_{w2}}{w}\frac{\partial k}{\partial x_j}\frac{\partial w}{\partial x_j} \tag{9.14}$$

The vector of conservative variables is $\mathbf{w} = [\rho k, \rho w]^T$. The convective and viscous flux vectors are

$$\mathbf{f}^{(c)} = \begin{bmatrix} \rho k (u_j n_j) \\ \rho w (u_j n_j) \end{bmatrix} \qquad \mathbf{f}^{(v)} = \begin{bmatrix} (\mu + \sigma_k \mu_t)\frac{\partial k}{\partial x_j}n_j \\ (\mu + \sigma_w \mu_t)\frac{\partial w}{\partial x_j}n_j \end{bmatrix}. \tag{9.15}$$

The source $\mathbf{q}$ is

$$\mathbf{q} = \begin{bmatrix} P - \beta^* \rho w k \\ \frac{\gamma}{\nu_t}P - \beta\rho w^2 + 2(1-F_1)\frac{\rho\sigma_{w2}}{w}\frac{\partial k}{\partial x_j}\frac{\partial w}{\partial x_j} \end{bmatrix} \tag{9.16}$$

Convective numerical fluxes: A simple upwinding scheme is as follows

$$\mathbf{F}_K^{(c)} = \begin{bmatrix} (\rho k)_l a_0 + (\rho k)_r a_1 \\ (\rho w)_l a_0 + (\rho w)_r a_1 \end{bmatrix} \tag{9.17}$$

where subscripts l and r denote values at the center nodes of the control volumes to the left and right of the K^{th} control surface, respectively. The variables a_0 and a_1 are given by

$$a_0 = \begin{cases} q_{lr} & \text{if } q_{lr} > 0 \\ 0 & \text{o.w.} \end{cases} \qquad a_1 = \begin{cases} 0 & \text{if } q_{lr} > 0 \\ q_{lr} & \text{o.w.} \end{cases} \tag{9.18}$$

where

$$q_{lr} = \frac{(\mathbf{u}_l \cdot \mathbf{n}) + (\mathbf{u}_r \cdot \mathbf{n})}{2}. \tag{9.19}$$

The corresponding Jacobian is

$$\frac{\partial \mathbf{F}_K^{(c)}}{\partial \mathbf{W}_J} = \begin{bmatrix} \frac{\partial \mathbf{F}_K^{(c)}(1)}{\partial \mathbf{W}_J(1)} & \frac{\partial \mathbf{F}_K^{(c)}(1)}{\partial \mathbf{W}_J(2)} \\ \frac{\partial \mathbf{F}_K^{(c)}(2)}{\partial \mathbf{W}_J(1)} & \frac{\partial \mathbf{F}_K^{(c)}(2)}{\partial \mathbf{W}_J(2)} \end{bmatrix} = \begin{bmatrix} a_0\delta_{lJ} + a_1\delta_{rJ} & 0 \\ 0 & a_0\delta_{lJ} + a_1\delta_{rJ} \end{bmatrix}. \tag{9.20}$$

Viscous numerical fluxes: the viscous fluxes can be discretized as follows

$$\mathbf{F}_K^{(v)} = \begin{bmatrix} (\mu + \sigma_k \mu_t)_{avg}\left[\frac{k_r - k_l}{l_{lr}}\mathbf{t}_{lr} + \nabla k_{avg} - (\nabla k_{avg} \cdot \mathbf{t}_{lr})\mathbf{t}_{lr}\right]\cdot \mathbf{n} \\ (\mu + \sigma_\omega \mu_t)_{avg}\left[\frac{\omega_r - \omega_l}{l_{lr}}\mathbf{t}_{lr} + \nabla\omega_{avg} - (\nabla\omega_{avg} \cdot \mathbf{t}_{lr})\mathbf{t}_{lr}\right]\cdot \mathbf{n} \end{bmatrix}. \tag{9.21}$$

where the subscript $_{avg}$ means the left and right values have been averaged, $\mathbf{t}_{lr}$ is the unit vector that points from the center of the l^{th} control volume (the one to the left of the face) to the center of the r^{th} control volume (the one to the right of the face), and l_{lr} is the length between these two centers. The corresponding Jacobian is approximated as follows

$$\frac{\partial \mathbf{F}_K^{(v)}}{\partial \mathbf{W}_J} = \begin{bmatrix} \frac{\partial \mathbf{F}_K^{(v)}(1)}{\partial \mathbf{W}_J(1)} & \frac{\partial \mathbf{F}_K^{(v)}(1)}{\partial \mathbf{W}_J(2)} \\ \frac{\partial \mathbf{F}_K^{(v)}(2)}{\partial \mathbf{W}_J(1)} & \frac{\partial \mathbf{F}_K^{(v)}(2)}{\partial \mathbf{W}_J(2)} \end{bmatrix}, \tag{9.22}$$

where

$$\frac{\partial \mathbf{F}_K^{(v)}(1)}{\partial \mathbf{W}_J(1)} = (\mu + \sigma_k \mu_t)_{avg} \frac{1}{l_{lr}} \mathbf{t}_{lr} \cdot \mathbf{n} \frac{\delta_{rJ}}{\rho_r} - (\mu + \sigma_k \mu_t)_{avg} \frac{1}{l_{lr}} \mathbf{t}_{lr} \cdot \mathbf{n} \frac{\delta_{lJ}}{\rho_l}, \tag{9.23}$$

$$\frac{\partial \mathbf{F}_K^{(v)}(2)}{\partial \mathbf{W}_J(2)} = (\mu + \sigma_\omega \mu_t)_{avg} \frac{1}{l_{lr}} \mathbf{t}_{lr} \cdot \mathbf{n} \frac{\delta_{rJ}}{\rho_r} - (\mu + \sigma_\omega \mu_t)_{avg} \frac{1}{l_{lr}} \mathbf{t}_{lr} \cdot \mathbf{n} \frac{\delta_{lJ}}{\rho_l} \tag{9.24}$$

and $\frac{\partial \mathbf{F}_K^{(v)}(1)}{\partial \mathbf{W}_J(2)} = \frac{\partial \mathbf{F}_K^{(v)}(2)}{\partial \mathbf{W}_J(1)} = 0$.

Sources: The discretized source terms are computed following eq. (9.16). The Jacobian is expressed as

$$\frac{\partial \mathbf{Q}_I}{\partial \mathbf{W}_J} = \begin{bmatrix} \dfrac{\partial \mathbf{Q}_I(1)}{\partial \mathbf{W}_J(1)} & \dfrac{\partial \mathbf{Q}_I(1)}{\partial \mathbf{W}_J(2)} \\ \dfrac{\partial \mathbf{Q}_I(2)}{\partial \mathbf{W}_J(1)} & \dfrac{\partial \mathbf{Q}_I(2)}{\partial \mathbf{W}_J(2)} \end{bmatrix}. \tag{9.25}$$

According to Wilcox p. 413, the elements of the matrix above are approximated as follows

$$\frac{\partial \mathbf{Q}_I(1)}{\partial \mathbf{W}_J(1)} \approx -\beta^* w_I \delta_{IJ} \qquad \frac{\partial \mathbf{Q}_I(2)}{\partial \mathbf{W}_J(2)} \approx -2\beta w_I \delta_{IJ} \qquad \frac{\partial \mathbf{Q}_I(1)}{\partial \mathbf{W}_J(2)} = \frac{\partial \mathbf{Q}_I(2)}{\partial \mathbf{W}_J(1)} \approx 0. \tag{9.26}$$

9.3   Implicit time integration

We combine eq. (9.10) for all I into a single equation as follows

$$\frac{d}{dt} \begin{pmatrix} \mathbf{W}_1 \\ \mathbf{W}_2 \\ \vdots \end{pmatrix} = \begin{pmatrix} -\frac{1}{\Omega_1} \mathbf{R}_1 \\ -\frac{1}{\Omega_2} \mathbf{R}_2 \\ \vdots \end{pmatrix}. \tag{9.27}$$

Note that the above is of the same form as eq. (2.2). Thus, the corresponding form of eq. (2.12) would be

$$\left[\frac{1}{\Delta t} \begin{pmatrix} \mathbf{I} & 0 & \cdots \\ 0 & \mathbf{I} & \\ \vdots & & \ddots \end{pmatrix} - \begin{pmatrix} -\frac{1}{\Omega_1} \frac{\partial \mathbf{R}_1(\mathbf{x}_1, \mathbf{x}_2, \dots)}{\partial \mathbf{x}_1} & -\frac{1}{\Omega_1} \frac{\partial \mathbf{R}_1(\mathbf{x}_1, \mathbf{x}_2, \dots)}{\partial \mathbf{x}_2} & \cdots \\ -\frac{1}{\Omega_2} \frac{\partial \mathbf{R}_2(\mathbf{x}_1, \mathbf{x}_2, \dots)}{\partial \mathbf{x}_1} & -\frac{1}{\Omega_2} \frac{\partial \mathbf{R}_2(\mathbf{x}_1, \mathbf{x}_2, \dots)}{\partial \mathbf{x}_1} & \\ \vdots & & \ddots \end{pmatrix}_{\mathbf{x}_\alpha = \mathbf{W}_\alpha^n} \right] \begin{pmatrix} \Delta \mathbf{W}_1 \\ \Delta \mathbf{W}_2 \\ \vdots \end{pmatrix}$$
$$= \begin{pmatrix} -\frac{1}{\Omega_1} \mathbf{R}_1(\mathbf{W}_1^n, \mathbf{W}_2^n, \dots) \\ -\frac{1}{\Omega_2} \mathbf{R}_2(\mathbf{W}_1^n, \mathbf{W}_2^n, \dots) \\ \vdots \end{pmatrix}. \tag{9.28}$$

Multiplying each of the major rows above one obtains

$$\left[\frac{1}{\Delta t} \begin{pmatrix} \Omega_1 \mathbf{I} & 0 & \cdots \\ 0 & \Omega_2 \mathbf{I} & \\ \vdots & & \ddots \end{pmatrix} + \begin{pmatrix} \frac{\partial \mathbf{R}_1(\mathbf{x}_1, \mathbf{x}_2, \dots)}{\partial \mathbf{x}_1} & \frac{\partial \mathbf{R}_1(\mathbf{x}_1, \mathbf{x}_2, \dots)}{\partial \mathbf{x}_2} & \cdots \\ \frac{\partial \mathbf{R}_2(\mathbf{x}_1, \mathbf{x}_2, \dots)}{\partial \mathbf{x}_1} & \frac{\partial \mathbf{R}_2(\mathbf{x}_1, \mathbf{x}_2, \dots)}{\partial \mathbf{x}_2} & \\ \vdots & & \ddots \end{pmatrix}_{\mathbf{x}_\alpha = \mathbf{W}_\alpha^n} \right] \begin{pmatrix} \Delta \mathbf{W}_1 \\ \Delta \mathbf{W}_2 \\ \vdots \end{pmatrix}$$
$$= \begin{pmatrix} -\mathbf{R}_1(\mathbf{W}_1^n, \mathbf{W}_2^n, \dots) \\ -\mathbf{R}_2(\mathbf{W}_1^n, \mathbf{W}_2^n, \dots) \\ \vdots \end{pmatrix}. \tag{9.29}$$

As previously noted, the only Jacobians $\partial \mathbf{R}_I / \partial \mathbf{W}_J$ that are non-zero are those for which $J \in M(I)$. Thus, the second submatrix of the above is mostly sparse. The Ith major row can be written as

$$\sum_{J=M(I)} \left[\frac{\Omega_I}{\Delta t} \delta_{IJ} + \left. \frac{\partial \mathbf{R}_I(\mathbf{x}_1, \mathbf{x}_2, \ldots)}{\partial \mathbf{x}_J} \right|_{\mathbf{x}_\alpha = \mathbf{W}_\alpha^n} \right] \Delta \mathbf{W}_J = -\mathbf{R}_I(\mathbf{W}_1^n, \mathbf{W}_2^n, \ldots). \tag{9.30}$$

Part V

Finite Element for PDE's

Chapter 10

Elliptic

- Consider the boundary value problem in which a solution u is sought such that

$$
\begin{aligned}
Au &= f & \text{in } \Omega = (0,1) \\
u &= 0 & \text{on } \Gamma = 0, 1
\end{aligned}
\tag{10.1}
$$

  where $Au = -(au')' + cu$.

- The weak formulation of the above is to find the weak solution $u \in H_0^1$ such that

$$
a(u, v) = (f, v) \qquad \forall v \in H_0^1,
\tag{10.2}
$$

  where $a(u, v) = \int_\Omega au'v' + cuv \, dx$, and $(f, v) = \int_\Omega fv \, dx$.

- Partition the domain into M grid elements, and introduce $S_h \subset H_0^1$ as the set of functions that are linear within each grid element. We now aim to find $u_h \in S_h$ such that

$$
a(u_h, v_h) = (f, v_h) \qquad \forall v_h \in S_h.
\tag{10.3}
$$

- $\{\Phi_i\}_{i=1}^{M-1}$ is the basis for S_h, where $M - 1$ is the total number of interior points. That is, any $v_h \in S_h$ can be written as $v_h = \sum_{i=1}^{M-1} V_i \Phi_i$. Equation (10.3) is then automatically satisfied if the following is satisfied

$$
a(u_h, \Phi_i) = (f, \Phi_i) \qquad \text{for } i = 1, ..., M - 1.
\tag{10.4}
$$

- Since $u_h \in S_h$, we can write $u_h(x) = \sum_{j=1}^{M-1} U_j \Phi_j(x)$. Thus, the above becomes

$$
\sum_{j=1}^{M-1} U_j a(\Phi_j, \Phi_i) = (f, \Phi_i) \qquad \text{for } i = 1, ..., M - 1.
\tag{10.5}
$$

- Define the vectors $\mathbf{U}$ and $\mathbf{b}$, as those whose components are U_j and (f, Φ_i), respectively. Define the matrix $\mathbf{A}$ as that whose components are $a(\Phi_j, \Phi_i)$, where i denotes the row and j the column. Then, the equation above can be written as

$$
\mathbf{AU} = \mathbf{b}.
\tag{10.6}
$$

Chapter 11

Parabolic

Chapter 12

Hyperbolic

Appendix A

Notes on functional analysis

A.1 Classification of methods

- Finite element method: local trial functions

- Spectral method: global trial functions

- Galerkin method: trial functions equal to test functions

- Collocation method: trial functions not equal to test functions (test functions are delta functions)

A.2 Some terminology

- Cauchy sequence: a sequence v_1, v_2, v_3, ... is a Cauchy sequence if for every possitive real number ϵ, there is a possitive integer N such that for all possitive integers $m, n > N$, $||v_m - v_n|| < \epsilon$.

- Complete inner produce space: an inner product space V is complete if every Cauchy sequence $\{v_i\}_{i=1}^{\infty}$ in V has a limit $v = \lim v_i \in V$.

- Compact set: a set is compact if it is bounded and closed.

- Coercive bilinear form: a bilinear form $a(:,:)$ is coercive in a Hilbert space V if

$$a(v, v) \geq \alpha ||v||_V^2, \qquad \forall v \in V, \qquad \text{with } \alpha > 0. \tag{A.1}$$

- Bounded linear form: a linear form is bounded in the normed vector space V if there exists an $M > 0$ such that $|L(v)| \leq M||v||$, for every $v \in V$.

- Bounded bilinear form: a bilinear form is bounded in the normed vector space V if there exists and $M > 0$ such that $|a(w, v)| \leq M||w|| \, ||v||$, for every $w, v \in V$.

A.3 Useful equalities and inequalities

$$|ab| = |a||b| \qquad \forall a, b \in \mathbb{C} \tag{A.2}$$

$$|a + b| \leq |a| + |b| \qquad \forall a, b \in \mathbb{C} \tag{A.3}$$

$$|(w, v)| \leq ||w|| \, ||v|| \qquad \forall v, w \in \text{Inner product space (Cauchy-Schwarz inequality)} \tag{A.4}$$

$$||w + v|| \leq ||w|| + ||v|| \qquad \forall v, w \in \text{Normed space (triangle inequality)} \tag{A.5}$$

$$\left| \int_a^b v(x) \, dx \right| \leq \int_a^b |v(x)| \, dx \tag{A.6}$$

$$\left\| \int_a^b v(x, y) \, dx \right\| \leq \int_a^b ||v(x, y)|| \, dx \text{ where the norm is over the y-domain.} \tag{A.7}$$

A.4 The weak derivative

If $v \in C^1(\bar{\Omega})$, then through integration by parts

$$\int_\Omega \frac{\partial v}{\partial x_i} \phi \, dx = -\int_\Omega v \frac{\partial \phi}{\partial x_i} \, dx \qquad \forall \phi \in C_0^1(\Omega). \tag{A.8}$$

However, if $v \in L_2(\Omega)$ but not necessarily in $C^1(\bar{\Omega})$, we cannot write the equation above. Instead, we ask, is there a function w such that the following holds?

$$\int_\Omega w\phi \, dx = -\int_\Omega v \frac{\partial \phi}{\partial x_i} \, dx \qquad \forall \phi \in C_0^1(\Omega). \tag{A.9}$$

This can be rewritten as $(w, \phi) = L(\phi)$, where $L(\phi) = -\int_\Omega v \frac{\partial \phi}{\partial x_i} dx$. If $L(\phi)$ is bounded in L_2, Riesz' representation theorem then states a unique solution $w \in L_2(\Omega)$ exists. This w is the weak derivative.

More generally, if $v \in C^k(\bar{\Omega})$, then through integration by parts

$$\int_\Omega D^\alpha v\phi \, dx = (-1)^{|\alpha|} \int_\Omega v D^\alpha \phi \, dx \qquad \forall |\alpha| \leq k, \, \forall \phi \in C_0^{|\alpha|}(\Omega). \tag{A.10}$$

However, if $v \in L_2(\Omega)$ but not necessarily in $C^k(\bar{\Omega})$, we cannot write the equation above. Instead, we ask, is there a function w such that the following holds?

$$\int_\Omega w\phi \, dx = (-1)^{|\alpha|} \int_\Omega v D^\alpha \phi \, dx \qquad \forall \phi \in C_0^{|\alpha|}(\Omega). \tag{A.11}$$

As before, if the left-hand-side operator is bounded, then we have a unique solution $w \in L_2(\Omega)$. This w is the weak derivative. Often, weak derivatives are referred to as "$D^\alpha v$ in the weak sense."

A.5 Function spaces

- C^0: the set of all continuous functions

- C^k the set of all functions whose derivatives up to order k all exist and are continuous. These are called continuously differentiable functions of order k.

- L_2: the set of all functions that are square integrable.

- H^k: the set of all L_2 functions whose weak partial derivatives up to order k also belong to L_2.

- Let Ω be a bounded domain in $\mathbb{R}^d$ with smooth or polygonal boundary. Then part of the Sobolev embedding theorem can be written as

$$H^k(\Omega) \subset C^l(\bar{\Omega}) \text{ if } k > l + d/2. \tag{A.12}$$

Thus, we have $H^m(\Omega) \subset C^{m-1}(\bar{\Omega})$ for $\Omega \in \mathbb{R}$ and $H^m(\Omega) \subset C^{m-2}(\bar{\Omega})$ for $\Omega \in \mathbb{R}^2$ or $\mathbb{R}^3$.


Figure A.1: Map of function spaces.

Space	Norm	Inner product
$C(M)$	$\|v\|_C = \sup\limits_{x \in M} \|v(x)\|$	X
$C^k(M)$	$\|v\|_{C^k} = \max\limits_{\|\alpha\| \le k} \|D^\alpha v\|_C$ $\|v\|_{C^k} = \max\limits_{\|\alpha\| = k} \|D^\alpha v\|_C$	X
$L_p(\Omega)$	$\|v\|_{L_p} = \left(\int_\Omega \|v\|^p \, dx \right)^{1/p}$	X
$L_2(\Omega)$	$\|v\|_{L_2} = \left(\int_\Omega \|v\|^2 \, dx \right)^{1/2}$	$(v,w) = \int_\Omega vw^* \, dx$
$H^k(\Omega)$	$\|v\|_k = \left(\sum\limits_{\|\alpha\| \le k} \|D^\alpha v\|^2 \right)^{1/2}$ $\|v\|_k = \left(\sum\limits_{\|\alpha\| = k} \|D^\alpha v\|^2 \right)^{1/2}$	$(v,w)_k = \sum\limits_{\|\alpha \le k\|} (D^\alpha v, D^\alpha w)$