Replication of the polytomous person-fit Monte Carlo in Beck (2023)

28 October 2026

Abstract

Do the classification rates and the ANOVA tables in Beck (2023) follow from the Monte Carlo described there? All 504 partial omega squared values in Appendix C agree with the printed F statistics at $N = 32{,}000$, to within 0.005. Specificity and negative predictive value in Tables A24–A26 sit within 0.006 of the identity that holds when 50 of 1,000 respondents are flagged. The sensitivity levels do not. None of the eighteen grand sensitivities fall inside a two-standard-error band, before or after Holm. The nearest cells are normed Guttman errors for midpoint responding, 0.0035 against a printed 0.00, and for extreme responding, 0.284 against 0.27.

1 The question, and the headline

This section answers whether the printed rates and the printed ANOVA tables come from the Monte Carlo in the dissertation. The ANOVA arithmetic and the relationship among the four rates do. The sensitivity levels do not, under the assumptions stated below.

Beck (2023) [1] studies whether three nonparametric person-fit statistics detect response bias on ordered polytomous items. The design is six bias types, four numbers of response options, four dimensionalities, and two test lengths: 192 conditions. Each condition has 900 ordinary respondents and 100 biased respondents, repeated 1,000 times. The statistics are $U3$, the normed number of Guttman errors, and the person coefficient H_i^T. The cutoff in each replication is the median of the 5th percentiles of 1,000 bootstrap samples. Tables A24–A26 collect the rates. Sensitivities run from 0.00, for midpoint responding on the normed Guttman errors and on $U3$, to 0.29, for careless responding on the normed Guttman errors. Specificities run from 0.94 to 0.98.

Two checks use only the printed numbers. Partial omega squared, computed from each printed F at $N = 32{,}000$, matches all 504 entries in Tables C1–C18 to within 0.005, which is the half-unit of the printed two-decimal column. When exactly 50 of 1,000 people are flagged and 100 of them are the biased respondents, specificity, positive predictive value, and negative predictive value are functions of sensitivity. Specificity and negative predictive value in Tables A24–A26 sit within 0.006 of that identity. Positive predictive value sits within 0.02.

The generative rerun does not land on the sensitivity column. The reported run uses the linear predictor in Equation 23 as printed, 40 replications, and an extreme-response constant $\varepsilon = 0.5$. Of the eighteen grand sensitivities, none fall inside a two-standard-error band, before or after Holm. The normed Guttman errors come nearest: midpoint responding is 0.0035 against 0.00, and extreme responding is 0.284 against 0.27. The combined standard errors are 0.00018 and 0.00088. Two factor-margin cells do match, and two more sit just outside the band. $U3$, computed from the same definition as PerFit 1.4.7, does not follow the printed $U3$ column on either tail. Beck

(2015) [2], cited for the moments, was not available on the first attempt to fetch it. The copy obtained after that failure prints scale correlations and factor loadings, not graded thresholds. Using those correlations in place of Table A1 moves the normed-Guttman rates by less than 0.01. A hand-written graded sampler, run for the same 40 replications, puts none of the eighteen grand sensitivities inside the band. The largest gap between that sampler and `mirt` on a grand sensitivity is 0.0041. PerFit 1.4.6, the release current in May 2023, and mokken 3.0.6 score the same matrices as PerFit 1.4.7 and mokken 3.1.2.

The original work is the design, the bias definitions, and the printed tables. The calculations below are ours: the arithmetic checks, the Monte Carlo, and the comparison. Multiplicity is applied only to our check that a printed rate and our rate agree. The dissertation's own tests are one classification per replication.

2 What we replicated

This section answers which printed claims agree with a direct calculation. Table 1 is that comparison. "Match" means the same number, or a Monte Carlo gap no larger than two combined standard errors. "Partial" means one piece of the claim holds and another does not. "Close" means a gap sitting on the edge of that band, or a gap that disappears at the printed rounding. "No match" means a rate that remains outside the band. The combined standard error uses the printed count of 1,000 replications and our count of 40, with our within-cell standard deviation as the plug-in for both.

The omega squared row is an algebraic check, not a second simulation. For an effect with degrees of freedom ν and printed F,

$$\hat{\omega}_p^2 = \frac{\nu(F-1)}{\nu(F-1)+N}, \qquad N = 32{,}000.$$

The largest absolute gap across the 504 effects is 0.0050. The script is `simulation/extract_published.py`, and the row-level file is `simulation/out/anova_check.csv`.

The identity row uses a fixed flag count. With 100 biased respondents and 50 flags,

$$\mathrm{TP} = 100\,s, \quad \mathrm{FP} = 50 - \mathrm{TP}, \quad \mathrm{spec} = \frac{900-\mathrm{FP}}{900}, \quad \mathrm{PPV} = \frac{\mathrm{TP}}{50}, \quad \mathrm{NPV} = \frac{850+\mathrm{TP}}{950},$$

where s is sensitivity. A 5% rule cannot produce a sensitivity above 0.50. Every printed grand sensitivity is at most 0.29, so the identity is inside that bound. The printed rows are averages of ratios, so the identity applied to the averaged sensitivity is an approximation. On the 18 grand rows other than the mean row, all three derived rates sit within 0.02 of the printed rates, and specificity and negative predictive value sit within 0.006. The file is `simulation/out/identity_residuals.csv`.

Table 2 is the normed-Guttman grand column at $\varepsilon = 0.5$. Midpoint responding is the floor in the dissertation and in the rerun. Extreme responding is the highest rate in that column once careless responding is set aside, in the dissertation and in the rerun. The levels still miss the two-standard-error band. Careless responding sits on the 0.50 ceiling, which is what perfect separation looks like when 50 flags are available for 100 biased respondents. The printed careless rate is 0.29.

The midpoint grand rate prints as 0.00 at two decimals, and 0.0035 also prints as 0.00. Against an exact zero the gap is about twenty standard errors, so the row stays a Monte Carlo miss, and it is also a rounding display. The same remark covers the factor-margin match at seven options, 0.0031 against 0.0026.

Claim	Published	Ours	Verdict
Partial omega squared, 504 effects	Two decimals in Tables C1–C18	From the printed F, within 0.005	match
Grand specificity and NPV	Tables A24–A26	Within 0.006 of the 5% identity	match
Grand positive predictive value	Tables A24–A26	Within 0.02 of that identity	close
Guttman, acquiescence, length 36	0.072	0.0718	match
Guttman, midpoint, seven options	0.0031	0.0026	match
Guttman, extreme, three dimensions	0.260	0.263	close
Guttman, extreme, six options	0.281	0.275	close
Guttman grand, midpoint	0.00	0.0035	no match
Guttman grand, extreme	0.27	0.284	no match
Guttman grand, careless, every item	0.29	0.500	no match
Eighteen grand sensitivities	Tables A24–A26	0 of 18 inside two SE; Holm keeps the misses	no match
$U3$ grand column, either tail	Same shape as the Guttman column	The two columns separate	no match

Table 1: Printed claims against our calculations. Rates are proportions. The Monte Carlo rows use $\varepsilon = 0.5$ and the aberrant-direction tail: low H_i^T, high normed Guttman errors, high $U3$.

H_i^T is higher than the printed column on five of the six biases. Disacquiescence is the nearest, 0.033 against 0.04, with combined standard error 0.00049. $U3$ on the upper tail flags midpoint responding at 0.34 where the page prints 0.00, and flags acquiescence at 0.51 where the page prints 0.05. The lower tail of $U3$ matches the printed midpoint zero in the $\varepsilon = 1$ run and misses it, at 0.0048, in the $\varepsilon = 0.5$ run. The rest of that lower-tail column does not follow the page.

Of the 60 factor-margin sensitivities for the normed Guttman errors at $\varepsilon = 0.5$, two are inside the raw band and two are close. After Holm, three of the sixty are retained as matches. The two raw matches are Table A6, test length 36, acquiescence, and Table A12, seven options, midpoint responding. The full grid is `simulation/out/comparison_eps05.csv`.

3 What we did ourselves, and what we took from others

This section answers which pieces are ours. The dissertation supplies the design, the equations, Tables A1–A3, and the result tables. We supply the Monte Carlo, the arithmetic checks, and the comparison.

Responses are drawn from `mirt` 1.36 [6] through `simulation/monte_carlo.R`. The person coefficient is the rearrangement formula in the `se = FALSE` branch of `mokken` 3.1.2 [7], written out in `simulation/personfit.R`. Normed Guttman errors and $U3$ follow the complete-data branches of PerFit 1.4.7 [8], in `simulation/personfit.R` and `simulation/personfit.R`. On six random

Bias	Published	Ours	SE	Verdict
Acquiescence	0.05	0.062	0.00055	no match
Disacquiescence	0.13	0.047	0.00055	no match
Midpoint	0.00	0.0035	0.00018	no match
Extreme	0.27	0.284	0.00088	no match
Social desirability	0.08	0.031	0.00042	no match
Careless	0.29	0.500	0.00005	no match

Table 2: Normed Guttman sensitivity, Tables A24, from 40 replications at $\varepsilon = 0.5$. The standard error is the combined standard error of the two means.

matrices the person coefficient matches `coefH` with a maximum absolute difference of 0. The other two statistics match the package before it rounds the exported scores to four decimals; the largest absolute difference against those rounded scores is 5×10^{-5}. That check is `simulation/out/validate_personfit.csv`. The graded probabilities from `mirt` match plogis$(a^\top\theta - b)$ with a maximum absolute difference of 0 in one and two factors.

R 4.3.3 [5] is the language because the dissertation names R. `mirt` is the generator the dissertation names. The current `mirt` asks for `Deriv`, and the current `Deriv` asks for R 4.5, so the run uses `mirt` 1.36 (21 March 2022) with `Deriv` 4.1.6 from the CRAN archive. `mokken` and PerFit are the scoring packages the dissertation names. MASS 7.3-60.0.1 [9] draws the latent normal vectors. There is no Lean component: the checks are a statistical Monte Carlo, so R is the right tool. Versions are in `simulation/out/session_info.txt`.

4 Assumptions

This section answers which inputs we supplied because the dissertation does not print them. Each subsection is one such input. A choice the dissertation states is recorded in Section 5.

4.1 The size of the extreme-response constant

Equation 26 prints ε as a constant and gives its sign. The magnitude is not printed. The reported run uses $\varepsilon = 0.5$, so midpoint boundaries are spread by $e^{0.5}$ and extreme boundaries are shrunk by $e^{-0.5}$. The same grid at $\varepsilon = 1$ gives an extreme-response Guttman sensitivity of 0.186. At $\varepsilon = 2$ that sensitivity is 0.074. At $\varepsilon = 0.5$ it is 0.284, against the printed 0.27. Midpoint sensitivity stays at the floor for all three values: 0.0035, 0.0017, and 0.000. The shift biases do not use ε, and their rates agree across the three runs to three decimals. The files are `simulation/out/mc_ink_eps0.5_c1_r40.csv`, `simulation/out/mc_ink_eps1_c1_r40.csv`, and `simulation/out/mc_ink_eps2_c1_r8.csv`.

4.2 Seven-option boundaries

Table A2, Figure 1, prints uniforms for four, five, and six options and has no row for seven. The prose names terciles, quartiles, and quintiles and stops at six options. Seven options need six boundaries. The run splits the widest six-option interval, from -13.71 to -6.68, at its midpoint, and uses the six contiguous intervals that produces. That choice is `simulation/monte_carlo.R`.

Uniform Distributions of Item Boundary Parameters by Condition

k	Cat. 1	Cat. 2	Cat. 3	Cat. 4
4	*U*(-13.71, -5.19)	*U*(-5.19, -2.51)	*U*(-2.51, 2.42)	
5	*U*(-13.71, -5.81)	*U*(-5.81, -2.19)	*U*(-2.19, 2.42)	*U*(1.5, 3)
6	*U*(-13.71, -6.68)	*U*(-6.68, -4.78)	*U*(-4.78, -3.09)	*U*(-3.09, -1.42)

Note. Cat stands for Category

Figure 1: Table A2. The $k = 7$ row is absent. For $k = 5$, category 3 and category 4 overlap.

4.3 One draw of the boundaries, then a sort

Table A2 gives distributions. The realized boundaries are not printed, and no seed is printed. The run draws each boundary once from its interval under seed 20230511, then sorts the boundaries within each item so they increase. For four and six options the intervals share only endpoints, so the sort does not move an interior draw. For five options, category 3 is $U(-2.19, 2.42)$ and category 4 is $U(1.5, 3)$, so independent draws can arrive out of order. The item indices in each of the 32 static tests are `simulation/out/item_samples.csv`.

4.4 Careless replacement of every item

The dissertation says a uniform random option replaces the raw response on the selected items, and that each option is equally likely. It does not say how many items are selected. The reported run replaces every item. Replacing a fraction 0.5, 0.2, or 0.1 of the items leaves the careless Guttman sensitivity at 0.500, 0.485, and 0.444, against the printed 0.29. The gap does not close under those fractions. The files are the `c0.5`, `c0.2`, and `c0.1` tables in `simulation/out`.

4.5 The sample standard deviation in the shift

Equations 24 and 25 add or subtract s_{δ_i}, the standard deviation of item i's boundaries. The run uses the sample standard deviation, with divisor $n - 1$. Figure 2 is the printed shift.

$$\delta^{*}_{ki} = \delta_{ki} + s_{\delta_i}, \tag{24}$$

Figure 2: Equation 24, the acquiescence shift.

4.6 Scaling constant D = 1

The paragraph under Equation 23 calls $D = 1.702$ optional and $D = 1$ the other choice. The run uses $D = 1$, which is the logistic metric of `mirt`'s graded generator.

4.7 One latent sample, then a trim to 900

The dissertation draws 1,000 latent vectors, drops zero-variance response rows, and then drops rows at random until 900 remain. The run draws one shared sample of 1,000 from the Table A1 normal distribution and trims each of the 32 response matrices separately. The means and covariances are Figure 3. The socially desirable means are the four printed values in Figure 4, with the same covariance.

Covariance Matrix and Means for Data Simulation

	Mean	**D1**	**D2**	**D3**	**D4**
D1	*0.03*	1.02			
D2	*0*	0.49	1.11		
D3	*0.09*	0.31	0.38	0.95	
D4	*0.02*	0.43	0.89	0.40	0.96

Figure 3: Table A1. The matrix is positive definite, with eigenvalues 2.52, 0.71, 0.67, and 0.14.

standard deviation below the latent means used to create the base data sets (the latent means will be: ξ_1 = -.982; ξ_2 = -.964; ξ_3 = -.903; and ξ_4 = -.868). All other aspects of this multivariate normal distribution were kept the same as the distribution used to generate

Figure 4: The socially desirable means on page 66.

4.8 A sample quantile in place of the bootstrap median

The dissertation takes the median of 1,000 bootstrap 5th percentiles. The run uses R's type-7 sample quantile at 0.05 or 0.95. On one continuous sample of size 1,000, that median and the sample 5th percentile differ by 3×10^{-4}. On a sample with a point mass, they differ by 6×10^{-4}. The file is `simulation/out/bootstrap_cutoff.csv`, from `simulation/bootstrap_cutoff.R`. The comparison bands are an order of magnitude larger than those gaps only for the careless ceiling, where the standard error is 5×10^{-5}. Elsewhere the quantile substitution is smaller than the band and does not account for the misses.

5 Ambiguities that were resolved

This section answers which readings of the page were settled by an artifact. Each subsection names the script, the output, and the command. The commit that contains them is the commit that added this note. Regenerate with the commands in `README.md`.

5.1 Equation 23 is the sum that multiplies the threshold by each slope

Figure 5 prints

$$P_{jk}(\theta) = \frac{1}{1 + \exp\left[-D \sum_{h=1}^{H} a_{jh}(\theta_h - b_{jk})\right]}.$$

The usual graded predictor, and `mirt`'s, is $a^\top\theta - b_{jk}$. The printed sum equals $a^\top\theta - b_{jk}\sum_h a_{jh}$. The rerun passes `mirt` the intercept $-b_{jk}\sum_h a_{jh}$. Under the usual intercept $-b_{jk}$, the trim to 900 non-constant rows fails on the grid: a direct run stopped with fewer than 900 such rows in the cells it reached. A single twelve-item slice under that usual intercept has 703 non-constant rows out of 1,000. The same slice under the printed sum has 754. The full printed-sum grid does trim to 900 in every cell. The script is `simulation/standard_collapse.R`. The generator is `simulation/monte_carlo.R`.

2016). One expression of the MGRM is given in Equation 23:

$$P_{jk}(\boldsymbol{\theta}) = \frac{1}{1 + \exp\left[-D \sum_{h=1}^{H} \left[a_{jh}\left(\theta_h - b_{jk}\right)\right]\right]}, \tag{23}$$

Figure 5: Equation 23 as printed.

5.2 The aberrant tail is the high tail for U3 and for Guttman errors

PerFit documents both statistics as increasing in misfit, from 0 to 1. H_i^T is low when a person is less scalable. The method chapter states one 5th-percentile rule for all three. Flagging the low tail of the normed Guttman errors, where many respondents share a value at the quantile, flags about 283 people rather than about 50, and the careless sensitivity on that tail is 0. Flagging the high tail flags about 51 people. The high tail is the reading in Table 2. The low tail is in the same output file, under the column prefix `G_lower`.

5.3 Table A1 is the lower triangle including the variances

The prose says the off-diagonal covariances run from 0.31 to 1.11. Figure 3 places 1.11 on the diagonal of the second dimension, and places 0.49, 0.31, 0.38, 0.43, 0.89, and 0.40 off the diagonal. The simulation uses the figure. The prose on the same page says the means run from -0.001 to 0.092. The figure prints 0, 0.02, 0.03, and 0.09. The simulation uses the figure.

5.4 The package scores match the fast formulas

`mokken::coefH` with standard errors on a $36 \times 1{,}000$ matrix exhausted memory in this environment. The `se = FALSE` branch is a covariance and a covariance of the column-sorted matrix, and it finishes in a fraction of a second. The validation command is `Rscript validate_personfit.R out`. The output is `simulation/out/validate_personfit.csv`.

6 What remains unresolved

This section answers which gaps are still open, and which variations were already run.

The eighteen grand sensitivities remain outside the two-standard-error band after Holm. The normed Guttman column has the same shape as the page: a floor at midpoint responding, a high rate at extreme responding, and a ceiling at careless responding. The levels differ. $\varepsilon \in \{0.5, 1, 2\}$ moves the extreme rate through 0.284, 0.186, and 0.074, against 0.27. The value 0.5 is the closest of those three and is still 0.014 above the page, with a standard error of 0.00088. Careless fractions 1, 0.5, 0.2, and 0.1 leave that sensitivity at 0.500, 0.500, 0.485, and 0.444, against 0.29. The fraction does not close the gap under this boundary draw.

$U3$ remains a separate miss. The statistic matches PerFit 1.4.7 before rounding. On these replicates it does not track the printed $U3$ column, which tracks the printed Guttman column. A different PerFit release from 2023, or a different boundary draw, could still produce that tracking. This run does not.

The realized boundaries, the item sample, and the seed are unprinted. A different draw from Table A2 can move a grand mean by more than the Monte Carlo standard error of 1,000 replications, because that standard error describes the redraw of the 100 biased respondents with the items held

fixed. Our band uses our within-cell dispersion as a stand-in for theirs. It is the right band for two runs of one fixed item set. It is a lower bound on the uncertainty that comes from redrawing the items. The misses are large beside that lower bound: several hundredths, on bands of about a thousandth. Redrawing the items remains a live explanation, and so does the unprinted ε.

The sentence that the socially desirable means lie one standard deviation below Table A1 does not recover -0.982, -0.964, -0.903, and -0.868. The run uses those four printed numbers.

7 What the 2015 thesis supplies

This section answers whether Beck (2015) [2] prints the moments and the item slopes the dissertation says it adapted. It prints scale means, scale correlations, and standardized factor loadings. It does not print graded-response boundaries. Beck, Albano, and Smith (2019) [3] compare these statistics on polytomous survey data. The dissertation attributes the boundary and discrimination ranges to fits in `ltm` [4], not to that article. An earlier request for the UTSA file returned HTTP 403. The copy used here is the same bitstream, retrieved after that failure. Its sha256 is `04258 70dc5f65ce8ca1d0c0d80b646e12d81a4c8bf2b2cc0c5dc80084c98c707`. The appendix numbers in the comparison are a transcription of the thesis appendix, checked against the PDF (sha256 `0425 870dc5f65ce8ca1d0c0d80b646e12d81a4c8bf2b2cc0c5dc80084c98c707`). Figure 6 is Table A4 of the thesis.

Means, SDs, and Factor Intercorrelations of MSARI

	M (*SD*)	Anger	Avoid	Alcohol	Agora
Anger	2.30(.91)	1.0			
Avoid	1.96(.92)	.43*	1.0		
Alcohol	1.85(.98)	.29*	.28*	1.0	
Agora	1.53(.72)	.37*	.81*	.33*	1.0

Note. N = 380. Anger = Anger Distress, Avoid = Social Avoidance, Alcohol = Alcohol Reliance, Agora = Agoraphobic Avoidance.

* = $p < .001$

Figure 6: Beck (2015), Table A4. Scale means, standard deviations, and factor correlations for the MSARI-28. $N = 380$.

The dissertation's Table A1 is not this table. The thesis correlations, in the order Anger, Avoid, Alcohol, Agora, are 0.43, 0.29, 0.37, 0.28, 0.81, and 0.33. The correlations implied by Table A1, in the order printed there, are 0.46, 0.32, 0.43, 0.37, 0.86, and 0.42. The largest absolute difference is 0.09. The scale-score covariance, using the printed standard deviations 0.91, 0.92, 0.98, and 0.72, differs from Table A1 by as much as 0.44. The scale means are 2.30, 1.96, 1.85, and 1.53. Table A1's means are near zero. Substituting the scale means into the graded generator leaves every cell with

fewer than 900 non-constant base rows, so that reading cannot be trimmed the way the dissertation describes.

Substituting the thesis correlations, with unit variances and means zero, and with socially desirable means at -1, does run. At 20 replications and $\varepsilon = 0.5$, the normed-Guttman grand sensitivities are 0.063, 0.045, 0.004, 0.291, 0.032, and 0.499, against 0.062, 0.047, 0.003, 0.284, 0.031, and 0.500 on Table A1. No grand sensitivity moves by as much as 0.01. The file is `simulation/out/mc_ink_thesis_corr_eps0.5_c1_r20.csv`.

A slope $a = \lambda/\sqrt{\psi}$ from a standardized loading λ and residual ψ, and the logistic form 1.702 times that slope, were applied to the seven CFA loadings on each factor. The logistic slopes run from 1.28 to 3.76. The dissertation's stated uniforms run from 1.80 to 6.65, and Table A3 realizes slopes up to 6.52. No assignment of the four factors puts the converted ranges on those uniforms. The conversion is `simulation/thesis_map.py` and `simulation/out/thesis_lambda_to_a.csv`. Those 28 logistic slopes, with Table A1 and $\varepsilon = 0.5$ held fixed, were run for eight replications. One cell, seven options and one dimension at length 12, kept 885 non-constant rows and was dropped. On the other 31 cells the normed-Guttman grand sensitivities are 0.031 for acquiescence, 0.122 for disacquiescence, 0.001 for midpoint responding, 0.292 for extreme responding, 0.017 for social desirability, and 0.485 for careless responding. Disacquiescence moves from 0.047 on Table A3 to 0.122, against the printed 0.13. The combined standard error is 0.0017, so the cell remains outside the band. Acquiescence moves from 0.062 to 0.031, away from the printed 0.05. Careless responding stays near the 0.50 ceiling. The file is `simulation/out/mc_ink_tablea1_thesis_cfa_eps0.5_c1_r8.csv`.

8 Why the sensitivities miss

This section answers which missing input can account for the sensitivity gaps, and which inputs were checked and set aside. The ranking uses the size of the movement each input produced.

Cause	Evidence for it	Evidence against it
Extreme-response constant	Extreme Guttman sensitivity moves from 0.074 at $\varepsilon = 2$ to 0.284 at $\varepsilon = 0.5$, toward the printed 0.27.	The closest of those three values is still 0.014 outside a band of width 0.0018. Acquiescence, disacquiescence, social desirability, and careless responding do not use ε, and they miss.
Item slopes and boundaries	Table A3 slopes reach 6.52. Converting the thesis loadings gives slopes from 1.28 to 3.76. Using those slopes moves disacquiescence from 0.047 to 0.122, against 0.13.	The converted ranges are not the stated uniforms. The same run moves acquiescence from 0.062 to 0.031, away from 0.05, and careless responding stays at 0.485. The thesis has no graded thresholds.
Careless-item fraction	The page does not say how many items are replaced.	Fractions 1, 0.5, 0.2, and 0.1 leave the rate between 0.44 and 0.50, against 0.29.
Unprinted boundary draw	The band is for one fixed item set. A new draw from Table A2 is a different experiment.	The gaps are several hundredths. That is possible for one unlucky draw, and it is large beside the redraw of the 100 biased respondents.
Latent covariance	The dissertation says the moments were adapted from Beck (2015).	The thesis correlations move the six Guttman rates by less than 0.01.
$U3$ implementation	The printed $U3$ column tracks the Guttman column. Our $U3$ does not.	Our $U3$ matches PerFit 1.4.7 and PerFit 1.4.6 before those packages round to four decimals. The Guttman misses do not depend on $U3$.
Generator and the trim to 900	The usual `mirt` intercept, and the thesis scale means, both fail the trim.	The printed-sum generator with Table A1 completes the trim and still misses. A hand-written sampler matches `mirt`'s category probabilities to 2×10^{-16} and its grand sensitivities to within 0.0041.
Bootstrap median versus the sample quantile	The dissertation uses the bootstrap median.	On two samples of size 1,000 the two cutoffs differ by 3×10^{-4} and 6×10^{-4}.
Flagging direction	The low tail of the normed Guttman errors flags about 283 people and gives careless sensitivity 0. The high tail flags about 51 and puts midpoint responding on the floor, which is the shape on the page.	The high tail is the comparison in Table 2, and the level gaps remain on that tail.

The first row is the strongest lever that was actually in our hands, and it does not close the column. The slope and boundary row is the live remainder: the thesis does not contain the thresholds the dissertation says were fit with `ltm` [4].

9 A second generator, and the May 2023 packages

This section answers whether the sensitivity misses are the choice of `mirt::simdata` or the 2025 release of PerFit. They are not. No grand sensitivity enters the two-standard-error band under the second generator.

The hand-written sampler is simulation/monte_carlo.R. It draws one uniform per person and item from the linear predictor in Equation 23. Its category probabilities match `mirt` with a maximum absolute difference of 2×10^{-16}, in simulation/out/generator_probs.csv. The same 40 replications, the same 192 conditions, and the same four rates were then drawn with that sampler. Against the printed tables, none of the eighteen aberrant-direction grand sensitivities, and none of the matching specificity, positive predictive value, or negative predictive value rows, fall inside the band, before or after Holm. The file is simulation/out/comparison_hand_all.csv . The two generators' grand sensitivities differ by at most 0.0041. Eight of those eighteen pairs sit outside two standard errors of each other. Three of the eight have a z between 2 and 3, and Holm brings those three inside. Five remain outside. The largest absolute gap is extreme responding on the normed Guttman errors, 0.284 on the `mirt` stream and 0.280 on the hand-written stream, both against the printed 0.27. Careless responding on that statistic differs by 0.0003 and is one of the five, because both rates sit on 0.50 and the standard error is about 6×10^{-5}. On the other three rates the largest absolute gap is 0.0089, for H_i^T positive predictive value under acquiescence. The comparison is simulation/out/generator_compare.csv.

PerFit 1.4.6, dated 15 October 2021, was the release current through May 2023. PerFit 1.4.7 is the 2025 release used in the first grid. `Gnormed.poly` and `U3poly` are the same in the two releases. mokken 3.0.6, dated 8 March 2021, was current until mokken 3.1.0 on 26 June 2023. Its `coefH` branch with standard errors turned off is the same rearrangement as mokken 3.1.2. `mirt` 1.39 was packaged on 29 May 2023 (Pacific). Its `simdata` body differs from `mirt` 1.36 by one example, and the two `src` trees match. Eight complete matrices, with four, five, six, and seven options and with 12 and 36 items, scored by PerFit 1.4.6 and by mokken 3.0.6, match the fast functions that match the later packages. Every maximum absolute difference in simulation/out/version_check.csv is 0. The 40-replication grid is already scored by those functions. Installing the May 2023 releases and rescoring matrices of this design's sizes therefore does not move a rate. No grand sensitivity enters the band under those releases. A second random grid under the old package names would redraw the respondents. It would not change the scoring rule that produced the misses.

10 Which checks were run

This section answers which of the checks that have closed gaps in earlier replications were applied here.

Check	Before this note's follow-up	Result
Reread the displayed equations and tables	Yes	Equation 23, Table A1, and Table A2 match the page images. The $k = 7$ row is absent.
Swap one assumption at a time	Epsilon and the careless fraction	Thesis correlations and the loading-to-slope map were added. Correlations move rates by less than 0.01. The slopes move disacquiescence close to the printed value and move acquiescence away from it.
Back-solve the unprinted constant from the margins	Yes, three values of ε	0.5 is the closest for extreme responding and remains outside the band.
Match the person-fit code to the packages	Yes	H_i^T matches `mokken`. $U3$ and the normed Guttman errors match PerFit 1.4.7 before rounding.
Hand-written generator against `mirt`	Probabilities only	Full 40-replication grid now run. Probabilities match to 2×10^{-16}. No grand sensitivity enters the printed band. The largest generator gap on a grand sensitivity is 0.0041.
Package versions from May 2023	No	PerFit 1.4.6 and mokken 3.0.6 are the releases current then. `mirt` 1.39 (29 May 2023, Pacific) has the same `simdata` body and the same `src` as 1.36, apart from one example. Same-matrix score differences are 0. The grid is already scored by those functions, so no grand sensitivity enters the band.
More replications	40	The combined standard errors on the grand rates are about 10^{-3} or smaller. A gap of 0.01 stays outside two standard errors at any larger replication count.

The bootstrap-median cutoff was checked on two artificial samples, not on every replication of the grid. The differences were 3×10^{-4} and 6×10^{-4}.

11 Code and source availability

This section answers where the inputs and the outputs live. The dated ledger is in `INVESTIGATION.md`.

The dissertation is Beck (2023) [1], `https://digitalcommons.unl.edu/cehsdiss/425`. The PDF used here has sha256 `86c3bb482efadc385cd52f7ea12dc33c50b9b70b4ce6111aedb075a12968f62b`. It is the Wayback snapshot `20240907085051` of `https://digitalcommons.unl.edu/cgi/viewcontent.cgi?article=1436&context=cehsdiss`. A direct request for that URL on 28 October 2026 returned a Cloudflare challenge page. The PDF is not in git.

The thesis is Beck (2015) [2], `https://rrpress.utsa.edu/server/api/core/bitstreams/4fbd58d2-5896-4dea-ab69-300c5c676a07/content`, ProQuest No. 1588285. An earlier fetch of that file returned HTTP 403. The copy obtained after that failure has sha256 `0425870dc5f65ce8ca1d0c0d80b646e12d81a4c8bf2b2cc0c5dc80084c98c707`. It is not in git. The loadings used in Section 7 are a transcription of the thesis appendix, checked against the PDF (sha256 `0425870dc5f65ce8ca1d0c0d80b646e12d81a4c8bf2b2cc0c5dc80084c98c707`).

No sentence in the dissertation names a script archive. The public GitHub account `MFBeck` has two repositories, `Hello_Jenkins` and `jenkins_test`, cloned on 28 October 2026; both are Jenkins demonstrations. An OSF search, a Zenodo search, and a GitLab search on that date did not return

a simulation archive for this dissertation. PerFit's source for the two polytomous statistics is the repository https://github.com/jorgetendeiro/PerFit, version 1.4.7.

12 Next steps

This section answers what would replace an assumption with a printed input. The 2015 thesis is in hand and does not print the graded thresholds. A seed, the `ltm` [4] boundary matrix, or an R `sessionInfo` record from the dissertation run would decide whether the sensitivity gaps are that unpublished fit. The check is the same Monte Carlo with those inputs in place of seed 20230511 and of $\varepsilon = 0.5$.

13 Artifacts

This section lists each claim, the file that holds it, and the command that regenerates it. Commands run from `formalization/polytomous-person-fit/simulation` unless the path says otherwise. The PDF path below is the copy named in Section 11.

Claim	File	Command
Discriminations, Tables A6–A26, Tables C1–C18	simulation/out/discriminations.csv and the published CSV files	`python3 extract_published.py PDF out`
Omega squared from the printed F	simulation/out/anova_check.csv	the same command
Identity residuals	simulation/out/identity_residuals.csv	the same command
Package agreement	simulation/out/validate_personfit.csv	`Rscript validate_personfit.R out`
Forty replications, $\varepsilon = 0.5$	simulation/out/mc_ink_eps0.5_c1_r40.csv	`Rscript monte_carlo.R out 40 ink 0.5 4 1`
Forty replications, $\varepsilon = 1$	simulation/out/mc_ink_eps1_c1_r40.csv	`Rscript monte_carlo.R out 40 ink 1 4 1`
Comparison, $\varepsilon = 0.5$	simulation/out/comparison_eps05.csv	`Rscript score_gaps.R` on that file
Quantile against bootstrap median	simulation/out/bootstrap_cutoff.csv	`Rscript bootstrap_cutoff.R out`
Loading-to-slope map	simulation/out/thesis_lambda_to_a.csv	`python3 thesis_map.py`
Thesis correlations, 20 replications	simulation/out/mc_ink_thesis_corr_eps0.5_c1_r20.csv	`Rscript monte_carlo.R out 20 ink 0.5 2 1 thesis_corr`
CFA slopes, eight replications	simulation/out/mc_ink_tablea1_thesis_cfa_eps0.5_c1_r8.csv	`Rscript monte_carlo.R out 8 ink 0.5 1 1 tablea1 thesis_cfa`
Hand-written generator, 40 replications	simulation/out/mc_hand_ink_tablea1_tablea3_eps0.5_c1_r40.csv	`Rscript monte_carlo.R out 40 ink 0.5 2 1 tablea1 tablea3 hand`
Hand generator against the printed tables	simulation/out/comparison_hand_all.csv	`Rscript score_gaps.R out/mc_hand_ink_tablea1_tablea3_eps0.5_c1_r40.csv out all comparison_hand_all.csv`
Category probabilities, hand against `mirt`	simulation/out/generator_probs.csv	`Rscript check_generator.R out`
Generator comparison	simulation/out/generator_compare.csv	`Rscript compare_generators.R out/mc_ink_eps0.5_c1_r40.csv out/mc_hand_ink_tablea1_tablea3_eps0.5_c1_r40.csv out`
May 2023 package scores	simulation/out/version_check.csv	`Rscript version_check.R out`
Crops	paper/figures	`python3 paper/figures/crop_pages.py PDF`

References

[1] M. F. Beck. *The Examination of Nonparametric Person-Fit Statistics as Appropriate Measures of Response Bias in Ordered Polytomous Items*. Ph.D. dissertation, University of Nebraska–Lincoln, May 2023. https://digitalcommons.unl.edu/cehsdiss/425.

[2] M. F. Beck. *The Multidimensional Social Anxiety Response Inventory (MSARI): Development and Preliminary Examination of Psychometric Properties*. Master's thesis, The University of Texas at San Antonio, 2015. ProQuest No. 1588285. https://rrpress.utsa.edu/server/api/core/bitstreams/4fbd58d2-5896-4dea-ab69-300c5c676a07/content.

[3] M. F. Beck, A. D. Albano, and W. M. Smith. Person-fit as an index of inattentive responding: A comparison of methods using polytomous survey data. *Applied Psychological Measurement*, 43:374–387, 2019.

[4] D. Rizopoulos. ltm: An R package for latent variable modeling and item response theory analyses. *Journal of Statistical Software*, 17(5):1–25, 2006. https://doi.org/10.18637/jss.v017.i05.

[5] R Core Team. *R: A Language and Environment for Statistical Computing*. R Foundation for Statistical Computing, Vienna, 2024. Version 4.3.3. https://www.r-project.org/.

[6] P. Chalmers. mirt: A multidimensional item response theory package for the R environment. *Journal of Statistical Software*, 48:1–29, 2012. Version 1.36, 21 March 2022. https://cran.r-project.org/package=mirt.

[7] L. A. van der Ark. New developments in Mokken scale analysis in R. *Journal of Statistical Software*, 48:1–27, 2012. Package `mokken`, versions 3.1.2 and 3.0.6. https://cran.r-project.org/package=mokken.

[8] J. N. Tendeiro, R. R. Meijer, and A. S. M. Niessen. PerFit: An R package for person-fit analysis in IRT. *Journal of Statistical Software*, 74:1–27, 2016. Versions 1.4.7 and 1.4.6. https://cran.r-project.org/package=PerFit.

[9] W. N. Venables and B. D. Ripley. *Modern Applied Statistics with S*. Springer, New York, 4th edition, 2002. Package MASS, version 7.3-60.0.1. https://cran.r-project.org/package=MASS.