Rectangle Criteria for Girth Eight in Cyclic Lifted-Product Codes: A Lean-Verified Answer and Decoding Consequences

October 22, 2026

Abstract

Freij-Hollanti, Morris and Šapokaitė asked for sufficient conditions, expressed through 2×2 submatrices, for a cyclic lifted-product Tanner graph to attain its maximum possible girth of eight, and for an analysis of the resulting decoding-relevant properties. We give an exact criterion: individual rectangle voltages must be nonzero and specified pairs of rectangle voltages must not cancel. The characterization for the expanded binary matrix is proved in Lean. For the degree-three case we derive a bijection between eight-cycles and minimum $(4, 4)$ absorbing sets, a stopping set lower bound, and local syndrome bounds. A connected girth-eight family with conductance tending to zero shows that the criterion alone does not ensure uniform expansion. Exhaustive optimization at lift size fourteen reduces the minimum absorbing-set count from 3,150 to 2,520 while preserving 252 physical and ten logical qubits. In an independent, paired min-sum experiment with 100,000 errors per noise level, the selected code's recovery failure rate falls from 4.385% to 2.523% at physical error probability 4%. We distinguish the formal theorem, written structural proofs, exact finite computations and statistical decoding evidence, and relate each to its mathematical predecessors.

1 The open question and the answer

In Section 5 of *Graphical Analysis of Lifted Product Code Constructions*, Freij-Hollanti, Morris and Šapokaitė explicitly ask for *"not just necessary, but sufficient conditions"* for the Tanner graph to have *"maximum possible girth of* 8*"*, together with the effects on other decoding-relevant graph properties [1]. The question concerns the cyclic, single-base-matrix lifted-product construction. It is presented as an open research question, rather than a numbered conjecture. Its first part asks for a definite mathematical criterion; its second part proposes a broader structural and experimental program.

We answer the first part by an equivalence in the entries of the original base matrix, not a test requiring construction of the much larger binary parity-check matrix. The second part is addressed by precise consequences for degree-three graphs, a limitation on expansion, and a finite optimization and decoding study. Table 1 specifies the extent of each answer. The degree-three conclusions concern fully populated 3×3 bases; the girth theorem holds in every dimension with at least two rows and two columns.

2 Predecessors and chronology

Fossorier's exponent-sum criterion supplies the classical short-cycle congruences [2]. Smarandache and Mitchell develop necessary and sufficient QC girth tests through matrix products and de-

Question	Answer	Evidence
Sufficient girth conditions	A necessary and sufficient rectangle-pair criterion	General Lean proof
Absorbing sets	In degree three, minimum sets are exactly the four-variable eight-cycle supports	Lean bijection; written $(4,4)$ profile
Stopping sets and syndromes	Stopping size at least six; local cancellation bounds	Lean general lower bound and witness
Connectivity and expansion	Connectivity is separate; connected girth-eight graphs can have vanishing conductance	Written argument; finite checks
Finite design and decoding	Exact fixed-size minimum; paired decoder comparison	Exhaustive search and Monte Carlo

Table 1: The answer to the two parts of the source question, with evidence levels.

rived submatrices [3]. Our walk-based proof specializes the classical congruences and supplies the reduction from the lifted-product support to the original input matrix.

Raveendran and Vasić describe the product eight-cycle mechanism in hypergraph-product graphs [4]. Zhang's thesis studies cyclic cancellation and cycle counting for lifted products under additional base-factor girth hypotheses [5]. Raveendran, Declercq and Vasić exhibit the eight-label cancellation directly for the same monomial LP family [6]. Okada and Kasai use a related coordinate-support argument and a forced eight-cycle in square-base hypergraph products with constrained CPM lifts [7]. These works provide the closest mechanisms behind the proof below. Their stated settings and conclusions are distinguished from our entrywise equivalence in Table 2.

The absorbing-set design perspective is established in classical coding theory by Wang, Dolecek, Zhang and Wesel [8] and its cycle consistency matrix development [9]. McMillon, Beemer and Kelley give extremal absorbing-set bounds, including the relevant girth-eight degree-three lower bound [10]. Morris, Pllaha and Kelley develop the quantum absorbing-set framework and its decoder interpretation [11]. Our consequences apply this framework to the characterized LP family. Abiad and Castriota's later spectral treatment counts cycles and absorbing configurations and bounds stopping sizes in a different QC-GHP/GB setting [12].

The chronology separates earlier ingredients from an answer to the stated question. In particular, the roughly 21.9 years between Fossorier's criterion and the question are not a claim that the full LP equivalence was already stated in 2004. The present answer assembles those methods into one exact input-matrix theorem with an explicit formal certificate. Measured instead to this manuscript, the March 2025 direct LP predecessor is 591 days (1.62 years) earlier, the April 2026 square-base predecessor is 175 days (0.48 years) earlier, and the July 2026 spectral study is 99 days (0.27 years) earlier. The main answer here follows the published question by 134 days (0.37 years).

3 Construction and notation

Let $r \geq 1$ and let $B = (B_{ij}) \in (\mathbb{Z}/r\mathbb{Z})^{m\times n}$, where $m, n \geq 2$. Every entry represents the circulant permutation $P^{B_{ij}}$; exponent zero represents an identity block. There are no missing input blocks. Write B^* for transposition followed by exponent negation. Expanding the block matrices

$$B_{\mathsf{X}} = [B \otimes I_n \mid I_m \otimes B^*], \qquad B_{\mathsf{Z}} = [I_n \otimes B \mid B^* \otimes I_m] \tag{1}$$

gives binary parity-check matrices $H_{\mathsf{X}}, H_{\mathsf{Z}}$ with $r(m^2+n^2)$ columns and rmn rows. This is the source paper's Equation (2.3) [1], within the established lifted-product framework [13, 6].

Work	Date used	Δ years	Contribution and relationship
Fossorier [2]	August 2004	-21.9	Classical QC cycle congruences; ingredients for the input-matrix tests.
Wang et al. [8]	May 31, 2011	-15.03	Absorbing-spectrum design and measured classical decoding gains.
McMillon et al. [10]	March 31, 2021	-5.19	Early online publication of extremal absorbing-set bounds.
Smarandache and Mitchell [3]	May 7, 2021	-5.09	Classical necessary/sufficient QC girth conditions via matrix products.
Raveendran–Vasić [4]	October 14, 2021	-4.65	Product eight-cycle and quantum trapping-set analysis.
Zhang [5]	March 27, 2024	-2.20	Thesis defense; LP cyclic cancellation with additional hypotheses.
Raveendran et al. [6]	March 10, 2025	-1.25	Same-family LP cancellation and controlled base-matrix decoding comparisons.
Morris et al. [11]	March 3, 2026	-0.27	Published quantum absorbing-set framework; earlier preprints precede this date.
Okada–Kasai, v1 [7]	April 30, 2026	-0.11	Related square-base support argument and forced eight-cycle.
Freij-Hollanti et al. [1]	June 10, 2026	0	Explicit sufficient-condition and decoding-properties question.
Abiad–Castriota [12]	July 15, 2026	$+0.10$	Related spectral enumeration and stopping-bound program.
Okada–Kasai, v3 [7]	September 11, 2026	$+0.25$	Expanded finite-instance certificates in the square-base setting.
This manuscript/artifact	October 22, 2026	$+0.37$	Exact Lean characterization, structural consequences and finite benchmark.

Table 2: Signed chronology relative to June 10, 2026. A negative number means preceding the question. Day-resolved entries use elapsed days divided by 365.2425; the August 2004 entry is month-resolved and rounded to one decimal. The present artifact is dated 134 days after the question. Dates identify the versions or publication milestones used, not dates of private discovery.

Use checks $C(i,j,a)$ and variables $L(k,j,b)$, $R(i,\ell,b)$, with fibers $a,b \in \mathbb{Z}/r\mathbb{Z}$. Adjacency in G_{X} is exactly

$$L(k,j,b) \sim C(i,j,b+B_{ik}), \tag{2}$$
$$R(i,\ell,b) \sim C(i,j,b-B_{\ell j}). \tag{3}$$

Left variables have degree m, right variables degree n, and checks degree $m+n$. Thus $m=n=3$ gives a $(3,6)$-biregular graph. Girth is the length of the shortest simple cycle; the explicit cycle below guarantees that the graphs considered here are not forests.

Define the rectangle and hexagon voltages

$$\mathcal{R}(a,b;c,d) = B_{ac} - B_{ad} + B_{bd} - B_{bc}, \tag{4}$$
$$\mathcal{Q}(a,b,c;d,e,f) = B_{ad} - B_{ae} + B_{be} - B_{bf} + B_{cf} - B_{cd}. \tag{5}$$

All arithmetic is in $\mathbb{Z}/r\mathbb{Z}$. Direct cancellation gives

$$\mathcal{Q}(a,b,c;d,e,f) = \mathcal{R}(a,b;d,e) + \mathcal{R}(b,c;d,f). \tag{6}$$

4 The exact girth-eight characterization

Theorem 4.1 (Rectangle-pair characterization)**.** *For the construction above, $g(G_{\mathsf{X}}) = 8$ if and only if both conditions hold:*

$$\mathcal{R}(a,b;c,d) \neq 0 \qquad \text{for } a \neq b,\ c \neq d; \tag{7}$$
$$\mathcal{R}(a,b;d,e) + \mathcal{R}(b,c;d,f) \neq 0 \qquad \text{for pairwise distinct } a,b,c \text{ and } d,e,f. \tag{8}$$

Equivalently, every eligible rectangle and every eligible hexagon voltage is nonzero. No connectedness, primality or normalization assumption is required.

The point of (8) is that nonzero individual rectangles do not prevent cancellation between two rectangles. The two conditions are tests on the original $m \times n$ matrix, including for the sparse product support of (1).

Lemma 4.2 (Four-cycle reduction)**.** *The graph G_{X} contains a four-cycle if and only if an eligible rectangle voltage of B vanishes.*

Proof. A four-cycle alternates between two variables and two checks. A variable and a neighboring projected check determine the variable fiber uniquely, and conversely a variable fiber determines the adjacent check fiber. Consequently distinct same-side vertices in this short cycle cannot have the same projection. Two left variables can share checks only when their second coordinates agree, yielding distinct row and column indices in B; closure is exactly (4). Two right variables give the transposed, negated criterion, which has the same zero set. A left and a right variable can share only the projected check at their common coordinate pair, and fiber uniqueness prevents them from sharing a second check. Thus a mixed four-cycle is impossible. Conversely, lifting a zero rectangle at any fixed unused coordinate produces four distinct vertices and hence a genuine four-cycle. □

Lemma 4.3 (Six-cycle reduction)**.** *The graph G_{X} contains a six-cycle if and only if an eligible hexagon voltage of B vanishes.*

Proof. In a simple six-cycle each pair among its three variables shares a check, and each pair among its three checks shares a variable. Fiber uniqueness therefore forces three distinct projections on each side.

The three projected checks form a triangle whose edges are labeled by the block type of the intervening variable. An L edge preserves the check's second coordinate; an R edge preserves its first coordinate. If both edge types occur, two edges share a type. Their coordinate equalities, combined with the third edge, identify two projected checks, a contradiction. Hence all three variables belong to the same block family. In the left family, a cycle can be written

$$L(d, j) \sim C(a, j) \sim L(e, j) \sim C(b, j) \sim L(f, j) \sim C(c, j) \sim L(d, j).$$

The fiber returns to its starting value exactly when $\mathcal{Q}(a, b, c; d, e, f) = 0$. The right family gives the transposed, signed version of the same collection of tests. Conversely, distinct row and column triples and a zero hexagon voltage lift to a simple six-cycle. □

The short-cycle closure calculations are the corresponding instances of Fossorier's QC criterion [2]. The coordinate reduction is related to the support argument of Okada and Kasai [7]; here it yields an equivalence for arbitrary fully populated rectangular exponent matrices.

Lemma 4.4 (Uniform eight-cycle)**.** *For every B with $m, n \geq 2$, the graph G_{X} contains a simple eight-cycle.*

Proof. Choose $i_0 \neq i_1$, $j_0 \neq j_1$, and arbitrary k, ℓ. The following vertices, listed in cycle order, satisfy (2)–(3):

$$\begin{array}{ll} C(i_0, j_0, B_{i_0k} - B_{\ell j_0}), & L(k, j_0, -B_{\ell j_0}), \\ C(i_1, j_0, B_{i_1k} - B_{\ell j_0}), & R(i_1, \ell, B_{i_1k}), \\ C(i_1, j_1, B_{i_1k} - B_{\ell j_1}), & L(k, j_1, -B_{\ell j_1}), \\ C(i_0, j_1, B_{i_0k} - B_{\ell j_1}), & R(i_0, \ell, B_{i_0k}). \end{array}$$

Distinct selected rows and columns give four distinct checks, two distinct left variables and two distinct right variables. The block families are disjoint. Thus the cycle is simple, regardless of its fiber values. □

This is the known LP cancellation mechanism [6], with explicit fibers and a separate simplicity check. Its product antecedents include [4, 5].

Proof of Theorem 4.1. Lemmas 4.2 and 4.3 equate the two voltage conditions with absence of all four- and six-cycles. Bipartiteness excludes odd cycles. Lemma 4.4 provides an eight-cycle, so the absence of shorter cycles is equivalent to girth eight. Finally, (6) rewrites the hexagon condition using only rectangle sums. □

Remark 4.5 (A useful failed shortcut). Over $\mathbb{Z}/3\mathbb{Z}$, the matrix $\left(\begin{smallmatrix} 0 & 0 & 0 \\ 0 & 1 & 2 \\ 0 & 2 & 1 \end{smallmatrix}\right)$ has no zero eligible rectangle but does have a zero hexagon and a simple six-cycle. Lean verifies this obstruction. It refutes the rectangle-only shortcut; the source paper does not assert that shortcut.

5 Lean certificate and mathematical scope

The formal development uses Lean 4.36.0-rc1 and Mathlib revision `5f7b4198d22a9c82e1c698a379334fe128095c82`. The main library contains 75 audited theorem declarations. Its final matrix theorem uses Mathlib's native simple-graph girth, together with an explicit binary expansion of H_{X}; the voltage graph is proved equal to that Tanner graph.

The following source corollary is an exact extract from the checked artifact, typeset using reversible TeX escapes. It expresses the sufficient-condition answer in rectangle-only form. A companion theorem proves necessity.

```
theorem sufficient_rectangle_conditions [Nontrivial I] [Nontrivial J]
    (B : I → J → ZMod r)
    (hRect : ∀ a b c d, a ≠ b → c ≠ d → baseRectangle B a b c d ≠ 0)
    (hPairs : ∀ a b c d e f, a ≠ b → b ≠ c → a ≠ c →
      d ≠ e → e ≠ f → d ≠ f →
      baseRectangle B a b d e + baseRectangle B b c d f ≠ 0) :
    (matrixTanner (hX B)).girth = 8 := by
  apply (matrixTanner_hX_girth_characterization B).mpr
  exact ⟨hRect, by simpa only [baseHexagon_eq_rectangle_add] using hPairs⟩
```

The listing's index types specialize to finite row and column sets, with at least two elements each, and positive r for the finite circulant interpretation. Internally, the graph lemmas are stated at greater generality. They establish projected distinctness, eliminate mixed block patterns, construct native simple cycles, and identify the graph with the expanded matrix. This is the formal content behind the brief final application, not a standalone one-line proof of the underlying mathematics.

Eight supplementary declarations in `CyclicDecoding.lean` prove the general two-error bound and concrete absorbing/stopping certificates; three in `CyclicOptimized.lean` prove the two selected candidates' girth. The three source-question corollaries are also supplementary. A further 29 audited declarations in `CyclicStructure.lean` prove the general absorbing-support/eight-cycle bijection, its counting corollary and minimum-size exclusion, and the general stopping bound. All observed axioms are among `propext`, `Classical.choice` and `Quot.sound`; the development uses no admitted proofs or native evaluation axiom. The structural results identified below are checked for arbitrary finite check types and finite selected-variable sets. The elementary $(4, 4)$ incidence count, the companion-stabilizer identification and the expansion argument retain written proofs.

6 Consequences for degree-three decoding graphs

Fix $m = n = 3$ and assume the conditions of Theorem 4.1. For a variable set S, induced check degree means degree in the graph on $S \cup N(S)$, including every edge from a selected variable.

Definition 6.1. An (a, b) *absorbing set* is a nonempty set of a variables whose induced graph has b odd-degree checks, such that every selected variable has strictly more even-degree than odd-degree check neighbors. It is *elementary* if every neighboring check has induced degree one or two. A *stopping set* is a nonempty variable set with no neighboring check of induced degree one.

These conventions agree with the source and quantum absorbing-set framework [1, 11]. The size lower bound in the next result is consistent with the established extremal bounds of [10].

Theorem 6.2 (Minimum absorbing sets)**.** *In any variable-degree-three Tanner graph of girth eight, no absorbing set has fewer than four variables. Its four-variable absorbing sets are exactly the supports of simple eight-cycles, with one such cycle per support. All are elementary* $(4, 4)$ *sets. Consequently their multiplicity equals the number of eight-cycles.*

Proof. A selected variable needs at least two even check neighbors. For at most three selected variables, each such check has degree two. No pair of variables can share two checks, as that would make a four-cycle. Sets of size one or two therefore fail absorption. A size-three set would need three pair checks forming a six-cycle, also excluded.

Take the four variables of an eight-cycle. An additional edge from one of its checks to another selected variable creates a four-cycle. An outside check meeting two selected variables creates a four-cycle when they are consecutive, or a six-cycle when they are opposite. Thus the four cycle checks have induced degree two and the four remaining neighbors are distinct checks of degree one. Each variable has two even neighbors and one odd neighbor.

Conversely, an absorbing set of four variables cannot meet a degree-four check: every other even check would share a pair with it and create a four-cycle, leaving each variable at most one even neighbor. Nor can it meet a degree-three check: each of that check's variables could then have at most one even neighbor, paired with the fourth variable. Hence all check degrees are at most two. Replace every degree-two check by an edge between its variables. The resulting normal graph is simple, triangle-free, has four vertices and minimum degree two. It is exactly a four-cycle. This also proves uniqueness of the corresponding Tanner eight-cycle. □

Lean proves the support characterization, exclusion of smaller nonempty absorbing sets, and a genuine equivalence between four-variable absorbing supports and unoriented eight-cycles. A cycle is represented by its variable and check supports with an explicit simple cyclic ordering; rotations and reversals are not counted separately. The development constructs a native Mathlib simple closed walk of length eight from each certificate and proves that the variable support uniquely determines the check support. The 4 odd-check count in the elementary $(4, 4)$ description is established by the written incidence argument above.

The conclusion is a sharp threshold, not removal of absorbing sets: Lemma 4.4 makes four-variable sets unavoidable in this model. It converts the next design objective into eight-cycle minimization.

Proposition 6.3 (Stopping size and a sharp example)**.** *A Tanner graph of girth at least eight and minimum variable degree $d \geq 2$ has stopping-set size at least $2d$. For the normalized 3×3 constructions here, this bound is attained at six.*

Proof. Choose a variable v in a stopping set and d of its check neighbors. Each check needs a second selected variable. These d witnesses are distinct, since a coincidence creates a four-cycle. Choose one witness a. At least $d - 1$ other checks of a each need another selected variable. The new witnesses are distinct and cannot equal v by the four-cycle exclusion; none can be a different first-level witness by the six-cycle exclusion. There are at least $1 + d + (d - 1) = 2d$ variables.

If the first row and column of B vanish, select

$$S_6 = \{L(0, j, 0) : 0 \leq j < 3\} \cup \{R(i, 0, 0) : 0 \leq i < 3\}. \tag{9}$$

Exactly the nine checks $C(i, j, 0)$ meet this set, each twice. It is a stopping set of size six and has zero syndrome. □

The general inequality is checked by `stopping_card_ge_twice_degree`; its hypotheses explicitly exclude four- and six-cycles, require a nonempty stopping set, and impose the degree lower bound only on its selected variables. The corollary `stopping_minimum_six` specializes it to degree three.

The same support is a row of H_{Z}, indexed by $(0, 0)$ and fiber zero. It represents a stabilizer, so this fact does not assign quantum logical distance six. For the binary classical kernel of H_{X}, the stopping lower bound and (9) do give minimum nonzero weight six. Lean checks the concrete induced-degree profile over $\mathbb{Z}/7\mathbb{Z}$.

Proposition 6.4 (Small-error syndrome bounds)**.** *In a four-cycle-free Tanner graph, errors at two distinct variables v, w produce at least $\deg(v) + \deg(w) - 2$ odd checks. In degree three and girth at least eight, one, two and three errors expose at least three, four and five degree-one checks, respectively.*

Proof. Distinct variables share at most one check. The two-error syndrome is $N(v) \triangle N(w)$, proving the first assertion; this argument is formalized in Lean. For S with $a \leq 3$ variables, the induced incidence graph is a forest, since any cycle would have length at most six. If $E = \sum_{v \in S} \deg(v)$ and there are $c \geq 1$ components, then $|N(S)| = E - a + c \geq E - a + 1$. If t checks have degree one, $E \geq t + 2(|N(S)| - t)$, whence $t \geq E - 2a + 2$. Set $E = 3a$. □

These are graph and syndrome statements. Failure-inducing sets also depend on decoder dynamics, as emphasized by [4, 11]. Section 9 tests that distinction directly.

7 Connectivity and a limitation on expansion

Girth eight alone does not ensure connectedness. For example, doubling every exponent of the modulus-seven matrix below and working modulo fourteen yields two components, because every edge preserves fiber parity. Direct BFS gives two components of 189 vertices each.

Theorem 7.1 (Connected girth eight with vanishing conductance)**.** *Let $r = 7k$, $k \geq 1$, and interpret the fixed integer matrix*

$$B_0 = \begin{pmatrix} 0 & 0 & 0 \\ 0 & 1 & 2 \\ 0 & 3 & 6 \end{pmatrix} \tag{10}$$

modulo r. The corresponding graphs are connected and have girth eight. For $k \geq 2$, their edge conductance satisfies

$$\phi(G_{\mathsf{X}}) \leq \frac{4}{3\lfloor r/2 \rfloor} \longrightarrow 0. \tag{11}$$

Proof. All eligible rectangle and hexagon sums for B_0 are nonzero modulo seven, as checked by Lean in the modulus-seven case. If any vanished modulo $7k$, it would vanish modulo seven. Theorem 4.1 thus gives girth eight for every k. The upper-left rectangle has voltage one, which generates the whole cyclic group. The source's connectivity criterion (Theorem 3.6 of [1]) therefore gives connectedness.

Let S contain all vertex types with fibers $0, \ldots, \lfloor r/2 \rfloor - 1$. Define

$$\phi(G_{\mathsf{X}}) = \min_{\varnothing \neq T \neq V} \frac{|\partial T|}{\min(\mathrm{vol}(T), \mathrm{vol}(V \setminus T))}.$$

There are nine degree-six checks and eighteen degree-three variables per fiber, or 108 units of volume. For $k \geq 2$, both fiber arcs have length at least seven. Each matching of displacement ϵ, where $|\epsilon| \leq 6$, crosses the cut in exactly $2|\epsilon|$ edges. The sum of the entries of B_0 is 12; each appears in three left and three right edge types. Thus $|\partial S| = 2 \cdot 6 \cdot 12 = 144$, and the smaller volume is $108\lfloor r/2 \rfloor$. This proves (11). □

The cuts at $r = 14, 28, 56$ have conductance ratios 0.190476, 0.095238 and 0.047619, respectively, confirmed by direct enumeration. These are upper bounds from specified cuts. They show that the girth criterion alone cannot provide a uniform expansion guarantee. Expansion remains a separate design objective, as in the source's hierarchy [1] and the related spectral program [12].

8 Exhaustive finite optimization

Fix lift size $r = 14$ and normalize the first row and column to zero:

$$B(a, b, c, d) = \begin{pmatrix} 0 & 0 & 0 \\ 0 & a & b \\ 0 & c & d \end{pmatrix}. \tag{12}$$

Girth eight forces each interior entry to be nonzero, leaving $13^4 = 28,561$ candidates. Applying the exact rectangle/hexagon tests and the connectivity condition $\gcd(14, a, b, c, d) = 1$ leaves 10,368 bases. In this normalized model the four interior exponents generate the cycle-voltage subgroup, which explains the gcd test.

The search partitions these bases into 25 orbits under row/column permutations, normalization, multiplication by units modulo fourteen, and transposition. For the gauge change $B'_{ij} = B_{ij}+u_i+v_j$, the graph isomorphism shifts fibers of $C(i, j)$ by $u_i - v_j$, of $L(k, j)$ by $-v_k - v_j$, and of $R(i, \ell)$ by $u_i + u_\ell$. Transposition exchanges block families, swaps check coordinates and negates fibers. These identities justify counting a representative of every orbit. The number 25 refers to this explicit symmetry group, rather than an assertion that no further graph isomorphisms exist.

Each representative is checked for connectedness by BFS. Eight-cycle counts are computed both by check-projection enumeration with four distinct variable labels and by an independent depth-eight traversal of the Tanner graph. The validation script compares both algorithms on all 25 representatives. It also checks explicit graph bijections for each symmetry type and repeats the search partition.

Proposition 8.1 (Computed fixed-size optimum)**.** *In the normalized connected girth-eight search at $r = 14$, the minimum number of four-variable absorbing sets is 2,520. Exactly 1,728 bases attain it, forming four orbits under the stated symmetries.*

Proposition 8.1 is established by exhaustive finite computation; it is not a Lean optimality theorem. The four representative interiors are

$$(1, 2, 4, 11), \quad (1, 3, 6, 10), \quad (1, 3, 7, 4), \quad (1, 4, 6, 2).$$

The first and third encode eight logical qubits. The second and fourth preserve the baseline's ten and are the primary rate-matched candidates:

$$B_2 = \begin{pmatrix} 0 & 0 & 0 \\ 0 & 1 & 3 \\ 0 & 6 & 10 \end{pmatrix}, \qquad B_4 = \begin{pmatrix} 0 & 0 & 0 \\ 0 & 1 & 4 \\ 0 & 6 & 2 \end{pmatrix}. \tag{13}$$

For both, $\operatorname{rank}(H_{\mathsf{X}}) = \operatorname{rank}(H_{\mathsf{Z}}) = 121$ and $K = 252 - 121 - 121 = 10$, by exact binary elimination. Lean independently verifies their girth eight. Their count is 20% below the baseline's 3,150 and 4.76% below the previous candidate $B(1, 2, 3, 8)$ with 2,646. Equal length and dimension do not imply equal quantum distance.

9 Measured decoding performance

9.1 Protocol and independent checks

We use syndrome normalized min-sum with a flooding schedule, normalization $\alpha = 0.8$, at most 100 iterations and message saturation at absolute LLR 50. The prior is $\log((1 - p)/p)$. The implementation uses fixed-point messages with twenty fractional bits, rounds normalization magnitudes

to the nearest integer with ties up, assigns positive sign to zero messages and hard bit zero to a zero posterior. It halts at the first syndrome match, including the initial zero estimate. There is no post-processing or per-design tuning. The syndrome min-sum method and LP simulation framework have prior treatments in [14, 15]; our fixed implementation is specified to make this comparison reproducible.

Errors are independent Bernoulli(p) in one Pauli sector, with perfect syndrome measurements. The decoder receives the syndrome and prior. The true error and H_{Z} are used only afterward for scoring. If $\hat{e}$ is the correction, recovery succeeds exactly when

$$e + \hat{e} \in \mathrm{row}_{\mathbb{F}_2}(H_{\mathsf{Z}}). \tag{14}$$

Thus nonzero stabilizer residuals count as success; syndrome mismatch or a nonstabilizer residual counts as failed recovery. This is the standard distinction between exact recovery, degeneracy and logical miscorrection [11]. The experiment is a one-sector code-capacity comparison, not a circuit-level or depolarizing-channel benchmark.

An independent Python implementation evaluates the direct extrinsic message equations and matches the C++ engine on 128 small cases, including an exact repetition-code oracle. Every primary code is checked on all single-qubit errors, zero error, an injected stabilizer and a constructed zero-syndrome logical operator. These checks distinguish the two cases in (14). All CSS row-pair orthogonality relations and GF(2) ranks are checked independently.

An exploratory experiment used 10,000 shared errors at each of five probabilities with seed 20261022. The confirmation uses a new seed, 20261023, and 100,000 independent errors at each of $p = 0.01, 0.02, 0.04$. At each probability all four rate-matched codes receive the same error patterns. The confirmation therefore comprises 300,000 independent patterns and 1.2 million decoder runs. Both rate-preserving structural minima were retained; selection did not use the confirmation outcomes.

9.2 Results

Code	$(4,4)$ sets	$p = 1\%$	$p = 2\%$	$p = 4\%$
$B_0 = B(1,2,3,6)$	3,150	0.033%	0.369%	4.385%
$B(1,2,3,8)$	2,646	0.031%	0.278%	2.750%
$B_2 = B(1,3,6,10)$	2,520	0.036%	0.251%	2.523%
$B_4 = B(1,4,6,2)$	2,520	0.035%	0.278%	2.607%

Table 3: Recovery failure rates, 100,000 trials per cell. Every code has 252 physical qubits, ten logical qubits, connectedness and girth eight.

At $p = 4\%$, B_2 has approximately 42.46% fewer failed recoveries than B_0. Wilson 95% marginal intervals are $[4.260\%, 4.514\%]$ and $[2.428\%, 2.622\%]$, respectively. Using the shared errors, the paired difference is -1.862 percentage points, with approximate pointwise 95% interval $[-2.011, -1.713]$. At $p = 2\%$, it is -0.118 points with interval $[-0.166, -0.070]$. At $p = 1\%$ there are only 33 baseline and 36 B_2 failures; the paired interval includes zero, so this experiment does not establish improvement there.

The two minima are not clearly distinguished: at $p = 4\%$ their paired difference is -0.084 points, with interval $[-0.208, +0.040]$. Intervals are pointwise and not corrected for multiple comparisons. We infer neither an asymptotic threshold nor a low-noise error-floor law from these measurements.

The improvement includes a large reduction in logical miscorrections. Mean iterations, counting failures at the limit, decrease from 9.689 for B_0 to 8.857 for B_2. Absorbing-set count is a structural

Code	Syndrome mismatch	Matched logical failure	Stabilizer successes*
B_0	2,981	1,404	5,834
$B(1,2,3,8)$	2,714	36	5,849
B_2	2,503	20	6,005
B_4	2,565	42	6,031

Table 4: Outcome decomposition at $p = 4\%$, per 100,000 trials. *Successful nonzero stabilizer residuals, in addition to exact error recovery.

selection objective; the exponent changes also affect algebraic and other graph properties, so the experiment does not isolate that count as the sole causal variable.

9.3 Exhaustive targeted errors and the earlier design framework

We additionally decode every exact four-variable absorbing support, with no other erroneous variables, at each of $p = 0.01, 0.02, 0.04$. Every support is checked directly for its $(4, 4)$ profile. The baseline fails on 378 of 3,150 supports, or 12%, always through a matched nonstabilizer residual. The previous best and both minima succeed on every support tested. Thus an absorbing support is not automatically failure-inducing for this min-sum decoder.

All failing baseline supports are mixed. Their residuals have weight six in 294 cases and weight eight in 84 cases. Explicit support witnesses are checked for zero syndrome and exclusion from $\mathrm{row}(H_{\mathsf{Z}})$. The weight-six witness bounds the baseline's distance in the tested Pauli sector by six. No exact optimized-code distance is assigned here. Under Bernoulli noise, these disjoint exact supports contribute $378p^4(1-p)^{248}$ to the baseline's failure probability; they are one error subclass, not an estimate of the full failure rate.

Raveendran, Declercq and Vasić already demonstrate that different base matrices can produce different decoding performance at equal length, rate and girth eight [6, Sec. V-A, Eq. (92), Fig. 1]. Their comparison uses 600-qubit codes and BP+OSD-10. Our baseline also satisfies their column-partition pattern $c_0 + c_2 = 2c_1$ modulo fourteen; the previous best and both minima avoid every corresponding three-column or three-row relation. This links our example to their low-weight-logical design framework without assigning an optimized distance or claiming a new decoder. The finite optimum and the specified min-sum benchmark are the concrete contributions of this study.

10 Reproducibility and remaining scope

The companion artifact is organized under `formalization/cyclic-lifts` in the anonymous project repository `https://github.com/alectionary/vibe-math`. The manuscript package contains a snapshot of all Lean sources, the pinned Lake configuration, experiment programs, JSON results, encoded paired outcomes and validation scripts needed for this paper. Its manifest records SHA-256 hashes; the snapshot does not depend on a moving branch or unpublished working tree. Build instructions are included with the package.

The library and consumers verify the main theorem and concrete certificates using the pinned Lean/Mathlib environment. The standard-library Python search and C++17 decoder reproduce the finite experiments. The statistical audit reconstructs counts and paired comparisons from stored per-trial flags. No physical experiments were performed.

The precise girth-condition question is settled by Theorem 4.1. Its decoding-properties continuation receives three complementary answers: structural consequences, a counterexample to uniform

expansion from girth alone, and an optimized finite code with a measured recovery improvement. A general classification across arbitrary degrees, exact optimized quantum distances, optimization over lift sizes, and comparisons across decoders and noisy measurement models remain separate tasks. The absorbing-support bijection and stopping lower bound are now Lean-checked general theorems. The elementary odd-check count, the companion-stabilizer identification and conductance argument remain available for further formalization.

Acknowledgments and research provenance. The question is credited to Ragnar Freij-Hollanti, Kirsten D. Morris and Patricija Šapokaitė; their structural program guided the choice of targets. The predecessor contributions credited in Section 2 guided the proof comparison and interpretation of decoding outcomes. OpenAI Codex was used for literature discovery, mathematical exploration, Lean development, experiment implementation and manuscript drafting.

References

[1] R. Freij-Hollanti, K. D. Morris and P. Šapokaitė, *Graphical Analysis of Lifted Product Code Constructions*, arXiv:2606.11987v1, June 10, 2026. `https://arxiv.org/abs/2606.11987v1`.

[2] M. P. C. Fossorier, *Quasi-Cyclic Low-Density Parity-Check Codes From Circulant Permutation Matrices*, IEEE Transactions on Information Theory **50**(8), 1788–1793, 2004. doi:10.1109/TIT.2004.831841.

[3] R. Smarandache and D. G. M. Mitchell, *Necessary and Sufficient Girth Conditions for Tanner Graphs of Quasi-Cyclic LDPC Codes*, arXiv:2105.03462v1, May 7, 2021. `https://arxiv.org/abs/2105.03462v1`.

[4] N. Raveendran and B. Vasić, *Trapping Sets of Quantum LDPC Codes*, Quantum **5**, 562, October 14, 2021. doi:10.22331/q-2021-10-14-562.

[5] B. Zhang, *On the Left-Right Lifted Product Quantum LDPC Code*, Master's thesis, Duke University, defended March 27, 2024, Section 3.3, Theorem 5. `https://dukespace.lib.duke.edu/server/api/core/bitstreams/8f596ec8-b362-43da-bf61-f8c26f0c5edc/content`.

[6] N. Raveendran, D. Declercq and B. Vasić, *On the Minimum Distances of Finite-Length Lifted Product Quantum LDPC Codes*, arXiv:2503.07567v1, March 10, 2025. `https://arxiv.org/abs/2503.07567v1`.

[7] K. Okada and K. Kasai, *High-Girth Regular Quantum LDPC Codes from Square-Base Hypergraph Products via CPM Lifts*, arXiv:2604.27817; v1 April 30, 2026; v3 September 11, 2026. `https://arxiv.org/abs/2604.27817v3`.

[8] J. Wang, L. Dolecek, Z. Zhang and R. Wesel, *Absorbing Set Spectrum Approach for Practical Code Design*, arXiv:1106.0057v1, May 31, 2011. `https://arxiv.org/abs/1106.0057v1`.

[9] J. Wang, L. Dolecek and R. Wesel, *The Cycle Consistency Matrix Approach to Absorbing Sets in Separable Circulant-Based LDPC Codes*, arXiv:1208.6094v2, December 5, 2012. `https://arxiv.org/abs/1208.6094v2`.

[10] E. McMillon, A. Beemer and C. A. Kelley, *Extremal absorbing sets in low-density parity-check codes*, Advances in Mathematics of Communications **17**(2), 465–483, 2023; published online March 31, 2021. doi:10.3934/amc.2021003.

[11] K. D. Morris, T. Pllaha and C. A. Kelley, *Absorbing sets in quantum LDPC codes*, Advances in Mathematics of Communications **23**, 234–254, 2026; published online March 3, 2026. doi:10.3934/amc.2026023.

[12] A. Abiad and N. Castriota, *Spectral and Additive Combinatorial Methods for Cycles and Absorbing Sets in Lifted-Product Quantum LDPC Codes*, arXiv:2607.13666v1, July 15, 2026. `https://arxiv.org/abs/2607.13666v1`.

[13] P. Panteleev and G. Kalachev, *Degenerate Quantum LDPC Codes With Good Finite Length Performance*, Quantum **5**, 585, 2021. doi:10.22331/q-2021-11-22-585.

[14] N. Raveendran, N. Rengaswamy, F. Rozpędek, A. Raina, L. Jiang and B. Vasić, *Finite Rate QLDPC-GKP Coding Scheme that Surpasses the CSS Hamming Bound*, Quantum **6**, 767, 2022. doi:10.22331/q-2022-07-20-767.

[15] N. Raveendran, J. Valls, A. K. Pradhan, N. Rengaswamy, F. Garcia-Herrero and B. Vasić, *Soft syndrome iterative decoding of quantum LDPC codes and hardware architectures*, EPJ Quantum Technology **10**, 45, October 19, 2023. doi:10.1140/epjqt/s40507-023-00201-1.