Incidence-sensitive stopping bounds and a Gram obstruction for QC-GHP codes

24 October 2026 | Checked stronger-bound follow-up to L-F16-stopping-bound

Abstract. We give a positive answer to the incidence-conditioned replacement question beyond the completed B1 example. For a two-part column partition, column degree at least γ, intersection limit σ within a part and $\tau \geq \sigma$ across parts, every nonempty stopping support satisfies $2(\gamma+\sigma) \leq (\sigma+\tau)|S|$. Explicit Sidon-support circulants give sparse binary CSS families with guarantee ceiling$(2(\gamma+1)/3)$; every fixed even γ admits arbitrarily long examples with a nontrivial logical class. Separately, an explicit weight-four/eight family has stopping distance and quantum logical distance exactly six at every positive multiple-of-39 lift. A repeated-constituent CSS counterpart has stopping distance two and the identical full real Gram matrix. Thus a universally valid lower bound using only that Gram data cannot certify these improvements. Every new proof and matrix/field bridge is checked in Lean.

Question / source	Answer and scope
Abiad-Castriota,15 July 2026, v1,Prop. 5.1,Remark 5.2,§6: useful parameters for the stated bound	Answered negatively by the previous universal theorem; unchanged here.
Same source: tighter spectral stopping bounds, including multi-eigenvalue refinements	A restricted obstruction: even the full real Gram matrix cannot distinguish the paired/repeated families. No universal disproof of all stronger spectral bounds.
This requested follow-up: incidence-conditioned replacement exceeding two on a sparse family beyond B1	YES. A reusable bound, explicit infinite families, nontrivial logical content, and a separate exact-six family.

The historical source question and this project-derived target are kept distinct. This paper adds no completed canonical author-question to the inventory. The proofs are published at an immutable source revision; all 23 Lean files, including audit programs and dependencies, have full current and pinned URLs below.

1. The two-block stopping bound

Let E(v,c) be a finite binary incidence relation. A stopping support S is nonempty and no check has exactly one selected neighbor. It need not be connected, elementary, or a stabilizer support. Partition the columns by a Boolean color. Suppose every selected column has at least γ neighbors, distinct selected columns of the same color have at most σ common neighbors, and columns of different colors have at most τ common neighbors, with σ≤τ. These hypotheses may be imposed globally to obtain a stopping-distance guarantee.

Theorem 1. Under these assumptions,

$$2(\gamma+\sigma) \le (\sigma+\tau)|S|.$$

If σ+τ>0 this gives the integer bound ceiling(2(γ+σ)/(σ+τ)). The division-free statement also handles zero intersection limits. Both parts are allowed to be empty individually; nonemptiness is required only for S.

Proof. Fix a selected column v. Every check incident with v must meet another selected column. Covering its neighbors by the intersections with the other selected columns gives $\gamma \le \Sigma_{w\in S, w\neq v} |N(v)\cap N(w)|$. Let p and q count selected columns in the two parts. A selected left column therefore gives γ+σ≤σp+τq; a selected right column gives γ+σ≤τp+σq. If both parts occur, add these inequalities. If only one occurs, the corresponding inequality gives γ+σ≤σ|S|, which is at least as strong because τ≥σ. This proves the claim. All covering, finite-sum, partition and one-part cases are checked in PartitionBound.lean.

Classical comparison. Kashyap-Vardy [2], Theorem 1, assumes uniform column size w and maximum distinct-column intersection μ; its bound is 1+w/μ. The same count appears in the checked division-free theorem γ+μ≤μ|S|. Retaining the two parts refines this classical argument. At γ=4,σ=1,τ=2, the uniform criterion gives three and Theorem 1 gives four. The exact-six result below uses additional finite incidence information. We make no claim that the elementary covering principle is new.

2. Sidon supports give verified incidence hypotheses

For a finite abelian group G, call a support T Sidon when equality a+b=c+d among its elements implies equality of the unordered pairs, including repeated elements. Let A be the binary circulant with $A_{c,j}=1$ exactly when c−j∈T, and set

$$H_X=H_Z=[A \mid A^T].$$

These are actual binary matrices with |G| rows and 2|G| columns. Their two column neighborhoods are j+T and j−T. A Sidon identity shows that distinct columns within one part share at most one check; across parts they share at most two. For the latter statement, after one common check c_0 is fixed, the only possible common checks are c_0 and $v+w-c_0$. The formal proof includes cardinality and empty-intersection cases. Every column has |T| neighbors and every row has 2|T| neighbors.

Circulants commute with their transposes. Hence $H_X H_Z^T = AA^T + A^TA = 0$ over F_2. This is precisely the scalar QC-GHP/generalized-bicycle form of [1,4], with $r_1=n_1=1$ and b=a. Applying Theorem 1 gives 3|S|≥2(|T|+1), without any spectral or girth assumption.

3. An explicit sparse family for every fixed guarantee

Theorem 2. Fix an even integer $\gamma \geq 2$. For any odd $n \geq 3^{\gamma}$, use $G = Z/n$ and

$$T = \{1, 3, 3^2, \ldots, 3^{\gamma-1}\}, \quad a(x) = \Sigma_{i=0}^{\gamma-1} x^{3^i},$$
$$H_X = H_Z = [A \mid A^T].$$

Then the matrices are binary CSS checks of column weight γ and row weight 2γ. Every nonempty stopping support has size at least $\lceil 2(\gamma+1)/3 \rceil$. The quantum code has a nontrivial logical class. For fixed γ, $n = 3^{\gamma}(2t+1), t \geq 0$, gives arbitrarily long matrices with the same degrees.

Proof of the support condition. Sort the exponents in $3^a + 3^b = 3^c + 3^d$, with $a \leq b$ and $c \leq d$. If $b < d$, the left side is at most $2 \cdot 3^b$, whereas the right side is at least $3^d \geq 3 \cdot 3^b$, a contradiction. The opposite inequality is symmetric; cancel the equal largest terms to identify the smaller exponents. Every relevant pair sum is below n, since $2 \cdot 3^{\gamma-1} < 3^{\gamma} \leq n$. Thus reduction modulo n preserves this Sidon property and all γ marks remain distinct. PowersThree.lean checks the inequalities, no-wrap cast bridge and cardinality; the support is not assumed Sidon as an unproved input.

Nontrivial quantum content. Take the binary word equal to one on every left variable and zero on the right. Its syndrome is zero because every row meets the left block in the even number γ. The sum of its left entries is one because n is odd. Every companion row has left sum zero, and so does every linear combination of companion rows. The word is therefore outside the stabilizer span. SidonMatrices.lean checks the finite-sum, binary-field and span-separation argument.

Fixed column / row weights	New guarantee / classical uniform guarantee
4 / 8	4 / 3
6 / 12	5 / 4
8 / 16	6 / 5
General even γ / 2γ	$\lceil 2(\gamma+1)/3 \rceil$ / $\lceil \gamma/2+1 \rceil$

Choosing γ first gives any desired fixed guarantee, and then length may increase with degrees fixed. This is not a claim of growing stopping distance at fixed degree, positive asymptotic rate, or practical parameter efficiency. The displayed sufficient length is exponential in γ. The known companion-row stopping mechanism gives a size 2γ upper witness; CSSStopping.lean checks that mechanism on the same binary matrices.

4. A separate family with exact stopping and logical distance six

Theorem 3. For every positive integer t, let $n = 39t$ and use $a(x) = 1 + x + x^4 + x^6$ with $H_X = H_Z = [A|A^T]$. There are $78t$ variables and $39t$ checks, column weight 4 and row weight 8. The stopping distance and the quantum logical distance are both exactly six.

The reusable intersection criterion proves four for this entire family. The stronger exact result is certified independently: simultaneous coordinate translation reduces the base $n = 39$ search to the two side representatives. A sound degree-one extension procedure rejects both roots with four further additions, excluding all stopping supports of size at most five. Its exact Boolean tests are reduced by Lean's kernel. No external search result is a premise.

4. Exact-six proof and source bridge, continued

Reduction modulo39 maps lifted column lists onto their base lists, lifts every incident base check, and is injective on each check’s neighbor set. The checked local-cover theorem therefore projects a stopping support to a base stopping support of no greater size. This transfers the lower bound six to every positive39-multiple lift; it is not extrapolation from sampled lengths.

A six-variable upper witness is

left(0), left(−5), left(−4),
right(1), right(5), right(6).

The six variables are distinct at every stated lift. Every incident check has a selected partner. A separate exact parity calculation shows that every selected check degree is even; the binary word is in the kernel. It has left weight three, whereas each companion row has left weight four. The same parity functional excludes every stabilizer combination. Every nonzero binary kernel word has stopping support, so the lower stopping bound gives logical weight at least six; the nontrivial six-word gives equality in both CSS sectors, which coincide here. Unlike the completed B1 family, this upper witness is a logical word rather than a companion row. It is also not assumed elementary: the independent base reconstruction has selected degrees zero, two and four.

BicycleMatrices.lean proves the actual circulant/transpose binary matrix entries equivalent to the incidence relation and checks CSS commutation. BicycleDegrees.lean proves dimensions and degrees. The translation, kernel certificate, cover, cardinality, syndrome and stabilizer-span bridges are all included in the proof chain. The statement does not assert a formula for the logical dimension. Independent binary elimination gives k=6 for the first three sampled lifts; that is a computation recorded separately, not a new general rank theorem.

5. What the full real Gram matrix cannot certify

Theorem 4. For the same constituent circulant A, define

Good: $H_X = H_Z = [A|A^T]$;
Bad: $H'_X = [A|A]$, $H'_Z = [A^T|A^T]$.

Both pairs are binary CSS checks with the same dimensions and degrees. Over the reals,

$$H_X H_X^T = AA^T + A^T A = 2AA^T = H'_X H'^T_X.$$

The bad X-matrix has two identical positive columns at each coordinate, yielding a stopping pair. Positive columns exclude singletons, so its stopping distance is exactly two. The good family of Theorem 3 has distance six. More generally the same identity holds for every support in Theorem 2, together with a bad stopping pair.

Let L be any proposed universally valid integer lower-bound function whose inputs consist only of this real Gram matrix and the shared dimensions/degrees. Validity on the bad counterpart forces $L \le 2$; identical input data force the same output on the good code. GramObstruction.lean, BadStopping.lean and SidonBad.lean prove this statement against the actual matrices and stopping supports. Any function of the complete Gram spectrum, or of eigenvectors determined solely by that Gram matrix, is included. An additional incidence hypothesis may distinguish the codes and is precisely what the replacement uses.

6. Exact comparison with spectral and known stopping bounds

The motivating source [1], Proposition 5.1, requires $\sigma_2(H_X)^2<\gamma/2$ and separately excludes the small root branch before concluding a stopping-distance lower bound. The preceding universal parameter theorem answers that proposition's useful-parameter question negatively in its stated scalar-factor model. That answer is preserved. Theorem 1 replaces its spectral step with incidence information; it does not claim parameters satisfying the source inequality.

Zhu-Chugg [3], Corollary 6, equations 41-42, give the two regular Tanner-graph expressions below, with N variables, column degree γ, row degree k and second Gram eigenvalue η:

$$N(2\gamma-\eta)/(\gamma k-\eta),$$
$$2N(2\gamma+k-2-\eta)/(k(\gamma k-\eta)).$$

Their usual regular connected setting and strict gap $\eta<\gamma k$ must be respected. If their hypotheses apply to both members of the paired/repeated comparison, validity and the identical Gram data prevent either expression from certifying more than two on the good member. If the strict gap fails, the displayed expressions are outside that regime. This comparison addresses these Gram-based guarantees; it does not dismiss every multi-eigenvector or incidence-dependent analysis in [3].

For illustration only, independently reconstructed $n=39$ matrices have $\eta\approx27.52509838<32$, and the two expressions are approximately-340.3332 and-58.9375. The same reconstruction checks exact integer Gram equality and CSS commutation for $t=1,\ldots,8$. Floating-point eigenvalues and sampled ranks are not premises in any theorem above.

Kashyap-Vardy [2] supplies the classical uniform-overlap criterion already sufficient for a positive answer exceeding two in the weight-four case. Theorem 1 improves its value by retaining the block partition. Schwartz-Vardy [5] emphasizes that stopping distance belongs to a specified parity-check matrix and that codeword supports are stopping sets. Their stopping redundancy instead optimizes over added checks; that problem is different from our fixed-H_X guarantee. The generic binary kernel/stopping bridge is checked here.

Wang-Pryadko [4], Eq.8, uses $H_X=[A|B]$,$H_Z^{\top}=[B;-A]$; our paired construction takes $B=A^{\top}$. Their distance bounds and gcd dimension formula concern logical code parameters. A logical-distance lower bound alone does not exclude non-codeword stopping supports. Kuo-Ouyang [6] studies decoders exploiting degeneracy; success of such a decoder does not establish a lower bound for ordinary peeling stopping sets. The known stabilizer upper mechanism and the new nontrivial logical upper witness are distinguished above.

Public GitHub comparisons include the pinned bicycle-race README, which describes logical-distance records, and the Kuo decoder repository metadata. Bounded web searches supplied no matching full theorem for the new complete target. The X index query returned no matches; authenticated Edge inspection was unavailable because the Mac was locked. These are documented coverage limits, not proofs of absence or priority. Named inaccessible or uninspected leads remain in the source ledger.

7. Evidence, inventory and remaining work

The current aggregate build and all 178 named-declaration audits pass in Lean4.36.0-rc1 with mathlib5f7b4198d22a9c82e1c698a379334fe128095c82. Only propext,Classical.choice and Quot.sound occur. The project contains 19 new modules and three frozen imported research

modules. Reproduce with lake build StrongerAnswer, followed by lake env lean AuditStronger.lean. The build log, complete signatures/axiom closure, source hashes and independent integer reconstruction accompany the archive.

Proof component	Checked source
Generic neighbor cover and two-block/uniform bounds	PartitionBound.lean
Sidon intersection limits and no-wrap powers-of-three support	SidonStopping.lean; PowersThree.lean
Binary matrices, CSS, degree counts and logical separation	SidonMatrices.lean; PowersFamily.lean
Rooted search soundness, two roots and cyclic covers	dependencies/IncidenceCore,List,Cover; BicycleBaseCore,Base,FamilyCore,Family
Concrete actual matrices, degrees, overlap and exact logical witness	BicycleMatrices,Degrees,Overlap,Logical; KernelStopping
Same-Gram identity, bad pair and universal-bound obstruction	GramObstruction; BadStopping; SidonBad
Known nonzero companion-row stopping mechanism	CSSStopping.lean
Consumers and exhaustive named-declaration audit	StrongerAnswer.lean; AuditStronger.lean

Four additional accessible main texts were screened for author-stated questions, with later same-paper answers checked. The shared inventory adds20 historical questions/directions, eight precise enough for its denominator:267→287 entries,135→143 eligible targets,110→114 papers and97→101 full-text main-paper screens. Completed canonical Lean targets remain five. New harvested questions have unassessed present resolution, Lean discovery and effort. They are not asserted still open today. Supplementary/final-version and retrieval gaps are explicit; the original parameter question stays answered negatively.

Question answered. Yes: an incidence-conditioned replacement improves on two on explicit sparse nontrivial QC-GHP families beyond B1, with a reusable bound and a separate exact-six family. **Still open in this checkpoint.** The best possible general incidence bound, tight stopping distances of the powers-of-three family, and stronger spectral bounds on classes distinguishable from the bad counterparts. **Next decisive step.** Tighten the spectral comparison and the incidence criterion while retaining faithful binary, cover and Lean interfaces. This is a bounded stronger-bound result, not a universal resolution of every meaning of the source’s broad research direction.

References

[1] Aida Abiad and Nichola Castriota. Spectral and Additive Combinatorial Methods for Cycles and Absorbing Sets in Lifted-Product Quantum LDPC Codes.15 July 2026, v1,Prop. 5.1,Remark 5.2,§6. https://arxiv.org/html/2607.13666v1

[2] Navin Kashyap and Alexander Vardy. Stopping Sets in Codes from Designs. Undated revised author manuscript; reports compositionSeptember 2003 and ISIT2003 presentation. Theorem 1. https://ece.iisc.ac.in/~nkashyap/Papers/stopsets.pdf

[3] Mingrui Zhu and Keith M.Chugg. Bounds on the Expansion Properties of Tanner Graphs. IEEE TIT53(12),4834-4840,December 2007. Corollary 6. https://hal.usc.edu/chugg/docs/pubs/zhu2007bounds.pdf

[4] Renyu Wang and Leonid P.Pryadko. Distance bounds for generalized bicycle codes. arXiv:2203.17216v1,31 March 2022; internal PDF date1 April 2022. https://arxiv.org/abs/2203.17216v1

[5] Moshe Schwartz and Alexander Vardy. On the Stopping Distance and the Stopping Redundancy of Codes. IEEE TIT52(3),922-932,March 2006. https://www.ece.mcmaster.ca/~schwam10/publications/MSjrnl6.pdf

[6] Kao-Yueh Kuo and Yingkai Ouyang. Degenerate quantum erasure decoding. npj Quantum Information12,75,2026. Inspected article-in-press main PDF; version distinctions in chronology. https://doi.org/10.1038/s41534-026-01212-3

[7] Earlier checked parameter-answer and B1 papers in this repository. The new target is distinct from the completed original proposition and completed B1 classification. https://github.com/alectionary/vibe-math/tree/master/formalization/stopping-bound

Appendix A. Actual checked Lean statements and proofs

The following excerpts are verbatim from the immutable checked sources. They expose the quantifiers and decisive proof steps. The complete dependency guide follows, and every file is linked individually in AppendixB. No numerical spectral premise is substituted for an actual matrix statement.

PartitionBound.lean

```
theorem partition_bound (color : V → Bool) (S : Finset V)
    (hS : Incidence.Stopping E S) (γ σ τ : ℕ) (hst : σ ≤ τ)
    (hdeg : ∀ v ∈ S, γ ≤ (neighbors E v).card)
    (hov : ∀ v ∈ S, ∀ w ∈ S, v ≠ w →
      overlap E v w ≤ if color v = color w then σ else τ) :
    2 * (γ + σ) ≤ (σ + τ) * S.card := by
  classical
  let P := S.filter (fun w => color w = false)
  let Q := S.filter (fun w => color w = true)
  have hcard : P.card + Q.card = S.card := by
    have h := card_filter_add_card_filter_not (s := S) (fun w => color w = false)
    simpa [P,Q,Bool.not_eq_false] using h
  have hfalse (v : V) (hv : v ∈ S) (hc : color v = false) :
      γ + σ ≤ σ * P.card + τ * Q.card := by
    have h := column_budget E color S hS γ σ τ hdeg hov v hv
    simpa [hc,P,Q,Bool.not_eq_false] using h
  have htrue (v : V) (hv : v ∈ S) (hc : color v = true) :
      γ + σ ≤ τ * P.card + σ * Q.card := by
    have h := column_budget E color S hS γ σ τ hdeg hov v hv
    simpa [hc,P,Q,Bool.not_eq_true,add_comm] using h
  by_cases hp : P.Nonempty
  · obtain ⟨v,hv⟩ := hp
    have hv' := mem_filter.mp hv
    have hb := hfalse v hv'.1 hv'.2
    by_cases hq : Q.Nonempty
    · obtain ⟨w,hw⟩ := hq
      have hw' := mem_filter.mp hw
      have hb' := htrue w hw'.1 hw'.2
      nlinarith
    · have hq0 : Q.card = 0 := card_eq_zero.mpr (not_nonempty_iff_eq_empty.mp hq)
      nlinarith [Nat.mul_le_mul_right P.card hst]
  · have hp0 : P.card = 0 := card_eq_zero.mpr (not_nonempty_iff_eq_empty.mp hp)
    obtain ⟨v,hv⟩ := hS.1
    have hc : color v = true := by
      cases hc : color v
      · have : v ∈ P := mem_filter.mpr ⟨hv,hc⟩
        exact False.elim (hp ⟨v,this⟩)
      · rfl
    have hb := htrue v hv hc
    nlinarith [Nat.mul_le_mul_right Q.card hst]
```

PowersFamily.lean

```
theorem positive_family (γ n : ℕ) [NeZero n]
    (hn : 3^γ ≤ n) (heven : Even γ) (hodd : Odd n) :
    let S := support γ n
    (SidonStopping.X (ZMod 2) S * (SidonStopping.X (ZMod 2) S)ᵀ = 0) ∧
    (∀ v, (Finset.univ.filter (fun c => SidonStopping.X (ZMod 2) S c v = 1)).card = γ) ∧
    (∀ c, (Finset.univ.filter (fun v => SidonStopping.X (ZMod 2) S c v = 1)).card = 2*γ) ∧
    (∀ T, Incidence.Stopping (SidonStopping.E S) T → 2*(γ+1) ≤ 3*T.card) ∧
    (SidonStopping.X (ZMod 2) S).mulVec (SidonStopping.leftOnes (G := ZMod n)) = 0 ∧
    (¬ ∃ a, (SidonStopping.X (ZMod 2) S)ᵀ.mulVec a =
      SidonStopping.leftOnes (G := ZMod n)) ∧
    (SidonStopping.X ℝ S * (SidonStopping.X ℝ S)ᵀ =
      SidonStopping.BadX ℝ S * (SidonStopping.BadX ℝ S)ᵀ) := by
  dsimp only
  have hcard := support_card γ n hn
  have he : Even (support γ n).card := by simpa [hcard] using heven
  refine ⟨SidonStopping.css _,?_,?_,?_,SidonStopping.leftOnes_kernel _ he,?_,SidonStopping.gram_equal _⟩
  · intro v; rw [SidonStopping.column_weight,hcard]
  · intro c; rw [SidonStopping.row_weight,hcard]
  · intro T hT
    simpa only [hcard] using SidonStopping.stopping_bound _ (sidon γ n hn) T hT
  · apply SidonStopping.leftOnes_not_stabilizer _ he
    simpa using hodd
```

KernelStopping.lean

```
theorem quantum_distance_six (h : 39 | n) :
    (HX (n := n) (ZMod 2) * (HZ (n := n) (ZMod 2))ᵀ = 0) ∧
    (∀ x : Var n → ZMod 2, x ≠ 0 → (HX (ZMod 2)).mulVec x = 0 →
      6 ≤ (BinaryStopping.support x).card) ∧
    (HX (ZMod 2)).mulVec (@word n) = 0 ∧
    (¬ ∃ a : Check n → ZMod 2, ((HZ (ZMod 2))ᵀ.mulVec a) = (@word n)) ∧
    (BinaryStopping.support (@word n)).card = 6 :=
  ⟨css,all_nonzero_kernel_weight_ge_six h,word_kernel h,word_not_stabilizer h,word_weight h⟩
```

SidonBad.lean

```
theorem gram_only_bound (S : Finset G)
    (lower : Matrix G G ℝ → ℕ)
    (valid_bad : ∀ T : Finset (Bool × G), Incidence.Stopping (badE S) T →
      lower (BadX ℝ S * (BadX ℝ S)ᵀ) ≤ T.card) :
    lower (X ℝ S * (X ℝ S)ᵀ) ≤ 2 := by
  rw [gram_equal]
  have h := valid_bad twin (twin_stopping S)
  simpa [twin_card] using h
```

Dependency guide

PartitionBound provides generic counting. SidonStopping and PowersThree prove incidence hypotheses constructively. SidonMatrices and PowersFamily supply actual binary CSS and nontrivial logical content. BicycleBaseCore/List dependencies give search soundness; BicycleBase rejects small roots; FamilyCore/Cover transfer exact6. BicycleMatrices/Degrees/Logical/KernelStopping check the actual code and logical witness. GramObstruction, BadStopping and SidonBad prove indistinguishability and exact bad stopping2. CSSStopping checks the known stabilizer upper mechanism. AuditStronger checks every named declaration, including all three frozen dependencies.

Appendix B. Full Lean URLs

All23 Lean files are included, with current and immutable clickable URLs. The immutable revision is 3e70cc79d7c4c171027a2a40f0757781d9787efb. The audit itself and all three inherited dependencies are listed.

AuditStronger.lean - axiom/signature audit

Current: https://github.com/alectionary/vibe-math/blob/master/formalization/stopping-bound/stronger/AuditStronger.lean

Immutable: https://github.com/alectionary/vibe-math/blob/3e70cc79d7c4c171027a2a40f0757781d9787efb/formalization/stopping-bound/stronger/AuditStronger.lean

BadStopping.lean - new checked proof module

Current: https://github.com/alectionary/vibe-math/blob/master/formalization/stopping-bound/stronger/BadStopping.lean

Immutable: https://github.com/alectionary/vibe-math/blob/3e70cc79d7c4c171027a2a40f0757781d9787efb/formalization/stopping-bound/stronger/BadStopping.lean

BicycleBase.lean - new checked proof module

Current: https://github.com/alectionary/vibe-math/blob/master/formalization/stopping-bound/stronger/BicycleBase.lean

Immutable: https://github.com/alectionary/vibe-math/blob/3e70cc79d7c4c171027a2a40f0757781d9787efb/formalization/stopping-bound/stronger/BicycleBase.lean

BicycleBaseCore.lean - new checked proof module

Current: https://github.com/alectionary/vibe-math/blob/master/formalization/stopping-bound/stronger/BicycleBaseCore.lean

Immutable: https://github.com/alectionary/vibe-math/blob/3e70cc79d7c4c171027a2a40f0757781d9787efb/formalization/stopping-bound/stronger/BicycleBaseCore.lean

BicycleDegrees.lean - new checked proof module

Current: https://github.com/alectionary/vibe-math/blob/master/formalization/stopping-bound/stronger/BicycleDegrees.lean

Immutable: https://github.com/alectionary/vibe-math/blob/3e70cc79d7c4c171027a2a40f0757781d9787efb/formalization/stopping-bound/stronger/BicycleDegrees.lean

BicycleFamily.lean - new checked proof module

Current: https://github.com/alectionary/vibe-math/blob/master/formalization/stopping-bound/stronger/BicycleFamily.lean

Immutable: https://github.com/alectionary/vibe-math/blob/3e70cc79d7c4c171027a2a40f0757781d9787efb/formalization/stopping-bound/stronger/BicycleFamily.lean

BicycleFamilyCore.lean - new checked proof module

Current: https://github.com/alectionary/vibe-math/blob/master/formalization/stopping-bound/stronger/BicycleFamilyCore.lean

Immutable: https://github.com/alectionary/vibe-math/blob/3e70cc79d7c4c171027a2a40f0757781d9787efb/formalization/stopping-bound/stronger/BicycleFamilyCore.lean

BicycleLogical.lean - new checked proof module

Current: https://github.com/alectionary/vibe-math/blob/master/formalization/stopping-bound/stronger/BicycleLogical.lean

Immutable: https://github.com/alectionary/vibe-math/blob/3e70cc79d7c4c171027a2a40f0757781d9787efb/formalization/stopping-bound/stronger/BicycleLogical.lean

Appendix B. Full Lean URLs (continued)

BicycleMatrices.lean - new checked proof module

Current: https://github.com/alectionary/vibe-math/blob/master/formalization/stopping-bound/stronger/BicycleMatrices.lean

Immutable: https://github.com/alectionary/vibe-math/blob/3e70cc79d7c4c171027a2a40f0757781d9787efb/formalization/stopping-bound/stronger/BicycleMatrices.lean

BicycleOverlap.lean - new checked proof module

Current: https://github.com/alectionary/vibe-math/blob/master/formalization/stopping-bound/stronger/BicycleOverlap.lean

Immutable: https://github.com/alectionary/vibe-math/blob/3e70cc79d7c4c171027a2a40f0757781d9787efb/formalization/stopping-bound/stronger/BicycleOverlap.lean

CSSStopping.lean - new checked proof module

Current: https://github.com/alectionary/vibe-math/blob/master/formalization/stopping-bound/stronger/CSSStopping.lean

Immutable: https://github.com/alectionary/vibe-math/blob/3e70cc79d7c4c171027a2a40f0757781d9787efb/formalization/stopping-bound/stronger/CSSStopping.lean

GramObstruction.lean - new checked proof module

Current: https://github.com/alectionary/vibe-math/blob/master/formalization/stopping-bound/stronger/GramObstruction.lean

Immutable: https://github.com/alectionary/vibe-math/blob/3e70cc79d7c4c171027a2a40f0757781d9787efb/formalization/stopping-bound/stronger/GramObstruction.lean

KernelStopping.lean - new checked proof module

Current: https://github.com/alectionary/vibe-math/blob/master/formalization/stopping-bound/stronger/KernelStopping.lean

Immutable: https://github.com/alectionary/vibe-math/blob/3e70cc79d7c4c171027a2a40f0757781d9787efb/formalization/stopping-bound/stronger/KernelStopping.lean

PartitionBound.lean - new checked proof module

Current: https://github.com/alectionary/vibe-math/blob/master/formalization/stopping-bound/stronger/PartitionBound.lean

Immutable: https://github.com/alectionary/vibe-math/blob/3e70cc79d7c4c171027a2a40f0757781d9787efb/formalization/stopping-bound/stronger/PartitionBound.lean

PowersFamily.lean - new checked proof module

Current: https://github.com/alectionary/vibe-math/blob/master/formalization/stopping-bound/stronger/PowersFamily.lean

Immutable: https://github.com/alectionary/vibe-math/blob/3e70cc79d7c4c171027a2a40f0757781d9787efb/formalization/stopping-bound/stronger/PowersFamily.lean

PowersThree.lean - new checked proof module

Current: https://github.com/alectionary/vibe-math/blob/master/formalization/stopping-bound/stronger/PowersThree.lean

Immutable: https://github.com/alectionary/vibe-math/blob/3e70cc79d7c4c171027a2a40f0757781d9787efb/formalization/stopping-bound/stronger/PowersThree.lean

Appendix B. Full Lean URLs (continued)

SidonBad.lean - new checked proof module

Current: https://github.com/alectionary/vibe-math/blob/master/formalization/stopping-bound/stronger/SidonBad.lean

Immutable: https://github.com/alectionary/vibe-math/blob/3e70cc79d7c4c171027a2a40f0757781d9787efb/formalization/stopping-bound/stronger/SidonBad.lean

SidonMatrices.lean - new checked proof module

Current: https://github.com/alectionary/vibe-math/blob/master/formalization/stopping-bound/stronger/SidonMatrices.lean

Immutable: https://github.com/alectionary/vibe-math/blob/3e70cc79d7c4c171027a2a40f0757781d9787efb/formalization/stopping-bound/stronger/SidonMatrices.lean

SidonStopping.lean - new checked proof module

Current: https://github.com/alectionary/vibe-math/blob/master/formalization/stopping-bound/stronger/SidonStopping.lean

Immutable: https://github.com/alectionary/vibe-math/blob/3e70cc79d7c4c171027a2a40f0757781d9787efb/formalization/stopping-bound/stronger/SidonStopping.lean

StrongerAnswer.lean - new checked proof module

Current: https://github.com/alectionary/vibe-math/blob/master/formalization/stopping-bound/stronger/StrongerAnswer.lean

Immutable: https://github.com/alectionary/vibe-math/blob/3e70cc79d7c4c171027a2a40f0757781d9787efb/formalization/stopping-bound/stronger/StrongerAnswer.lean

dependencies/IncidenceCore.lean - inherited proof dependency

Current:
https://github.com/alectionary/vibe-math/blob/master/formalization/stopping-bound/stronger/dependencies/IncidenceCore.lean

Immutable: https://github.com/alectionary/vibe-math/blob/3e70cc79d7c4c171027a2a40f0757781d9787efb/formalization/stopping-bound/stronger/dependencies/IncidenceCore.lean

dependencies/IncidenceCover.lean - inherited proof dependency

Current:
https://github.com/alectionary/vibe-math/blob/master/formalization/stopping-bound/stronger/dependencies/IncidenceCover.lean

Immutable: https://github.com/alectionary/vibe-math/blob/3e70cc79d7c4c171027a2a40f0757781d9787efb/formalization/stopping-bound/stronger/dependencies/IncidenceCover.lean

dependencies/IncidenceList.lean - inherited proof dependency

Current:
https://github.com/alectionary/vibe-math/blob/master/formalization/stopping-bound/stronger/dependencies/IncidenceList.lean

Immutable: https://github.com/alectionary/vibe-math/blob/3e70cc79d7c4c171027a2a40f0757781d9787efb/formalization/stopping-bound/stronger/dependencies/IncidenceList.lean

Appendix C. Source chronology and explicit calendar deltas

Civil calendar days to 2026-10-24; exact dates give exact differences. Month/year precision yields inclusive minimum/maximum day ranges; dates are not invented. Date ranges are clipped to the revision because these records already existed then. Source age is not unresolved-problem duration.

The ledger includes inherited comparison sources, all newly used primary papers, public software snapshots and held discovery leads. A held lead has an inspection-only delta when its earliest date was not assessed. This does not make the inspection its publication date. Source age is not an unsolved duration.

Source / role	Milestone, date and calendar days	Access / precision
F16: Abiad-Castriota: motivating parameter question; Original question; Prop.5.1 / Remark5.2 / §6	first and inspected v1: 2026-07-15; 101 days (day)	inspected full text
F68: Tanner: Minimum Distance Bounds by Graph Analysis; Classical spectral ingredient	earliest inspected manuscript: 2000-07-26; 9586 days (day) journal milestone: 2001; 9063-9427 days (year)	inspected full text
F67: Zhu-Chugg: Bounds on the Expansion Properties of Tanner Graphs; Classical stopping bound; exact Cor.6 comparison	conference predecessor metadata: 2005-09-28; 7696 days (day) inspected journal version: 2007-12; 6872-6902 days (month)	inspected full text
F69: Panteleev-Kalachev: Degenerate Quantum LDPC Codes With Good Finite Length Performance; Scalar-factor construction	first v1: 2019-04-04; 2760 days (day) inspected v3: 2021-11-12; 1807 days (day) journal milestone: 2021-11-22; 1797 days (day)	inspected full text
F70: Leverrier-Zemor: Quantum Tanner codes; Constituent Ramanujan comparison	first v1: 2022-02-28; 1699 days (day) inspected v3: 2022-09-16; 1499 days (day) PDF internal date: 2022-09-19; 1496 days (day)	inspected full text
F71: Feng-Li: Spectra of Hypergraphs and Applications; Classical source cited by Remark5.2; not a proof premise	publication metadata: 1996-09; 10981-11010 days (month)	abstract only full text gap
F72: Li-Sole: Spectra of Regular Graphs and Hypergraphs and Orthogonal Polynomials; Classical comparison lead; not a proof premise	publication metadata: 1996; 10889-11254 days (year)	partial web text archival gap
F73: Prabhu et al.: On the Efficacy of the Peeling Decoder for the Quantum Expander Code; Known stopping-set mechanisms and expansion conditions	first v1: 2025-04-30; 542 days (day) inspected v2: 2025-05-29; 513 days (day)	inspected full text
F74: Wang-Kulkarni-Poor: Finding All Small Error-Prone Substructures in LDPC Codes; Classical rooted narrowing and branch-and-bound	related first preprint: 2006-05-19; 7463 days (day) inspected current-version date: 2009-04-22; 6394 days (day) journal issue: 2009-05; 6355-6385 days (month)	inspected full text
F75: Yao-Gokduman-Pfister: Cluster Decomposition for Improved Erasure Decoding of Quantum LDPC Codes; B1 simulations / peeling-cluster comparison	first and inspected v1: 2024-12-11; 682 days (day)	inspected full text

Source / role	Milestone, date and calendar days	Access / precision
Connolly2024: Connolly-Londe-Leverrier-Delfosse: Fast erasure decoder for hypergraph product codes; Original stabilizer-support mechanism, credited through inspected F73/F75	first v1: 2022-08-01; 1545 days (day) v3 metadata: 2024-08-21; 794 days (day) journal publication: 2024-08-27; 788 days (day)	metadata only full text not consulted
F76: Prabhu-Gayathri-Kumar: On the Analysis of Stopping Sets Associated with the Quantum Hypergraph Product Code; Later comparison lead; no exact theorem claim	conference metadata: 2026; 0-296 days (year)	full text access gap
RosnesYtrehus2007: Rosnes-Ytrehus: An Algorithm to Find All Small-Size Stopping Sets of Low-Density Parity-Check Matrices; Bibliography-only enumeration lead	conference year: 2007; 6872-7236 days (year)	bibliography only not used as theorem evidence
Morris2025: Kirsten Morris: Analysis of Graph-based Decoders for Quantum Low Density Parity Check Codes; Discovery trail through existing dissertation inventory	repository source version: 2025-08; 419-449 days (month)	discovery record not new full text screen
qLDPCOrg/qLDPC: qLDPCOrg/qLDPC pinned snapshot; Software/infrastructure snapshot, not original publication age	inspected commit: 2026-10-23; 1 days (day)	pinned source or infrastructure
Lcrypto/Stopping-sets-enumerator: Lcrypto/Stopping-sets-enumerator pinned snapshot; Software/infrastructure snapshot, not original publication age	inspected commit: 2023-10-29; 1091 days (day)	pinned source or infrastructure
leanprover-community/mathlib4: leanprover-community/mathlib4 pinned snapshot; Software/infrastructure snapshot, not original publication age	inspected commit: 2026-10-21; 3 days (day)	pinned source or infrastructure
X-source-announcement: mathCObot source-paper announcement; Accessible X comparison; not a mathematical answer	post UTC date: 2026-07-16; 100 days (day)	post inspected in parent audit
X-earlier-result: A_Lectionary earlier absorbing-set announcement; Earlier repository result; different target	post UTC date: 2026-10-24; 0 days (day)	post inspected in parent audit
other-code-snapshots: Other inspected GitHub mirrors/README-only code; Secondary discovery/control sources; no theorem or earliest-publication claim	recorded inspection: 2026-10-24; 0 days (day)	inspection date only earliest dates unassessed
Lean-runtime: Lean4.36.0-rc1 runtime; Pinned proof checker; release-age claim not made	recorded use: 2026-10-24; 0 days (day)	use date only release date unassessed

Source / role	Milestone, date and calendar days	Access / precision
F77: Schwartz-Vardy: stopping distance and stopping redundancy; Classical matrix-dependent stopping convention, codeword mechanism and distinct-column criterion	first preprint metadata: 2005-03-23; 7885 days (day) journal revised manuscript: 2005-12-09; 7624 days (day) inspected journal issue: 2006-03; 7512-7542 days (month)	inspected full text
F78: Wang-Pryadko: Distance bounds for generalized bicycle codes; Binary GB/CSS construction convention and logical-distance comparison	first and inspected v1 submission: 2022-03-31; 1668 days (day) PDF internal date: 2022-04-01; 1667 days (day)	inspected full text
F79: Kuo-Ouyang: Degenerate quantum erasure decoding; Quantum-aware decoding comparison; article-in-press main text screened	first preprint metadata: 2024-11-20; 703 days (day) received: 2025-05-31; 511 days (day) accepted: 2026-02-23; 243 days (day) publication / inspected article-in-press: 2026-03-13; 225 days (day) version of record metadata: 2026-04-29; 178 days (day)	inspected full text
F80: Kashyap-Vardy: Stopping Sets in Codes from Designs; Classical uniform-overlap lower bound, Theorem1	reported conference presentation: 2003; 8333-8697 days (year) reported original composition: 2003-09; 8425-8454 days (month) inspected revised author manuscript: 2026-10-24; 0 days (day)	full web text screened direct pdf download403 transcription archived
gideonlsx/bicycle-race: gideonlsx/bicycle-race pinned public repository; README/software comparison; not theorem evidence	inspected commit: 2026-10-11; 13 days (day)	public metadata or readme inspected
kywukuo/qLDPC_dec: kywukuo/qLDPC_dec pinned public repository; README/software comparison; not theorem evidence	inspected commit: 2026-01-26; 271 days (day)	public metadata or readme inspected
new-proof-checkpoint: This stronger-bound proof checkpoint; Checked mathematical source, not a priority date	new research and proof-source checkpoint: 2026-10-24; 0 days (day)	checked lean source
held-lead-1: Generalized Bicycle Codes with Low Connectivity: Minimum Distance Bounds and Hook Errors; Encountered lead, no theorem premise or zero-question claim	inspection only: 2026-10-24; 0 days (day)	metadata or abstract only fulltext unassessed
held-lead-2: Spectral Theory of Semisimple Bivariate Bicycle Codes; Encountered lead, no theorem premise or zero-question claim	inspection only: 2026-10-24; 0 days (day)	metadata or abstract only fulltext unassessed
held-lead-3: Logical Operator Decomposition for Distance Analysis of Bivariate Bicycle Codes; Encountered lead, no theorem premise or zero-question claim	inspection only: 2026-10-24; 0 days (day)	metadata or abstract only fulltext unassessed
held-lead-4: Permutation Decoding and the Stopping Redundancy Hierarchy; Encountered lead, no theorem premise or zero-question claim	inspection only: 2026-10-24; 0 days (day)	metadata or abstract only fulltext unassessed

Source / role	Milestone, date and calendar days	Access / precision
held-lead-5: Quantum Maxwell Erasure Decoder for qLDPC codes; Encountered lead, no theorem premise or zero-question claim	inspection only: 2026-10-24; 0 days (day)	metadata or abstract only fulltext unassessed
held-lead-6: Minimum Pseudo-Weight and Minimum Pseudo-Codewords of LDPC Codes; Encountered lead, no theorem premise or zero-question claim	inspection only: 2026-10-24; 0 days (day)	metadata or abstract only fulltext unassessed

Inspection-only dates are explicitly distinguished from publication dates. The Kashyap-Vardy author manuscript is undated after its reported2003 composition; its web transcription hash is not a PDF hash. Supplementary/final-version, citation-index and X access gaps remain named. Date differences are source ages, not durations of unsolved problems.

Investigation record: the new three-hour block began24October2026,22:59:20UTC, with deadline25October2026,01:59:20UTC. The first aggregate source build/audit completed at 2026-10-24T23:36:01.519761+00:00. The initial mathematical and formal checkpoint precedes manuscript rendering/publication; later revisions record their own times. This is separate from the earlier source-question investigation and the101 calendar days since the15July source.