

Estructuras de Datos

EEDD - GRAN DOCTORADO EN INGENIERIA DE INFORMÁTICA - UCO

Estructuras lineales:
Arrays


Contenidos

- Características de la estructuras lineales.
- Arrays:
 - Array.
 - Array dinámico.
 - Array dinámico circular.

EEDD - GRADO EN ING. INFORMÁTICA - UCO

Introducción

- Estructuras lineales.
 - Contenedores de datos genéricos.
 - Relación 1-1: cada elemento tiene un predecesor y un sucesor (salvo el inicial y el final).
 - Indicadas cuando se realiza un proceso secuencial de los datos.



Arrays

- Arrays.

Array[T]:

- Makers:**

- `make(size:Integer):Array[T]`
 - *pre-c: size>0*

- Observers:**

- `size():Integer`
- `get(i:Integer)`
 - *pre-c: i>=0 and i<size()*

- Modifiers:**

- `set(i:Integer, item:T)`
 - *pre-c: i>=0 and i<size()*
 - *post-c: get(i)==item*

```
Algorithm Array::make(size:Integer):Integer //0(1)
```

```
Begin
```

```
    mem_ <- getMemory(size(T)*size)
```

```
    size_ <- size
```

```
End.
```

```
Algorithm Array::size():Integer //0(1)
```

```
Begin
```

```
    Return size_
```

```
End.
```

```
Algorithm Array::get(i:Integer):T //0(1)
```

```
Begin
```

```
    Return convert[T](mem_+i*size(T))
```

```
End.
```

```
Algorithm DArray::set(i:Integer, v:T) //0(1)
```

```
Begin
```


```
    copy(memDir(v),memDir(v)+size(T), mem_+i*size(T))
```

```
End.
```

Array[T]

`mem_:MemoryChunck`

`size_:Integer`



Arrays

- Array dinámico.

DArray[T] extends Array[T]:

- **Makers:**

- **make():DArray**

- *post-c: capacity()=1*
 - *post-c: size()=0*

- **Observers:**

- **capacity():Integer**

- **isEmpty():Bool**

- *post-c: !retV || size()=0*

- **isFull():Bool**

- *post-c: !retV || capacity()=size()*

- **Modifiers:**

- **pushBack(v:T)**

- *post-c: size()=old.size()+1*
 - *post-c: get(size()-1)==v*

- **popBack()**

- *prec-c: !isEmpty()*
 - *post-c: size()=old.size()-1*
 - *post-c: size()>=1 → get(size()-1)=old.get(old.size()-2)*

Es un X
que
además ...

Valor
retornado

El estado
antes de
realizar la
operación.

- **Modifiers:**

- **insert(i:Integer, v:T)**

- *pre-c: 0 ≤ i < size()*
 - *post-c: size()=old.size()+1*
 - *post-c: get(i)=v*

- **remove(i)**

- *pre-c: 0 ≤ i < size()*
 - *post-c: size()=old.size()-1*
 - *post-c: i==size() or get(i)=old.get(i+1)*

- **Invariants:**

- *size() ≤ capacity()*



Arrays

- Array dinámico: diseño.

```
Algorithm DArray::isEmpty():Bool //O(1)
Return size()==0
```

```
Algorithm DArray::isFull():Bool //O(1)
Return size()==capacity()
```

```
Algorithm DArray::pushBack(v:T) //O(1)
Begin
  If (isFull()) Then
    grow(_data)
    data_.set(size_, v)
    size_ ← size_ + 1
End.
```

```
Algorithm DArray::popBack()//O(1)
Begin
  size_ ← size_ - 1
End.
```

```
Algorithm DArray::grow()//O( )
Begin
  tmp ← Array(capacity()*2)
  copy[T](data_.mem_, 0, size_, tmp.mem_)
  data_ ← tmp
End.
```

```
Algorithm DArray::insert(i:Integer, v:T)//O( )
Begin
  If (isFull()) then
    grow()
  For j ← size_ - 1 To i Inc -1 Do
    data_.set(j+1, data_.get(j))
  data_.set(i, v)
  size_ ← size_ + 1
End.
```

```
Algorithm DArray::remove(i:Integer)//O( )
Begin
  For j ← i To _size-2 Inc 1 Do
    data_.set(j, data_.get(j+1))
  size_ ← size_ - 1
End.
```

DArray[T]:
data_:Array[T]
size_:Integer




Arrays

- Array dinámico circular.

CArray[T] extends DArray[T]:

- Makers:**
 - make():CArray**
 - post-c: capacity()=1
 - post-c: size()=0
- Observers:**
- Modifiers:**
 - pushFront(v:T)**
 - post-c: size()=old.size()+1
 - post-c: get(0)=v
 - popFront()**
 - prec-c: !isEmpty()
 - post-c: size()=old.size()-1
 - post-c: isEmpty() || get(0)=old.get(1)



```
Algorithm cInc(i:Integer, capacity:Integer):Integer
//0(1)
Begin
    Return (i+1)%capacity
End.
```

```
Algorithm cDec(i:Integer, capacity:Integer):Integer
//0(1)
Begin
    Return (i-1+capacity)%capacity
End.
```

Arrays

- Array dinámico circular.

```
Algorithm DArray::capacity():Integer
Return data_.size()
```

```
Algorithm DArray::size():Integer
Return size_
```

```
Algorithm DArray::pushBack(v:T) //O(n) CA(1)
Begin
  If isEmpty() Then
    front_ <- 0
    back_ <- 0
  Else
    If (isFull()) Then
      grow()
      back_ <- cInc(back_, capacity())
    End-If
    data_.set(back_, v)
    size_ <- size_ + 1
  End.
```


```
Algorithm DArray::popBack() //O(1)
Begin
  back_ <- cDec(back_, capacity())
  size_ <- size_ - 1
End.
```

```
Algorithm DArray::pushFront(v:T) //O(n) CA(1)
Begin
  If isEmpty() Then
    front_ <- 0
    back_ <- 0
  Else
    If (isFull()) Then
      grow()
      front_ <- cDec(front_, capacity())
    End-If
    data_.set(front_, v)
    size_ <- size_ + 1
  End.
```

```
Algorithm DArray::popFront() //O(1)
Begin
  front_ <- cInc(front_, capacity())
  size_ <- size_ - 1
End.
```

CArray[T]

```
data_ :Array[T]
front_:Integer
back_ :Integer
size_ :Integer.
```



Arrays

- Array dinámico circular.

```
Algorithm DArray::get(i:Integer):T //O(1) CA(1)
Begin
    Return data_.get((front_+i)%capacity())
End.
```

```
Algorithm DArray::set(i:Integer, v:T) //O(1)
Begin
    data_.set((front_+i)%capacity(), v)
End.
```

```
Algorithm DArray::grow(data:Array[T]) //O(n)
Begin
    tmp <- Array(capacity()*2)
    For i <- 0 TO size()-1 Inc 1 Do
        tmp.set(i, get(i))
    front_ <- 0
    back_ <- size_-1
    data <- tmp
End.
```

```
Algorithm DArray::insert(pos:Integer, v:T) //O(n)
Begin
    If pos=0 Then
        push_front(v)
    Else
        If (isFull()) Then
            grow()
        size_ <- size_ + 1
        For i <- size()-2 To pos Inc -1 Do
            set(i+1, get(i))
        set(pos, v)
        back_ <- cInc(back_, capacity())
    End-If
End.
```

```
Algorithm DArray::remove(pos:Integer) //O(n)
Begin
    For i <- pos TO size()-2 Inc 1 Do
        set(i, get(i + 1))
    back_ <- cDec(back_, capacity())
    size_ <- size_ - 1
End.
```

Arrays

- Array dinámico circular.

```
Algorithm fold(out:Stream, data:CDArray[T]) //O( n )
Var
  i: Integer
Begin
  out.write('[')
  For i<-0 TO data.size()-1 Inc 1 Do
    out.write(' ', a.get(i))
  out.write(']')
End.
```

```
Algorithm unfold(in:Stream):CDArray[T] //O( n )
Var
  token:String
  data:CDArray[t]
Begin
  in.read(token)
  If token = '[' Then
    in.read(token)
    While Not in.eof() And token <> ']' Do
      data.pushBack(T(token))
      in.read(token)
    End-While
    If token <> ']' Then
      Error ('Wrong format')
    Else
      Error ('Worng format')
    Return data
  End.
```

→ "palabra", unidad mínima de significado

Resumiendo

- El Array está pensado principalmente para tener un acceso aleatorio con $O(1)$ a costa de tener un tamaño fijo \rightarrow uso ineficiente de la memoria.
- El Array dinámico permite un uso más eficiente de la memoria al poder modificar su tamaño pero con coste $O(N)$ y coste amortizado $O(1)$.
- El Array dinámico circular permite crecer el array tanto por la cabeza como por la cola.

Referencias

- Lecturas recomendadas:
 - Caps. 8 y 9 de “Estructuras de Datos”, A. Carmona y otros. U. de Córdoba. 1999.
 - Caps 6 y 7 de “*Data structures and software development in an object oriented domain*”, Tremblay J.P. y Cheston, G.A. Prentice-Hall, 2001.
 - Wikipedia.