


Scientific Machine Learning for Exact Recovery of Nonlinear PDEs



Aleksei Sorokin¹²³, Fred Hickernell¹, Pieterjan Robbe², Mohamed Wahib³,
Houman Owhadi⁴, Aras Bacho⁴, Xianjin Yang⁴, Matthieu Darcy⁴,
Theo Bourdais⁴, Edo Calvello⁴, Bamdad Hosseini⁵, Alexandre Hsu⁵

¹Illinois Tech, Department of Applied Math, Chicago IL, USA

²Sandia National Laboratories, Livermore CA, USA

³RIKEN Center for Computational Science, Tokyo Japan

⁴California Institute of Technology, Pasadena, California

⁵University of Washington, Seattle, Washington

Background

PhD Student in Applied Math at Illinois Tech in Chicago IL, advisor Fred J Hickernell

- (Quasi-)Monte Carlo for fast high dimensional integration
- Gaussian Process Modeling with structure-exploits for scalable UQ
- Scientific Software Development for distribution of efficient algorithms

US DOE SCGSR Fellow¹ at Sandia National Laboratories in Livermore CA

- Multilevel (Quasi-)Monte Carlo for multi-fidelity or infinite-dimensional problems
- Scientific machine learning (SciML) for solving nonlinear PDEs

Intern in the RIKEN CCS AI-HPC Research Team in Tokyo Japan

- SciML for Exact PDE Recovery focused on applications to inverse problems
- HPC Compatible Implementations supporting multi-GPU parallelism

¹Department of Energy Office of Science Graduate Student Research Program





Quasi-Monte Carlo Methods

Efficient algorithms for high dimensional numerical integration [Choi et al., 2022, Hickernell et al., 2025]

$$\mu = \int_{\mathcal{T}} g(\mathbf{t}) \lambda(d\mathbf{t}) = \int_{[0,1]^d} f(\mathbf{x}) d\mathbf{x} \approx \frac{1}{n} \sum_{i=1}^n f(\mathbf{x}_i), \quad \mathbf{x}_1, \dots, \mathbf{x}_n \in [0,1]^d$$


Classic Monte Carlo has error like $\mathcal{O}(1/\sqrt{n})$ using IID points $[\mathbf{x}_i]_{i=1}^n$

QMC has errors like $\mathcal{O}(1/n)$ using low discrepancy (LD) points with greater uniformity



Adaptive QMC Stopping Criterion

Automatically choose sample size n to meet user specified error tolerances [Sorokin and Rathinavel, 2022]



pip install `qmcipy`: QMC Python software qmcpy.readthedocs.io/en/latest/


Gaussian Process Regression with Structure-Exploits

Scalable kernel interpolation with built in uncertainty quantification (UQ) [Rathinavel and Hickernell, 2019, 2022]


$$f(\mathbf{x}) \approx \mathbf{K}(\mathbf{x})^T \mathbf{K}^{-1} \mathbf{f}$$

- SPD kernel $K(\cdot, \cdot)$
- Points $[\mathbf{x}_i]_{i=1}^n$
- Values $\mathbf{f} = [f(\mathbf{x}_i)]_{i=1}^n$
- Basis $\mathbf{K}(\cdot) = [K(\cdot, \mathbf{x}_i)]_{i=1}^n$
- Gram matrix $\mathbf{K} = [K(\mathbf{x}_i, \mathbf{x}_j)]_{i,j=1}^N$

SI Lattice K



DSI Digital Net K



Classic GPR costs $\mathcal{O}(n^3)$ as we must compute the matrix inverse \mathbf{K}^{-1}

Fast GPR cost only $\mathcal{O}(n \log n)$ by pairing (SI/DSI) kernels K to LD points $[\mathbf{x}_i]_{i=1}^n$





- Exploit structure in the Gram matrix \mathbf{K} : diagonalizable by fast Fourier transforms

Fast Gaussian Process Regression

SE grid
error = 3.7e-2
time = 1.6e0
MLL = 6.3e3

SI lattice
error = 2.8e-2
time = 8.0e-4
MLL = -3.8e2

DSI digital net
error = 2.6e-2
time = 1.5e-3
MLL = -4.5e3



pip install **fastgps**: Scalable GPR Python software alegresor.github.io/fastgps

Nonlinear PDEs with Random Coefficients

Applications in Fluid Mechanics, Geophysics, Medical Imaging, ...

Nonlinear PDE $F(v^*|c) = 0$, solution v^* , random coefficient c

Nonlinear Elliptic PDE

$$F(v|c) = -\Delta v + \kappa v^3 - c$$

Burgers' Equation with an implicit time stepping scheme (step size h_t , constant $\kappa > 0$)

$$F(v|c) = v - h_t(\kappa \nabla^2 v - v \nabla v) - c$$

Nonlinear Darcy flow with forcing term f

$$F(v|c) = -e^c[\nabla c \cdot \nabla v + \nabla^2 v] + \kappa v^3 - f$$

Full Waveform Inversion sets $F(v|c) = P(v) - c$ where P a numerical forward solver

The Newton–Kantorovich Iteration

A relaxed Gauss–Newton algorithm for root finding in Hilbert spaces of functions [Polyak, 2006]

Nonlinear PDE $F(v^*) = 0$, solution v^* , random coefficient c

Given c and a relaxation parameter $\lambda > 0$, an **optimal update** $\delta^*(v)$ is

$$\operatorname{argmin}_{\delta} (\|F(v + \delta)\|^2 + \lambda \|\delta\|^2) \approx - \left[\frac{\partial F^T}{\partial v}(v) \frac{\partial F}{\partial v}(v) + \lambda I \right]^{-1} \frac{\partial F^T}{\partial v}(v) F(v) =: \delta^*(v)$$


The Newton–Kantorovich iteration with learning rate $\alpha > 0$ sets

$$v_{n+1} = v_n + \alpha \delta^*(v_n)$$

Relaxation λ interpolates between gradient descent and Gauss–Newton updates

Newton–Kantorovich Iteration for Full Waveform Inversion

Finds subsurface velocity from a surface acoustic signal [Deng et al., 2022, Virieux and Operto, 2009]



SciML for Exact Recovery of Nonlinear PDEs

Learning the approximate Hessian operator enables sciML to converge to machine precision

$$v_{n+1}(c) = v_n(c) - \alpha H^{-1}(v, c, \lambda) \frac{\partial F^T}{\partial v}(v, c) F(v, c)$$

$$H(v, c, \lambda) = L(v, c, \lambda) L^T(v, c, \lambda) = \frac{\partial F^T}{\partial v}(v, c) \frac{\partial F}{\partial v}(v, c) + \lambda I$$

	Existing sciML Methods	Novel CHONKNORIS Method
Learn to predict	a function (operator learning)	an operator (learning to learn)
Learned Map	$c \mapsto v_S$	$(v, c, \lambda) \mapsto L(v, c, \lambda)$
Input \mapsto Output Sizes	$\mathcal{O}(N) \mapsto \mathcal{O}(N)$	$\mathcal{O}(N) \mapsto \mathcal{O}(N^2)$
Achievable Errors	$\approx \mathcal{O}(10^{-2})$ or $\mathcal{O}(10^{-3})$	machine precision $\mathcal{O}(10^{-16})$


Existing sciML methods

- artificial neural networks [Li et al., 2020, Lu et al., 2021]
- kernel methods [Batlle et al., 2024, Kadri et al., 2016, Nelsen and Stuart, 2021]
- hybrid approaches [Mora et al., 2025, Owhadi, 2023, Owhadi and Yoo, 2019]

Nonlinear Elliptic PDE

CHONKNORIS achieves machine precision recovery in 12 iterations







$$F(v|c) = -\Delta v + \kappa v^3 - c, \quad \left[\frac{\partial F}{\partial v}(v) \right](h) = [-\Delta + 3\kappa v^2](h)$$



- CHONKNORIS requires more iterations but avoids cubic inversion cost in NK
- Initial guess from existing sciML method can accelerate convergence

Burgers' Equation with Shocks via Implicit Time Stepping


CHONKNORIS (at each time step) recovers solutions f to within 10^{-16} error





CHONKNORIS Requires a Scalable Implementation and Careful Tuning

Darcy equation with 15×15 discretization requires predicting over $> 25k$ outputs
Automatic selection of (λ, α) improve stability, e.g., using line search


- Relaxation λ must be adaptively decreased for convergence to machine precision
- Learning rate α trades off convergence speed and robustness






Darcy Flow in Two Dimensions



Classic operator learning error
 L_2 relative error = 1.3e-03




Our CHONKNORIS method
 L_2 relative error = 7.3e-16




Machine Precision Foundation Modeling for Common Jacobian Structures

CHONKNORIS trained on 1D PDEs can exactly recover unseen Sine–Gordon and Klein–Gordon PDEs



Full Waveform Inversion

CHONKNORIS can exactly recover rough solutions at low resolutions



CHONKNORIS struggles to predict the ill conditioned matrices from

- fine discretizations
- rough coefficients
- near convergence perturbations

RIKEN-CCS Experience

Thank you to Dr Wahib and the AI-HPC team!


- Everyone was engaging, helpful, and kind
- Smooth onboarding and supportive staff

Provided access to large-scale HPC machines

- Implemented multi-GPU acceleration
- Evaluated Jacobians with millions of entries
- Trained large scale AI models

Appreciated the culture in Tokyo

- Business professional atmosphere
- Respectful, clean, and safe



Benten Pond near Tokyo Tower

RIKEN-CCS Experience

Thank you to Dr Wahib and the AI-HPC team!

- Everyone was engaging, helpful, and kind
- Smooth onboarding and supportive staff


Provided access to large-scale HPC machines

- Implemented multi-GPU acceleration
- Evaluated Jacobians with millions of entries
- Trained large scale AI models

Appreciated the culture in Tokyo

- Business professional atmosphere
- Respectful, clean, and safe

Thank you for listening! Connect or follow my research at alegresor.github.io



Benten Pond near Tokyo Tower

References I

Pau Batlle, Matthieu Darcy, Bamdad Hosseini, and Houman Owhadi. Kernel methods are competitive for operator learning. *Journal of Computational Physics*, 496: 112549, 2024.

Sou-Cheng T. Choi, Fred J. Hickernell, Rathinavel Jagadeeswaran, Michael J. McCourt, and Aleksei G. Sorokin. Quasi-Monte Carlo software. In Alexander Keller, editor, *Monte Carlo and Quasi-Monte Carlo Methods*, pages 23–47, Cham, 2022. Springer International Publishing. ISBN 978-3-030-98319-2.

Chengyuan Deng, Shihang Feng, Hanchen Wang, Xitong Zhang, Peng Jin, Yinan Feng, Qili Zeng, Yinpeng Chen, and Youzuo Lin. Openfwi: Large-scale multi-structural benchmark datasets for full waveform inversion. *Advances in Neural Information Processing Systems*, 35:6007–6020, 2022.

Fred J. Hickernell, Nathan Kirk, and Aleksei G. Sorokin. Quasi-monte carlo methods: What, why, and how?, 2025. URL <https://arxiv.org/abs/2502.03644>.

References II

- Hachem Kadri, Emmanuel Duflos, Philippe Preux, Stéphane Canu, Alain Rakotomamonjy, and Julien Audiffren. Operator-valued kernels for learning from functional response data. *Journal of Machine Learning Research*, 17(20):1–54, 2016.
- Zongyi Li, Nikola Kovachki, Kamyar Azizzadenesheli, Burigede Liu, Kaushik Bhattacharya, Andrew Stuart, and Anima Anandkumar. Fourier neural operator for parametric partial differential equations. *arXiv preprint arXiv:2010.08895*, 2020.
- Lu Lu, Pengzhan Jin, Guofei Pang, Zhongqiang Zhang, and George Em Karniadakis. Learning nonlinear operators via deeponet based on the universal approximation theorem of operators. *Nature machine intelligence*, 3(3):218–229, 2021.
- Carlos Mora, Amin Yousefpour, Shirin HosseiniMardi, Houman Owhadi, and Ramin Bostanabad. Operator learning with gaussian processes. *Computer Methods in Applied Mechanics and Engineering*, 434:117581, 2025.

References III

Nicholas H Nelsen and Andrew M Stuart. The random feature model for input-output maps between banach spaces. *SIAM Journal on Scientific Computing*, 43(5):A3212–A3243, 2021.

Houman Owhadi. Do ideas have shape? idea registration as the continuous limit of artificial neural networks. *Physica D: Nonlinear Phenomena*, 444:133592, 2023.

Houman Owhadi and Gene Ryan Yoo. Kernel flows: From learning kernels from data into the abyss. *Journal of Computational Physics*, 389:22–47, 2019.

Boris Teodorovich Polyak. Newton-kantorovich method and its global convergence. *Journal of Mathematical Sciences*, 133:1513–1523, 2006.

Jagadeeswaran Rathinavel and Fred J. Hickernell. Fast automatic bayesian cubature using lattice sampling. *Statistics and Computing*, 29(6):1215–1229, Sep 2019. ISSN 1573-1375. doi: 10.1007/s11222-019-09895-9. URL <http://dx.doi.org/10.1007/s11222-019-09895-9>.

References IV

Jagadeeswaran Rathinavel and Fred J Hickernell. Fast automatic bayesian cubature using sobol sampling. In *Advances in Modeling and Simulation: Festschrift for Pierre L'Ecuyer*, pages 301–318. Springer, 2022.

Aleksei G Sorokin and Jagadeeswaran Rathinavel. On bounding and approximating functions of multiple expectations using quasi-monte carlo. In *International Conference on Monte Carlo and Quasi-Monte Carlo Methods in Scientific Computing*, pages 583–599. Springer, 2022.

Jean Virieux and Stéphane Operto. An overview of full-waveform inversion in exploration geophysics. *Geophysics*, 74(6):WCC1–WCC26, 2009.