


## Multi-objective optimization of adhesive bonding process in constrained and noisy settings

Alejandro Morales-Hernández<sup>1,2</sup>, Ineke Van Nieuwenhuyse<sup>1,2</sup>, Sebastian Rojas Gonzalez<sup>1,2,3</sup>, Jeroen Jordens<sup>4</sup>, Maarten Witters<sup>4</sup>, Bart Van Dorrick<sup>4</sup>


<sup>1</sup> Flanders Make@U Hasselt and Data Science Institute, Hasselt University, Belgium  
<sup>2</sup> Department of Mathematics and Statistics, Faculty of Sciences, Hasselt University, Belgium  
<sup>3</sup> Surrogate Modeling Lab, Ghent University, Belgium  
<sup>4</sup> CoDesignG, Flanders Make, Belgium

This research is supported by the Flanders Artificial Intelligence Research Program



1


## Motivation



- Need for better fuel efficiency
- Results in lighter bodies, new materials
- Which tend to be more fragile, more difficult to join
- The right bonding process will improve strength

- Multi-objective optimization
  - Minimize cost **VS.** Maximize tensile strength
- Real experimentation is **expensive** and yield **noisy outputs**
  - The same process configuration generates different break strength/type of failure
- Different types of failure
  - Adhesive, cohesive, or substrate failure


2




3

**Efficiently** find good process parameters with a minimal set of experiments, and considering the **trade-off** between tensile strength and production cost


- Gaussian Process Regression (GPR) to account for the heterogeneous noise
- Acquisition function to sequentially (one-by-one) suggest new process parameter configurations to be evaluated.
  - GPR model and feasibility prediction)



✗ Burned sample



✗ Adhesive failure



✓ Substrate failure

Tensile strength


Production cost

$$\min [-TS(x), PC(x)]$$


$$\text{s.t. } 0.5 - Pf(x) \leq 0$$

probability that a process configuration  $x$  is feasible


4




5




6




7




8




9




10




11




12




13



14



15



16

## Conclusions and future work

- The use of machine learning techniques holds great promise in solving complex and expensive optimization problems, as it allows to obtain high-quality solutions within a smaller number of experiments, compared with evolutionary algorithms
- The use of the infill criterion allows the algorithm to efficiently search for the Pareto-optimal process settings, exploiting the information that has been learned from the already observed process settings (through the GPR and LRC models)
- Future research will focus on the inclusion of a third objective (minimization of the debonding break strength), account for the uncertainty in the feasibility, and the deployment of an interactive tool for real lab experiments.

***Thanks  
Q & A***

17

18