

Python API

Integración python

[Introducción](#)
[Driver API](#)
[Github](#)

Conexión

```
import clickhouse_connect
```

```
client = clickhouse_connect.get_client(  
    host='clickhouse',  
    port=8123,  
    username='ibd00',  
    password='xxxxx',  
    database='ibd00'  
)
```

Client query Method

Mecanismo básico para obtener un lote de registros del servidor ClickHouse. Utiliza el **formato nativo de ClickHouse a través de, ojo, HTTP** para transmitir conjuntos de datos de gran tamaño (hasta aproximadamente un millón de filas) de manera eficiente. Devuelve el resultado como un objeto *QueryResult*

```
# https://clickhouse.com/docs/integrations/language-clients/python/driver-api#client-query-method  
result = client.query('SELECT ip, uuid, url, osinfo, uaname, devname, meth, uref, status_code, ts FROM  
ibd00.accesos')  
for row in result.result_rows:  
    print(row)
```

```
(IPv4Address('138.122.195.222'), 'c6947993bd75a541ce087c7b1d328230db3dc910', '/apache-log/access.log',  
'Fedora:Fedora:', 'Firefox', 'Other', 'GET', 'http://www.almhuetten-raith.at/', 200, datetime.datetime(2022, 1, 4,  
9, 9, 31, 10000))  
(IPv4Address('138.128.59.173'), '3bbb8d412534bb70252fb5a0a343dcf119ac3154', '/index.php?  
option=com_easyblog&view=dashboard&layout=write', 'Linux:Linux:', 'Chrome', 'Other', 'GET', 'http://www.almhuetten-  
raith.at/', 404, datetime.datetime(2022, 1, 6, 16, 36, 41, 10000))  
(IPv4Address('138.128.106.194'), 'd26a41fc46bb877933f59a12d76cf7ad4c40eb95', '/apache-log/access.log',  
'Windows:Windows 8.1:8.1', 'Chrome', 'Other', 'GET', 'http://www.almhuetten-raith.at/', 200, datetime.datetime(2022,  
1, 4, 1, 55, 41, 10000))
```

NumPy, Pandas, and Arrow queries

El conector ofrece métodos especializados para trabajar con [NumPy](#), [Pandas](#) y [Arrow](#)

```
# https://clickhouse.com/docs/integrations/language-clients/python/advanced-querying#pandas-queries  
import pandas as pd  
  
result = client.query_df(  
    'SELECT ip, uuid, url, status_code, ts FROM ibd00.accesos WHERE IPv4NumToString(ip) LIKE %(mask)s',  
    {'mask': '138.128.%'}  
)  
result.head()
```

	ip	uuid	url	status_code	ts
0	138.128.59.173	3bbb8d412534bb70252fb5a0a343dcf119ac3154	/index.php? option=com_easyblog&view=dashboard&...	404	2022-01-06 16:36:41.010
1	138.128.106.194	d26a41fc46bb877933f59a12d76cf7ad4c40eb95	/apache-log/access.log	200	2022-01-04 01:55:41.010

