

S3 Source



Documentación Oficial

[Generalized Amazon S3 Source Connector for Confluent Platform](#)

- **Connector Operation Mode:** *RESTORE_BACKUP*

[Configuration Reference for Amazon S3 Sink Connector for Confluent Platform](#)

Partitioner Parameters (Backup and Restore Connector Only)

`partitioner.class`

The partitioner to use when reading data from the store.

- Type: class
- **Default:** `io.confluent.connect.storage.partitionner.DefaultPartitioner`
- Importance: high

`partition.field.name`

The name of the partitioning field when `FieldPartitioner` is used.

- Type: list
- **Default:** `""`
- Importance: medium

`path.format`

This configuration that was **used to set the format of the data directories when partitioning with a *TimeBasedPartitioner***

- Type: string
- **Default:** `""`
- Importance: medium

Source Safety

```
-----  
-- S3 Source - Safety  
-----  
CREATE SOURCE CONNECTOR `source-safety` WITH(  
  "connector.class" = 'io.confluent.connect.s3.source.S3SourceConnector',
```



```

"confluent.topic.bootstrap.servers" = 'kafka:9092',
"confluent.license" = '',
"confluent.license.topic.replication.factor" = '1',
"confluent.topic.replication.factor" = '1',
"storage.class" = 'io.confluent.connect.s3.storage.S3Storage',
"format.class" = 'io.confluent.connect.s3.format.json.JsonFormat',
"topics.dir" = 'safety',
"tasks.max" = '1',
"s3.bucket.name" = '4stations',
"s3.region" = 'eu-west-2',
"aws.access.key.id" = 'YA9JokyWUb2hFUbKYEEN',
"aws.secret.access.key" = '0k2ornkQpVTqUrBb0EsEX0nBEEWgJf4AFQOU407Y',
"store.url" = 'https://izar.ls.fi.upm.es:30009',
"partitioner.class" =
'io.confluent.connect.storage.partitionner.TimeBasedPartitionner',
"path.format" = '\'\hour\''=HH',
"locale" = 'es-ES',
"timezone" = 'Europe/Madrid',
"key.converter" = 'org.apache.kafka.connect.storage.StringConverter',
"key.converter.schema.registry.url" = 'http://schema-registry:8081',
"key.converter.schemas.enable" = 'false',
"value.converter" = 'org.apache.kafka.connect.json.JsonConverter',
"value.converter.schema.registry.url" = 'http://schema-registry:8081',
"value.converter.schemas.enable" = 'false');

```

Source Traffic

```

-----
-- S3 Source - Traffic
-----
CREATE SOURCE CONNECTOR `source-traffic` WITH(
  "connector.class" = 'io.confluent.connect.s3.source.S3SourceConnector',
  "confluent.topic.bootstrap.servers" = 'kafka:9092',
  "confluent.license" = '',
  "confluent.license.topic.replication.factor" = '1',
  "confluent.topic.replication.factor" = '1',
  "storage.class" = 'io.confluent.connect.s3.storage.S3Storage',
  "format.class" = 'io.confluent.connect.s3.format.avro.AvroFormat',
  "topics.dir" = 'traffic',
  "tasks.max" = '1',
  "s3.bucket.name" = '4stations',
  "s3.region" = 'eu-west-2',
  "aws.access.key.id" = 'YA9JokyWUb2hFUbKYEEN',
  "aws.secret.access.key" = '0k2ornkQpVTqUrBb0EsEX0nBEEWgJf4AFQOU407Y',
  "store.url" = 'https://izar.ls.fi.upm.es:30009',
  "partitioner.class" =
'io.confluent.connect.storage.partitionner.DefaultPartitionner',
  "key.converter" = 'io.confluent.connect.avro.AvroConverter',
  "key.converter.schema.registry.url" = 'http://schema-registry:8081',
  "key.converter.schemas.enable" = 'false',
  "value.converter" = 'io.confluent.connect.avro.AvroConverter',
  "value.converter.schema.registry.url" = 'http://schema-registry:8081',
  "value.converter.schemas.enable" = 'false');

```

