

JDBC Sink

Tabla *MariaDB*

```
-- MariaDB
--
DROP TABLE `failures`;
CREATE TABLE `failures` (
  `station` varchar(20) CHARACTER SET latin1 COLLATE latin1_spanish_ci NOT
  NULL,
  `equipment` varchar(20) CHARACTER SET latin1 COLLATE latin1_spanish_ci NOT
  NULL,
  `hh` varchar(2) NOT NULL,
  `nf` integer NOT NULL,
  `df` double NOT NULL,
  PRIMARY KEY (`station`,`equipment`,`hh`)
) ENGINE=InnoDB DEFAULT CHARSET=latin1;
```

Conector *Sink*

```
-- Kafka
--
CREATE SINK CONNECTOR `sink-jdbc-failures` WITH(
  "connector.class" = 'io.confluent.connect.jdbc.JdbcSinkConnector',
  "connection.url" = 'jdbc:mysql://mariadb:3306/demos?
serverTimezone=Europe/Madrid',
  "topics" = 'stfail',
  "table.name.format" = 'failures',
  "key.converter" = 'io.confluent.connect.avro.AvroConverter',
  "key.converter.schema.registry.url" = 'http://schema-registry:8081',
  "key.converter.schemas.enable" = 'true',
  "value.converter" = 'io.confluent.connect.avro.AvroConverter',
  "value.converter.schema.registry.url" = 'http://schema-registry:8081',
  "value.converter.schemas.enable" = 'true',
  "connection.user" = 'santiago',
  "connection.password" = 'SuZi0545',
  "auto.create" = 'false',
  "pk.mode" = 'record_key',
  "pk.fields" = '',
  "fields.withelists" = 'nf,df',
  "insert.mode" = 'upsert',
  "delete.enabled" = 'false',
  "tasks.max" = '1');
```

