

# MariaDB

## Tabla *songs*

Esta tabla es requerida en el tutorial [JDBCSink1](#)

```
CREATE TABLE `songs` (  
  `ids` int(11) NOT NULL AUTO_INCREMENT,  
  `title` varchar(100) CHARACTER SET latin1 COLLATE latin1_spanish_ci NOT  
NULL,  
  `album` varchar(100) CHARACTER SET latin1 COLLATE latin1_spanish_ci NOT  
NULL,  
  `duration` varchar(10) CHARACTER SET latin1 COLLATE latin1_spanish_ci NOT  
NULL,  
  `release` int(11) DEFAULT NULL,  
  `artist` varchar(50) CHARACTER SET latin1 COLLATE latin1_spanish_ci NOT  
NULL,  
  `type` varchar(25) CHARACTER SET latin1 COLLATE latin1_spanish_ci NOT NULL,  
  `filename` varchar(50) CHARACTER SET latin1 COLLATE latin1_spanish_ci NOT  
NULL,  
  `fechreg` timestamp NOT NULL DEFAULT CURRENT_TIMESTAMP ON UPDATE  
CURRENT_TIMESTAMP,  
  PRIMARY KEY (`ids`)  
) ENGINE=InnoDB DEFAULT CHARSET=latin1;
```

## Tablas *albsong1* y *albsong2*

Estas tablas son requeridas en los tutoriales [JDBCSink1](#) y [JDBCSink2](#)

```
-- Las dos tablas son idénticas pero reciben datos desde conectores diferentes  
--  
CREATE TABLE `albsong1` (  
  `artist` varchar(100) CHARACTER SET latin1 COLLATE latin1_spanish_ci NOT  
NULL,  
  `album` varchar(100) CHARACTER SET latin1 COLLATE latin1_spanish_ci NOT  
NULL,  
  `n` integer NOT NULL,  
  `fechreg` timestamp NOT NULL DEFAULT CURRENT_TIMESTAMP ON UPDATE  
CURRENT_TIMESTAMP,  
  PRIMARY KEY (`artist`, `album`)  
) ENGINE=InnoDB DEFAULT CHARSET=latin1;  
  
CREATE TABLE `albsong2` (  
  `artist` varchar(100) CHARACTER SET latin1 COLLATE latin1_spanish_ci NOT  
NULL,  
  `album` varchar(100) CHARACTER SET latin1 COLLATE latin1_spanish_ci NOT  
NULL,
```

```
`n` integer NOT NULL,  
`fechreg` timestamp NOT NULL DEFAULT CURRENT_TIMESTAMP ON UPDATE  
CURRENT_TIMESTAMP,  
PRIMARY KEY (`artist`,`album`)  
) ENGINE=InnoDB DEFAULT CHARSET=latin1;
```