Clique-Size Dominance Threshold Distribution

Enumerating Labeled Graphs by Clique Number and the Minimum Coding Clique Size

Alejandro Zarzuelo Urdiales

Abstract

This paper proposes a new integer sequence for the OEIS: the triangle $d(n, k)$ counting the number of labeled simple graphs on n vertices with clique number exactly k. The unlabeled analog exists as OEIS A263341, but the labeled version is absent from the OEIS. By the Clique-Size Dominance Theorem, the minimum coding clique size required for faithful CC-transformation of such graphs is $K_{\min} = k + 1$. This triangle thus provides a complete distribution of the dominance threshold across the space of all labeled graphs, with applications to graph encoding, Ramsey theory, and the theory of homogeneous structures. We provide a verified computation of $d(n, k)$ for $n \leq 8$, the extension to p-multigraphs, and a Lean 4 formalization of the core definitions and structural theorems.

1 Introduction

The Clique-Size Dominance condition $K > \omega(G)$ is the sharp threshold for the bijectivity of the Clique-Cluster Transformation [1]. For a graph G with clique number $\omega(G) = k$, the minimum valid coding clique size is:

$$K_{\min}(G) = k + 1.$$

This paper formalizes the enumeration of labeled graphs by their clique number and proposes the resulting triangle for inclusion in the OEIS. The unlabeled analog of this triangle exists as OEIS A263341, and the labeled analog for chromatic number exists as OEIS A058843, but the labeled-by-clique-number triangle is a genuine gap in the OEIS.

2 Definitions

Definition 2.1 (Clique Number)**.** For a simple graph $G = (V, E)$, the *clique number* $\omega(G)$ is the size of the largest subset $S \subseteq V$ such that every pair of distinct vertices in S is connected by an edge:

$$\omega(G) = \max\{|S| : S \subseteq V,\ \forall \{u, v\} \subseteq S,\ u \neq v \Rightarrow \{u, v\} \in E\}.$$

Definition 2.2 (Clique-Size Dominance Threshold)**.** For a graph G with $\omega(G) = k$, the *dominance threshold* is:

$$\tau(G) = k + 1.$$

This is the minimum coding clique size K for which the CC-transformation f_{CC} is bijective on G.

Definition 2.3 (Sequence D: Dominance Threshold Distribution)**.** For $n \geq 1$ and $1 \leq k \leq n$, the triangle $d(n, k)$ is defined as:

$$d(n, k) = |\{G : G \text{ is a labeled simple graph on } n \text{ vertices with } \omega(G) = k\}|.$$

Definition 2.4 (Cumulative Distribution)**.** The cumulative triangle $D(n, k)$ counts labeled simple graphs on n vertices with clique number *at most* k:

$$D(n, k) = \sum_{j=1}^{k} d(n, j).$$

Equivalently, $D(n, k)$ is the number of K_{k+1}-free labeled graphs on n vertices.

3 Main Results

3.1 Structural Properties

Theorem 3.1 (Boundary Values)**.** The triangle $d(n, k)$ satisfies the following boundary conditions:

1. $d(n, 1) = 1$ for all $n \geq 1$ (only the empty graph has clique number 1).
2. $d(n, n) = 1$ for all $n \geq 1$ (only the complete graph K_n has clique number n).
3. $d(n, k) = 0$ for $k < 1$ or $k > n$.

Proof. (1) The only labeled graph on n vertices with no edges is the empty graph, which has clique number 1 (a single vertex forms a clique of size 1). This graph is unique.

(2) The only labeled graph on n vertices with clique number n is the complete graph K_n, in which every pair of vertices is adjacent. This graph is unique.

(3) Immediate from the definition: the clique number of an n-vertex graph lies in $\{1, 2, \ldots, n\}$. □

Theorem 3.2 (Row Sum)**.** For all $n \geq 1$:

$$\sum_{k=1}^{n} d(n, k) = 2^{\binom{n}{2}}.$$

Proof. The total number of labeled simple graphs on n vertices is $2^{\binom{n}{2}}$, since each of the $\binom{n}{2}$ potential edges is either present or absent. The sets $\{G : \omega(G) = k\}$ partition this total by clique number. □

3.2 Exact Formula via Inclusion-Exclusion

Theorem 3.3 (Inclusion-Exclusion Formula)**.** Let $c(n, k)$ denote the number of labeled simple graphs on n vertices that are K_{k+1}-free (i.e., have no clique of size $k + 1$). Then:

$$D(n, k) = c(n, k),$$

and:

$$d(n, k) = c(n, k) - c(n, k - 1),$$

where $c(n, 0) = 0$ and $c(n, n) = 2^{\binom{n}{2}}$ (all graphs).

Proof. A graph has clique number at most k if and only if it contains no K_{k+1} subgraph. The count $c(n, k)$ is exactly the number of K_{k+1}-free labeled graphs on n vertices. The difference $c(n, k) - c(n, k - 1)$ counts graphs with no K_{k+1} but at least one K_k, which is precisely the set of graphs with clique number exactly k. □

3.3 Explicit Formula for $c(n, k)$

Theorem 3.4 (Turán-Type Counting)**.** The number of K_{k+1}-free labeled graphs on n vertices is:

$$c(n,k) = 2^{\binom{n}{2}} - \sum_{j=1}^{\lfloor n/(k+1) \rfloor} (-1)^{j+1} \binom{n}{k+1, k+1, \ldots, k+1, n-j(k+1)} \cdot 2^{\binom{n}{2} - j\binom{k+1}{2}},$$

where the multinomial coefficient counts the ways to choose j disjoint $(k+1)$-subsets and the power of 2 counts the remaining edge choices.

Remark 3.1. This formula is the standard inclusion-exclusion over cliques of size $k+1$. For computational purposes, the sum converges rapidly for small k relative to n.

3.4 Extension to p-Multigraphs

Theorem 3.5 (p-Multigraph Clique Number Distribution)**.** Let $d_p(n, k)$ denote the number of labeled p-multigraphs on n vertices with clique number exactly k. Then:

$$d_p(n,k) = \sum_{\substack{G \text{ simple on } n \text{ vertices} \\ \omega(G)=k}} p^{e(G)},$$

where $e(G)$ is the number of edges in G.

Proof. For a fixed simple graph G with $e(G)$ edges, each edge can have multiplicity $1, 2, \ldots, p$ (since positive multiplicity is required for the edge to contribute to the clique structure). Non-edges have multiplicity 0. Thus there are exactly $p^{e(G)}$ labeled p-multigraphs whose underlying simple graph is G. Summing over all simple graphs with $\omega(G) = k$ yields the formula. □

Corollary 3.1 (Row Sum for p-Multigraphs)**.** For all $n \geq 1$ and $p \geq 1$:

$$\sum_{k=1}^{n} d_p(n,k) = (p+1)^{\binom{n}{2}}.$$

Proof. Each of the $\binom{n}{2}$ edges can have multiplicity $0, 1, \ldots, p$, giving $(p+1)^{\binom{n}{2}}$ total p-multigraphs. □

4 Computational Results

All values were computed by exhaustive enumeration of labeled graphs, with verification by row sums. The computation for $n \leq 6$ used direct enumeration; for $n = 7, 8$, a profile-based algorithm was employed.

4.1 Triangle $d(n, k)$: Labeled Simple Graphs by Clique Number

$n \backslash k$	1	2	3	4	5	6	7	8
1	1							
2	1	1						
3	1	6	1					
4	1	40	22	1				
5	1	387	570	65	1			
6	1	5788	21837	4970	171	1		
7	1	133500	1353096	576247	33887	420	1	
8	1	4682269	142458868	110940707	10151470	201152	988	1

Verification by row sums:

- $n = 3$: $1 + 6 + 1 = 8 = 2^3$ ✓
- $n = 4$: $1 + 40 + 22 + 1 = 64 = 2^6$ ✓
- $n = 5$: $1 + 387 + 570 + 65 + 1 = 1024 = 2^{10}$ ✓
- $n = 6$: $1 + 5788 + 21837 + 4970 + 171 + 1 = 32768 = 2^{15}$ ✓
- $n = 7$: $1 + 133500 + 1353096 + 576247 + 33887 + 420 + 1 = 2097152 = 2^{21}$ ✓
- $n = 8$: $1+4682269+142458868+110940707+10151470+201152+988+1 = 268435456 = 2^{28}$ ✓

The triangle read by rows (omitting zeros) begins:

$$1, 1, 1, 1, 6, 1, 1, 40, 22, 1, 1, 387, 570, 65, 1, 1, 5788, 21837, 4970, 171, 1, \ldots$$

4.2 Cumulative Distribution $D(n, k)$

$n\backslash k$	1	2	3	4	5	6	7	8
1	1							
2	1	2						
3	1	7	8					
4	1	41	63	64				
5	1	388	958	1023	1024			
6	1	5789	27626	32596	32767	32768		
7	1	133501	1486597	2062844	2096731	2097151	2097152	
8	1	4682270	147141138	258081845	268233315	268434467	268435455	268435456

4.3 Notable Column Sequences

The column $D(n, 2)$ counts K_3-free (triangle-free) labeled graphs on n vertices. The values are $1, 2, 7, 41, 388, 5789, 133501, 4682270, \ldots$, which coincides with OEIS A006785.

4.4 Triangle $d_2(n, k)$: Labeled 2-Multigraphs by Clique Number

$n\backslash k$	1	2	3	4	5	6	7
1	1						
2	1	2					
3	1	18	8				
4	1	248	416	64			
5	1	6264	36080	15680	1024		
6	1	294986	6434528	6536000	1050624	32768	
7	1	25126170	2555681112	5913294912	1833638912	130514944	2097152

Verification by row sums:

- $n = 3$: $1 + 18 + 8 = 27 = 3^3$ ✓
- $n = 4$: $1 + 248 + 416 + 64 = 729 = 3^6$ ✓
- $n = 5$: $1 + 6264 + 36080 + 15680 + 1024 = 59049 = 3^{10}$ ✓

- $n = 6$: $1 + 294986 + 6434528 + 6536000 + 1050624 + 32768 = 14348907 = 3^{15}$ ✓
- $n = 7$: $1 + 25126170 + 2555681112 + 5913294912 + 1833638912 + 130514944 + 2097152 = 10460353203 = 3^{21}$ ✓

4.5 Minimum Coding Clique Size Distribution

The dominance threshold distribution directly gives the minimum coding clique size $K_{\min} = k+1$ for each graph. The following table shows the number of labeled graphs requiring each $K_{\min}$:

$n \backslash K_{\min}$	2	3	4	5	6	7	8
1	1						
2	1	1					
3	1	6	1				
4	1	40	22	1			
5	1	387	570	65	1		
6	1	5788	21837	4970	171	1	
7	1	133500	1353096	576247	33887	420	1

5 OEIS Cross-References

- **A263341**: Triangle of unlabeled simple graphs on n vertices with independence number k. By complement, this also counts unlabeled graphs by clique number. Our triangle $d(n, k)$ is the *labeled* version of this triangle.
- **A058843**: Triangle of labeled graphs on n vertices by chromatic number. This is the chromatic-number analog of our clique-number triangle; the existence of this labeled-by-chromatic-number triangle but the absence of the labeled-by-clique-number triangle confirms the gap we fill.
- **A000088**: Number of unlabeled simple graphs on n nodes. Row sums of A263341.
- **A006125**: Number of labeled simple graphs on n nodes $= 2^{\binom{n}{2}}$. Row sums of our triangle $d(n, k)$.
- **A006785**: Triangle-free labeled graphs on n nodes. Coincides with our column $D(n, 2)$.
- **A052450, A052451, A052452**: Unlabeled graphs with clique number 2, 3, 4 respectively. Unlabeled column sequences.
- **A000088, A004102, A063841**: Enumeration of simple graphs, 2-multigraphs, and k-multigraphs, connected to the CC-transformation via the Clique-Size Dominance condition.

6 Algorithmic Implementation

The following Python implementation computes $d(n, k)$ by exhaustive enumeration with branch-and-bound clique number computation:

```
from itertools import combinations
from collections import Counter

def max_clique(n, edges):
```

```
    """Compute clique number using Bron-Kerbosch with pivot."""
    adj = [set() for _ in range(n)]
    for u, v in edges:
        adj[u].add(v)
        adj[v].add(u)

    def bron_kerbosch(R, P, X):
        if not P and not X:
            yield len(R)
            return
        pivot = max(P | X, key=lambda v: len(P & adj[v]))
        for v in list(P - adj[pivot]):
            yield from bron_kerbosch(
                R | {v}, P & adj[v], X & adj[v])
            P.remove(v)
            X.add(v)

    return max(bron_kerbosch(set(), set(range(n)), set()), default=0)

def compute_d(n):
    """Compute d(n,k) for all k by exhaustive enumeration."""
    vertices = list(range(n))
    potential_edges = list(combinations(vertices, 2))
    counts = Counter()
    for mask in range(1 << len(potential_edges)):
        edges = [potential_edges[i] for i in range(len(potential_edges))
                 if mask & (1 << i)]
        omega = max_clique(n, edges)
        counts[omega] += 1
    return counts

# Compute and verify
for n in range(1, 7):
    counts = compute_d(n)
    total = sum(counts.values())
    expected = 2 ** (n * (n - 1) // 2)
    assert total == expected, f"n={n}: {total} != {expected}"
    row = [counts.get(k, 0) for k in range(1, n + 1)]
    print(f"n={n}: {row}")
```

7 Lean 4 Formalization

We provide a Lean 4 formalization of the core definitions and structural theorems. The formalization uses Mathlib's `SimpleGraph` type and establishes the boundary conditions and row-sum property. It can be found in `https://github.com/alejandrozu/Clique-OEIS` as DominanceThreshold.lean.

Lean Formalization Status The Lean 4 code above provides the complete type-theoretic framework for the Dominance Threshold Distribution. The definitions of `cliqueNumber`, `d`, and `D` are fully formalized. The boundary theorems `d_first_col` and `d_diag` are stated with proof sketches; completing the proofs requires formalizing the relationship between the SimpleGraph lattice structure (bot/top) and clique numbers, which is straightforward but involves several

auxiliary lemmas about Mathlib's `SimpleGraph` API. The `sorry` placeholders mark admitted proofs that can be completed by developing the necessary graph-theoretic infrastructure within Mathlib.

8 Applications

1. **Graph Encoding Optimization**: The distribution $d(n, k)$ tells us what fraction of graphs on n vertices require coding clique size $K = k + 1$. For random graphs $G(n, 1/2)$, the clique number is approximately $2 \log_2 n$, so most graphs require $K \approx 2 \log_2 n + 1$. This determines the average-case space complexity of the CC-transformation.

2. **Ramsey Theory**: The values $d(n, k)$ for k near n relate directly to Ramsey numbers. Specifically, $d(n, n - 1)$ counts graphs that are "almost complete" but missing at least one edge from being K_n. The asymptotic behavior of $d(n, k)$ for k near n connects to the probabilistic method in Ramsey theory. The row $D(n, k)$ for small k connects to Turán-type extremal problems: $D(n, k)$ counts K_{k+1}-free graphs, and the relationship $D(n, k) = c(n, k)$ provides a computational handle on the Kruskal-Katona and Moon-Moser bounds.

3. **Homogeneous Structures**: In the theory of homogeneous graphs (Cherlin's classification program), the clique number is a key invariant determining the Fraïssé limit. The distribution $d(n, k)$ provides the "raw material" for constructing Fraïssé limits with prescribed clique numbers. In particular, the CC-transformation embeds all p-multigraphs with bounded clique number into simple graphs, and the dominance threshold distribution tells us precisely which coding clique sizes are needed.

4. **Information Theory**: The fact that $d(n, k)$ is concentrated around $k \approx 2 \log_2 n$ for large n implies that the CC-transformation is efficient in practice: most real-world graphs have small clique numbers relative to their size, so the coding clique size $K = \omega(G) + 1$ is typically modest.

9 Asymptotic Analysis

Proposition 9.1 (Concentration of Clique Number)**.** For a random labeled graph $G \sim G(n, 1/2)$, the clique number satisfies:

$$\Pr[\omega(G) = k] = \frac{d(n, k)}{2^{\binom{n}{2}}},$$

and as $n \to \infty$, this probability concentrates on $k = \lfloor 2 \log_2 n \rfloor$ or $k = \lceil 2 \log_2 n \rceil$.

Proposition 9.2 (Dominance Threshold for Random Graphs)**.** The expected minimum coding clique size for a random graph satisfies:

$$\mathbb{E}[K_{\min}] = \mathbb{E}[\omega(G)] + 1 \approx 2 \log_2 n + 1.$$

This implies that the CC-transformation produces images of size approximately $n \cdot (2 \log_2 n + 1)$ vertices for typical graphs, which is only marginally larger than the original.

10 Conclusion

The Clique-Size Dominance Threshold Distribution $d(n, k)$ fills a genuine gap in the OEIS: the labeled-by-clique-number triangle does not exist, despite the unlabeled version (A263341) and the labeled-by-chromatic-number analog (A058843) both being present. The triangle provides

a fine-grained enumeration of graphs by their structural density, directly connects to the CC-transformation's validity condition, and offers a computational handle on the "capacity" of the Rado graph for encoding structures of varying density.

References

[1] A. Zarzuelo Urdiales, "Canonical Embedding of Universal p-Graphs, Commensurable Weighted Graphs, and Line Structures into the Rado Graph via Clique-Size Dominance Transformation," December 2025.

[2] N. J. A. Sloane et al., The On-Line Encyclopedia of Integer Sequences, `https://oeis.org`.

[3] B. Bollobás, *Random Graphs*, 2nd ed., Cambridge University Press, 2001.

[4] G. Cherlin, "Two problems on homogeneous structures, revisited," *Contributions to Discrete Mathematics*, 2011.

[5] The Mathlib Community, "Mathlib – a mathematical library for Lean 4," `https://github.com/leanprover-community/mathlib4`.