



http://localhost:3000/



Performance



Accessibility



Best Practices



SEO



PWA



Performance

Values are estimated and may vary. The [performance score is calculated](#) directly from these metrics. [See calculator.](#)




0–49



50–89



90–100



METRICS

[Expand view](#)

- First Contentful Paint

0.7 s

- ▲ Largest Contentful Paint

3.7 s

- Total Blocking Time

100 ms


- Cumulative Layout Shift

0

- Speed Index

0.7 s

[View Treemap](#)




Show audits relevant to: [All](#) [FCP](#) [LCP](#) [TBT](#) [CLS](#)

DIAGNOSTICS

⚠ Largest Contentful Paint element — 3,710 ms

This is the largest contentful element painted within the viewport. [Learn more about the Largest Contentful Paint element](#) [LCP]

Element



section.relative.overflow-hidden.py-28.px-4.bg-gray-900.md:px-8

Phase	% of LCP	Timing
TTFB	3%	130 ms
Load Delay	79%	2,940 ms
Load Time	2%	90 ms
Render Delay	15%	550 ms

⚠ Properly size images — Potential savings of 580 KiB

Serve images that are appropriately-sized to save cellular data and improve load time. [Learn how to size images](#).

NEXT: Use the `next/image` component to set the appropriate sizes. [Learn more](#).

URL	Resource Size	Potential Savings
unsplash.com	667.5 KiB	552.9 KiB
 i /photo-161...?q=... (images.unsplash.com)	368.2 KiB	326.0 KiB
mg.h-full.w-full.object-cover.object-center		
 i /photo-161...?q=... (images.unsplash.com)	228.3 KiB	172.1 KiB
mg.h-full.w-full.object-cover.object-center		
 i /photo-159...?q=... (images.unsplash.com)	55.9 KiB	42.1 KiB
mg.h-full.w-full.object-cover.object-center		
 i /photo-162...?q=... (images.unsplash.com)	15.0 KiB	12.7 KiB
mg.h-full.w-full.object-cover.object-center		
discordapp.com	30.8 KiB	27.5 KiB
img.w-32	...118.../foreveryou.png? ex=6582147e&is=656f9f7e&hm=1da73ad...& (cdn.discordapp.com)	30.8 KiB
		27.5 KiB

⚠ Eliminate render-blocking resources — Potential savings of 320 ms



Resources are blocking the first paint of your page. Consider delivering critical JS/CSS inline and deferring all non-critical JS/styles. [Learn how to eliminate render-blocking resources.](#) FCP LCP

NEXT Use the `next/script` component to defer loading of non-critical third-party scripts. [Learn more.](#)

URL	Transfer Size	Potential Savings
JSDelivr CDN Cdn	283.4 KiB	530 ms
...fonts/remixicon.css (cdn.jsdelivr.net)	13.7 KiB	250 ms
...dist/tailwind.min.css (cdn.jsdelivr.net)	269.7 KiB	280 ms

▲ Reduce unused CSS — Potential savings of 307 KiB ^

Reduce unused rules from stylesheets and defer CSS not used for above-the-fold content to decrease bytes consumed by network activity. [Learn how to reduce unused CSS.](#) FCP LCP

NEXT Consider setting up PurgeCSS in `Next.js` configuration to remove unused rules from stylesheets. [Learn more.](#)

URL	Transfer Size	Potential Savings
JSDelivr CDN Cdn	308.2 KiB	306.6 KiB
...dist/tailwind.min.css (cdn.jsdelivr.net)	269.7 KiB	268.7 KiB
...css/bootstrap.min.css (cdn.jsdelivr.net)	24.8 KiB	24.3 KiB
...fonts/remixicon.css (cdn.jsdelivr.net)	13.7 KiB	13.7 KiB

▲ Defer offscreen images — Potential savings of 139 KiB ^

Consider lazy-loading offscreen and hidden images after all critical resources have finished loading to lower time to interactive. [Learn how to defer offscreen images.](#)

NEXT Use the `next/image` component instead of `` to automatically lazy-load images. [Learn more.](#)

URL	Resource Size	Potential Savings
unsplash.com	138.8 KiB	138.8 KiB
 img.absolute.inse t-0.h-full.w- full.object- cover.bg- cover.bg-bottom	/photo-164...?q=... (images.unsplash.com)	138.8 KiB

▲ Reduce unused JavaScript — Potential savings of 43 KiB

Reduce unused JavaScript and defer loading scripts until they are required to decrease bytes consumed by network activity. [Learn how to reduce unused JavaScript.](#) LCP

NEXT Use Webpack Bundle Analyzer to detect unused JavaScript code. [Learn more](#)

URL	Transfer Size	Potential Savings
Google CDN Cdn	30.4 KiB	22.8 KiB
...3.5.1/jquery.min.js (ajax.googleapis.com)	30.4 KiB	22.8 KiB
JSDelivr CDN Cdn	23.5 KiB	20.1 KiB
...js/bootstrap.bundle.min.js (cdn.jsdelivr.net)	23.5 KiB	20.1 KiB
...js/src/tooltip.js	2.9 KiB	2.5 KiB
...js/src/carousel.js	2.0 KiB	1.9 KiB
...js/src/dropdown.js	1.9 KiB	1.6 KiB
...js/src/modal.js	1.6 KiB	1.5 KiB
...js/src/collapse.js	1.3 KiB	1.2 KiB

■ Minify CSS — Potential savings of 7 KiB

Minifying CSS files can reduce network payload sizes. [Learn how to minify CSS.](#) FCP LCP

URL	Transfer Size	Potential Savings
:root, :host { --fa-font-solid: normal 900 1em/1 'Font Awesome 6 Solid'; --fa-font-regular: nor...	9.3 KiB	7.3 KiB

■ Minify JavaScript — Potential savings of 72 KiB ^

Minifying JavaScript files can reduce payload sizes and script parse time. [Learn how to minify JavaScript.](#) FCP LCP

URL	Transfer Size	Potential Savings
Unattributable	153.7 KiB	66.5 KiB
chrome-extension://fmkadmapgofadopljbjfkapdkoienihi/build/react_devtools_backend_compact.js	153.7 KiB	66.5 KiB
localhost 1st Party	10.7 KiB	5.2 KiB
...chunks/webpack.js?ts=170... (localhost)	10.7 KiB	5.2 KiB

■ Serve images in next-gen formats — Potential savings of 26 KiB ^

Image formats like WebP and AVIF often provide better compression than PNG or JPEG, which means faster downloads and less data consumption. [Learn more about modern image formats.](#)

~~NEXT~~ Use the `next/image` component instead of `` to automatically optimize image format. [Learn more.](#)

URL	Resource Size	Potential Savings
discordapp.com	30.8 KiB	26.2 KiB
img.w-32 ...118.../foreveryou.png?ex=6582147e&is=656f9f7e&hm=1da73ad...&(cdn.discordapp.com)	30.8 KiB	26.2 KiB

■ Image elements do not have explicit `width` and `height` ^

Set an explicit width and height on image elements to reduce layout shifts and improve CLS. [Learn how to set image dimensions](#) CLS

NEXT Use the `next/image` component to make sure images are always sized appropriately. [Learn more](#).

URL	
discordapp.com	
img.h-12	...118.../foreveryou.png?ex=6582147e&is=656f9f7e&hm=1da73ad...& (cdn.discordapp.com)
img.w-32	...118.../foreveryou.png?ex=6582147e&is=656f9f7e&hm=1da73ad...& (cdn.discordapp.com)

■ Avoid serving legacy JavaScript to modern browsers — Potential savings of 0 KiB

Polyfills and transforms enable legacy browsers to use new JavaScript features. However, many aren't necessary for modern browsers. For your bundled JavaScript, adopt a modern script deployment strategy using `module/nomodule` feature detection to reduce the amount of code shipped to modern browsers, while retaining support for legacy browsers. [Learn how to use modern JavaScript](#) [TBT]

URL	Potential Savings
localhost 1st Party	0.0 KiB
...chunks/main.js?ts=170... (localhost)	0.0 KiB
:3000/_next/static/c...ts=1702938842871:38	@babel/plugin-transform-classes

■ Page prevented back/forward cache restoration — 3 failure reasons

Many navigations are performed by going back to a previous page, or forwards again. The back/forward cache (`bfcache`) can speed up these return navigations. [Learn more about the bfcache](#)

Failure reason	Failure type
Pages with WebSocket cannot enter back/forward cache.	Pending browser support
http://localhost:3000	
Pages whose main resource has <code>cache-control:no-store</code> cannot enter back/forward cache.	Not actionable
http://localhost:3000	
WebSocketSticky	Not actionable
http://localhost:3000	

■ Avoid enormous network payloads — Total size was 3,801 KiB



Large network payloads cost users real money and are highly correlated with long load times. [Learn how to reduce payload sizes.](#) [LCP]

Show 3rd-party resources (6)

URL	Transfer Size
localhost 1st Party	2,458.3 KiB
...pages/index.js?ts=170... (localhost)	1,178.8 KiB
...chunks/main.js?ts=170... (localhost)	1,157.5 KiB
...pages/_app.js?ts=170... (localhost)	76.2 KiB
...media/c9a5bc6a7c948fb0-s.p.woff2 (localhost)	45.7 KiB
unsplash.com	854.0 KiB
/photo-161...?q=... (images.unsplash.com)	368.5 KiB
/photo-161...?q=... (images.unsplash.com)	228.5 KiB
/photo-164...?q=... (images.unsplash.com)	138.9 KiB
/photo-148...?q=... (images.unsplash.com)	62.1 KiB
/photo-159...?q=... (images.unsplash.com)	56.1 KiB
JSDelivr CDN Cdn	269.7 KiB
...dist/tailwind.min.css (cdn.jsdelivr.net)	269.7 KiB

○ JavaScript execution time — 0.3 s



Consider reducing the time spent parsing, compiling, and executing JS. You may find delivering smaller JS payloads helps with this.

[Learn how to reduce Javascript execution time.](#) [TBT]

URL	Total CPU Time	Script Evaluation	Script Parse
localhost 1st Party	377 ms	199 ms	85 ms
...chunks/main.js?ts=170... (localhost)	163 ms	114 ms	39 ms
...pages/index.js?ts=170... (localhost)	130 ms	80 ms	41 ms
http://localhost:3000	84 ms	4 ms	4 ms
Unattributable	58 ms	2 ms	0 ms
Unattributable	58 ms	2 ms	0 ms

Minimizes main-thread work — 0.6 s



Consider reducing the time spent parsing, compiling and executing JS. You may find delivering smaller JS payloads helps with this. [Learn how to minimize main-thread work](#) TBT

Category	Time Spent
Script Evaluation	294 ms
Other	116 ms
Script Parsing & Compilation	101 ms
Style & Layout	53 ms
Parse HTML & CSS	46 ms
Rendering	7 ms

Avoid long main-thread tasks — 2 long tasks found



Lists the longest tasks on the main thread, useful for identifying worst contributors to input delay. [Learn how to avoid long main-thread tasks](#) TBT

URL	Start Time	Duration
localhost 1st Party		306 ms
...chunks/main.js?ts=170... (localhost)	2,529 ms	175 ms
...pages/index.js?ts=170... (localhost)	3,560 ms	131 ms

○ Avoids an excessive DOM size — 233 elements ^

A large DOM will increase memory usage, cause longer [style calculations](#), and produce costly [layout reflows](#). [Learn how to avoid an excessive DOM size.](#) TBT

Statistic	Element	Value
Total DOM Elements		233
Maximum DOM Depth	 span#headlessui-label-:Rdljl4mm:.sr-only	14
Maximum Child Elements	 body	7

○ User Timing marks and measures — 42 user timings ^

Consider instrumenting your app with the User Timing API to measure your app's real-world performance during key user experiences. [Learn more about User Timing marks.](#)

NEXT Consider using Next.js Analytics to measure your app's real-world performance. [Learn more.](#)

Name	Type	Start Time	Duration
Next.js-before-hydration	Measure	0.00 ms	524.46 ms
Next.js-hydration	Measure	524.46 ms	70.60 ms
_v3	Mark	0.00 ms	

Name	Type	Start Time	Duration
__v3	Mark	0.00 ms	
beforeRender	Mark	524.46 ms	
afterHydrate	Mark	595.05 ms	
--schedule-state-update-16-Tabs2	Mark	1,607.82 ms	
--render-start-16	Mark	1,607.95 ms	
--component-render-start-Tabs2	Mark	1,608.11 ms	
--component-render-stop	Mark	1,608.33 ms	
--render-stop	Mark	1,608.94 ms	
--commit-start-16	Mark	1,608.96 ms	
--react-version-18.2.0	Mark	1,609.02 ms	
--profiler-version-1	Mark	1,609.02 ms	
--react-internal-module-start- at eval (webpack-internal://./node_modules/react/cjs/react.development.js:25:62)	Mark	1,609.09 ms	
--react-internal-module-stop- at eval (webpack-internal://./node_modules/react/cjs/react.development.js:2736:61)	Mark	1,609.09 ms	
--react-internal-module-start- at eval (webpack-internal://./node_modules/scheduler/cjs/scheduler.development.js:24:62)	Mark	1,609.10 ms	
--react-internal-module-stop- at eval (webpack-internal://./node_modules/scheduler/cjs/scheduler.development.js:630:61)	Mark	1,609.10 ms	
--react-internal-module-start- at eval (webpack-internal://./node_modules/react-dom/cjs/react-dom.development.js:24:62)	Mark	1,609.10 ms	
--react-internal-module-stop- at eval (webpack-internal://./node_modules/react-dom/cjs/react-dom.development.js:29859:61)	Mark	1,609.11 ms	
--react-lane-labels-Sync,InputContinuousHydration,InputContinuous,DefaultHydration,Default,TransitionHydration,Transition,Transition,Transition,Transition,Transition,Transition,Trans	Mark	1,609.13 ms	

Name	Type	Start Time	Duration
ition,Transition,Transition,Transition,Transition,Transition,Transition,Transition,Trans ition,Transition,Retry,Retry,Retry,Retry,SelectiveHydration,IdleHydration,Idl e,Offscreen			
--layout-effects-start-16	Mark	1,609.46 ms	
--layout-effects-stop	Mark	1,609.49 ms	
--commit-stop	Mark	1,609.88 ms	
--schedule-state-update-16-Tabs2	Mark	2,610.85 ms	
--render-start-16	Mark	2,610.96 ms	
--component-render-start-Tabs2	Mark	2,611.07 ms	
--component-render-stop	Mark	2,611.20 ms	
--render-stop	Mark	2,611.70 ms	
--commit-start-16	Mark	2,611.71 ms	
--react-version-18.2.0	Mark	2,611.72 ms	
--profiler-version-1	Mark	2,611.72 ms	
--react-internal-module-start- at eval (webpack- internal:///./node_modules/react/cjs/react.development.js:25:62)	Mark	2,611.73 ms	
--react-internal-module-stop- at eval (webpack- internal:///./node_modules/react/cjs/react.development.js:2736:61)	Mark	2,611.74 ms	
--react-internal-module-start- at eval (webpack- internal:///./node_modules/scheduler/cjs/scheduler.development.js:24:62)	Mark	2,611.74 ms	
--react-internal-module-stop- at eval (webpack- internal:///./node_modules/scheduler/cjs/scheduler.development.js:630:61)	Mark	2,611.75 ms	
--react-internal-module-start- at eval (webpack- internal:///./node_modules/react-dom/cjs/react-dom.development.js:24:62)	Mark	2,611.76 ms	
--react-internal-module-stop- at eval (webpack- internal:///./node_modules/react-dom/cjs/react-dom.development.js:29859:61)	Mark	2,611.76 ms	

Name	Type	Start Time	Duration
--react-lane-labels-- Sync,InputContinuousHydration,InputContinuous,DefaultHydration,Default,TransitionHydration,Transition,Transition,Transition,Transition,Transition,Transition,Transition,Transition,Transition,Transition,Transition,Transition,Transition,Transition,Transition,Transition,Retry,Retry,Retry,Retry,SelectiveHydration,IdleHydration,Idle,Offscreen	Mark	2,611.77 ms	
--layout-effects-start-16	Mark	2,611.97 ms	
--layout-effects-stop	Mark	2,611.98 ms	
--commit-stop	Mark	2,612.07 ms	

Initial server response time was short — Root document took 20 ms ^

Keep the server response time for the main document short because all other requests depend on it. [Learn more about the Time to First Byte metric.](#) [FCP](#) [LCP](#)

URL	Time Spent
localhost 1st Party	20 ms
http://localhost:3000	20 ms

Avoid chaining critical requests — 5 chains found ^

The Critical Request Chains below show you what resources are loaded with a high priority. Consider reducing the length of chains, reducing the download size of resources, or deferring the download of unnecessary resources to improve page load. [Learn how to avoid chaining critical requests.](#) [FCP](#) [LCP](#)

Maximum critical path latency: **110.394 ms**

Initial Navigation



 ...chunks/react-refresh.js?ts=170... (localhost) - 17.333 ms, 24.39 KiB		
Minimize third-party usage — Third-party code blocked the main thread for 0 ms		
Third-party code can significantly impact load performance. Limit the number of redundant third-party providers and try to load third-party code after your page has primarily finished loading. Learn how to minimize third-party impact. <small>TBT</small>		
Third-Party	Transfer Size	Main-Thread Blocking Time
unsplash.com	869 KiB	0 ms
/photo-161...?q=... (images.unsplash.com)	368 KiB	0 ms
/photo-161...?q=... (images.unsplash.com)	228 KiB	0 ms
/photo-164...?q=... (images.unsplash.com)	139 KiB	0 ms
/photo-148...?q=... (images.unsplash.com)	62 KiB	0 ms
/photo-159...?q=... (images.unsplash.com)	56 KiB	0 ms
JSDelivr CDN <small>Cdn</small>	332 KiB	0 ms
...dist/tailwind.min.css (cdn.jsdelivr.net)	270 KiB	0 ms
...css/bootstrap.min.css (cdn.jsdelivr.net)	25 KiB	0 ms
...js/bootstrap.bundle.min.js (cdn.jsdelivr.net)	24 KiB	0 ms
discordapp.com	31 KiB	0 ms
...118.../foreveryou.png?ex=6582147e&is=656f9f7e&hm=1da73ad...& (cdn.discordapp.com)	31 KiB	0 ms
Google CDN <small>Cdn</small>	30 KiB	0 ms
...3.5.1/jquery.min.js (ajax.googleapis.com)	30 KiB	0 ms
Google Dictionary (by Google) <small>Chrome Extension</small>	3 KiB	0 ms
Google Fonts <small>Cdn</small>	1 KiB	0 ms

More information about the performance of your application. These numbers don't [directly affect](#) the Performance score.

PASSED AUDITS (18)

Hide

 Efficiently encode images	

Optimized images load faster and consume less cellular data. [Learn how to efficiently encode images.](#)

NEXT Use the next/image component instead of to adjust image quality. [Learn more.](#)

● Enable text compression

Text-based resources should be served with compression (gzip, deflate or brotli) to minimize total network bytes. [Learn more about text compression.](#)

[FCP](#) [LCP](#)

NEXT Enable compression on your Next.js server. [Learn more.](#)

● Preconnect to required origins

Consider adding preconnect or dns-prefetch resource hints to establish early connections to important third-party origins. [Learn how to preconnect to required origins.](#)

[FCP](#) [LCP](#)

● Avoid multiple page redirects

Redirects introduce additional delays before the page can be loaded. [Learn how to avoid page redirects.](#)

[FCP](#) [LCP](#)

○ Preload key requests

Consider using <link rel=preload> to prioritize fetching resources that are currently requested later in page load. [Learn how to preload key requests.](#)

[FCP](#) [LCP](#)

● Use HTTP/2

HTTP/2 offers many benefits over HTTP/1.1, including binary headers and multiplexing. [Learn more about HTTP/2.](#)

● Use video formats for animated content

Large GIFs are inefficient for delivering animated content. Consider using MPEG4/WebM videos for animations and PNG/WebP for static images instead of GIF to save network bytes. [Learn more about efficient video formats](#)

[LCP](#)

● Remove duplicate modules in JavaScript bundles

Remove large, duplicate JavaScript modules from bundles to reduce unnecessary bytes consumed by network activity. [TBT](#)

● Preload Largest Contentful Paint image

If the LCP element is dynamically added to the page, you should preload the image in order to improve LCP. [Learn more about preloading LCP elements.](#)

[LCP](#)

NEXT Use the next/image component and set "priority" to true to preload LCP image. [Learn more](#).

- Uses efficient cache policy on static assets — 0 resources found

A long cache lifetime can speed up repeat visits to your page. [Learn more about efficient cache policies](#).

NEXT Configure caching for immutable assets and Server-side Rendered (SSR) pages. [Learn more](#).

- All text remains visible during webfont loads

Leverage the font-display CSS feature to ensure text is user-visible while webfonts are loading. [Learn more about font-display](#).

[FCP] [LCP]


- Lazy load third-party resources with facades

Some third-party embeds can be lazy loaded. Consider replacing them with a facade until they are required. [Learn how to defer third-parties with a facade](#). [\[TBT\]](#)

- Largest Contentful Paint image was not lazily loaded

Above-the-fold images that are lazily loaded render later in the page lifecycle, which can delay the largest contentful paint. [Learn more about optimal lazy loading](#). [\[LCP\]](#)

Element



section.relative.overflow-hidden.py-28.px-4.bg-gray-900.md:px-8

- Avoid large layout shifts

These DOM elements contribute most to the CLS of the page. [Learn how to improve CLS](#) [\[CLS\]](#)

- Uses passive listeners to improve scrolling performance

Consider marking your touch and wheel event listeners as `passive` to improve your page's scroll performance. [Learn more about adopting passive event listeners](#).

- Avoids `document.write()`

For users on slow connections, external scripts dynamically injected via `document.write()` can delay page load by tens of seconds.

[Learn how to avoid `document.write\(\)`.](#)

○ Avoid non-composited animations

Animations which are not composited can be janky and increase CLS. [Learn how to avoid non-composited animations](#) [CLS]

● Has a `<meta name="viewport">` tag with `width` or `initial-scale`

A `<meta name="viewport">` not only optimizes your app for mobile screen sizes, but also prevents [a 300 millisecond delay to user input](#). [Learn more about using the viewport meta tag.](#) [TBT]



Accessibility

These checks highlight opportunities to [improve the accessibility of your web app](#).


Automatic detection can only detect a subset of issues and does not guarantee the accessibility of your web app, so [manual testing](#) is also encouraged.

CONTRAST


▲ Background and foreground colors do not have a sufficient contrast ratio.

Low-contrast text is difficult or impossible for many users to read. [Learn how to provide sufficient color contrast](#).

Failing Elements



`a.ml-3.text-sm.font-medium.text-red-400.hover:text-red-300`



`div.bg-white`



`div.text-lg.flex.items-center.text-red-400`

★★★★★ 1932 reviews
56943 People waiting for the item

Failing Elements



div.bg-white



p

button.py-2.px-6.me-2.border-0.text-white.font-semibold.text-sm.rounded-md.bg-neutral-800/60.hover:bg-neutral-800.transition-all.duration-500



body

These are opportunities to improve the legibility of your content.

NAMES AND LABELS

⚠ Links do not have a discernible name

^

Link text (and alternate text for images, when used as links) that is discernible, unique, and focusable improves the navigation experience for screen reader users. [Learn how to make links accessible.](#)

Failing Elements

a

a

These are opportunities to improve the semantics of the controls in your application. This may enhance the experience for users of assistive technology, like a screen reader.


NAVIGATION

⚠ Heading elements are not in a sequentially-descending order

^

Properly ordered headings that do not skip levels convey the semantic structure of the page, making it easier to navigate and understand when using assistive technologies. [Learn more about heading order.](#)

Failing Elements



h4.text-
xl

These are opportunities to improve keyboard navigation in your application.

ARIA

⚠ Values assigned to `role=""` are not valid ARIA roles.

ARIA roles enable assistive technologies to know the role of each element on the web page. If the `role` values are misspelled, not existing ARIA role values, or abstract roles, then the purpose of the element will not be communicated to users of assistive technologies. [Learn more about ARIA roles](#).

Failing Elements



label#headlessui-label-Rdjl4mm:.sr-only

These are opportunities to improve the usage of ARIA in your application which may enhance the experience for users of assistive technology, like a screen reader.

ADDITIONAL ITEMS TO MANUALLY CHECK (10)

Hide

○ Interactive controls are keyboard focusable

^

Custom interactive controls are keyboard focusable and display a focus indicator. [Learn how to make custom controls focusable](#).

○ Interactive elements indicate their purpose and state

^

Interactive elements, such as links and buttons, should indicate their state and be distinguishable from non-interactive elements. [Learn how to decorate interactive elements with affordance hints](#).

○ The page has a logical tab order

^

Tabbing through the page follows the visual layout. Users cannot focus elements that are offscreen. [Learn more about logical tab ordering](#).

○ Visual order on the page follows DOM order ^

DOM order matches the visual order, improving navigation for assistive technology. [Learn more about DOM and visual ordering](#).

○ User focus is not accidentally trapped in a region ^

A user can tab into and out of any control or region without accidentally trapping their focus. [Learn how to avoid focus traps](#).

○ The user's focus is directed to new content added to the page ^

If new content, such as a dialog, is added to the page, the user's focus is directed to it. [Learn how to direct focus to new content](#).

○ HTML5 landmark elements are used to improve navigation ^

Landmark elements (<main>, <nav>, etc.) are used to improve the keyboard navigation of the page for assistive technology. [Learn more about landmark elements](#).

○ Offscreen content is hidden from assistive technology ^

Offscreen content is hidden with display: none or aria-hidden=true. [Learn how to properly hide offscreen content](#).

○ Custom controls have associated labels ^

Custom interactive controls have associated labels, provided by aria-label or aria-labelledby. [Learn more about custom controls and labels](#).

○ Custom controls have ARIA roles ^

Custom interactive controls have appropriate ARIA roles. [Learn how to add roles to custom controls](#).

These items address areas which an automated testing tool cannot cover. Learn more in our guide on [conducting an accessibility review](#).

PASSED AUDITS (22)

Hide

● [aria-*] attributes match their roles ^

Each ARIA role supports a specific subset of aria-* attributes. Mismatching these invalidates the aria-* attributes. [Learn how to match ARIA attributes to their roles](#).

- `[aria-hidden="true"]` is not present on the document `<body>`

^

Assistive technologies, like screen readers, work inconsistently when `aria-hidden="true"` is set on the document `<body>`. [Learn how `aria-hidden` affects the document body.](#)

- `[role]`s have all required `[aria-*]` attributes

^

Some ARIA roles have required attributes that describe the state of the element to screen readers. [Learn more about roles and required attributes.](#)

- Elements with an ARIA `[role]` that require children to contain a specific `[role]` have all required children.

^

Some ARIA parent roles must contain specific child roles to perform their intended accessibility functions. [Learn more about roles and required children elements.](#)

- `[aria-*]` attributes have valid values

^

Assistive technologies, like screen readers, can't interpret ARIA attributes with invalid values. [Learn more about valid values for ARIA attributes.](#)

- `[aria-*]` attributes are valid and not misspelled

^

Assistive technologies, like screen readers, can't interpret ARIA attributes with invalid names. [Learn more about valid ARIA attributes.](#)

- Buttons have an accessible name

^

When a button doesn't have an accessible name, screen readers announce it as "button", making it unusable for users who rely on screen readers. [Learn how to make buttons more accessible.](#)

- Image elements have `[alt]` attributes

^

Informative elements should aim for short, descriptive alternate text. Decorative elements can be ignored with an empty alt attribute. [Learn more about the alt attribute.](#)

- `[user-scalable="no"]` is not used in the `<meta name="viewport">` element and the `[maximum-scale]` attribute is not less than 5.

^

Disabling zooming is problematic for users with low vision who rely on screen magnification to properly see the contents of a web page. [Learn more about the viewport meta tag.](#)

- `[aria-hidden="true"]` elements do not contain focusable descendants

^

Focusable descendants within an `[aria-hidden="true"]` element prevent those interactive elements from being available to users of assistive technologies like screen readers. [Learn how `aria-hidden` affects focusable elements.](#)

● `[role]` values are valid ^

ARIA roles must have valid values in order to perform their intended accessibility functions. [Learn more about valid ARIA roles.](#)

● ARIA toggle fields have accessible names ^

When a toggle field doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. [Learn more about toggle fields.](#)

● Document has a `<title>` element ^

The title gives screen reader users an overview of the page, and search engine users rely on it heavily to determine if a page is relevant to their search. [Learn more about document titles.](#)

● `[id]` attributes on active, focusable elements are unique ^

All focusable elements must have a unique `id` to ensure that they're visible to assistive technologies. [Learn how to fix duplicate `ids`.](#)

● `<html>` element has a `[lang]` attribute ^

If a page doesn't specify a `lang` attribute, a screen reader assumes that the page is in the default language that the user chose when setting up the screen reader. If the page isn't actually in the default language, then the screen reader might not announce the page's text correctly. [Learn more about the `lang` attribute.](#)

● `<html>` element has a valid value for its `[lang]` attribute ^

Specifying a valid [BCP 47 language](#) helps screen readers announce text properly. [Learn how to use the `lang` attribute.](#)

● Form elements have associated labels ^

Labels ensure that form controls are announced properly by assistive technologies, like screen readers. [Learn more about form element labels.](#)

● Links are distinguishable without relying on color. ^

Low-contrast text is difficult or impossible for many users to read. Link text that is discernible improves the experience for users with low vision. [Learn how to make links distinguishable.](#)

- Lists contain only `` elements and script supporting elements (`<script>` and `<template>`).

^

Screen readers have a specific way of announcing lists. Ensuring proper list structure aids screen reader output. [Learn more about proper list structure.](#)

- List items (``) are contained within ``, `` or `<menu>` parent elements

^

Screen readers require list items (``) to be contained within a parent ``, `` or `<menu>` to be announced properly. [Learn more about proper list structure.](#)

- No element has a `[tabindex]` value greater than 0

^

A value greater than 0 implies an explicit navigation ordering. Although technically valid, this often creates frustrating experiences for users who rely on assistive technologies. [Learn more about the tabindex attribute.](#)

- Image elements do not have `[alt]` attributes that are redundant text.

^

Informative elements should aim for short, descriptive alternative text. Alternative text that is exactly the same as the text adjacent to the link or image is potentially confusing for screen reader users, because the text will be read twice. [Learn more about the alt attribute.](#)

NOT APPLICABLE (34)

Hide

- `[accesskey]` values are unique

^

Access keys let users quickly focus a part of the page. For proper navigation, each access key must be unique. [Learn more about access keys.](#)

- `button`, `link`, and `menuitem` elements have accessible names

^

When an element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. [Learn how to make command elements more accessible.](#)

- Elements with `role="dialog"` or `role="alertdialog"` have accessible names.

^

ARIA dialog elements without accessible names may prevent screen readers users from discerning the purpose of these elements. [Learn how to make ARIA dialog elements more accessible.](#)

- ARIA input fields have accessible names

^

When an input field doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. [Learn more about input field labels.](#)

○ ARIA [meter](#) elements have accessible names ^

When a meter element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. [Learn how to name meter elements.](#)

○ ARIA [progressbar](#) elements have accessible names ^

When a progressbar element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. [Learn how to label progressbar elements.](#)

○ [\[role\]](#)s are contained by their required parent element ^

Some ARIA child roles must be contained by specific parent roles to properly perform their intended accessibility functions. [Learn more about ARIA roles and required parent element.](#)

○ Elements with the [role=text](#) attribute do not have focusable descendants. ^

Adding role=text around a text node split by markup enables VoiceOver to treat it as one phrase, but the element's focusable descendants will not be announced. [Learn more about the role=text attribute.](#)

○ ARIA [tooltip](#) elements have accessible names ^

When a tooltip element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. [Learn how to name tooltip elements.](#)

○ ARIA [treeitem](#) elements have accessible names ^

When a treeitem element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. [Learn more about labeling treeitem elements.](#)

○ The page contains a heading, skip link, or landmark region ^

Adding ways to bypass repetitive content lets keyboard users navigate the page more efficiently. [Learn more about bypass blocks.](#)

○ [<dl>](#)'s contain only properly-ordered [<dt>](#) and [<dd>](#) groups, [<script>](#), [<template>](#) or [<div>](#) elements. ^

When definition lists are not properly marked up, screen readers may produce confusing or inaccurate output. [Learn how to structure definition lists correctly.](#)

○ Definition list items are wrapped in [<dl>](#) elements ^

Definition list items (`<dt>` and `<dd>`) must be wrapped in a parent `<d1>` element to ensure that screen readers can properly announce them. [Learn how to structure definition lists correctly.](#)

○ ARIA IDs are unique ^

The value of an ARIA ID must be unique to prevent other instances from being overlooked by assistive technologies. [Learn how to fix duplicate ARIA IDs.](#)

○ No form fields have multiple labels ^

Form fields with multiple labels can be confusingly announced by assistive technologies like screen readers which use either the first, the last, or all of the labels. [Learn how to use form labels.](#)

○ `<frame>` or `<iframe>` elements have a title ^

Screen reader users rely on frame titles to describe the contents of frames. [Learn more about frame titles.](#)

○ `<html>` element has an `[xml:lang]` attribute with the same base language as the `[lang]` attribute. ^

If the webpage does not specify a consistent language, then the screen reader might not announce the page's text correctly. [Learn more about the lang attribute.](#)

○ Input buttons have discernible text. ^

Adding discernable and accessible text to input buttons may help screen reader users understand the purpose of the input button. [Learn more about input buttons.](#)

○ `<input type="image">` elements have `[alt]` text ^

When an image is being used as an `<input>` button, providing alternative text can help screen reader users understand the purpose of the button. [Learn about input image alt text.](#)

○ Elements with visible text labels have matching accessible names. ^

Visible text labels that do not match the accessible name can result in a confusing experience for screen reader users. [Learn more about accessible names.](#)

○ The document does not use `<meta http-equiv="refresh">` ^

Users do not expect a page to refresh automatically, and doing so will move focus back to the top of the page. This may create a frustrating or confusing experience. [Learn more about the refresh meta tag.](#)

○ [`` elements have alternate text](#)

^

Screen readers cannot translate non-text content. Adding alternate text to `<object>` elements helps screen readers convey meaning to users. [Learn more about alt text for object elements.](#)

○ [Select elements have associated label elements.](#)

^

Form elements without effective labels can create frustrating experiences for screen reader users. [Learn more about the select element.](#)

○ [Skip links are focusable.](#)

^

Including a skip link can help users skip to the main content to save time. [Learn more about skip links.](#)

○ [Tables have different content in the summary attribute and `<caption>`.](#)

^

The summary attribute should describe the table structure, while `<caption>` should have the onscreen title. Accurate table mark-up helps users of screen readers. [Learn more about summary and caption.](#)

○ [Tables use `<caption>` instead of cells with the `\[colspan\]` attribute to indicate a caption.](#)

^

Screen readers have features to make navigating tables easier. Ensuring that tables use the actual caption element instead of cells with the `[colspan]` attribute may improve the experience for screen reader users. [Learn more about captions.](#)

○ [` ` elements in a large `<table>` have one or more table headers. |](#)

^

Screen readers have features to make navigating tables easier. Ensuring that `<td>` elements in a large table (3 or more cells in width and height) have an associated table header may improve the experience for screen reader users. [Learn more about table headers.](#)

○ [Cells in a `<table>` element that use the `\[headers\]` attribute refer to table cells within the same table.](#)

^

Screen readers have features to make navigating tables easier. Ensuring `<td>` cells using the `[headers]` attribute only refer to other cells in the same table may improve the experience for screen reader users. [Learn more about the headers attribute.](#)

○ [` ` elements and elements with `\[role="columnheader"/"rowheader"\]` have data cells they describe. |](#)

^

Screen readers have features to make navigating tables easier. Ensuring table headers always refer to some set of cells may improve the experience for screen reader users. [Learn more about table headers.](#)

○ [`\[lang\]` attributes have a valid value](#)

^

Specifying a valid [BCP 47 language](#) on elements helps ensure that text is pronounced correctly by a screen reader. [Learn how to use the lang attribute.](#)

○ `<video>` elements contain a `<track>` element with `[kind="captions"]` ^

When a video provides a caption it is easier for deaf and hearing impaired users to access its information. [Learn more about video captions.](#)

○ All heading elements contain content. ^

A heading with no content or inaccessible text prevent screen reader users from accessing information on the page's structure. [Learn more about headings.](#)

○ Identical links have the same purpose. ^

Links with the same destination should have the same description, to help users understand the link's purpose and decide whether to follow it. [Learn more about identical links.](#)

○ Touch targets have sufficient size and spacing. ^

Touch targets with sufficient size and spacing help users who may have difficulty targeting small controls to activate the targets. [Learn more about touch targets.](#)



Best Practices

GENERAL

⚠ Browser errors were logged to the console ^

Errors logged to the console indicate unresolved problems. They can come from network request failures and other browser concerns.

[Learn more about this errors in console diagnostic audit](#)

Source	Description
webpack-internal:////...	Warning: A future version of React will block javascript: URLs as a security precaution. Use event handlers instead if you can. If you need to generate unsafe HTML try using dangerouslySetInnerHTML instead. React was passed %s.%s "javascript:(0)" at a at p at div at div at Banner at div at Home at

Source	Description
ay/dist/client.js:2	div at RootLayout (webpack-internal:///./pages/layout.tsx:14:11) at MyApp (webpack-internal:///./pages/_app.tsx:13:11) at PathnameContextProviderAdapter (webpack-internal:///./node_modules/next/dist/shared/lib/router/adapters.js:79:11) at ErrorBoundary (webpack-internal:///./node_modules/next/dist/compiled/@next/react-dev-overlay/dist/client.js:2:5389) at ReactDevOverlay (webpack-internal:///./node_modules/next/dist/compiled/@next/react-dev-overlay/dist/client.js:2:7785) at Container (webpack-internal:///./node_modules/next/dist/client/index.js:78:1) at AppContainer (webpack-internal:///./node_modules/next/dist/client/index.js:182:11) at Root (webpack-internal:///./node_modules/next/dist/client/index.js:396:11)

⚠ Issues were logged in the [Issues](#) panel in Chrome Devtools ^

Issues logged to the [Issues](#) panel in Chrome Devtools indicate unresolved problems. They can come from network request failures, insufficient security controls, and other browser concerns. Open up the [Issues](#) panel in Chrome DevTools for more details on each issue.

Issue type
<p>Cookie</p> <p>/photo-162...?q=... (images.unsplash.com) /photo-159...?q=... (images.unsplash.com) /photo-161...?q=... (images.unsplash.com) /photo-161...?q=... (images.unsplash.com) ...118.../foreveryou.png?ex=6582147e&is=656f9f7e&hm=1da73ad...& (cdn.discordapp.com) /photo-164...?q=... (images.unsplash.com) /photo-148...?q=... (images.unsplash.com)</p>

🕒 Detected JavaScript libraries ^

All front-end JavaScript libraries detected on the page. [Learn more about this JavaScript library detection diagnostic audit.](#)

Name	Version
Bootstrap	5.0.2
jQuery	3.5.1

Name	Version
Next.js	13.5.6

⚠ Missing source maps for large first-party JavaScript

Source maps translate minified code to the original source code. This helps developers debug in production. In addition, Lighthouse is able to provide further insights. Consider deploying source maps to take advantage of these benefits. [Learn more about source maps](#).

Show 3rd-party resources (1)

URL	Map URL
localhost 1st Party	
...pages/index.js?ts=170...	(localhost)
	Large JavaScript file is missing a source map
...chunks/main.js?ts=170...	(localhost)
	Large JavaScript file is missing a source map
Unattributable	
chrome-extension://fmkadmapgofadopljbjfkapdkoienihi/build/react_devtools_backend_compact.js	chrome-extension://fmkadmapgofadopljbjfkapdkoienihi/build/react_devtools_backend_compact.js.map
	Warning: missing 60 items in `sourcesContent`
JSDelivr CDN Cdn	
...js/bootstrap.bundle.min.js (cdn.jsdelivr.net)	...js/bootstrap.bundle.min.js.map (cdn.jsdelivr.net)

TRUST AND SAFETY

○ Ensure CSP is effective against XSS attacks
A strong Content Security Policy (CSP) significantly reduces the risk of cross-site scripting (XSS) attacks. Learn how to use a CSP to prevent XSS

Description	Directive	Severity
No CSP found in enforcement mode		High

PASSED AUDITS (10)

Hide

● Uses HTTPS	^
All sites should be protected with HTTPS, even ones that don't handle sensitive data. This includes avoiding mixed content , where some resources are loaded over HTTP despite the initial request being served over HTTPS. HTTPS prevents intruders from tampering with or passively listening in on the communications between your app and your users, and is a prerequisite for HTTP/2 and many new web platform APIs. Learn more about HTTPS .	
● Avoids deprecated APIs	^
Deprecated APIs will eventually be removed from the browser. Learn more about deprecated APIs .	
● Allows users to paste into input fields	^
Preventing input pasting is a bad practice for the UX, and weakens security by blocking password managers. Learn more about user-friendly input fields .	
● Avoids requesting the geolocation permission on page load	^
Users are mistrustful of or confused by sites that request their location without context. Consider tying the request to a user action instead. Learn more about the geolocation permission .	
● Avoids requesting the notification permission on page load	^
Users are mistrustful of or confused by sites that request to send notifications without context. Consider tying the request to user gestures instead. Learn more about responsibly getting permission for notifications .	
● Displays images with correct aspect ratio	^
Image display dimensions should match natural aspect ratio. Learn more about image aspect ratio .	
● Serves images with appropriate resolution	^
Image natural dimensions should be proportional to the display size and the pixel ratio to maximize image clarity. Learn how to provide responsive images .	

● Page has the HTML doctype

^

Specifying a doctype prevents the browser from switching to quirks-mode. [Learn more about the doctype declaration.](#)

● Properly defines charset

^

A character encoding declaration is required. It can be done with a `<meta>` tag in the first 1024 bytes of the HTML or in the Content-Type HTTP response header. [Learn more about declaring the character encoding.](#)

● Avoids `unload` event listeners

^

The `unload` event does not fire reliably and listening for it can prevent browser optimizations like the Back-Forward Cache. Use `pagehide` or `visibilitychange` events instead. [Learn more about unload event listeners](#)

NOT APPLICABLE (1)

Hide

○ Fonts with `font-display: optional` are preloaded

^

Preload optional fonts so first-time visitors may use them. [Learn more about preloading fonts](#)



SEO

These checks ensure that your page is following basic search engine optimization advice. There are many additional factors Lighthouse does not score here that may affect your search ranking, including performance on [Core Web Vitals](#). [Learn more about Google Search Essentials.](#)

CRAWLING AND INDEXING

⚠ Links are not crawlable

^

Search engines may use `href` attributes on links to crawl websites. Ensure that the `href` attribute of anchor elements links to an appropriate destination, so more pages of the site can be discovered. [Learn how to make links crawlable](#)

Uncrawlable Link

a.mr-2.text-sm.font-medium.text-gray-900

Uncrawlable Link

To appear in search results, crawlers need access to your app.

ADDITIONAL ITEMS TO MANUALLY CHECK (1)

Hide

Structured data is valid

^

Run the [Structured Data Testing Tool](#) and the [Structured Data Linter](#) to validate structured data. [Learn more about Structured Data](#).

Run these additional validators on your site to check additional SEO best practices.

PASSED AUDITS (9)

Hide

Has a `<meta name="viewport">` tag with `width` or `initial-scale`

^

A `<meta name="viewport">` not only optimizes your app for mobile screen sizes, but also prevents [a 300 millisecond delay to user input](#). [Learn more about using the viewport meta tag](#). [TBT](#)

Document has a `<title>` element

^

The title gives screen reader users an overview of the page, and search engine users rely on it heavily to determine if a page is relevant to their search. [Learn more about document titles](#).

Document has a meta description

^

Meta descriptions may be included in search results to concisely summarize page content. [Learn more about the meta description](#).

Page has successful HTTP status code

^

Pages with unsuccessful HTTP status codes may not be indexed properly. [Learn more about HTTP status codes](#).

Links have descriptive text

^

Descriptive link text helps search engines understand your content. [Learn how to make links more accessible](#).

Page isn't blocked from indexing

^

Search engines are unable to include your pages in search results if they don't have permission to crawl them. [Learn more about crawler directives](#).

● Image elements have [\[alt\]](#) attributes

^

Informative elements should aim for short, descriptive alternate text. Decorative elements can be ignored with an empty alt attribute.

[Learn more about the alt attribute.](#)

● Document has a valid [hreflang](#)

^

hreflang links tell search engines what version of a page they should list in search results for a given language or region. [Learn more about hreflang.](#)

● Document avoids plugins

^

Search engines can't index plugin content, and many devices restrict plugins or don't support them. [Learn more about avoiding plugins.](#)

NOT APPLICABLE (4)

Hide

○ robots.txt is valid

^

If your robots.txt file is malformed, crawlers may not be able to understand how you want your website to be crawled or indexed. [Learn more about robots.txt.](#)

○ Document has a valid [rel=canonical](#)

^

Canonical links suggest which URL to show in search results. [Learn more about canonical links.](#)

○ Document uses legible font sizes

^

Font sizes less than 12px are too small to be legible and require mobile visitors to “pinch to zoom” in order to read. Strive to have >60% of page text ≥12px. [Learn more about legible font sizes.](#)

○ Tap targets are sized appropriately

^

Interactive elements like buttons and links should be large enough (48x48px), or have enough space around them, to be easy enough to tap without overlapping onto other elements. [Learn more about tap targets.](#)



PWA

These checks validate the aspects of a Progressive Web App. [Learn what makes a good Progressive Web App.](#)

INSTALLABLE

⚠️ Web app manifest or service worker do not meet the installability requirements — 1 reason

Service worker is the technology that enables your app to use many Progressive Web App features, such as offline, add to homescreen, and push notifications. With proper service worker and manifest implementations, browsers can proactively prompt users to add your app to their homescreen, which can lead to higher engagement. [Learn more about manifest installability requirements.](#)

Failure reason

Page has no manifest <link> URL

PWA OPTIMIZED

⚠️ Is not configured for a custom splash screen [Failures: No manifest was fetched.](#)

A themed splash screen ensures a high-quality experience when users launch your app from their homescreens. [Learn more about splash screens.](#)

⚠️ Does not set a theme color for the address bar. [Failures: No manifest was fetched, No `<meta name="theme-color">` tag found.](#)

The browser address bar can be themed to match your site. [Learn more about theming the address bar.](#)

ⓘ Content is sized correctly for the viewport

If the width of your app's content doesn't match the width of the viewport, your app might not be optimized for mobile screens. [Learn how to size content for the viewport.](#)

ⓘ Has a <meta name="viewport"> tag with width or initial-scale

A <meta name="viewport"> not only optimizes your app for mobile screen sizes, but also prevents [a 300 millisecond delay to user input](#). [Learn more about using the viewport meta tag.](#) 

⚠️ Manifest doesn't have a maskable icon [No manifest was fetched](#)

A maskable icon ensures that the image fills the entire shape without being letterboxed when installing the app on a device. [Learn about maskable manifest icons.](#)

ADDITIONAL ITEMS TO MANUALLY CHECK (3)

Hide

Site works cross-browser ^

To reach the most number of users, sites should work across every major browser. [Learn about cross-browser compatibility.](#)

Page transitions don't feel like they block on the network ^

Transitions should feel snappy as you tap around, even on a slow network. This experience is key to a user's perception of performance. [Learn more about page transitions.](#)

Each page has a URL ^

Ensure individual pages are deep linkable via URL and that URLs are unique for the purpose of shareability on social media. [Learn more about providing deep links.](#)

These checks are required by the baseline [PWA Checklist](#) but are not automatically checked by Lighthouse. They do not affect your score but it's important that you verify them manually.

 Captured at Dec 18, 2023, 5:34

PM EST

 Initial page load

 Emulated Desktop with

Lighthouse 11.2.0

 Custom throttling

 Single page load

 Using Chromium 120.0.0.0 with
devtools

Generated by **Lighthouse** 11.2.0 | [File an issue](#)