Introduction to Data Science

BASIC TRACK · LECTURE 1



Data science in the age of AI

How data become decisions, and how AI changes the way the work is done

Prof. Dimitar Trajanov, PhD
Prof. Igor Mishkovski, PhD
Prof. Andrea Kulakov, PhD
Prof. Slobodan Kalajdziski, PhD

"Ss. Cyril and Methodius" University in Skopje
FACULTY OF COMPUTER SCIENCE AND ENGINEERING

Vezilka
EuroHPC Joint Undertaking
Co-funded by the European Union
Republic of North Macedonia
Ministry of Digital Transformation

Agenda

1. **Data science and its foundations**
   Definition, paradigms, skills, machine learning
2. **Generative AI and language models**
   Next-token generation, temperature, open and closed models
3. **From language models to AI agents**
   Autonomy levels, time horizon, failure modes
4. **Data-science work in the age of AI**
   Labour market, adoption, trust, vibe coding
5. **The data science process**
   Six steps on one running example
6. **Responsible use of AI and learning with AI**
   Trustworthy AI, EU AI Act, personal data, course rules

Learning objectives of the lecture

- After this lecture, the student is able to:
  - Define data science and distinguish it from statistics, machine learning and artificial intelligence.
  - Distinguish traditional programming from **machine learning** and name the main types of learning tasks.
  - Explain how a large language model generates text **one token at a time** and how temperature changes the output.
  - Grade the autonomy of an AI agent and name the characteristic **failure modes** of language models.
  - Carry a question through the **six steps** of the data science process on a running example.
  - Apply the requirements of trustworthy AI, the AI-literacy duty of the EU AI Act and the rules for personal data.
  - Apply the rules for the use of AI in this course.

01

Data science and its foundations

What data science is, the paradigm on which it rests, who practises it, and how machines learn from data



Data science: definition and neighbouring fields

- *Data science* is the discipline of turning data into **reliable knowledge and decisions**, through acquisition, analysis, modelling and communication.
- *Statistics* supplies inference: estimates, uncertainty and tests.
- *Machine learning* (ML) supplies models that learn patterns from data and predict.
- *Artificial intelligence* (AI) is the wider field of systems that perform tasks requiring intelligence; ML is **its dominant method**.
- *Business intelligence* (BI) reports **what happened**; data science also asks why and what will happen.




Figure 1 — data science spans several fields

The four paradigms of science and the data-driven paradigm




Figure 2 — after Hey, Tansley and Tolle (2009)

- Science has advanced through **four paradigms**, each added to the previous ones rather than replacing them.
  - Empirical observation; theoretical laws (from about 1650); computational science (from about 1950).
- The fourth, *data-driven paradigm* lets a computer **derive the model from data** instead of from equations written by people.
  - Examples: speech recognition, protein structure prediction, personalised medicine and game playing.
- Its growth depends on **open-source libraries**, cheap computation and large data sets.

The three essential skills of a data scientist





Figure 4 — after D. Conway (2010)

- Data science requires **three skills at once**: programming, mathematics and statistics, and domain expertise.
  - Programming acquires and processes data at scale.
  - Statistics separates signal from noise and quantifies uncertainty.
  - Domain expertise poses the right question and judges the answer.
- Programming with domain knowledge but **without statistics** is the *danger zone*: results look plausible and are unsupported.
- AI tools now write much of the code, which **raises the weight** of statistics and domain judgement.

Traditional programming versus machine learning



- In traditional programming a person writes the rules; in machine learning **the rules are estimated from examples** of inputs and outputs.
  - Example: the area of a circle is programmed as $\pi \cdot r^2$, or learned from measured pairs of radius and area; the learned rule is approximate.

Machine learning: definition, types and tasks

- A program **learns from experience E** with respect to tasks T and measure P if its performance on T, measured by P, improves with E.
  - T. M. Mitchell, *Machine Learning*, 1997.
- *Supervised learning* uses **labelled examples** to predict a target.
- *Unsupervised learning* finds structure, such as groups, **without labels**.
- *Reinforcement learning* learns actions from **rewards** over time.
- ML cannot supply data it was not given: it assumes the future **resembles the training data**, and it finds correlation, not cause.

Classification
Which category? Spam or not; land-use class

Regression
How much? Tomorrow's PM10 level

Clustering
Which group? Customer segments

Anomaly detection
Is it unusual? Sensor faults, fraud

Recommendation
What is similar? Products, articles

Reinforcement
Which action? Control, games

Figure 5 — tasks that ML solves

The course in four phases: the twelve lectures

Data · L1–L4	Learning · L5–L8	Deep learning · L9–L10	LLMs, agents · L11–L12
■ L1 Data science and AI	■ L5 Regression	■ L9 Neural networks	■ L11 LLMs as data tools: RAG, evaluation
■ L2 Acquiring and querying data	■ L6 Classification, ensembles	■ L10 Language models, transformers	■ L12 AI agents, responsible AI
■ L3 Exploration and inference	■ L7 Evaluation, selection		
■ L4 Preparation, features	■ L8 Unsupervised learning		

Course goal

Carry a real question from raw data to a validated, explained result, and direct, check and explain the AI tools that help along the way.

Case study: one question across the data science lifecycle

Question: on which days does PM10 in Skopje exceed the EU daily limit of 50 µg/m³, and can weather data predict them?

1 Goal	2 Retrieve	3 Prepare	4 Explore	5 Model	6 Present
A charter: the decision is a winter health warning.	Hourly PM10 and daily weather from open APIs.	Hours averaged to days; weather joined by date.	Seasonal profile; PM10 against temperature.	Regression on weather; hold-out years 2024–2025.	Exceedance days per year, updated monthly.
Taught in L1	Taught in L2	Taught in L4	Taught in L3	Taught in L5–L10	Taught in L7, L11–L12

- The lecture follows **one Macedonian air-quality question** through every step; Section 05 shows each step on real data for Skopje, 2015–2025.
  - Data: Copernicus CAMS model PM10 and ERA5 weather, retrieved through the Open-Meteo APIs; station data of the Ministry of Environment are an alternative source.

02

Generative AI and large language models

From models that separate classes to models that generate text: how they work, how capable they are and what they cost



Discriminative versus generative models




Figure 6 — one data set, two kinds of model

- A *discriminative model* learns **P(y | x)**: the boundary between classes. Logistic regression, SVMs and most classifiers are of this kind.
- A *generative model* learns **the distribution of the data** itself, P(x) or P(x | y), and can therefore sample new instances.
- Today's generative AI rests on two families: **transformers**, mostly for text and code, and **diffusion models**, mostly for images, audio and video.
  - GANs and VAEs, cited as the examples in earlier versions of this course, are now niche methods.
- A modern generative model must describe every feature of the data, so it needs **far more data and parameters** than a classifier for the same task.

Software 1.0, 2.0 and 3.0: three ways to program a computer

Software 1.0	Software 2.0	Software 3.0
Program = source code	**Program = neural-network weights**	**Program = a prompt in natural language**
Written by a programmer, line by line	Learned by optimisation from labelled data	Written in English or Macedonian
Runs on a computer; programmable since the 1940s	A fixed-function network, such as AlexNet (2012)	Runs on an LLM, a programmable network (2020s)

- The three paradigms **coexist**: a modern data application mixes hand-written code, trained models and prompts, and each needs its own tests.
  - After A. Karpathy, “Software Is Changing (Again)”, Y Combinator AI Startup School, June 2025.

How a large language model generates text




4 One token is sampled, appended to the context, and the loop repeats

The | ␣capital | ␣of | ␣France | ␣is | ␣Paris

A reasoning model first generates intermediate tokens, a chain of thought, and then the answer; the extra tokens cost time and money and often improve multi-step problems.

- An LLM is pre-trained to **predict the next token**, then tuned with human feedback; generating text is repeated prediction, so every answer is a sample from a distribution.
  - A *token* is a word or word fragment; the *context window* is the number of tokens the model reads at once.

Worked example: next-token sampling and temperature



- Scores (*logits*) for six candidate tokens; the values are **illustrative**, the computation is exact.
- Softmax at T = 1 gives ‘Paris’ **84 %**; at T = 2 only **53 %**.
- Higher temperature flattens the distribution; T → 0 always picks the top token.
- The same sentence costs **7 tokens in English** and **10 in Macedonian**.

Open-weight and closed models: the capability gap




Figure 10 — in 2025 data the best open-weight models trailed the best closed models by less than one year; by May 2026 the lag had narrowed to about four months (Epoch AI).


03

From language models to AI agents

How the autonomy of an agent is graded, how the length of the tasks that agents complete is measured, and how an agent can be steered by the data it reads



AI autonomy levels: decisions retained and transferred



- Each level transfers **one further class of decision** from the person to the system; the bar lengths are **schematic, not measured**.
  - An audit of 28 products described as agents found **5 operating above Level 2** (AI Agents lecture series, FCSE, Skopje, 2026).

The time horizon of AI agents, 2020 to 2026





Figure 12 — task length, in human working time, completed unaided

- The *50 % time horizon* is the length of a task, in human working time, at which a model **succeeds half the time** (METR).
  - GPT-3, 2020: **8.6 seconds**; Claude Opus 4.6, February 2026: **11 h 59 min**; Claude Mythos Preview, April 2026: **about 17 h**.
- The horizon has **doubled every 128.7 days** since 2023, against 187.8 days over the whole series.
  - The frontier line joins the state-of-the-art models; the faint points are the other measured models.
- At 80 % reliability the horizon is far shorter, which is why agents remain **under supervision**.
  - Source: METR, time-horizon series 1.1, page updated 8 May 2026.

LLM failure modes: amnesia, gullibility and prompt injection

Anterograde amnesia: the weights do not learn after training. Since 2025 agents carry memory across sessions by saving notes (CLAUDE.md, AGENTS.md) and reloading them: retrieval, not learning.



- An LLM is **gullible**: it follows instructions found in data, so an agent that reads untrusted text can be steered by an attacker.
  - Defences: least-privilege tools, sandboxing, approval of 28 products described as agents found **5 operating above Level 2** (AI Agents lecture series, FCSE, Skopje, 2026) – agent-washing.


04

Data-science work in the age of AI

What surveys and benchmarks show about AI spending, the labour market, and AI tools and agents in daily work, 2025–2026



The data-science labour market: projected growth



- United States employment of data scientists is projected to grow **from 275,600 to 371,000** jobs.
- About **24,800 openings** a year.
- Median pay: $120,230 (2025).
  - Source: United States Bureau of Labor Statistics, Occupational Outlook Handbook, 2025–35 projections.
- WEF (2025): **big data specialists** are the fastest-growing job to 2030.

AI tools in development work: adoption and trust

84 %

Use or plan to use AI tools
Up from 76 % in 2024

51 %

Of professionals use AI daily
Professional developers, 2025

59 %

Use AI agents at work
April 2026; 31 % in 2025

33 %

Trust the accuracy of AI output
46 % distrust it

- Adoption is almost universal and trust is low: AI output is used, but it **has to be verified** before it is relied upon.
  - Sources: Stack Overflow Developer Survey 2025 (49,000+ respondents, July 2025); Stack Overflow AI-agent pulse survey (about 1,100 respondents, April 2026, published 27 May 2026).
- Daily agent use rose **from 14 % to 37 %**; among agent users, Claude Code rose from 41 % to 55 % (Stack Overflow, April 2026).
- The surveys describe developers in general; **data-science-specific** figures of comparable quality are not available.

Vibe coding: definition and scope

> Vibe coding is the production of software by prompting an LLM and accepting its output without reading or understanding the generated code.
>
> — After A. Karpathy, post on X, 2 February 2025; Collins Word of the Year 2025

- Vibe coding suits **disposable prototypes**; an analysis whose result informs a decision requires code that has been read and tested.
  - METR (July 2025): experienced developers were 19 % slower with AI tools while believing they were 20 % faster; the February 2026 follow-up suggests a speed-up but is weak evidence.


05

The data science process

Six steps from question to deployed result, shown on the Skopje air-quality example of Section 01




The six-step data science process



Exploration often reveals data problems (back to step 3); modelling often shows that the question was too broad (back to step 1).

- The process of Cielen, Meysman and Ali (2016) has **six steps**, and it is **iterative**: each step can return the work to an earlier one.
  - Each step is taught in a later lecture of this course, as shown under the arrows.

Where the working time of a data scientist goes



- Loading and cleansing: **45 %** in 2020, **about 38 %** in 2022; still the largest share.
- The ‘80 %’ **misreads a 2016 survey**: a share of respondents, not of hours.
- AI-generated preparation code **can fail silently**, as in a wrong join.
  - Sources: Anaconda, State of Data Science 2020 and 2022, self-reported; CrowdFlower, 2016.

Step 1: the project charter of the running example

- A *project charter* fixes **goal, scope and success measure** before any data are collected.
- It states the research goal, mission and context, method, resources, feasibility, deliverables and a timeline.
- Many failed projects fail here: the analysis **answers a question that nobody asked**.
- The success criterion is set in advance, so the result **cannot be redefined** after the fact.
  - The charter is agreed with the person who will use the result.
- Every later step of the running example **refers back** to this charter.

Project charter — Skopje PM10	
Goal	Predict days above 50 µg/m³ one day ahead
Context	Winter health warnings for the city
Data	PM10 and weather, 2015–2025, open sources
Method	Regression; hold-out years 2024–2025
Success	Error below a no-skill baseline
Deliverable	Notebook, report, monthly update
Timeline	Four weeks; review after week 2

Figure 16 — a charter in seven fields

Step 2: retrieving internal, external and open data

- *Internal data* sit in databases, warehouses and lakes, and sometimes in spreadsheets; **access rights** are often the slowest part.
- *External data* are bought from providers or obtained through **APIs**.
  - Social-media APIs have been restricted or paid since 2023 and are no longer a default source.
- *Open data* are published under licences that **permit reuse**: data.gov.mk, MakStat, Eurostat, Copernicus.
- Every source is recorded with its **licence, date and version** (Lecture 2).

Copernicus CAMS
Modelled PM10, hourly (used)

ERA5 reanalysis
Daily weather (used)

Open-Meteo APIs
Access to both, JSON (used)

MOEPP stations
Measured air quality

data.gov.mk
National open-data portal

MakStat
State Statistical Office

Figure 17 — red: sources used here

Step 3: preparing the data — cleansing, joining, transforming

Hourly PM10 96,432 rows → **Average** to days → **Join daily** weather by date → **Check ranges** and gaps → **Derive month** and season

date	pm10 µg/m³	temp °C	wind max km/h	precip mm	month
2015-01-01	25.9	-12.7	12.1	0.0	1
2015-01-02	58.0	-8.4	11.7	0.0	1
2015-01-03	52.2	-0.3	7.9	0.0	1
2015-01-04	29.1	2.2	14.8	1.7	1
2015-01-05	20.1	-1.0	16.2	0.6	1

Result: 4,018 daily rows, 2015-01-01 to 2025-12-31; no missing values after the join; PM10 ranges from 4.4 to 155.4 µg/m³.

- Preparation **changes the data**, so every operation is scripted and logged: rows in, rows out, and the reason for any removal.
  - Cleansing fixes errors; integration joins sources on a shared key; transformation derives the features the model needs (Lecture 4).

Step 4: exploring seasonality and the effect of temperature




Figure 18 — January mean 50 µg/m³ against July 21: PM10 rises on cold days (heating). CAMS model values are smoother than station measurements.

Step 5: modelling with a hold-out period

- A linear regression on temperature, wind, rain and month is fitted on **2015–2023** (3,287 days).
- The years **2024–2025** (731 days) are held out and used once, for the final score.
- *Mean squared error*: MSE = $(1/n)\ \Sigma\ (y_i - \hat{y}_i)^2$, the average squared distance from the truth.
  - Squaring penalises large errors most; RMSE, its square root, is in µg/m³.
- RMSE falls from **17.4** (predict the training mean) to **14.8 µg/m³**: the model beats the no-skill baseline.
- Model choice also weighs **explainability and maintenance**, not only error.




Figure 19 — red line: perfect prediction

Step 6: presenting results and automating the analysis

- A result is presented as **the answer to the charter's question**, with its uncertainty and its limitations.
- Exceedance days fell from **61** in 2015 to **31** in 2025 in the model data; the EU allows 35 a year.
- A repeated analysis is **automated**: a script refreshes data, model and report on a schedule.
  - Sometimes only model scoring is automated; sometimes a dashboard replaces the report.
- A report also states what the data **cannot show**: these are model estimates, not station measurements.




Figure 20 — red: above 35 days allowed

06

Responsible use of AI

Measured benefits and risks, trustworthy AI, the legal duty of AI literacy and the rules for personal data



Risks of AI systems and the safeguard for each

Unreliable outputs

Agent success on real computer tasks rose from 66 % (2025) to 75 % (2026), still one failure in four. Safeguard: tests on the institution's own tasks and a reviewer who may reject any output.

Loss of competence

Unaided adenoma detection fell from 28.4 % to 22.4 % after months of AI-assisted colonoscopy. Safeguard: assessment and training without AI.

Discrimination and privacy

Error rates differ across groups and languages. Safeguard: minimal data, a test for each affected group and a human appeal.

Misuse and security

Prompt injection beat 2024-25 models about half the time in ten attempts; the best 2026 model, 2 % in 15. Safeguard: limited permissions and a tested ability to suspend.

- No single safeguard is complete, so safeguards are **applied in combination**, and deployment is suspended while a serious failure remains unresolved.
  - Sources: AI Index 2026; International AI Safety Report 2026; NIST AI 600-1 (2024); OECD (2024); WHO (2021).

Trustworthy AI: three components

> Trustworthy AI has three components, which should be met throughout the system's entire life cycle: it should be **lawful**, it should be **ethical**, and it should be **robust**, both from a technical perspective and taking into account its social environment.
>
> Ethics Guidelines for Trustworthy AI, High-Level Expert Group on AI, 2019

- *Lawful*: **compliance with the law** applicable to the system and its domain; *ethical*: autonomy, **prevention of harm**, fairness and explicability.
- *Robust*: **dependable behaviour** in actual use; the three components are **cumulative rather than alternative**.

The EU AI Act: AI literacy and the application timeline

- *AI literacy* is the skill and understanding needed to **use AI systems knowingly**, aware of their opportunities, risks and harms.
- Article 4 has applied since **2 February 2025** to providers and deployers of AI systems.
- The Digital Omnibus on AI, **Regulation (EU) 2026/1744**, in force since 27 July 2026, recast it.
  - Organisations must now **support** the AI literacy of staff, not ensure a sufficient level.
- AI in education is **high-risk** from 2 December 2027.




Figure 21 — dates as amended in July 2026

Personal data, consumer chatbots and academic integrity

	Local or approved tool	Consumer chatbot
Public or synthetic data	**Permitted** Course work on open data sets	**Permitted, disclosed** Declared in the AI-use statement
Personal or secret data	**Approved tools only** Local models, contracted services	**Not permitted** Personal data, secrets, .env files

Figure 22 — which data may go where

- A prompt to a consumer chatbot **sends the data to the provider**, where it may be stored and, depending on the settings, used for training.
- Personal data fall under the **GDPR** and the Macedonian Law on Personal Data Protection (2020).
- Academic integrity: AI use is **declared** in an AI-use statement: tool, prompts, what was checked and how.
  - Undeclared AI-generated work is treated as plagiarism.
- Course rule: **no personal data** in any external AI tool; a local model through Ollama is used instead.


07

Learning in the age of AI: use it or lose it

What removing physical effort did to the body, what the early evidence shows for the mind, and how to use AI so that the skill stays yours



Practice with AI rises, the exam without AI falls



- Field experiment, about **1,000 high-school students** in Türkiye; change in grades against students without AI.
- With plain chat, practice grades rose **48 %**, but the exam without AI fell **17 %**: AI was used as a crutch.
- A tutor that **gives hints, not answers** raised practice 127 % with no significant loss in the exam.
  - Source: Bastani et al., PNAS 122(26), 2025; OECD Digital Education Outlook 2026.

Using AI in this course so that the skill stays yours

1 Think first, then ask

Write your own plan or first draft before the prompt; starting alone keeps recall and engagement high.

2 Ask why, not only what

Ask for an explanation with every piece of code; the high scorers did exactly this.

3 Predict before you run

Write down the expected output, then run the cell; a wrong prediction is a lesson.

4 Debug it yourself first

Read the traceback before pasting it; debugging showed the largest skill gap.

5 Hints, not answers

Tell the assistant to act as a tutor: questions and hints, no finished solution.

6 Own every line

The oral defence asks you to explain your own code; code you cannot explain is not your work.

- The effort that feels slow is **what builds the skill**; the goal is to **use AI as a coach, not as a crutch**.
  - Sources: OECD Digital Education Outlook 2026; Shen and Tamkin (2026); Bastani et al. (2025); Bjork (1994), desirable difficulties.

Key takeaways

- ✓ Data science turns data into **reliable decisions**; it combines programming, statistics and domain expertise.
- ✓ Machine learning **learns the rule from examples** instead of receiving it from a programmer.
- ✓ An LLM samples the next token: **fluent output is not verified output**.
- ✓ Agents are graded by the decisions transferred to them, and they are **supervised** in practice.
- ✓ The six-step process is **iterative**, and data preparation takes the largest share of the time.
- ✓ Effortful use of AI builds the skill; **delegated use** does not.



Questions

Co-funded by the European Union through the EuroHPC Joint Undertaking under Grant Agreement No 101263128, and by the Ministry of Digital Transformation of the Republic of North Macedonia. Views and opinions expressed are those of the author(s) only and do not necessarily reflect those of the European Union or the EuroHPC JU.

Vezilka

AI Factories

EuroHPC Joint Undertaking

Co-funded by the European Union

Republic of North Macedonia
Ministry of Digital Transformation