

Structural Properties of Networks

I. Makarov & L.E. Zhukov

Moscow Institute of Physics and Technology

Network Science




- Global, statistical properties of the networks:
 - average node degree (degree distribution)
 - average clustering
 - average path length
- Local, per vertex properties:
 - node centrality
 - page rank
- Pairwise properties:
 - node equivalence
 - node similarity
 - correlation between pairs of vertices (node values)

Structural equivalence

Definition

Structural equivalence: two vertices are structurally equivalent if their respective sets of in-neighbors and out-neighbors are the same






	u1	u2	v1	v2	w
u1	0	0	1	1	0
u2	0	0	1	1	0
v1	0	0	0	1	1
v2	0	0	1	0	1
w	0	0	0	0	0

rows and columns of adjacency matrix of structurally equivalent nodes are identical, "connect to the same neighbors"

Structural equivalence


- In order for adjacent vertices to be structurally equivalent, they should have self loops.
- Sometimes called "strong structural equivalence"
- Sometimes relax requirements for self loops for adjacent nodes



Structural similarity

Definition

Two nodes are similar to each other if they share many neighbors.



- Jaccard similarity

$$J(v_i, v_j) = \frac{|\mathcal{N}(v_i) \cap \mathcal{N}(v_j)|}{|\mathcal{N}(v_i) \cup \mathcal{N}(v_j)|}$$

- Cosine similarity (vectors in n -dim space)

$$\sigma(v_i, v_j) = \cos(\theta_{ij}) = \frac{\mathbf{v}_i^T \mathbf{v}_j}{|\mathbf{v}_i| |\mathbf{v}_j|} = \frac{\sum_k A_{ik} A_{kj}}{\sqrt{\sum A_{ik}^2} \sqrt{\sum A_{jk}^2}}$$

- Pearson correlation coefficient:

$$r_{ij} = \frac{\sum_k (A_{ik} - \langle A_i \rangle)(A_{jk} - \langle A_j \rangle)}{\sqrt{\sum_k (A_{ik} - \langle A_i \rangle)^2} \sqrt{\sum_k (A_{jk} - \langle A_j \rangle)^2}}$$

Similarity measures


- Unweighted undirected graph $A_{ik} = A_{ki}$, binary matrix, only 0 and 1
- $\sum_k A_{ik} = \sum_k A_{ik}^2 = k_i$ - node degree
- $\sum_k A_{ik} A_{kj} = (A^2)_{ij} = n_{ij}$ - number of shared neighbors
- Cosine similarity (vectors in n -dim space)

$$\sigma(v_i, v_j) = \cos(\theta_{ij}) = \frac{n_{ij}}{\sqrt{k_i k_j}}$$


- Pearson correlation coefficient:

$$r_{ij} = \frac{n_{ij} - \frac{k_i k_j}{n}}{\sqrt{k_i - \frac{k_i^2}{n}} \sqrt{k_j - \frac{k_j^2}{n}}}$$

Similarity matrix



Graph



Node similarity matrix

Regular equivalence

Definition


Two vertices are regularly equivalent if they are equally related to equivalent others.

- Quantitative measure - similarity score σ_{ij} (recursive definition):

$$\sigma_{ij} = \alpha \sum_{k,l} A_{ik} A_{jl} \sigma_{kl}$$

- should have high σ_{ii} - self similarity

$$\sigma_{ij} = \alpha \sum_{k,l} A_{ik} A_{jl} \sigma_{kl} + \delta_{ij}$$



Regular similarity


- A vertex j is similar to vertex i (dashed line) if i has a network neighbor v (solid line) that is itself similar to j

$$\sigma_{ij} = \alpha \sum_v A_{iv} \sigma_{vj} + \delta_{ij}$$

$$\sigma = \alpha A \sigma + I$$

- Closed form solution:

$$\sigma = (I - \alpha A)^{-1}$$



- G - directed graph
- Two vertices are similar if they are referenced by similar vertices
- $s(a, b)$ - similarity between a and b , $I()$ - set of in-neighbours

$$s(a, b) = \frac{C}{|I(a)||I(b)|} \sum_{i=1}^{I(a)} \sum_{j=1}^{I(b)} s(I_i(a), I_j(b)), \quad a \neq b$$

$$s(a, a) = 1$$

- Matrix notation:

$$S_{ij} = \frac{C}{k_i k_j} \sum_{k,m} A_{ki} A_{mj} S_{km}$$

- Iterative solution starting from $s_0(i, j) = \delta_{ij}$

Jeh and Widom, 2002

Mixing patterns

Network mixing patterns

- **Assortative mixing**, "like links with like", attributed of connected nodes tend to be more similar than if there were no such edge
- **Disassortative mixing**, "like links with dislike", attributed of connected nodes tend to be less similar than if there were no such edge

Vertices can mix on any vertex attributes (age, sex, geography in social networks), unobserved attributes, vertex degrees

Examples:


assortative mixing - in social networks political beliefs, obesity, race

disassortative mixing - dating network, food web (predator/prey),

economic networks (producers/consumers)

Assortative mixing

- Political polarization on Twitter: political retweet network ,red color - "right-learning" users, blue color - "left learning" users



- Assortative mixing = homophily

Conover et al., 2011

Mixing by categorical attributes

- Vertex categorical attribute (c_i -label): color, gender, ethnicity
- How much more often do attributes match across edges than expected at random?
- Modularity :

$$Q = \frac{m_c - \langle m_c \rangle}{m} = \frac{1}{2m} \sum_{ij} \left(A_{ij} - \frac{k_i k_j}{2m} \right) \delta(c_i, c_j)$$

- m_c - number of edges between vertices with same attributes
 $\langle m_c \rangle$ - expected number of edges within the same class in random network
- Assortativity coefficient:

$$\frac{Q}{Q_{max}} = \frac{\sum_{ij} \left(A_{ij} - \frac{k_i k_j}{2m} \right) \delta(c_i, c_j)}{2m - \sum_{ij} \frac{k_i k_j}{2m} \delta(c_i, c_j)}$$

Mixing by scalar values

- Vertex scalar value (attribute) - x_i
- How much more similar are attributes across edges than expected at random?
- Average and covariance over edges

$$\langle x \rangle = \frac{\sum_i k_i x_i}{\sum_i k_i} = \frac{1}{2m} \sum_i k_i x_i = \frac{1}{2m} \sum_{ij} A_{ij} x_i$$

$$var = \frac{1}{2m} \sum_{ij} A_{ij} (x_i - \langle x \rangle)^2 = \frac{1}{2m} \sum_i k_i (x_i - \langle x \rangle)^2$$

$$cov = \frac{1}{2m} \sum_{ij} A_{ij} (x_i - \langle x \rangle)(x_j - \langle x \rangle)$$

- Assortativity coefficient

$$r = \frac{cov}{var} = \frac{\sum_{ij} \left(A_{ij} - \frac{k_i k_j}{2m} \right) x_i x_j}{\sum_{ij} \left(k_i \delta_{ij} - \frac{k_i k_j}{2m} \right) x_i x_j}$$

Mixing by node degree

- Assortative mixing by node degree, $x_i \leftarrow k_i$

$$r = \frac{\sum_{ij} \left(A_{ij} - \frac{k_i k_j}{2m} \right) k_i k_j}{\sum_{ij} \left(k_i \delta_{ij} - \frac{k_i k_j}{2m} \right) k_i k_j}$$

- Computations:

$$S_1 = \sum_i k_i = 2m$$

$$S_2 = \sum_i k_i^2$$

$$S_3 = \sum_i k_i^3$$


$$S_e = \sum_{ij} A_{ij} k_i k_j$$

- Assortativity coefficient


$$r = \frac{S_e S_1 - S_2^2}{S_3 S_1 - S_2^2}$$

Mixing by node degree

- Assortative network: interconnected high degree nodes - core, low degree nodes - periphery
- Disassortative network: high degree nodes connected to low degree nodes, star-like structure




Assortative network



Disassortative network

Degree correlation



from A.L. Barabasi, 2016

References

- White, D., Reitz, K.P. Measuring role distance: structural, regular and relational equivalence. Technical report, University of California, Irvine, 1985
- S. Borgatti, M. Everett. The class of all regular equivalences: algebraic structure and computations. Social Networks, v 11, p65-68, 1989
- E. A. Leicht, P. Holme, and M. E. J. Newman. Vertex similarity in networks. Phys. Rev. E 73, 026120, 2006
- G. Jeh and J. Widom. SimRank: A Measure of Structural-Context Similarity. Proceedings of the eighth ACM SIGKDD, p 538-543. ACM Press, 2002
- M. E. J. Newman. Assortative mixing in networks. Phys. Rev. Lett. 89, 208701, 2002.
- M. Newman. Mixing patterns in networks. Phys. Rev. E, Vol. 67, p 026126, 2003
- M. McPherson, L. Smith-Lovin, and J. Cook. Birds of a Feather: Homophily in Social Networks, Annu. Rev. Sociol, 27:415-44, 2001.