

160050030_160050031_160050033_Assignment3

by Vikrant Garg

Submission date: 02-Sep-2018 09:41PM (UTC+0800)

Submission ID: 995937417

File name: report.txt (7.44K)

Word count: 988

Character count: 6054

```
function imd = sobelOp(im,dir)
```

4

```
%UNTITLED3 Summary of this function goes here
```

```
% Detailed explanation goes here
```

```
%Sobel matrix
```

```
if dir == 'x'; sobelMat = [-1 0 1;-2 0 2;-1 0 1]; end
```

```
if dir == 'y'; sobelMat = [1 2 1; 0 0 0; -1 -2 -1]; end
```

```
%padding image with the same values at boundary
```

```
imt = cat(2,im(:,1),im);
```

```
imt = cat(2,imt(:,end),imt);
```

```
imt = cat(1,imt(1,:),imt);
```

```
imt = cat(1,imt(end,:),imt);
```

8

```
[row,col] = size(im);
```

```
imd = zeros(row,col);
```

```
for i = 1:row
```

```
    for j = 1:col
```

```
        m1 = imt(i:i+2,j:j+2).*sobelMat;
```

```
        imd(i,j) = abs(sum(sum(m1)));
```

```
    end
```

```
end
```

```
end
```

```
function imo = gaussianSmooth(im,ss)
```

```
    11 %UNTITLED2 Summary of this function goes here
```

```
%return gaussian smoothed image
```

```
% Detailed explanation goes here
```

```
%size
```

```
    3 [row,col] = size(im);
```

```
imo = zeros(row,col);
```

```
for i = 1:row
```

```
    for j = 1:col
```

```
        l = floor(j - 3*ss);
```

```
        if (l < 1); l = 1; end
```

```
        r = floor(j + 3*ss);
```

```
        if (r > col); r = col; end
```

```
        t = floor(i - 3*ss);
```

```
        if (t < 1); t = 1; end
```

```
        b = floor(i + 3*ss);
```

```
        if (b > row); b = row; end
```

```
        X = im(t:b,l:r);
```

```
        sp_r = 1:b-t+11;
```

```
sp_r = sp_r';
```

```
sp_r = repmat(sp_r,1,r-l+1);
```

```
sp_c = 1:r-l+1;
```

```
sp_c = repmat(sp_c,b-t+1,1);
```

```
9 sp_r = sp_r - (i - t + 1);
```

```
sp_c = sp_c - (j - l + 1);
```

```
sp_r = sp_r.*sp_r;
```

```
sp_c = sp_c.*sp_c;
```

```
sp = sp_r + sp_c;
```

```
sp = exp((-0.5/ss^2)*sp);
```

```
imo(i,j) = sum(sum(sp.*X))/sum(sum(sp));
```

```
2 end
```

```
end
```

```
end
```

```
%% MyMainScript
```

```
tic;
```

```
%% Your code here
```

```
load('../data/boat.mat')
```

```
imageOrig = imageOrig/256;
```

```
myHarrisCornerDetector(imageOrig,2,2,0.05);
```

```
toc;
```

```
function [] = myHarrisCornerDetector(im,s1,s2,k)
```

4

```
%UNTITLED Summary of this function goes here
```

```
% Detailed explanation goes here
```

```
%%
```

```
%%%%%%%%%%%%%%Testing Block%%%%%%%%%%%%%%
```

```
% load('../data/boat.mat')
```

```
% im = imageOrig/256;
```

```
% s1 = 2;
```

```
% s2 = 2;
```

```
%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
```

```
%size
```

```
[row,col] = size(im);
```

```
img1 = gaussianSmooth(im,s1); %smoothing 1
```

```
%X derivative
```

```
imgx = sobelOp(img1,'x');
```

```
% Y derivative
```

```
imgy = sobelOp(img1,'y');
```

```
imgx2 = imgx.*imgx;
```

```
imgy2 = imgy.*imgy;
```

```
imgxy = imgx.*imgy;
```

```
A11 = zeros(3, row, col);
```

```
A12 = zeros(row, col);
```

```
A22 = zeros(row, col);
```

```
for i = 1:row
```

```
    for j = 1:col
```

```
        l = floor(j - 3*s2);
```

```
        if (l < 1); l = 1; end
```

```
        r = floor(j + 3*s2);
```

```
        if (r > col); r = col; end
```

```
        t = floor(i - 3*s2);
```

```
        if (t < 1); t = 1; end
```



```
b = floor(i + 3*s2);
```

```
if (b > row); b = row; end
```

```
A11t = imgx2(t:b,l:r);
```

```
A12t = imgxy(t:b,l:r);
```

```
A22t = imgy2(t:b,l:r);
```

```
sp_r = 1:b-t+1;
```

```
sp_r = sp_r';
```

```
sp_r = repmat(sp_r,1,r-l+1);
```

```
sp_c = 1:r-l+1;
```

```
sp_c = repmat(sp_c,b-t+1,1);
```

```
sp_r = sp_r - (i - t + 1);
```

```
sp_c = sp_c - (j - l + 1);
```

```
sp_r = sp_r.*sp_r;
```

```

sp_c = sp_c.*sp_c;

sp = sp_r + sp_c;

sp = exp((-0.5/s2^2)*sp);

sp_sum = sum(sum(sp));

A11(i,j) = sum(sum(A11t.*sp))/sp_sum;

A12(i,j) = sum(sum(A12t.*sp))/sp_sum;

A22(i,j) = sum(sum(A22t.*sp))/sp_sum;

end

end

%% Harris corner-ness measure

% k = 0.05;

5
trace = A11+A22;

C = A11.*A22 - A12.^2 - k*(trace.^2);

```

```
C = C/max(max(C));
```

```
%% eigenvalues
```

```
eigen1 = (A11+A22 + sqrt((A11-A22).^2 + 4*A12.^2))/2;
```

```
eigen2 = (A11+A22 - sqrt((A11-A22).^2 + 4*A12.^2))/2;
```

```
%figures
```

```
myNumOfColors=200;
```

```
myColorScale = [(0:1/(myNumOfColors-1):1)',(0:1/(myNumOfColors-1):1)'];
```

```
figure(1)
```

```
imshow(mat2gray(imgx))
```

```
colormap(myColorScale);
```

```
colormap gray;
```

```
figure(2)
```

```
imshow(mat2gray(imgy))
```

```
colormap(myColorScale);
```

```
colormap gray;
```

```
figure(3)
```

```
imshow(mat2gray(eigen1))
```

```
colormap(myColorScale);
```

```
colormap gray;
```

```
colorbar
```

```
figure(4)
```

```
imshow(mat2gray(eigen2))
```

```
colormap(myColorScale);
```

```
colormap gray;
```

```
colorbar
```

%%

figure(5)

imshow(C)

```
colormap(myColorScale);
```

```
colormap gray;
```

colorbar

end

%%%

%%%%%%%%%

```
function [] = myMeanShiftSegmentation(filename,hr,hs,nitr,nnbr)
```

4 %UNTITLED4 Summary of this function goes here

% Detailed explanation goes here

Test block

```
% filename = '../data/baboonColor.png';

% hr = 250;

% hs = 100;

%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%

% read image

im= imread(filename);

% im=mat2gray(im);

% filter image

im = imgaussfilt(im,1);

% resize image

im=imresize(im,.5);

[row,col,~] = size(im);

% uplmg = zeros(row,col,3);
```

```
% selecting n nearest neighbours
```

```
% n = 75;
```

```
% gradient steps
```

```
% tau = 3;
```

```
wait = waitbar(0,'Wait');
```

```
%%%
```

```
feature=zeros(5,6*row*col);
```

```
for i = 1:row
```

```
    for j=1:col
```

```
        feature(:,i*col - col +j)=[i;j;im(i,j,1); im(i,j, 2); im(i,j,3);];
```

```
    end
```

```
end
```

```
X=feature';
```

```
X = cast(X,'double');
```

```
7 X(:, 3:5) = X(:, 3:5)/(hr);
```

```
X(:, 1:2) = X(:, 1:2)/(hs);
```

```
for z = 1:nitr
```

```
7 % X(:, 3:5) = X(:, 3:5)/(hr);
```

```
% X(:, 1:2) = X(:, 1:2)/(hs);
```

```
Mdl = KDTreeSearcher(X);
```

```
[idx,D] = knnsearch(Mdl,X,'K',nnbr); % finding indexes of k nearest nbrs to (i,j) pixel by
```

```
color
```

```
res = exp(-(D.^2));
```

```
suma=sum(res,2);
```

```
7 % X(:, 3:5) = X(:, 3:5)*(hr);
```

```
% X(:, 1:2) = X(:, 1:2)*(hs);
```



```
X(:,3) = sum(res.*reshape(X(idx(:,:),3),[],nnbr),2)./suma;
```

```
X(:,4) = sum(res.*reshape(X(idx(:,:),4),[],nnbr),2)./suma;
```

```
X(:,5) = sum(res.*reshape(X(idx(:,:),5),[],nnbr),2)./suma;
```

```
waitbar(z/nitr,wait,'Chill bro, we are still computing..');
```

```
end
```

```
close(wait)
```

```
final_im = zeros(row,col,3);
```

```
for i = 1:row
```

```
    for j = 1:col
```

```
        final_im(i,j,:) = X(i*col-col+j,3:5);
```

```
    end
```

```
end
```

```
%%
```

```
%figures
```

```
2  
myNumOfColors=200;
```

```
myColorScale = [(0:1/(myNumOfColors-1):1)',(0:1/(myNumOfColors-  
1):1)',(0:1/(myNumOfColors-1):1)'];
```

```
subplot(1,2,1);
```

```
imshow(imread(filename));
```

```
colormap(myColorScale);
```

```
subplot(1,2,2);
```

```
imshow(final_im);
```

```
title(['hr=' num2str(hr) 'hs=' num2str(hs)] )
```

```
colormap(myColorScale);
```

```
end
```

```
%% MyMainScript
```

```
tic;
```

```
%% Your code here
```

```
% myMeanShiftSegmentation(filename, hr, hs, number_of_iteration,
```

```
number_of_neighbour);
```

```
figure(1)
```

```
myMeanShiftSegmentation('./data/baboonColor.png', 250, 100, 20, 100);
```

```
% figure(2)
```

```
% myMeanShiftSegmentation('./data/baboonColor.png', 500, 100, 20, 100);
```

```
% figure(3)
```

```
% myMeanShiftSegmentation('./data/baboonColor.png', 250, 200, 20, 100);
```

```
% figure(4)
```

```
% myMeanShiftSegmentation('./data/baboonColor.png', 250, 100, 40, 100);
```

```
% figure(5)
```

```
% myMeanShiftSegmentation(' ../data/baboonColor.png', 250, 100, 20, 500);
```

```
%%
```

```
toc;
```

Assignment 3 Question 2

Files Included--

myMainScript.m

myMeanShiftSegmentation.m

Resized image to 256*256

Parameters- hs=100; hr=250; number of iteration =20; number of neighbor =100

Output:

Justification for optimum values:

hs: On decreasing its value we saw that segments were not formed clearly i.e. image

was just

smoothed and no clear cut segments were visible and on increasing its value we saw

that too

many segments were formed

hr: On increasing its value we saw that colors were mixing hence merging unnecessary

amounts of segments. And on decreasing its value we saw that colors were not properly

mixed

i.e. there were many local maximas(converging points were increased) hence many

segments

were shown.

ASSIGNMENT 3 QUESTION 1

Files included --

gaussianSmooth.m

myMainScript.m

myHarrisCornerDetector.m

sobelOp.m

Parameters - gaussian parameter 1 (s_1) = 2 gaussian parameter 2 (s_2) = 2

Cornerness measure (k) = 0.05

OUTPUT -

For boat.mat

Figure 1 - X derivative Figure 2 Y derivative Figure 3 --- Eigenvalue 1 Figure 4 -- Eigenvalue

2 Figure 5 -- Cornerness - Measure

Description

White spots in figure 5 are corresponding to corners in original images. $K = 0.05$ is

optimal

value. For $k = 0.1$ and 0.2 corners are missing out. And for K around 0.01 white spots

corresponding to edges also appear.

ORIGINALITY REPORT

25%

SIMILARITY INDEX

14%

INTERNET SOURCES

16%

PUBLICATIONS

16%

STUDENT PAPERS

PRIMARY SOURCES

1

amaliepews.blogg.no

Internet Source

4%

2

Submitted to Indian Institute of Technology,
Bombay

Student Paper

4%

3

Submitted to University of Southern California

Student Paper

4%

4

ebalda.blogspot.com

Internet Source

3%

5

"Applications of Quantum Mechanics",
Quantum Physics, 2007

Publication

2%

6

Submitted to Associatie K.U.Leuven

Student Paper

2%

7

Tom Lyche, Jean-Louis Merrien. "Exercises in
Computational Mathematics with MATLAB",
Springer Nature America, Inc, 2014

Publication

2%

9

Berndt, Jürgen. "Totally Geodesic Submanifolds of Riemannian Symmetric Spaces", Springer Proceedings in Mathematics & Statistics, 2014.

Publication

1%

10

Nourhan El Beheiry, Mohamed El Sharkawy, Mona Lotfy, Said Elnoubi. "Modifications to fast and efficient spatial error concealment technique for block-based video coding systems", 2009 52nd IEEE International Midwest Symposium on Circuits and Systems, 2009

Publication

<1%

11

Shengrong Gong, Chunping Liu, Yi Ji, Baojiang Zhong, Yonggang Li, Husheng Dong. "Advanced Image and Video Processing Using MATLAB", Springer Nature America, Inc, 2019

Publication

<1%

Exclude quotes Off

Exclude matches Off

Exclude bibliography Off

160050030_160050031_160050033_Assignment3

PAGE 1

PAGE 2

PAGE 3

PAGE 4

PAGE 5

PAGE 6

PAGE 7

PAGE 8

PAGE 9

PAGE 10

PAGE 11

PAGE 12

PAGE 13

PAGE 14

PAGE 15

PAGE 16

PAGE 17

PAGE 18

PAGE 19

PAGE 20

PAGE 21
