

Learning To Love The DAG For Fun And Profit

Jonathan "Duke" Leto @dukeleto letolabs.com duke@leto.net nit() 2/3

@dukeleto

Sponsors



Sponsors

shutterstock

Sponsors



Sponsors





- PDX Git Together
- Git consulting
- Parrot Virtual Machine
- Google Summer of Code
- BrewPony
- ...
- Too many things...

- A DAG (Directed Acyclic Graph)
- A content tracker
- A diverse community with a common bond
- A collection of implementations

DAG = Directed Acyclic Graph

- a "Tree of Arrows"
- You can't be your own Grandpa
- Graph = nodes + vertices

A content tracker

- Originally "an information manager from hell"
- · Track changes in content, storing the diffs
- An empty directory has no content

A diverse community with a common bond

- Started with Linus in kernel-land and then spread quickly
- Now: web app developers, UI designers, scientists, professors...

A Collection of Implementations

- "official" Git 1.x
- JGit Git 1.x server in Java
- libgit2 "fresh start" linkable library in C
- js-git Very alpha implementation in Javascript

Git 1.x

- /bin/sh
- C
- Perl (git svn, git add -i)
- Some optional optimized assembly

JGit

- Git server written in Java
- Eclipse
- Gerrit Code Review
- various commercial products

libgit2.github.com

- No dependencies
- ANSI 89 C for max(portability)
- Linkable, re-entrant C library
- Designed for multi-threading
- Funded by: Github + Microsoft

Using libgit2 from Perl 5

- use Git::Raw;
- Low-level access to Git objects
- Plumbing, not porcelain

```
Git::Raw example
use Git::Raw:
my v = \dot{git} : //github.com/git/git.git';
my $repo = Git::Raw::Repository->clone($url,
             'git', { bare \Rightarrow 0 });
# print all the tags of the repository
for my $tag (@{ $repo -> tags }) {
    sav $taq -> name:
```

Using Git from Perl 5

use Git::Repository;

- Shells out to normal git binary
- Implements plumbing + porcelain

```
Git.init() 18/3
```

What *is* Git, exactly? Git::Repository example

```
use Git::Repository;
```

my \$url = 'git://github.com/git/git.git';

\$r->run(\$command => @arguments, \$options);

```
Git::Repository->run( clone => $url => $dir );
my $r = Git::Repository->new( $dir );
# run an arbitrary Git command
my $command = "stash";
my @arguments = '';
my $options = {};
```

my\$dir = 'qit';

github.com/creationix/js-git

- Git in Pure JavaScript
- Currently only read-only support
- Funded on bountysource.com
- Large donations from Mozilla + Adobe

Git + Perl community similarities

- Perl 5 ~ Git 1.x
- Perl 6 ∼ libgit2

Using Git

Git - The command line isn't the only way

- git gui
- Github for Mac/Windows
- GitX-dev
- Atalassian SourceTree

Recent Features: 1.8.4

git clean -i "interactive cleaning"

Useful Features

git checkout "checkout the last branch I was on"

Useful Features

git merge "merge the last branch I was on"

Useful Features

git blame -L 20,50 foo.txt # lines 20-50 git blame -L 10,+10 foo.txt # lines 10-20 git blame -L 50,-10 foo.txt # lines 40-50

Coming Soon! in 1.8.5

git log HEAD <=> git log @

Coming Soon! in 1.8.5

git -C foo/ status \sim make -C foo/

Extra Credit

```
# Read the first Git commit by Linus himself
# Thu Apr 7 15:13:13 2005
$ git clone git://github.com/git/git.git
$ git show e83c5163
```

How I Can Help You

Git It Together

- Educating stakeholders on the value of Git
- On-site Training
- Implementing Git at your organization
 - Converting from cvs|svn|? → Git
 - Continuous Integration
 - Deployment from Git
 - Custom workflow creation + documentation
- letolabs.com

git merge -s=social

- @dukeleto
- 209.691.DUKE
- · letolabs.com
- duke@leto.net
- linkedin.leto.net
- · IRC: dukeleto on Freenode, Mozilla, Perl

Mahalo!

