
Low-Overhead Dirty Access Tracking in GPU-UVM

Aditi Khandelia Arush Upadhyaya Kushagra Srivastava Sankalp Mittal Vidhi Jain

April 24, 2026

Project Overview

Iterative pre-copy live migration transfers memory pages from a running process to a destination host while the process continues to execute, repeating the transfer for pages that were dirtied during the previous round until the remaining working set is small enough to complete migration with a brief final pause. The efficiency of this scheme depends entirely on the ability to identify, at the end of each round, *exactly* which pages were written. For CPU memory, the Linux kernel provides this capability through soft-dirty bits embedded in page-table entries, readable via `/proc/PID/pagemap`. No analogous mechanism exists for GPU-managed memory. NVIDIA’s Unified Virtual Memory (UVM) subsystem, which underpins `cudaMallocManaged` and handles demand-paging between host and device, exposes no interface for querying which pages a process has modified. Consequently, any migration or checkpointing system must conservatively copy the *entire* GPU memory footprint on every iteration, rendering iterative pre-copy migration of large GPU workloads impractical.

This project addresses that gap by implementing **per-process dirty page tracking** directly within the open-source NVIDIA UVM kernel module. UVM already intercepts every GPU page fault to manage demand-paging; we augment the write-fault servicing path to record each written page in an in-kernel data structure, without introducing any additional hardware overhead. A **procfs**-based interface allows a privileged user to start and stop tracking epochs, perform atomic cutover snapshots, pause and resume recording, and retrieve the set of pages written by a given process with **page-level granularity** and a per-page **nanosecond-resolution timestamp** suitable for ordering events across migration rounds.

The core mechanism exploits the GPU’s demand-paging fault path. At the start of each tracking epoch, write permissions are *downgraded* from all currently mapped GPU pages, leaving them readable but not writable. Any subsequent GPU write generates a replayable fault; the driver’s fault-servicing path records the faulting page and timestamp before restoring write permission and replaying the instruction. Pages that are only read never fault and are not recorded, eliminating the overhead of tracking read-only accesses. Formal determinism guarantees ensure that no write escapes recording and that the boundary between consecutive migration rounds is precisely defined through a barrier-protected atomic table swap.

Group Details

Following are the details of the group members:

Name	Roll No.	Email ID
Aditi Khandelia	220061	aditikh22@iitk.ac.in
Arush Upadhyaya	220213	arushu22@iitk.ac.in
Kushagra Srivastava	220573	skushagra22@iitk.ac.in
Sankalp Mittal	220963	sankalpm22@iitk.ac.in
Vidhi Jain	221191	vidhijain22@iitk.ac.in

Implementation

End-to-end Workflow




Figure 1: End-to-end workflow of the dirty page tracking system, illustrating procfs control paths, GPU fault handling, and state transitions.

State Machine

Dirty tracking is modelled as a single-owner lifecycle state machine, with all lifecycle operations serialized by `uvm_dirty_lifecycle_lock` and guarded by owner-PID checks. The states are:

1. **Tracking stopped.** `started=false`, `active=false`, `snapshot_pending=false`.
2. **Tracking active with snapshot.** `started=true`, `active=true`, `snapshot_pending=true`.
3. **Tracking active without snapshot.** `started=true`, `active=true`, `snapshot_pending=false`.
4. **Tracking paused with snapshot.** `started=true`, `active=false`, `snapshot_pending=true`.
5. **Tracking paused without snapshot.** `started=true`, `active=false`, `snapshot_pending=false`.




Figure 2: State-transition diagram for dirty-tracking lifecycle states.

Transitions that violate owner checks, state preconditions, or snapshot guards are rejected by the procfs handlers.

Permission Lifecycle

Figure 1 captures the permission policy used to turn hardware write access into explicit software-recorded dirty events.

Start/Resume phase At `start` (and again at `resume`), the implementation walks the owner VA space and revokes GPU write-class permissions from mapped pages, forcing tracked mappings to `READ_ONLY`. Before revocation, per-page write/atomic masks are snapshot so `stop` can restore exact pre-tracking permissions.

Active tracking phase During replayable fault servicing:

1. Read faults remain mapped as `READ_ONLY` and are not inserted into the dirty set.
2. Write/atomic faults are serviced with writable permissions (`READ_WRITE` or `READ_WRITE_ATOMIC`), and the page number plus timestamp are inserted into the live dirty table.

This enforces first-write capture while preserving normal execution after fault resolution.

Paused phase When paused, dirty recording is disabled, but fault handling still progresses: read paths remain `READ_ONLY`, while write/atomic paths may regain writable permissions for correctness and forward progress. Because `active=false`, no dirty inserts are emitted in this interval.

Cutover/Dump phase `query_cutover` requires `snapshot_pending==false`. Under the query barrier, it swaps out the live table into a frozen snapshot and installs a new live table so recording can continue. `query_dump` then consumes that frozen snapshot: in `delta` mode it emits snapshot contents directly; in `cumulative` mode it merges snapshot entries into the cumulative table before output.

Stop phase `stop` restores the previously captured per-page write/atomic permission masks and tears down live, snapshot, and cumulative tracking state, returning the system to its pre-tracking permission configuration.

Modified Driver Files

All driver modifications reside under `kernel-open/nvidia-uvm/`. The files containing functionality added or significantly modified by us are:

1. **`uvm_common.h / uvm_common.c`**
The primary implementation file. Defines `struct dirty_page_info` (page number, timestamp) and the three global dirty-set tables (`g_dirty_ds`, `g_dirty_ds_snapshot`, `g_dirty_ds_cumulative`). Implements table lifecycle (`uvm_dirty_page_table_init`, `uvm_dirty_page_table_destroy`), fault recording (`uvm_dirty_page_table_record`), snapshot management (`uvm_dirty_new_snapshot`, `uvm_dirty_merge_snapshot_into_cumulative_locked`), and all eight procfs handler implementations including `uvm_dirty_procfs_init`. Exports function pointers (`uvm_dirty_invalidate_fn`, `uvm_dirty_activate_now_fn`, `uvm_dirty_barrier_end_fn`, `uvm_dirty_query_barrier_begin_fn`, `uvm_dirty_query_barrier_end_fn`) that are registered from `uvm_va_space.c` at module init.
2. **`uvm_dirty_ds.h`**
Defines the `uvm_dirty_ds_ops` interface (`init`, `insert`, `lookup`, `for_each_in_range`, `destroy`), the `uvm_dirty_ds` struct holding ops pointer, backend-private data, and statistics, and inline timing wrappers for all operations.
3. **`uvm_dirty_ds_xarray.c`**
xarray backend using atomic `xa_cmpxchg` for first-write-wins insert.
4. **`uvm_dirty_ds_vector.c`**
Sorted dynamic array backend with binary-search insert and lookup.

5. **uvm_dirty_ds_vector_unsorted.c**
Unsorted append-order vector with spinlock, preserving fault-arrival order.
6. **uvm_dirty_ds_linked_list.c**
Singly-linked list with sentinel node.
7. **uvm_dirty_ds_nested_bitmap.c**
Two-level hierarchical bitmap for sparse page sets.
8. **uvm_dirty_ds_chunked.c**
Chunked vector with a background kthread sorter for deferred ordering.
9. **uvm_gpu_replayable_faults.c**
The write-fault hook. After standard fault servicing, checks `uvm_dirty_tracking_active()` and `service_access_type >= UVM_FAULT_ACCESS_TYPE_WRITE`, then calls `uvm_dirty_page_table_record` with the faulting page number and `ktime_get_ns()` timestamp.
10. **uvm_va_space.c**
Implements the barrier infrastructure. `uvm_dirty_downgrade_all_permissions` walks all va-ranges and va-blocks for the owner's `va_space`, calling `uvm_va_block_revoke_prot_mask` with `UVM_PROT_READ_WRITE` to strip write access from all GPU PTEs, followed by `uvm_tracker_wait` to confirm GPU processing. `uvm_dirty_query_barrier_begin` and `uvm_dirty_query_barrier_end` implement the cutover barrier by locking all parent GPU replayable-fault ISRs and spinning until the fault buffer is empty. `uvm_va_space_dirty_init` registers all five function pointers at module init.
11. **uvm_va_space.h**
Declares `uvm_va_space_dirty_init`, the registration hook invoked during module initialisation.
12. **uvm_va_block.c**
`compute_new_permission` modified to force `READ_ONLY` on read faults when tracking is active for the faulting `va_space`'s owner, preventing read faults from obtaining write mappings that would bypass recording.
13. **uvm_migrate.c**
`block_migrate_map_unmapped_pages` modified to map GPU-migrated pages as `READ_ONLY` when tracking is active, closing the `cudaMemPrefetchAsync` bypass.
14. **uvm_va_block.h**
Extends per-GPU va-block state with `dirty_downgraded_pages` and `dirty_downgraded_atomic_pages` masks used to restore exact pre-tracking permissions at stop.
15. **uvm_procfs.c**
Integrates the dirty-tracking `procfs` interface into `/proc/driver/nvidia-uvm/` by invoking `uvm_dirty_procfs_init(uvm_proc_dir)` during `procfs` setup.
16. **nvidia-uvm-sources.Kbuild**
Adds all dirty data-structure backend source files (`uvm_dirty_ds_xarray.c`, `uvm_dirty_ds_bitmap.c`, `uvm_dirty_ds_vector.c`, `uvm_dirty_ds_vector_unsorted.c`, `uvm_dirty_ds_chunked.c`, `uvm_dirty_ds_nested_bitmap.c`, `uvm_dirty_ds_linked_list.c`) to the module build list.
17. **uvm.c**
Top-level integration; calls `uvm_va_space_dirty_init` during module initialisation so callback pointers are registered before tracking control paths execute.

Procfs Interface

Eight `procfs` entries are created under `/proc/driver/nvidia-uvm/`:

1. **dirty_tracking_start (write)**
 Input: "<pid> <delta|cumulative>"
 Initializes a fresh live table for the target PID, selects query mode (**delta** or **cumulative**), executes permission downgrade over the owner's managed GPU mappings, and finally enables recording.
 The request is rejected if tracking is already started, if the input format is invalid, or if initialization/callback setup fails.
2. **dirty_tracking_stop (write)**
 Input: "<pid>"
 Restores previously downgraded GPU page permissions, destroys all tracking state (live/snapshot/cumulative), clears snapshot-pending state, and flushes accumulated DS statistics to `/tmp/uvm_dirty_ds_stats.txt`.
 The request is rejected if the supplied PID is not the active owner.
3. **dirty_tracking_pause (write)**
 Input: "<pid>"
 Establishes the query barrier, sets **active=false**, and then releases the barrier. This ensures pause is synchronized with replayable-fault ISR state.
 The request is rejected if the PID does not match the active owner or if tracking is not currently active.
4. **dirty_tracking_resume (write)**
 Input: "<pid>"
 Re-executes the same downgrade/activate/barrier-end sequence used by **start**, re-establishing deterministic write-fault capture after a paused interval.
5. **dirty_tracking_query_cutover (write)**
 Input: "<pid>"
 Acquires the query barrier, atomically swaps **live** → **snapshot** under write lock, installs a fresh live table, updates epoch metadata, sets **g_snapshot_pending=true**, and releases the barrier.
 The request is rejected if the previous snapshot has not yet been consumed by **query_dump**.
6. **dirty_tracking_query_dump (read)**
 No input payload (read endpoint). Requires **g_snapshot_pending=true**.
 In **delta** mode, emits only the current frozen snapshot. In **cumulative** mode, first merges snapshot contents into **g_dirty_ds_cumulative** (first-write-wins), then emits the cumulative union.
 Output includes a header line followed by one line per page: `0xaddr timestamp_ns`.
 Snapshot consumption is overflow-safe: when **seq_file** overflows, snapshot state is retained and replayed on the next read.
7. **dirty_ds_stats_toggle (write)**
 Input: "enable" or "disable"
 Enables or disables instrumentation for DS and callback timing counters. Writing **enable** also resets all counters/timers to zero to provide a clean measurement window.
8. **dirty_ds_stats (read)**
 Read-only statistics snapshot for the current session.
 Reports operation counts and average latency for init/insert/lookup/for-each/destroy, average lock-wait components, and callback timing for invalidate, activate-now, and barrier-end.

Design Choices

Determinism Guarantees

Write-Capture Determinism The implementation provides deterministic *first-write capture* for GPU pages while tracking is active. A page is recorded exactly when its first qualifying write/atomic fault is serviced after permissions have been re-armed to read-only.

1. **Arming at lifecycle boundaries.** **dirty_tracking_start** and **dirty_tracking_resume** invoke the registered downgrade callback, which walks the owner VA-space and revokes GPU write-class permissions

(`READ_WRITE/ATOMIC`) from currently mapped pages. This forces subsequent writes to fault before regaining writable mappings.

2. **No non-write false positives, no prefetch bypass.** Dirty insertion is gated to write-class accesses only. Read/prefetch paths are kept read-only for the tracked owner, and GPU migration of previously unmapped pages under active tracking is also mapped read-only, so `cudaMemPrefetchAsync`-style migrations do not silently bypass write-fault capture.
3. **Single insertion point in fault service.** Recording occurs in replayable fault servicing only when `active=true` and `service_access_type >= UVM_FAULT_ACCESS_TYPE_WRITE`, at which point the page number and `ktime_get_ns()` timestamp are inserted into the live table.
4. **Exactly-once entry semantics per live table (epoch).** Backend insertion is first-write-wins (duplicates are ignored), so within a given live table, repeated writes to the same page do not create duplicate entries or overwrite the original timestamp. In `delta` mode, each `cutover` installs a fresh live table, so the same page may appear again in a later epoch only if it faults again after mappings become faultable.

This yields deterministic capture semantics for migration accounting: each qualifying write/atomic fault contributes one stable dirty record in the current live table. Subsequent writes to an already writable page are not re-faulted, so they are not re-recorded until mappings become faultable again (for example at `resume` or a new `start`).

Epoch Determinism on start/resume The epoch entry path is implemented through the same callback chain in both `start` and `resume`: `uvm_dirty_invalidate_fn()` → `uvm_dirty_activate_now_fn()` → `uvm_dirty_barrier_end_fn()`.

In `uvm_va_space_dirty_init`, these are registered to `uvm_dirty_downgrade_all_permissions`, `uvm_dirty_activate_now`, and `uvm_dirty_barrier_end` respectively.

1. **Begin-side locking and ownership resolution.** `uvm_dirty_downgrade_all_permissions` calls `uvm_dirty_barrier_begin`, which acquires `g_uvm_global.va_spaces.lock` and resolves the unique owner `va_space` for the tracking PID, returning an error if there is not exactly one `va_space` registered under that TGID and keeping `va_spaces.lock` held on success. Unlike the query barrier (used in pause/cutover), the start barrier does *not* spin on the fault buffer; it only acquires locks. This is safe because the immediately following `va_space_down_write` lock prevents all fault service during the critical section, so no faults need to be flushed. `uvm_dirty_downgrade_all_permissions` then calls `uvm_va_space_down_write(va_space)` itself, bringing the VA-space write lock under the same critical section as `va_spaces.lock`.
2. **Permission downgrade while barrier is held.** Under both locks, it walks all managed VA ranges and VA blocks, snapshots per-page write/atomic PTE bitmasks into `dirty_downgraded_pages/dirty_downgraded_atomic_pages` for later restoration at `stop`, revokes GPU write-class permissions via `uvm_va_block_revoke_prot_mask`, and drains each block's GPU tracker (`uvm_tracker_wait`) to confirm GPU TLB invalidations have completed before advancing to the next block.
3. **Activate-before-end ordering.** On success, downgrade returns with both barrier locks still held (`va_spaces.lock` and the `va_space` write lock). The handler then calls `uvm_dirty_activate_now_fn(active=true)` while both locks are still held, and only afterwards calls `uvm_dirty_barrier_end_fn`, which releases `uvm_va_space_down_write` and `g_uvm_global.va_spaces.lock`. This ordering eliminates two race windows that would silently lose first-write events:
 - **Race A - active before downgrade.** If `active=true` were set before pages are revoked to read-only, writes to still-writable pages would complete without faulting and would not be recorded.
 - **Race B - downgraded but not yet active.** If pages were revoked to read-only while `active=false`, write faults arriving in that window would be serviced (the fault handler grants `READ_WRITE` for forward progress) but not inserted into the dirty table, silently missing the first-write event.

Holding `uvm_va_space_down_write` throughout the transition prevents all fault service for the owner va-space during the critical section. After the function returns and locks are released, any write fault to a downgraded page is recorded deterministically because both conditions are satisfied: `active=true` and permissions are `READ_ONLY`.

4. **start semantics.** `start` first creates fresh table state (and cumulative state in cumulative mode), then executes the activation chain, so it establishes a new epoch from a clean live table.
5. **resume semantics.** `resume` is accepted only for owner PID with `started=true`, `active=false`. It re-runs the same lock+downgrade activation chain without reinitializing tables, so recorded entries are preserved across pause/resume.
6. **Precise inclusion/exclusion boundary.** Writes before successful `start` are outside the epoch; writes during pause are excluded (`active=false`); writes after successful `start/resume` are included through the write-fault capture path.

Epoch Determinism on pause The pause operation must establish a precise cutoff where all faults in-flight at the moment of pause are resolved before recording is disabled. This ensures the dirty set captures a deterministic boundary: all writes before pause are recorded; all writes after pause are not.

1. **Query barrier for synchronization.** `dirty_tracking_pause` acquires the query barrier (`uvm_dirty_query_barrier_begin`), which locks all GPU replayable-fault ISRs and spins until the fault buffer is empty. This ensures no fault is mid-service when recording is disabled.
2. **Atomic recording disable.** While the query barrier is held (ISRs locked, fault buffer empty), `active` is set to `false` via `WRITE_ONCE` to prevent the compiler from optimizing or reordering the write. Subsequent faults arriving at the fault handler see `active=false` and skip dirty insertion.
3. **Barrier release enables new faults.** After setting `active=false`, the query barrier is released, unblocking ISRs and fault buffer processing. Any write faults after this point are serviced (mappings remain faultable) but not recorded, ensuring the pause boundary is sharp and deterministic.
4. **Preserved state across pause/resume.** Pause does not modify permissions or destroy tables. The live table, permission state, and accumulated entries remain intact. Resume re-executes the downgrade+activate sequence without reinitializing, so the epoch continues deterministically.

Epoch Determinism on stop The stop operation must guarantee that the tracking session is completely torn down and permissions are exactly restored to their pre-tracking state. This ensures deterministic cleanup and prevents resource leaks or stale permissions.

1. **Permission restoration from snapshot.** At `stop`, `uvm_dirty_restore_fn` is called, which walks all VA blocks for the owner and restores the per-page write/atomic permission masks that were captured at `start/resume`. This restores GPU PTEs to their exact pre-tracking configuration, undoing the downgrade and enabling future non-tracked access.
2. **Table destruction and state cleanup.** `uvm_dirty_page_table_destroy(false)` deallocates all three tables (live, snapshot, cumulative), freeing associated backend resources. The global state is reset: `started=false`, `active=false`, and `snapshot_pending=false`. Statistics are flushed to `/tmp/uvm_dirty_ds_stats.txt` for post-session analysis.
3. **Ownership and state validation.** `stop` validates that the requesting PID matches the current owner (if tracking was started for a specific PID). This prevents unauthorized cleanup and ensures teardown is tied to the correct session.
4. **Deterministic session boundary.** The combination of permission restoration, table destruction, and state reset establishes a precise end-of-epoch boundary. Any query cutover/dump operations must complete before `stop`; once `stop` succeeds, the session is completely dismantled and a new session can be initialized.

Epoch Determinism on query_cutover The cutover operation must establish a precise snapshot boundary such that the dirty set can be consistently queried without blocking new fault recording. All faults before cutover are in the old live table; all faults after belong to the new live table.

1. **Snapshot guard and query barrier.** `query_cutover` first validates that no previous snapshot is pending (`g_snapshot_pending==false`), ensuring only one snapshot exists at a time. It then acquires the query barrier (`uvm_dirty_query_barrier_begin`), which locks all GPU replayable-fault ISRs and spins until the fault buffer is empty.
2. **Atomic table swap and epoch increment.** While the query barrier is held and the DS write lock is acquired, the operation performs three atomic steps: (1) saves current live table to snapshot (`g_dirty_ds_snapshot = g_dirty_ds`), (2) installs fresh live table (`g_dirty_ds = new_live`), and (3) increments the epoch counter (`g_dirty_epoch += 1`). The snapshot epoch is synchronized (`g_dirty_snapshot_epoch = g_dirty_epoch`).
3. **Precise cutover boundary.** Because the query barrier holds ISRs locked and the fault buffer is confirmed empty during the swap, no fault service can interleave with the table swap. Faults arriving after barrier release see the new live table; those in-flight during swap are guaranteed to have completed before the swap (or arrived after and went to new table).
4. **Snapshot consumption guard.** After cutover, `g_snapshot_pending` is set to `true`, preventing a new cutover until the snapshot is consumed by `query_dump`. This enforces strict cutover-dump ordering and prevents snapshot loss.

Epoch Determinism on query_dump The dump operation must return a consistent snapshot of the dirty set at the time of the preceding cutover. The output must reflect exactly the pages recorded between the previous dump and the current cutover.

1. **Snapshot presence and mode validation.** `query_dump` first validates that a snapshot exists and is pending (`g_snapshot_pending==true` and `g_dirty_ds_snapshot.priv != NULL`). The query mode (delta or cumulative) is checked to determine which table to emit.
2. **Cumulative merge with first-write-wins.** In cumulative mode, the snapshot is merged into the cumulative table (`uvm_dirty_merge_snapshot_into_cumulative_locked`) using first-write-wins semantics: entries already in cumulative are not overwritten. This preserves the earliest timestamp for each page across all query windows in the session.
3. **Consistent read under lock.** The read lock on `uvm_dirty_ds_rwsem` is held while iterating the query table (`uvm_dirty_ds_for_each_in_range`). This prevents the table from being modified (cutover swaps require write lock) and ensures the output is consistent with the table state at read-lock acquisition.
4. **Overflow-safe snapshot persistence.** If the `seq_file` buffer overflows (`seq_has_overflowed`), the snapshot is preserved (not destroyed) and `g_snapshot_pending` remains true. The caller retries the read with a larger buffer, and the snapshot is replayed identically. Only when the entire output fits is the snapshot destroyed and `g_snapshot_pending` cleared, allowing the next cutover.

Data Structures

Global state Three `uvm_dirty_ds` instances hold the tracking data:

1. `g_dirty_ds` — live table; the fault handler inserts here on every qualifying write fault while `active=true`.
2. `g_dirty_ds_snapshot` — frozen copy created by `query_cutover`; exists only between a cutover and the subsequent `query_dump`. Once consumed the pointer is set to `NULL`.
3. `g_dirty_ds_cumulative` — session-union table used in cumulative mode; each `query_dump` merges the snapshot into this table with first-write-wins semantics before emitting output.

Backend abstraction layer The three tables all share a single generic interface defined in `uvm_dirty_ds.h`. The design follows the ops-table (vtable) pattern common in the Linux kernel: a `struct uvm_dirty_ds_ops` holds five function pointers, and each backend fills in its own implementations at module link time. This separates the *interface* (what operations exist and what they mean) from the *implementation* (how a particular data structure carries them out), so a new backend can be plugged in by pointing `g_dirty_ds.ops` at a different ops struct — no other code needs to change.

The ops table (`struct uvm_dirty_ds_ops`)

- `init(ds)` — allocates and initialises the backend-private state, storing the pointer in `ds->priv`. Called once per table lifetime under the DS write lock.
- `insert(ds, page_num, timestamp)` — records a dirty page with its first-write timestamp. All backends implement first-write-wins: if `page_num` is already present the call is a no-op and the original timestamp is preserved. Called from the fault-handler hot path.
- `lookup(ds, page_num)` — returns a pointer to the `dirty_page_info` for the given page, or `NULL` if not dirty. Used by the cumulative merge path and the snapshot-persistence guard.
- `for_each_in_range(ds, start, end, fn, ctx)` — iterates all dirty pages whose page number falls in `[start, end]` and invokes the callback `fn(page_num, timestamp, ctx)` for each. Used by `query_dump` to emit output and by the cumulative merge path.
- `destroy(ds)` — frees all entries and the backend-private state, then sets `ds->priv = NULL`. Called under the DS write lock at `stop` or on error unwind.

The container (`struct uvm_dirty_ds`) Each of the three global tables is an instance of:

```
struct uvm_dirty_ds {
    const struct uvm_dirty_ds_ops *ops;
    void *priv;
    struct uvm_dirty_ds_stats stats;
};
```

`ops` is a compile-time constant pointing to the chosen backend. `priv` is the backend-private allocation (e.g. the `struct xarray*` for the `xarray` backend); it is `NULL` when the table is not initialised, which is how `uvm_dirty_tracking_started()` checks whether a session is active. `stats` holds per-table instrumentation counters (see below).

Inline timing wrappers Rather than scattering timing code into each backend, `uvm_dirty_ds.h` provides five `static inline` wrappers — one per op — that intercept every call when `ds->stats.enabled` is true:

1. Record `ktime_get()` before the call.
2. Dispatch through `ds->ops->op(...)`.
3. Add `ktime_to_ns(ktime_sub(ktime_get(), t0))` to the corresponding `atomic64_t` accumulator.
4. Increment the matching `atomic_long_t` count.

The `unlikely()` guard on `stats.enabled` means the check is predicted-not-taken in normal operation, so the instrumentation path imposes no measurable overhead when disabled. Because both the accumulator and the count are atomics, concurrent fault-handler threads can update them without a lock.

Instrumentation via procfs The two procfs entries `dirty_ds_stats_toggle` and `dirty_ds_stats` expose the accumulated measurements:

- Writing "enable" to `dirty_ds_stats_toggle` sets `stats.enabled = true` and resets all counters to zero, giving a clean measurement window. Writing "disable" stops accumulation.
- Reading `dirty_ds_stats` calls `nv_procfs_read_dirty_ds_stats`, which reports for each operation: call count, average end-to-end latency in nanoseconds, and average time spent blocked waiting for the DS rwsem. It also reports average latency for the three lifecycle callbacks (`invalidate`, `activate_now`, `barrier_end`). On stop, the same counters are flushed to `/tmp/uvm_dirty_ds_stats.txt` for offline analysis.

The lock-wait fields (`insert_lock_wait_ns`, `lookup_lock_wait_ns`, `for_each_lock_wait_ns`) measure the time each hot-path call spends blocked in `down_read` before reaching the backend, separating contention cost from pure algorithmic cost. This lets us attribute latency to lock pressure vs. backend complexity when comparing backends under load.

Backend implementations Seven backends are implemented, each compiled unconditionally into the module. The active backend is selected at compile time by setting the `.ops` pointer in the static `g_dirty_ds` initialiser; switching requires only a one-line source change. Table 1 summarises the key properties of each.

Backend	Insert	Lookup	Iterate	Notes
xarray	$O(1)$ amortised	$O(1)$	$O(n)$	atomic <code>xa_cmpxchg</code> ; timestamps stored
sorted vector	$O(n)$	$O(\log n)$	$O(\log n + k)$	binary-search insert; no internal lock
unsorted vector	$O(n)$	$O(n)$	$O(n)$	append-only; IRQ-safe spinlock
linked list	$O(n)$	$O(n)$	$O(n)$	sentinel head; no extra lock
nested bitmap	$O(1)$	$O(1)$	$O(B + k)$	2-level xarray+bitmap; timestamps stored
chunked vector	$O(1)$ amortised	$O(\log n + n_c)$	$O(n)$	background kthread sort

Table 1: Backend summary. n = dirty page count, k = pages in query range, w = word size in bits, B = number of allocated VA blocks, n_c = entries in active (unsorted) chunk.

xarray (`uvm_dirty_ds_xarray.c`) Uses the Linux `xarray` (a radix-tree variant) keyed by page number. Insert performs a fast non-atomic `xa_load` check first; if the page is absent it allocates a `dirty_page_info` and calls `xa_cmpxchg(GFP_ATOMIC)`, which atomically inserts only if the slot is still empty. A non-NULL return from `xa_cmpxchg` means another thread won the race (first-write-wins), so the redundant allocation is freed. Lookup is a single `xa_load`. Iteration uses `xa_find` with an advancing index. Memory is proportional to the number of dirty pages; the xarray allocates nodes on demand.

Sorted vector (`uvm_dirty_ds_vector.c`) Maintains a `kvmalloc`'d pointer array kept sorted in ascending page number order at all times. Insert uses binary search (`vec_lower_bound`) to locate the insertion point in $O(\log n)$, then `memmove` to shift the tail in $O(n)$. Deduplication is a pointer comparison at the found position. Lookup is binary search: $O(\log n)$. `for_each_in_range` binary-searches to the start of the range and then walks sequentially. The array doubles in capacity when full (`kvmalloc_array + memcpy + kvfree`). This backend relies on the outer DS rwsem for thread safety and carries no internal lock (the commented-out spinlock was removed in favour of the rwsem).

Unsorted vector (`uvm_dirty_ds_vector_unsorted.c`) A variant that appends entries in fault-arrival order without sorting. Insert performs an $O(n)$ linear dedup scan then an $O(1)$ tail append. Lookup and `for_each_in_range` are both $O(n)$ linear scans. The backend embeds its own `spinlock_t` and uses `spin_lock_irqsave` / `spin_unlock_irqrestore` around every mutation, making it safe in IRQ context independently of the outer rwsem. This backend trades query speed for insertion simplicity and fault-arrival-order preservation.

Linked list (`uvm_dirty_ds_linked_list.c`) A singly-linked list with a sentinel head node whose `info` field is `NULL`. Both the list struct and each `dirty_ll_node` are heap-allocated. Insert walks the list for dedup ($O(n)$) then appends a new tail node. Lookup and iteration are also $O(n)$ walks. The list carries no internal lock, relying on the outer rwsem. It serves primarily as a correctness baseline and debugging aid.

Nested bitmap (`uvm_dirty_ds_nested_bitmap.c`) A two-level structure: an `xarray` maps VA-block indices (each block covers 512 pages, matching the UVM 2 MB VA-block size) to `struct block_entry` values, each of which holds a 512-bit bitmap and a 512-element timestamp array. Insert derives the block index and in-block offset in $O(1)$, calls `xa_cmpxchg` to lazily allocate the block entry on first use, then issues `test_and_set_bit`: if the bit was clear (first write to this page) it stores the timestamp with `WRITE_ONCE`; if already set it is a no-op. Lookup is `xa_load + test_bit`: $O(1)$. Iteration walks only the allocated blocks via `xa_find`, then uses `find_next_bit` within each block's bitmap, giving $O(B + k)$ where B is the number of allocated blocks. The design gives $O(1)$ insert and $O(1)$ lookup and also stores timestamps and avoids the 32 MB fixed allocation for sparse working sets.

Chunked vector (`uvm_dirty_ds_chunked.c`) Splits entries into a sequence of fixed-capacity chunks. New entries are appended in $O(1)$ to the current *active chunk* under an IRQ-safe `spinlock_t`. When the active chunk fills, it is *sealed* (a new chunk is allocated and installed with a `WRITE_ONCE` on `num_chunks`) and a background kthread (`uvm_dirty_sorter`) is woken via a wait queue to sort it using the kernel's `sort()`. Once a chunk is sorted, its `sorted` flag is published with `smp_store_release` so readers can use it via `smp_load_acquire` without taking the spinlock. Lookup and `for_each_in_range` for sealed sorted chunks use binary search; for the unsorted active chunk they fall back to a linear scan under the spinlock. This design defers the $O(n \log n)$ sort cost to a background thread, keeping the fault-handler insert path at $O(1)$ amortised while still providing sorted output for the dump path. Up to `MAX_CHUNKS = 64` chunks are supported; the kthread is stopped on `destroy`.

Concurrency Design

The dirty-tracking pipeline spans two execution contexts that run concurrently: (1) the GPU replayable-fault bottom-half thread that calls `uvm_dirty_page_table_record` on every qualifying write fault, and (2) user-space procs callers that drive lifecycle transitions. Six distinct synchronization primitives coordinate these contexts.

1. `uvm_dirty_ds_rwsem` - table read/write semaphore Declared with `DECLARE_RWSEM` in `uvm_common.c`, this kernel read-write semaphore is the primary guard for the three global dirty-set table pointers (`g_dirty_ds`, `g_dirty_ds_snapshot`, `g_dirty_ds_cumulative`) and for the session-metadata fields (`g_dirty_owner_tgid`, `g_snapshot_pending`, `g_dirty_epoch`).

- **Read side (shared).** All hot-path operations take the read side so that multiple CPUs can record dirty pages concurrently without blocking each other. Specifically, `uvm_dirty_page_table_record` (fault-handler insert), `uvm_dirty_page_table_lookup`, `uvm_dirty_tracking_started`, and `uvm_owner_tgid_with_dirty_tracking_started` all acquire `down_read`. The dump handler's iteration over the query table (`uvm_dirty_ds_for_each_in_range`) also runs under `down_read`, preventing a concurrent cutover from swapping the pointer mid-iteration.
- **Write side (exclusive).** Only three operations require exclusive access: table initialisation (`uvm_dirty_page_table_init`), table destruction (`uvm_dirty_page_table_destroy`), and the cutover pointer swap inside `uvm_dirty_new_snapshot`. Each holds `down_write` only for the brief critical section during which the live or snapshot pointer is replaced; insert-path threads block for this interval and then resume on the new table.

Replacing a simple mutex with an rwsem here was a deliberate performance choice: the fault-handler path can be invoked concurrently from multiple CPU cores, and taking an exclusive lock per insert would serialise all of them. Under the rwsem, inserts from N cores proceed in parallel; the write side is held only for the $O(1)$ pointer swap during cutover.

2. `uvm_dirty_lifecycle_lock` - procs serialisation mutex Declared with `DEFINE_MUTEX` in `uvm_common.c`, this mutex ensures that at most one procs lifecycle operation is in progress at any time. All eight procs handlers acquire it on entry and release it on return, including `start`, `stop`, `pause`, `resume`, `query_cutover`, and `query_dump`. Without this mutex, two concurrent `start` calls could both pass the “not started” guard and double-initialise tables; a concurrent `stop` and `cutover` could destroy tables that `cutover`

is mid-swap. The mutex also serialises multi-step operations like **start** (which calls **init**, then **downgrade**, then **activate**, then **barrier-end** as a sequence) against any interleaving call.

3. `g_uvm_global.va_spaces.lock` - global VA-space list mutex This pre-existing UVM mutex protects the global linked list of registered `uvm_va_space_t` objects. The dirty-tracking code acquires it in two places:

- **Start barrier** (`uvm_dirty_barrier_begin`). Held while scanning the list to locate the unique `va_space` whose `owner_tgid` matches the tracking target. It is kept held throughout the downgrade walk and released only by `uvm_dirty_barrier_end` after `active` has been set to `true`. This prevents a concurrent `uvm_open` or GPU registration from inserting a new `va_space` for the same TGID between the ownership check and the permission walk.
- **Query barrier** (`uvm_dirty_query_barrier_begin`). Held while scanning for the owner `va_space` and while acquiring per-GPU ISR locks (see below). Released by `uvm_dirty_query_barrier_end` after all ISR locks have been dropped.

4. `va_space->lock` - per-VA-space reader/writer semaphore Each `uvm_va_space_t` carries an rwsem wrapped behind `uvm_va_space_down_write` / `uvm_va_space_down_read`. The write side additionally acquires two helper mutexes (`serialize_writers_lock` and `read_acquire_write_release_lock`) to implement priority inversion avoidance. The dirty-tracking code uses this lock in two modes:

- **Write mode - start/resume downgrade.** `uvm_dirty_downgrade_all_permissions` calls `uvm_va_space_down_write` (after `g_uvm_global.va_spaces.lock` is already held). The write lock excludes all fault-service threads, which hold the read side while processing faults for that VA space. The permission walk and the subsequent `active=true` write both occur while the write lock is held, closing both Race A (activate before downgrade) and Race B (downgrade before activate) described in the Determinism section.
- **Read mode - query barrier GPU enumeration.** `uvm_dirty_query_barrier_begin` takes `uvm_va_space_down_read` to iterate the set of registered GPUs safely before locking per-GPU ISR state. The read lock is held until the ISR locks have been acquired and the fault buffer is confirmed empty, then released by `uvm_dirty_query_barrier_end`.

5. `va_block->lock` - per-VA-block mutex Each `uvm_va_block_t` carries a `uvm_mutex_t` that protects its PTE bitmasks and GPU state. `uvm_dirty_downgrade_all_permissions` acquires this lock for each block while it snapshots the per-page write/atomic permission bitmasks into `dirty_downgraded_pages` and `dirty_downgraded_atomic_pages`, issues `uvm_va_block_revoke_prot_mask`, and calls `uvm_tracker_wait` to confirm GPU TLB invalidation. The block lock is taken only while processing that block and released before moving to the next; it is nested inside the `va_space` write lock.

6. Per-GPU ISR lock - replayable-fault service lock `uvm_parent_gpu_replayable_faults_isr_lock` acquires the ISR service lock (`parent_gpu->isr.replayable_faults.service_lock`) from a non-interrupt context. To prevent an interrupt storm, taking this lock also disables the hardware replayable-fault interrupt for that GPU; fault interrupts are re-enabled when the lock is released by the corresponding unlock call.

This lock is used exclusively in the **query barrier** (`uvm_dirty_query_barrier_begin`). After taking `va_spaces.lock` and `va_space_down_read`, the barrier iterates all parent GPUs registered to the owner VA space and acquires the ISR lock for each. With all ISR locks held, no new fault bottom-half can be scheduled. The barrier then spins on `uvm_parent_gpu_replayable_faults_pending` until the fault buffer is drained, confirming that every in-flight fault has completed service. Only after this confirmation does the caller proceed to swap tables (cutover) or disable recording (pause), ensuring a precise, race-free boundary.

7. WRITE_ONCE / READ_ONCE on `g_uvm_dirty_tracking_active` The boolean flag `g_uvm_dirty_tracking_active` is the hottest read in the entire pipeline: the fault handler checks it on every qualifying write fault before deciding whether to insert a dirty record. Rather than taking any lock for this check, the flag is accessed through `READ_ONCE` in `uvm_dirty_tracking_active()` and written through `WRITE_ONCE` in `uvm_dirty_set_tracking_active()` and `uvm_dirty_page_table_destroy()`. These barriers prevent the compiler from caching, tearing, or reordering the access. Correctness of the surrounding critical sections is guaranteed by the query barrier or the `va_space` write lock held at the moment `WRITE_ONCE` executes; `READ_ONCE` provides only visibility, not ordering.

8. Backend-level locks Two backends introduce additional internal locking beneath the rwsem:

- **Unsorted-vector spinlock.** `uvm_dirty_ds_vector_unsorted.c` embeds a `spinlock_t` in the vector struct, acquired with `spin_lock_irqsave` / `spin_unlock_irqrestore` around each append, lookup, and iteration. The IRQ-save variant is necessary because this backend is called from the fault bottom-half, which can run with local interrupts enabled; a plain spin lock would deadlock if an interrupt preempted the lock holder and tried to re-acquire it.
- **xarray atomic compare-and-swap.** `uvm_dirty_ds_xarray.c` uses `xa_cmpxchg` with `GFP_ATOMIC` for first-write-wins insert. The xarray data structure maintains its own internal spinlock; `xa_cmpxchg` performs a single atomic conditional store under that lock without requiring the caller to take any additional lock. A non-NULL return value indicates the page was already present (a later write), and the allocation is freed; a NULL return confirms the entry was inserted as the first write.

Lock ordering summary To prevent deadlock, all code that acquires multiple locks does so in the following fixed order (outer to inner):

```
lifecycle_lock → va_spaces.lock → va_space.lock  
→ ISR locks → va_block.lock → ds_rwlock
```

The fault handler (bottom-half context) enters only from `va_space.lock` (read) downward and never acquires `lifecycle_lock` or `va_spaces.lock`, so it cannot participate in a cycle with the lifecycle path. The dump handler holds `lifecycle_lock` and `ds_rwlock` (read) simultaneously but never acquires `va_spaces.lock`, keeping it disjoint from the downgrade path.

Prefetching

Prefetch faults are treated as non-dirtying events in the tracking pipeline. Hardware prefetch accesses are decoded as `UVM_FAULT_ACCESS_TYPE_PREFETCH`, while dirty insertion in `uvm_gpu_replayable_faults.c` is gated by `service_access_type >= UVM_FAULT_ACCESS_TYPE_WRITE` together with `uvm_dirty_tracking_active()`. Therefore, prefetch/read faults never insert entries into the dirty table directly. This includes access-counter-driven paths, which are also serviced as prefetch-class accesses in UVM's fault/migration pipeline.

To prevent prefetch from silently restoring writable mappings, the permission path in `compute_new_permission()` (`uvm_va_block.c`) clamps read/prefetch promotion paths back to `UVM_PROT_READ_ONLY` for the tracked owner. This preserves first-write capture by ensuring that a later true write still faults before any dirty insertion occurs.

The migration path is also constrained. In `block_migrate_map_unmapped_pages()` (`uvm_migrate.c`), GPU-destination pages are mapped as `READ_ONLY` while tracking is started. This closes the `cudaMemPrefetchAsync`-style bypass in which unmapped pages could otherwise become writable without passing through normal replayable-fault permission computation.

Finally, if a prefetch request violates logical permissions, replayable-fault servicing marks it as an invalid prefetch (`mark_fault_invalid_prefetch`) instead of routing it through fatal write/atomic cancellation. This keeps forward progress intact while maintaining strictly write-triggered dirty accounting.

Testing and Analysis

The testing and analysis was done in two parts

- **Correctness Testing**
- **Performance Testing**

Correctness Testing

The correctness was evaluated using CUDA tests under `correctness_tests`. The suites are intended to cover the following categories

1. **access_type_filtering**
Tests that only writes (including atomic read-modify-write operations) are recorded as dirty, while pure reads leave no trace. Also verifies that prefetched pages are properly tracked and that distinct access types to the same page are correctly de-duplicated.
2. **address_range_filtering**
Verifies that dirty tracking correctly isolates multiple non-contiguous allocations, handles concurrent multi-threaded writes to distinct sub-ranges, and produces page-aligned dump entries even when GPU accesses are at sub-page granularity. Also tests that inverted or zero-length range arguments do not suppress entries, and that pages whose PTEs were established before `start_track` are still captured when written after tracking begins.
3. **backend_correctness**
Validates fundamental invariants of the tracking system, all dump entries must be page-aligned with no duplicates, sparse write patterns must not produce phantom entries, and timestamps within and across epochs must be non-decreasing. Also verifies that freeing an allocation does not erase its tracking records, a page allocated after tracking is still tracked, and that empty epochs between writes yield empty dumps.
4. **cumulative_mode**
Confirms that cumulative mode accumulates pages across epochs (all pages from prior windows remain visible in subsequent dumps) and that re-writing an already-tracked page does not create a duplicate or update its timestamp (first-write-wins semantics hold across epochs). A stop/restart in delta mode is also verified to reset the tracking state completely.
5. **determinism**
Tests the cutover border: pages written before cutover must appear in the resulting snapshot while pages written after must not, even when the two write phases are interleaved closely in time. Also tests pause/resume semantics, verifying that writes issued during a pause are not recorded and that tracking resumes cleanly after `resume_track`.
6. **first_write_wins**
Verifies the *first write wins policy*, re-writing the same page must not update its timestamp or produce a duplicate entry. This is tested both for sequential re-writes and for 64 concurrent CUDA streams racing to write the same page simultaneously. Also confirms that after cutover (without PTE re-invalidation), a second write to the same page does not re-appear in the next epoch.
7. **footprint_clearing**
Checks that stopping tracking fully restores page permissions: pages that were `READ_WRITE` before tracking must be `READ_WRITE` again, and pages that had no prior GPU mapping must not be spuriously granted `READ_WRITE` on stop. Since there is no user space API to verify this is done via write latency. Idempotency across multiple consecutive start/stop cycles is also verified.
8. **lifecycle_races**
Stress-tests concurrent and destructive lifecycle transitions: stop while a GPU kernel is writing, rapid start/stop cycling, two processes attempting simultaneous tracking (second must get `EBUSY`), owner process death (next process must recover cleanly), stop while a dump is being read, pause with in-flight faults, and resume correctly re-downgrading PTEs.
9. **ordering**
Validates temporal ordering guarantees, writes before `start_track` must not appear in the dump, timestamps must be monotonically non-decreasing, queries in cumulative mode must be non-destructive, and epoch isolation must hold. Also tests concurrent CUDA streams and high-volume sentinel/flood write patterns to verify timestamp ordering under load.
10. **procfs_robustness**
Tests error handling on invalid procfs interactions: double `start`, `stop` without `start`, stopping with a wrong PID, malformed input strings, double cutover without an intervening dump, and cutover or dump without an active session. All calls must return well-defined errors without crashing or corrupting driver state.
11. **scale**
Exercises the backing data structure at scale, 100K page single epoch writes, incremental growth across many cutover/dump cycles, small chunk procfs reads of large dumps, and writes near the maximum span of a bitmap based backend to catch off by one or capacity errors.
12. **snapshot_isolation**
Verifies snapshot atomicity, pages written after cutover must not appear in the current snapshot, empty epochs must not carry over pages from the previous epoch, concurrent inserts during a dump read must not corrupt the snapshot, and a second read of an already drained delta mode dump must return zero entries.

13. **stats_accuracy**
Validates the diagnostic stats interface, the insert counter must match the number of distinct pages written, counters must reset to zero on stop/start, lock-wait counters must be non-negative, and stats must be disabled (zeroed or unavailable) by default.
14. **table_lifecycle**
Tests the dirty-tracking table through basic create/destroy cycles, verifying that reinitialisation clears all entries, that stop/start produces an empty table, that multiple reinit cycles are stable under stress, and that two independent allocations tracked in one session both appear correctly in the dump.
15. **generic**
A broad integration suite covering the core procfs interface (**dirty_tracking_start/stop/query_cutover/query_dump**). Validates that writes are tracked, reads are not, cutover atomically snapshots the epoch, stop fully resets state, **cudaFree** does not remove entries, and cumulative vs. delta mode behave as specified.
Although this adds no new functionality in addition to the other suites This acts as a quick screening to check if the basic functionalities work.

Observations The tests were run as root, and the current implementation passed every test that is present in the repository. The aggregate result was **69/69 passed**: **table_lifecycle** 5/5, **ordering** 8/8, **determinism** 2/2, **first_write_wins** 3/3, **cummulative_mode** 3/3, **address_range_filtering** 5/5, **access_type_filtering** 4/4, **snapshot_isolation** 4/4, **backend_correctness** 9/9, **procfs_robustness** 6/6, **lifecycle_races** 7/7, **scale** 4/4, **stats_accuracy** 4/4, and the **generic** suite 12/12. The per-test runners for the suites report runtimes between 1.95 s and 3.05 s.

Suite	Test	Purpose	Result	Time
Table Lifecycle	tc01_basic_lifecycle	Basic start→write→cutover→dump→stop cycle	PASS	2.00s
Table Lifecycle	tc02_reinit_clears_entries	Reinit clears all tracked entries	PASS	1.99s
Table Lifecycle	tc03_stop_start_empty_table	stop+start yields an empty table	PASS	1.95s
Table Lifecycle	tc04_multi_reinit_stress	Multiple reinit cycles are stable under stress	PASS	2.01s
Table Lifecycle	tc05_two_allocs_one_table	Two allocations both appear in one session's dump	PASS	1.95s
Ordering	tc01_write_before_start	Pre-start writes do not appear in any dump	PASS	2.00s
Ordering	tc02_ts_monotonic	Timestamps are monotonically non-decreasing	PASS	2.01s
Ordering	tc03_query_nondestructive	Cumulative dump reads are non-destructive	PASS	2.00s
Ordering	tc04_empty_table_active	Active session with no writes returns empty dump	PASS	2.00s
Ordering	tc05_epoch_isolation	Each epoch's dump contains only that epoch's writes	PASS	2.02s
Ordering	tc06_concurrent_streams	Timestamps ordered correctly across concurrent streams	PASS	1.99s
Ordering	tc07_sentinel_flood	Sentinel page timestamp precedes 1M-thread flood	PASS	1.95s
Ordering	tc08_flood_between_queries	Phase-A max timestamp $\leq$ phase-B min timestamp	PASS	1.98s
Determinism	tc01_cutover_dump_border	Pre-cutover pages in snap1; post-cutover pages in snap2	PASS	1.99s
Determinism	tc02_pause_resume_semantics	Paused writes not recorded; resume re-arms tracking	PASS	2.02s
First Write Wins	tc01_same_page_repeat_write	Re-writing a page preserves original timestamp	PASS	1.99s
First Write Wins	tc02_concurrent_same_page	64 streams racing on one page produce exactly 1 entry	PASS	2.00s
First Write Wins	tc03_redirty_after_cutover	Post-cutover re-write does not appear in next epoch	PASS	2.02s

Continued on next page

Suite	Test	Purpose	Result	Time
Cumulative Mode	tc01_cumulative_basic	Epoch 2 dump contains all pages from both epochs	PASS	2.03s
Cumulative Mode	tc02_cumul_vs_delta_consist.	Each delta dump is a subset of the cumulative dump	PASS	2.44s
Cumulative Mode	tc03_cumul_redirty_idempotent	Re-writing a tracked page produces no duplicate	PASS	2.10s
Cumulative Mode	tc04_cumul_stop_start_accum.	Stop+restart resets state completely in delta mode	PASS	2.00s
Addr. Range Filtering	tc01_two_alloc_range_isolation	Two allocations are isolated in a single session	PASS	1.99s
Addr. Range Filtering	tc02_range_seq_reads_threaded	Concurrent threaded writes to distinct sub-ranges	PASS	2.03s
Addr. Range Filtering	tc03_subpage_start_rounding	Sub-page accesses produce page-aligned dump entries	PASS	2.05s
Addr. Range Filtering	tc04_inverted_and_zero_range	Inverted/zero-length range does not suppress entries	PASS	2.06s
Addr. Range Filtering	tc05_filter_before_start_track	Pages with pre-start PTEs still tracked when written	PASS	2.07s
Access Type Filtering	tc01_read_only_no_dirty	Read-only GPU access produces no dirty entries	PASS	2.05s
Access Type Filtering	tc02_atomic_does_dirty	Atomic RMW records the page as dirty	PASS	2.00s
Access Type Filtering	tc03_read_then_write_distinct	Read half leaves no trace; write half is tracked	PASS	2.00s
Access Type Filtering	tc04_prefetch_no_dirty	Prefetched pages are not recorded as dirty	PASS	2.01s
Snapshot Isolation	tc01_post_cutover_writes_excl.	Post-cutover writes excluded from current snapshot	PASS	2.01s
Snapshot Isolation	tc02_empty_epoch_no_carryover	Empty epoch yields no carryover from previous epoch	PASS	2.07s
Snapshot Isolation	tc03_conc._insert_during_dump	Concurrent inserts do not corrupt snapshot being read	PASS	2.17s
Snapshot Isolation	tc04_multiple_readers_same_snap.	Second read of drained delta dump returns 0 entries	PASS	2.02s
Backend Correctness	tc01_all_entries_page_aligned	All dump entries are page-aligned, no duplicates	PASS	2.03s
Backend Correctness	tc02_sparse_write_pattern	Sparse writes produce no phantom entries	PASS	2.01s
Backend Correctness	tc03_address_monotonic_in_dump	Reports whether dump output is address-monotonic	PASS	1.96s
Backend Correctness	tc04_multiple_allocs_independent	Multiple allocations tracked independently, no aliasing	PASS	2.03s
Backend Correctness	tc05_invalidate_doesnt_clear	cudaFree does not remove tracking entries	PASS	2.01s
Backend Correctness	tc06_ts_monotonic_within_epoch	Timestamps non-decreasing within a single epoch	PASS	2.00s
Backend Correctness	tc07_cross_epoch_ts_ordering	Max ts of epoch $N \leq$ min ts of epoch $N+1$	PASS	2.01s
Backend Correctness	tc08_empty_epoch_between_writes	Empty epoch between writes yields empty dump	PASS	2.02s
Backend Correctness	tc09_alloc_after_start_tracked	Post-start allocation captured when written	PASS	2.04s
Procf's Robustness	tc01_double_start	Second start returns EBUSY; state intact	PASS	2.03s
Procf's Robustness	tc02_stop_without_start	stop without prior start returns error	PASS	2.00s
Procf's Robustness	tc03_wrong_pid_stop	Wrong-PID stop returns error; own session unaffected	PASS	1.97s

Continued on next page

Suite	Test	Purpose	Result	Time
Procfcs Robustness	tc04_malformed_start_write	Malformed start strings return EINVAL	PASS	1.99s
Procfcs Robustness	tc05_double_cutover_no_dump	Second cutover returns EBUSY; snapshot preserved	PASS	1.99s
Procfcs Robustness	tc06_cutover_without_start	Cutover/dump without active session return errors	PASS	2.01s
Lifecycle Races	tc01_stop_while_kernel_running	stop during active GPU write does not crash	PASS	1.99s
Lifecycle Races	tc02_rapid_start_stop_cycle	Rapid start/stop cycles leave no leaks or corruption	PASS	2.00s
Lifecycle Races	tc03_conc._start_two_processes	Second process attempting start receives EBUSY	PASS	1.95s
Lifecycle Races	tc04_owner_process_dies	New session works after owner process is killed	PASS	2.04s
Lifecycle Races	tc05_stop_while_dump_reading	stop during slow dump read does not deadlock	PASS	3.05s
Lifecycle Races	tc06_pause_with_inflight_faults	Pause stops recording; resume re-enables it	PASS	1.99s
Lifecycle Races	tc07_resume_re_downgrade	Resume re-downgrades PTEs so writes are re-tracked	PASS	2.01s
Scale	tc01_large_page_count	100K pages tracked in one epoch without truncation	PASS	2.29s
Scale	tc02_repeated_growth_and_query	Incremental growth over many cutover/dump cycles	PASS	2.04s
Scale	tc03_procfcs_paginated_read	Small-chunk dump reads produce correct output	PASS	2.01s
Scale	tc04_near_bitmap_max	Full-span write near bitmap backend capacity limit	PASS	2.00s
Stats Accuracy	tc01_insert_count_matches_pages	Insert counter equals number of distinct pages written	PASS	2.02s
Stats Accuracy	tc02_stats_reset_on_reinit	Stats counters reset to zero on stop+start	PASS	2.01s
Stats Accuracy	tc03_lock_wait_nonneg	Lock-wait counter is non-negative after a session	PASS	1.96s
Stats Accuracy	tc04_stats_disabled_by_default	Stats disabled by default; toggle required	PASS	1.97s
Footprint Clearing	tc01_rw_restored_after_stop	Pre-tracking RW pages restored to RW after stop	PASS	1.99s
Footprint Clearing	tc02_fresh_pages_still_fault	Unmapped pages not spuriously granted RW on stop	PASS	2.02s
Footprint Clearing	tc03_idempotent_cycles	Multiple start/stop cycles each leave pages in RW state	PASS	1.95s
Generic	test_dirty_tracking_suite	Integration smoke test covering all core behaviors	PASS	2.02s

Performance Testing

The performance overhead of the dirty-tracking pipeline was evaluated using the `run_overhead_benchmark.sh` script, which measures wall-clock time for each benchmark with tracking **OFF** (baseline) and tracking **ON**, then reports average wall time, standard deviation, and overhead percentage in a CSV. Each benchmark is repeated **REPS** times (default: 5) and the results are averaged. The following benchmarks cover a representative range of access patterns.

1. `int_set_uvm` (4K stride)

A synthetic write-only benchmark that initialises every integer in a UVM-managed array using a 4K-page stride access pattern. Because every access touches a fresh page, this maximises the number of UVM

fault events and therefore the number of dirty-tracking insertions per byte written, making it the most stress-intensive case for the tracking pipeline.

2. **int_set_uvm (sequential)**

The same synthetic write benchmark executed with a sequential (coalesced) access pattern. Compared to the 4K-stride variant, sequential access generates far fewer fault events per byte written and serves as a control for separating per-fault overhead from per-byte overhead.

3. **polybench GEMM**

A standard general matrix multiplication ($C += \alpha AB + \beta C$) from the Polybench/GPU suite. GEMM is compute-intensive with high arithmetic density; dirty-tracking overhead is expected to be small relative to total execution time, providing a reference for acceptable overhead on compute-bound kernels.

4. **polybench 2MM**

A two-step matrix multiplication that chains two GEMM-style kernels. Relative to single GEMM it produces a larger write footprint across multiple output matrices, exercising the tracking table’s ability to handle a wider set of dirty pages without performance degradation.

5. **polybench BICG**

A BiConjugate Gradient solver kernel that is predominantly read-heavy. Because dirty tracking only intercepts write faults, this benchmark is expected to show near-zero overhead and acts as a *control* to confirm that read-heavy workloads are unaffected by the tracking mechanism.

6. **polybench MVT**

A matrix-vector transpose kernel that is read-mostly with a small write component. Like BICG it exercises the case where most memory traffic is read-only, but the presence of writes allows verification that the small write footprint is correctly recorded.

7. **Rodinia Needle (Needleman–Wunsch)**

A dynamic-programming sequence-alignment kernel from the Rodinia suite, adapted with a `-mb` flag to control working-set size. It exhibits a mix of reads and writes across a 2-D score matrix, providing a representative real-world workload with moderate write density.

Memory Configurations Each benchmark is run across eight working-set sizes that span both the *in-GPU* regime and the *oversubscribed* regime:

- **In-GPU** (fits in VRAM of the test A40, ≈ 45 GB): 512 MB, 4 GB, 8 GB, 16 GB, 32 GB, 40 GB.
- **Oversubscribed** (exceeds GPU VRAM, triggers UVM eviction to host): 48 GB, 64 GB.

The rationale for this split is that dirty-tracking overhead is incurred only when UVM fault handlers fire. In the in-GPU regime, faults are rare after the initial page population, so overhead is expected to be low. In the oversubscribed regime, pages are repeatedly evicted and re-faulted, amplifying the per-fault cost and making tracking overhead more visible.

Benchmark and Configuration Table The full set of $7 \times 8 = 56$ benchmark/configuration pairs is listed below.

Benchmark	Working Set	Memory Mode	Purpose
int_set_uvm (4K stride)	512 MB	In-GPU	Stress minimal write footprint with maximum per-page fault rate
int_set_uvm (4K stride)	4 GB	In-GPU	Scale fault count, still below VRAM limit
int_set_uvm (4K stride)	8 GB	In-GPU	Mid-range write-heavy, all pages resident in VRAM
int_set_uvm (4K stride)	16 GB	In-GPU	Larger footprint, tracking table stress
int_set_uvm (4K stride)	32 GB	In-GPU	Near-limit, still fits in GPU
int_set_uvm (4K stride)	40 GB	In-GPU	Maximum in-GPU size
int_set_uvm (4K stride)	48 GB	Oversubscribed	Begin eviction regime; overhead amplified by re-faulting
int_set_uvm (4K stride)	64 GB	Oversubscribed	Heavy eviction; worst-case per-fault overhead
int_set_uvm (sequential)	512 MB	In-GPU	Control: coalesced writes, fewer faults than 4K-stride
int_set_uvm (sequential)	4 GB	In-GPU	Scale sequential writes
int_set_uvm (sequential)	8 GB	In-GPU	Mid-range sequential writes

Continued on next page

Benchmark	Working Set	Memory Mode	Purpose
<code>int_set_uvm</code> (sequential)	16 GB	In-GPU	Large sequential footprint
<code>int_set_uvm</code> (sequential)	32 GB	In-GPU	Near-limit sequential
<code>int_set_uvm</code> (sequential)	40 GB	In-GPU	Maximum in-GPU sequential
<code>int_set_uvm</code> (sequential)	48 GB	Oversubscribed	Sequential writes with UVM eviction
<code>int_set_uvm</code> (sequential)	64 GB	Oversubscribed	Heavy sequential eviction
polybench GEMM	512 MB	In-GPU	Small matrix multiply; low overhead expected
polybench GEMM	4 GB	In-GPU	Mid-size compute-bound GEMM
polybench GEMM	8 GB	In-GPU	Standard large GEMM
polybench GEMM	16 GB	In-GPU	Large GEMM, tracking table stress
polybench GEMM	32 GB	In-GPU	Near-limit GEMM
polybench GEMM	40 GB	In-GPU	Maximum in-GPU GEMM
polybench GEMM	48 GB	Oversubscribed	GEMM with eviction; compute vs. fault overhead trade-off
polybench GEMM	64 GB	Oversubscribed	GEMM under heavy eviction
polybench 2MM	512 MB	In-GPU	Chained GEMM; dual output write footprint
polybench 2MM	4 GB	In-GPU	Mid-size dual GEMM
polybench 2MM	8 GB	In-GPU	Standard 2MM workload
polybench 2MM	16 GB	In-GPU	Large 2MM
polybench 2MM	32 GB	In-GPU	Near-limit 2MM
polybench 2MM	40 GB	In-GPU	Maximum in-GPU 2MM
polybench 2MM	48 GB	Oversubscribed	2MM with eviction
polybench 2MM	64 GB	Oversubscribed	2MM under heavy eviction
polybench BICG	512 MB	In-GPU	Read-heavy control; overhead ≈ 0 expected
polybench BICG	4 GB	In-GPU	Scale read-heavy control
polybench BICG	8 GB	In-GPU	Mid-range read-heavy
polybench BICG	16 GB	In-GPU	Large read-heavy workload
polybench BICG	32 GB	In-GPU	Near-limit read-heavy
polybench BICG	40 GB	In-GPU	Maximum in-GPU read-heavy
polybench BICG	48 GB	Oversubscribed	Read-heavy with eviction
polybench BICG	64 GB	Oversubscribed	Read-heavy under heavy eviction
polybench MVT	512 MB	In-GPU	Read-mostly; small write component should be tracked
polybench MVT	4 GB	In-GPU	Scale read-mostly workload
polybench MVT	8 GB	In-GPU	Mid-range read-mostly
polybench MVT	16 GB	In-GPU	Large read-mostly
polybench MVT	32 GB	In-GPU	Near-limit read-mostly
polybench MVT	40 GB	In-GPU	Maximum in-GPU read-mostly
polybench MVT	48 GB	Oversubscribed	Read-mostly with eviction
polybench MVT	64 GB	Oversubscribed	Read-mostly under heavy eviction
Rodinia Needle	512 MB	In-GPU	Mixed read/write DP kernel; small score matrix
Rodinia Needle	4 GB	In-GPU	Mid-size sequence alignment
Rodinia Needle	8 GB	In-GPU	Standard Needle workload
Rodinia Needle	16 GB	In-GPU	Large DP score matrix
Rodinia Needle	32 GB	In-GPU	Near-limit DP matrix
Rodinia Needle	40 GB	In-GPU	Maximum in-GPU DP matrix
Rodinia Needle	48 GB	Oversubscribed	Needle with UVM eviction
Rodinia Needle	64 GB	Oversubscribed	Needle under heavy eviction

Future Work

Source Code

Development Environment

Development and testing are conducted on a dedicated virtual machine (`dirtyvm`) running:

- Linux kernel version 6.8 (custom build)
- Modified NVIDIA UVM driver version 580.65.06 (loaded as a kernel module)

Repository

The full source code is hosted at:

<https://github.com/aleph-5/open-gpu-kernel-modules>

This is a fork of NVIDIA's open-source GPU kernel modules, with our modifications applied on top.

Instructions for Run

Declaration

We declare that the work presented in this report is our own, except where otherwise acknowledged. We have also read and understood the University's policy on plagiarism and academic integrity, and we confirm that this report complies with those standards.