Save

GET | http://localhost:5000/

Params | Authorization | Headers (6) | Body | Scripts | Settings

Query Params

	Key	Value	Description	
	Key	Value	Description	

Body | Cookies | Headers (8) | Test Results

200 OK · 83 ms · 296 B · Save R

HTML ∨ | ▷ Preview | Visualize ∨

1   Bienvenido a la API de usuarios ✎

GET ∨ | http://localhost:5000/users | **Send**

Params | Authorization ● | Headers (7) | Body | Scripts | Settings

Auth Type

Bearer Token ∨

Token | •••••••••••••••••••••••••••••••• 👁 🔒

The authorization header will be automatically
generated when you send the request. Learn
more about Bearer Token authorization.

Body | Cookies | Headers (8) | Test Results

200 OK · 701 ms · 10.02 KB · Save Respon

{} JSON ∨ | ▷ Preview | Visualize ∨

```
36        password : $2b$10$obF9fhon7VI8JrnSpC8MdOc2yeOmkEUlN1X1wQgZ.pBZGIKUBQ6ly
37    },
38    {
39        "id": 21,
40        "name": "Luis Aragon.",
41        "email": "luis@gmail.com",
42        "password": "$2b$10$obF9fhon7VI8JrnSpC8MdOc2yeOmkEUrNfXlwQgZ.pBZGIKUBQ6ly"
43    },
44    {
45        "id": 23,
46        "name": "Andrea Yesenia",
47        "email": "andrea@example.com",
48        "password": "$2b$10$obF9fhon7VI8JrnSpC8MdOc2yeOmkEUrNfXlwQgZ.pBZGIKUBQ6ly"
```

▶ Runner | Start Proxy | Cookies | Vault

Save   Share

GET   http://localhost:5000/users/71   **Send**

Params   Authorization ●   Headers (7)   Body   Scripts   Settings   Cookies

Auth Type

Bearer Token

The authorization header will be automatically generated when you send the request. Learn more about Bearer Token authorization.

Token   ●●●●●●●●●●●●●●●●●●●●●●●●●●●●

Body   Cookies   Headers (8)   Test Results   200 OK   2.63 s   383 B   Save Response

{} JSON   Preview   Visualize

```
1  {
2      "id": 71,
3      "name": "Miguel esta Actualizado",
4      "email": "miguelcambiocorreo@mail.com",
5      "password": "viscaweb_viscatalunia"
6  }
```

POST   http://localhost:5000/users   **Send**

Params   Authorization ●   Headers (9)   Body ●   Scripts   Settings   Cookies

none   form-data   x-www-form-urlencoded   raw   binary   GraphQL   JSON   Schema   Beautify

```
1
2      {
3      "name": "Ale rivera Estuvo Aqui",
4      "email": "aler_thisisprueba@gmail.com",
5      "password": "holadesdepostmanequisde"
6  }
7
```

Body   Cookies   Headers (8)   Test Results   201 Created   2.29 s   390 B   Save Response

{} JSON   Preview   Visualize

```
1  {
2      "id": 188,
3      "name": "Ale rivera Estuvo Aqui",
4      "email": "aler_thisisprueba@gmail.com",
5      "password": "holadesdepostmanequisde"
6  }
```

Save ⌄   Share

PUT ⌄   http://localhost:5000/users/188   **Send**

Params   Authorization ●   Headers (9)   Body ●   Scripts   Settings   C

○ none   ○ form-data   ○ x-www-form-urlencoded   ● raw   ○ binary   ○ GraphQL   JSON ⌄   ⚙ Schema   Be

```
1
2   {
3     "name": "Ale rivera aquiequisde",
4     "email": "aleriv@gmail.com"
5   }
```

Body   Cookies   Headers (8)   Test Results   🕐   **200 OK** · 649 ms · 374 B   🌐   🔤 Save Respons

{} JSON ⌄   ▷ Preview   🖼 Visualize ⌄

```
1   {
2     "id": 188,
3     "name": "Ale rivera aquiequisde",
4     "email": "aleriv@gmail.com",
5     "password": "holadesdepostmanequisde"
6   }
```

Ale ri   Aa ab .*   ? of 1   ↑ ↓ ☰ ✕

DELETE ⌄   http://localhost:5000/users/188   **Send** ⌄

Params   Authorization ●   Headers (7)   Body   Scripts   Settings   **Cookies**

Auth Type

Bearer Token ⌄

The authorization header will be automatically
generated when you send the request. Learn
more about Bearer Token authorization.

Token   •••••••••••••••••••••••••••••• 👁 🔒⚠

Body   Cookies   Headers (8)   Test Results   🕐   **200 OK** · 637 ms · 298 B   🌐   🔤 Save Response ⋯

{} JSON ⌄   ▷ Preview   🖼 Visualize ⌄

```
1   {
2     "message": "Usuario eliminado"
3   }
```