Scan Report

July 2, 2026

Summary

This document reports on the results of an automatic security scan. All dates are displayed using the timezone "Coordinated Universal Time", which is abbreviated "UTC". The task was "test". The scan started at Thu Jul 2 21:28:54 2026 UTC and ended at Thu Jul 2 22:02:38 2026 UTC. The report first summarises the results found. Then, for each host, the report describes every issue found. Please consider the advice given in each description, in order to rectify the issue.

Contents

1 Result Overview 2

2 Results per Host 2

2.1 192.168.32.101 . . . 2

2.1.1 Medium 8443/tcp . . . 2

2.1.2 Medium 3389/tcp . . . 3

2.1.3 Low general/tcp . . . 4

1 Result Overview

Host	Critical	High	Medium	Low	Log	False P.
192.168.32.101	0	0	2	1	0	0
Total: 1	0	0	2	1	0	0

Vendor security updates are not trusted.
Overrides are off. Even when a result has an override, this report uses the actual threat of the result.
Information on overrides is included in the report.
Notes are included in the report.
This report might not show details of all issues that were found.
Issues with the threat level "Log" are not shown.
Issues with the threat level "Debug" are not shown.
Issues with the threat level "False Positive" are not shown.
Only results with a minimum QoD of 70 are shown.

This report contains all 3 results selected by the filtering described above. Before filtering there were 49 results.

2 Results per Host

2.1 192.168.32.101

Host scan start Thu Jul 2 21:29:57 2026 UTC
Host scan end Thu Jul 2 22:02:35 2026 UTC

Service (Port)	Threat Level
8443/tcp	Medium
3389/tcp	Medium
general/tcp	Low

2.1.1 Medium 8443/tcp

Medium (CVSS: 4.0)

NVT: SSL/TLS: Certificate Signed Using A Weak Signature Algorithm

Summary
The remote service is using a SSL/TLS certificate in the certificate chain that has been signed using a cryptographically weak hashing algorithm.

Quality of Detection (QoD): 80%

Vulnerability Detection Result

```
The following certificates are part of the certificate chain but using insecure
↪signature algorithms:
Subject:              CN=DESKTOP-9K1O4BT
Signature Algorithm:  sha1WithRSAEncryption
```

Solution:
Solution type: Mitigation
Servers that use SSL/TLS certificates signed with a weak SHA-1, MD5, MD4 or MD2 hashing algorithm will need to obtain new SHA-2 signed SSL/TLS certificates to avoid web browser SSL/TLS certificate warnings.

Vulnerability Insight
The following hashing algorithms used for signing SSL/TLS certificates are considered cryptographically weak and not secure enough for ongoing use:
- Secure Hash Algorithm 1 (SHA-1)

... continues on next page ...

... continued from previous page ...

- Message Digest 5 (MD5)
- Message Digest 4 (MD4)
- Message Digest 2 (MD2)

Beginning as late as January 2017 and as early as June 2016, browser developers such as Microsoft and Google will begin warning users when visiting web sites that use SHA-1 signed Secure Socket Layer (SSL) certificates.
NOTE: The script preference allows to set one or more custom SHA-1 fingerprints of CA certificates which are trusted by this routine. The fingerprints needs to be passed comma-separated and case-insensitive:
Fingerprint1
or
fingerprint1, Fingerprint2

Vulnerability Detection Method
Check which hashing algorithm was used to sign the remote SSL/TLS certificate.
Details: `SSL/TLS: Certificate Signed Using A Weak Signature Algorithm`
OID:1.3.6.1.4.1.25623.1.0.105880
Version used: `2021-10-15T11:13:32Z`

References
url: https://blog.mozilla.org/security/2014/09/23/phasing-out-certificates-with-sha-1-based-signature-algorithms/

[return to 192.168.32.101]

2.1.2 Medium 3389/tcp

Medium (CVSS: 4.0)

NVT: SSL/TLS: Certificate Signed Using A Weak Signature Algorithm

Summary
The remote service is using a SSL/TLS certificate in the certificate chain that has been signed using a cryptographically weak hashing algorithm.

Quality of Detection (QoD): 80%

Vulnerability Detection Result

```
The following certificates are part of the certificate chain but using insecure
↪signature algorithms:
Subject:              CN=DESKTOP-9K104BT
Signature Algorithm:  sha1WithRSAEncryption
```

Solution:
Solution type: Mitigation
Servers that use SSL/TLS certificates signed with a weak SHA-1, MD5, MD4 or MD2 hashing algorithm will need to obtain new SHA-2 signed SSL/TLS certificates to avoid web browser SSL/TLS certificate warnings.

Vulnerability Insight
The following hashing algorithms used for signing SSL/TLS certificates are considered cryptographically weak and not secure enough for ongoing use:
- Secure Hash Algorithm 1 (SHA-1)
- Message Digest 5 (MD5)
- Message Digest 4 (MD4)
- Message Digest 2 (MD2)

Beginning as late as January 2017 and as early as June 2016, browser developers such as Microsoft and Google will begin warning users when visiting web sites that use SHA-1 signed Secure Socket Layer (SSL) certificates.
NOTE: The script preference allows to set one or more custom SHA-1 fingerprints of CA certificates which are trusted by this routine. The fingerprints needs to be passed comma-separated and case-insensitive:
Fingerprint1
or
fingerprint1, Fingerprint2

Vulnerability Detection Method
Check which hashing algorithm was used to sign the remote SSL/TLS certificate.
Details: `SSL/TLS: Certificate Signed Using A Weak Signature Algorithm`
OID:1.3.6.1.4.1.25623.1.0.105880
Version used: `2021-10-15T11:13:32Z`

... continues on next page ...

... continued from previous page ...

References
url: https://blog.mozilla.org/security/2014/09/23/phasing-out-certificates-with-sha-1-based-signature-algorithms/

[return to 192.168.32.101]

2.1.3 Low general/tcp

Low (CVSS: 2.6)

NVT: TCP Timestamps Information Disclosure

Summary
The remote host implements TCP timestamps and therefore allows to compute the uptime.

Quality of Detection (QoD): 80%

Vulnerability Detection Result
It was detected that the host implements RFC1323/RFC7323.
The following timestamps were retrieved with a delay of 1 seconds in-between:
Packet 1: 853311
Packet 2: 854378

Impact
A side effect of this feature is that the uptime of the remote host can sometimes be computed.

Solution:
Solution type: Mitigation
To disable TCP timestamps on linux add the line 'net.ipv4.tcp_timestamps = 0' to /etc/sysctl.conf. Execute 'sysctl -p' to apply the settings at runtime.
To disable TCP timestamps on Windows execute 'netsh int tcp set global timestamps=disabled'
Starting with Windows Server 2008 and Vista, the timestamp can not be completely disabled.
The default behavior of the TCP/IP stack on this Systems is to not use the Timestamp options when initiating TCP connections, but use them if the TCP peer that is initiating communication includes them in their synchronize (SYN) segment.
See the references for more information.

Affected Software/OS
TCP implementations that implement RFC1323/RFC7323.

Vulnerability Insight
The remote host implements TCP timestamps, as defined by RFC1323/RFC7323.

Vulnerability Detection Method
Special IP packets are forged and sent with a little delay in between to the target IP. The responses are searched for a timestamps. If found, the timestamps are reported.
Details: TCP Timestamps Information Disclosure
OID:1.3.6.1.4.1.25623.1.0.80091
Version used: 2023-12-15T16:10:08Z

References
url: https://datatracker.ietf.org/doc/html/rfc1323
url: https://datatracker.ietf.org/doc/html/rfc7323
url: https://web.archive.org/web/20151213072445/http://www.microsoft.com/en-us/download/details.aspx?id=9152
url: https://www.fortiguard.com/psirt/FG-IR-16-090

[return to 192.168.32.101]