

Using CriticMarkup with pandoc

Kolen Cheung

Using CriticMarkup with pandoc—not a filter but a preprocessor.

Definition of CriticMarkup

- Deletions: This is ~~is~~-a test.
- Additions: This is a test.
- Substitutions: This ~~isn't~~is a test.
- Highlighting: This is a **test**.
- Comments: This is a test.

What is a test
for?

The Scripts

These scripts are supposed to be in the same folder:

- `criticmarkup-accept.py`
- `criticmarkup-reject.py`
- `pandoc-criticmarkup.sh`

The `criticmarkup-accept.py` and `criticmarkup-reject.py` are extracted from the OS X System Services from CriticMarkup Toolkit.

Note on LaTeX Output: Usepackage Required

Note that the latex output requires the LaTeX packages `color` and `soul`. As you can see from this markdown file, I used a hack to guarantee your pandoc standard template also use them, like this: `fontfamily: lmodern,color,soul`.

In my personal use, I have an YAML of `usepackage: [color,soul]` that in my template will added `\usepackage{color,soul}`. See `ickc/pandoc-templates` at `latex-usepackage-hyperref` for details.

Usage

`pandoc-criticmarkup.sh [options...] [file]`

Options:

- accept: `-a`
- reject: `-r`
- permanent: `-p`
- show diff: `-d`
 - `-d html`: targeting html output using RAW HTML
 - `-d latex`: targeting LaTeX output using RAW LaTeX
 - `-d pdf`: same as above

If permanent is used, it will overwrite the original, if not, it will output to `stdout`. In most situation permanent should be used with `-a` or `-r` only, but it can be used with `-d` as well.

`-a`, `-r`, `-d` are supposed to use separately:

- If `-d` is used, the others are ignored,
- if `-r` is used, `-a` is ignored

It can be used with the pandoc commands, like these (see `build.sh` for more examples):

```
## Showing Difference and not overwriting
./pandoc-criticmarkup.sh -d html README.md | pandoc -s -o README.html
./pandoc-criticmarkup.sh -d pdf README.md | pandoc -s -o README.pdf
## accept or reject while overwriting the source
./pandoc-criticmarkup.sh -ap README-accept.md
./pandoc-criticmarkup.sh -rp README-reject.md
```

Appendix

CSS

An optional CSS `pandoc-criticmarkup.css` make the deletions and additions more obvious in HTML output.

Mapping for Showing Differences

critic markup	HTML	LaTeX
<code>\st{[text]}</code>	<code>[text]</code>	<code>\st{[text]}</code>

critic markup	HTML	LaTeX
<code>\underline{[text]}</code>	<code><ins>[text]</ins></code>	<code>\underline{[text]}</code>
<code>\st{[text1]}\underline{[text2]}</code>	<code>[text1]<ins>[text2]</ins></code>	<code>\del{[text1]}\underline{[text2]}</code>
<code>\hl{[text]}</code>	<code><mark>[text]</mark></code>	<code>\hl{[text]}</code>
<code>\marginpar{[text]}</code>	<code><aside>[text]</aside></code>	<code>\marginpar{[text]}</code>