

## Práctica de Triggers I

1. Dada la tabla Products de la base de datos stores7 se requiere crear una tabla **Products\_historia\_precios** y crear un trigger que registre los cambios de precios que se hayan producido en la tabla **Products**.

Tabla **Products\_historia\_precios**

- Stock\_historia\_Id Identity (PK)
- Stock\_num
- Manu\_code
- fechaHora (grabar fecha y hora del evento)
- usuario (grabar usuario que realiza el cambio de precios)
- unit\_price\_old
- unit\_price\_new
- estado char default 'A' check (estado IN ('A','I'))

```
CREATE TABLE products_historia_precios (  
    stock_historia_id int IDENTITY(1,1) PRIMARY KEY,  
    stock_num smallint,  
  
    manu_code char(3),  
    fechaHora datetime,  
    usuario varchar(20),  
    unit_price_old decimal(6,2),  
    unit_price_new decimal(6,2),  
    estado char DEFAULT 'A' CHECK(estado IN('A','I'))  
);
```

Opción 1

```
CREATE TRIGGER cambio_precios_TR ON products  
AFTER UPDATE AS  
BEGIN  
    DECLARE @unit_price_old decimal(6,2)  
    DECLARE @unit_price_new decimal(6,2)  
    DECLARE @stock_num smallint  
    DECLARE @manu_code char(3)  
  
    DECLARE precios_stock CURSOR FOR  
    SELECT i.stock_num,i.manu_code, i.unit_price, d.unit_price  
        FROM inserted i JOIN deleted d  
        ON (i.stock_num = d.stock_num and i.manu_code = d.manu_code)  
    WHERE i.unit_price != d.unit_price  
  
    OPEN precios_stock  
  
    FETCH NEXT FROM precios_stock  
    INTO @stock_num, @manu_code, @unit_price_new, @unit_price_old  
  
    WHILE @@FETCH_STATUS = 0  
    BEGIN  
        INSERT INTO products_historia_precios  
            (stock_num, manu_code, unit_price_new, unit_price_old,  
            fechaHora, usuario)  
        VALUES  
            (@stock_num, @manu_code, @unit_price_new, @unit_price_old,  
            GETDATE(), SYSTEM_USER)
```

```

FETCH NEXT FROM precios_stock
  INTO @stock_num, @manu_code, @unit_price_new, @unit_price_old

END

CLOSE precios_stock
DEALLOCATE precios_stock
END;

```

## Opción 2

```

CREATE OR ALTER TRIGGER cambio_precios_TR ON products
AFTER UPDATE AS
BEGIN

    INSERT INTO products_historia_precios
    (stock_num, manu_code, unit_price_new, unit_price_old, fechaHora, usuario)
    SELECT i.stock_num,i.manu_code, i.unit_price, d.unit_price , GETDATE(), CURRENT_USER
    FROM inserted i JOIN deleted d
        ON (i.stock_num = d.stock_num and i.manu_code = d.manu_code)
        WHERE i.unit_price != d.unit_price

END;

```

2. Crear un trigger sobre la tabla **Products\_historia\_precios** que ante un delete sobre la misma realice en su lugar un update del campo estado de 'A' a 'I' (inactivo).

```

CREATE TRIGGER delete_stock_historia ON products_historia_precios
INSTEAD OF DELETE AS
BEGIN
    DECLARE @stock_historia_id int

    DECLARE stock_historia_borrado CURSOR FOR
        SELECT stock_historia_id FROM deleted

    OPEN stock_historia_borrado

    FETCH NEXT FROM stock_historia_borrado
    INTO @stock_historia_id

    WHILE @@FETCH_STATUS = 0
    BEGIN
        UPDATE products_historia_precios
            SET estado = 'I' WHERE stock_historia_id = @stock_historia_id

        FETCH NEXT FROM stock_historia_borrado
        INTO @stock_historia_id
    END
    CLOSE stock_historia_borrado
    DEALLOCATE stock_historia_borrado
END;

```

3. Validar que sólo se puedan hacer inserts en la tabla Products en un horario entre las 8:00 AM y 8:00 PM. En caso contrario enviar un error por pantalla.

## OPCION 1

```

CREATE TRIGGER inserts_stock ON products

```

```

INSTEAD OF INSERT
AS
BEGIN
    IF (DATEPART(HOUR, GETDATE()) BETWEEN 8 AND 20)
    BEGIN
        INSERT INTO products
            (stock_num, manu_code, unit_price, unit_code)
        SELECT stock_num, manu_code, unit_price, unit_code
        FROM inserted

    END
    ELSE
    BEGIN
        RAISERROR('Maestro que hace a esta hora laburando?', 16, 1)

    END
END;

```

#### OPCION 2

```

CREATE or ALTER TRIGGER inserts_stock ON products
AFTER INSERT AS
BEGIN
    IF (DATEPART(HOUR, GETDATE()) NOT BETWEEN 8 AND 20)
    BEGIN
        THROW 50000, 'Maestro que hace a esta hora laburando?', 1

    END
END;

```

4. Crear un trigger que ante un borrado sobre la tabla **ORDERS** realice un borrado en cascada sobre la tabla **ITEMS**, validando que sólo se borre 1 orden de compra. Si detecta que están queriendo borrar más de una orden de compra, informará un error y abortará la operación.

```

CREATE TRIGGER delete_orders_and_items ON orders
INSTEAD OF DELETE AS
BEGIN
    DECLARE @order_num smallint

    IF ((SELECT COUNT(*) FROM deleted) > 1)
    BEGIN
        THROW 50000, 'No se pueden eliminar mas de una orden a la vez', 1

    END
    ELSE
    BEGIN
        SELECT @order_num = order_num FROM deleted;

        DELETE FROM items WHERE order_num = @order_num;
        DELETE FROM orders WHERE order_num = @order_num;

    END
END;

```

5. Crear un trigger de insert sobre la tabla **items** que al detectar que el código de fabricante (manu\_code) del producto a comprar no existe en la tabla **manufact**, inserte una fila en dicha tabla con el manu\_code ingresado, en el campo manu\_name la descripción 'Manu Orden 999' donde 999 corresponde al nro. de la orden de compra a la que pertenece el ítem y en el campo lead\_time el valor 1.

```

CREATE TRIGGER insert_items ON items
INSTEAD OF INSERT

```

```

AS
BEGIN
    DECLARE @manu_code char(3)
    DECLARE @order_num smallint

    DECLARE items_insertados CURSOR FOR
    SELECT manu_code, order_num FROM inserted

    OPEN items_insertados

    FETCH NEXT FROM items_insertados
    INTO @manu_code, @order_num

    WHILE @@FETCH_STATUS = 0
    BEGIN
        IF NOT EXISTS (SELECT * FROM manufact WHERE manu_code = @manu_code)
        BEGIN
            INSERT INTO manufact(manu_code, manu_name, lead_time)
            VALUES(@manu_code, 'Manu orden ' + trim(str(@order_num)), 1)
        END

        FETCH NEXT FROM items_insertados
        INTO @manu_code, @order_num

    END

    CLOSE items_insertados
    DEALLOCATE items_insertados

    INSERT INTO items(item_num, order_num, manu_code, stock_num, quantity, unit_price)
    SELECT item_num, order_num, manu_code, stock_num, quantity, unit_price FROM
inserted

END;

```

6. Crear tres triggers (Insert, Update y Delete) sobre la tabla **Products** para replicar todas las operaciones en la tabla **Products\_replica**, la misma deberá tener la misma estructura de la tabla **Products**.

```

CREATE TABLE Products_replica(
    stock_num smallint,
    manu_code char(3),
    unit_price decimal(6,2),
    unit_code smallint,
    constraint pk_products_replica
    primary key (stock_num, manu_code));

CREATE TRIGGER replica_insert ON products
AFTER INSERT
AS
BEGIN
    INSERT INTO Products_replica
    (stock_num, manu_code, unit_price, unit_code)
    SELECT stock_num, manu_code, unit_price, unit_code FROM inserted
END;

CREATE TRIGGER replica_delete ON products
AFTER DELETE
AS
BEGIN

```

```
DELETE sr FROM Products_replica sr
JOIN deleted d ON (sr.stock_num = d.stock_num AND sr.manu_code = d.manu_code)
END;
```

```
CREATE TRIGGER replica_update ON products
AFTER UPDATE AS
BEGIN
    UPDATE sr SET sr.unit_price = i.unit_price,
                 sr.unit_code = i.unit_code
    FROM Products_replica sr JOIN inserted i
        ON (sr.stock_num = i.stock_num AND sr.manu_code = i.manu_code)
END;
```

7. Crear la vista **Productos\_x\_fabricante** que tenga los siguientes atributos:

**Stock\_num, description, manu\_code, manu\_name, unit\_price**

Crear un trigger de Insert sobre la vista anterior que ante un insert, inserte una fila en la tabla Products, pero si el manu\_code no existe en la tabla manufact, inserte además una fila en dicha tabla con el campo lead\_time en 1.

```
CREATE VIEW productos_x_fabricante AS
SELECT p.stock_num, p.manu_code, tp.description, m.manu_name, p.unit_price
FROM products p JOIN manufact m ON p.manu_code = m.manu_code
JOIN product_types tp on p.stock_num = tp.stock_num;
```

```
CREATE TRIGGER insert_productos_x_fabricante_TR ON productos_x_fabricante
INSTEAD OF INSERT AS
BEGIN
    DECLARE @stock_num smallint
    DECLARE @manu_code char(3)
    DECLARE @description varchar(15)
    DECLARE @manu_name varchar(15)
    DECLARE @unit_price decimal(6,2)

    DECLARE insert_cursor CURSOR FOR
        SELECT stock_num, manu_code, description, manu_name, unit_price
        FROM inserted

    OPEN insert_cursor

    FETCH NEXT FROM insert_cursor
    INTO @stock_num, @manu_code, @description, @manu_name, @unit_price

    WHILE @@FETCH_STATUS = 0
    BEGIN
        IF NOT EXISTS (SELECT 1 FROM manufact WHERE manu_code = @manu_code)
        BEGIN
            INSERT INTO manufact(manu_code, manu_name, lead_time)
            VALUES(@manu_code, @manu_name, 1)
        END

        INSERT INTO products (stock_num, manu_code, unit_price)
        VALUES(@stock_num, @manu_code, @unit_price)

        FETCH NEXT FROM insert_cursor
        INTO @stock_num, @manu_code, @description, @manu_name, @unit_price
    END
    CLOSE insert_cursor
    DEALLOCATE insert_cursor
END;
```