



TF-TRANSMISSION FLUID

75W/90

FLUIDO
100% SINTETICO
API GL-5/MT-1



1L



TF-TRANSMISSION FLUID

75W/90

- API MT-1 / GL-5 / GL-4 • SAE J2360 • MB 235.8 • IVECO •
- SCANIA STO 1:0 • MAN 341 TYPE E3/Z2 • MAN 342 TYPE M3 •
- VOLVO 97312 • DAF • MACK GO-J • MIL-PRF-2105E •
- ZF TE-ML 02B, 05B • ZF TE-ML 07A • ZF TE-ML 12B, 12L •
- ZF TE-ML 12N, 16F • ZF TE-ML 17B, 19C • ZF TE-ML 21B •
- DD DFS93K219.01 • ARVIN MERITOR 0-76-N •

IT TF - TRANSMISSION FLUID 75W/90: lubrificante totalmente sintetico per l'impiego in trasmissioni soggette a requisiti molto severi in materia di cambi di carica lubrificante prolungati e prestazioni richieste. Questa tipologia di fluido è appositamente studiato per sopportare ottimamente condizioni di carico elevato, casi di Estreme Pressioni (EP) e carichi d'urto. TF - TRANSMISSION FLUID 75W/90 è il risultato del perfetto equilibrio tra oli sintetici e un'additivazione innovativa che fornisce notevoli vantaggi se confrontato con gli oli per gli ingranaggi convenzionali.

GB TF - TRANSMISSION FLUID 75W/90: 100% synthetic lubricant for use in transmissions subject to very high requirements severe changes in long-term lubricant changes e services required. This type of fluid is specially designed to withstand load conditions optimally high, cases of Extreme Pressures (EP) and shock loads. TF - TRANSMISSION FLUID 75W90 is the result of the perfect balance between synthetic oils and an innovative additive that provides considerable advantages when compared with oils for conventional gears.

Prodotto da REA CCIAA NA n°614040
Distribuito da REA n°840368



1Le

 **MADE IN ITALY**



TF-TRANSMISSION FLUID

ATF 3
AUTOMATIC TRANSMISSION



1L



TF-TRANSMISSION FLUID **ATF 3 AUTOMATIC TRANSMISSION**

- DEXRON IIIH DEXRON IIIG • DEXRON IID • ALLISON C-4 •
ALLISON TES-389 • CAT TO-2 MOPAR +3 • MOPAR +4 •
• MAN 339 Z1, V1 • MAN 339 Z2, V2 •
- MB 236.1 • MB 236.5 • MB 236.6 • MB 236.7 • MB 236.9 •
• MB 236.10 • MB 236.11 • ATF TASA VOITH 55.6335 •
• VOITH 56.6336 • VOLVO 97340 • VOLVO 97341 •
• ZF TE-ML 02F • ZF TE-ML 03D • ZF TE-ML 05L, 21L •
• ZF TE-ML 09 • ZF TE-ML 11A, 11B • ZF TE-ML 14A, 04D •
• ZF TE-ML 16L • ZF TE-ML 17C •

IT Lubrificante per trasmissioni automatiche di autovetture e veicoli industriali pesanti con trasmissioni sintetiche Hydrocracked ed un pacchetto dedicato. Previene l'ossidazione e riduce i fenomeni d'attrito e formazione di morchie, lacche e altre tipologie di depositi.

GB Lubricant for automatic transmissions of passenger cars and heavy commercial vehicles with transmissions GM pre-2005, where required a fluid with specific DEXRON ® III and II. Hydrocracked formulated with synthetic base oils and a dedicated packet, it prevents oxidation and reduces the friction phenomena, corrosion and wear. In addition, it also offers better protection against the formation of sludge, varnish and other types of deposits.

Prodotto da REA CCIAA NA n°614040
Distribuito da REA n°840368



1Le

 **MADE IN ITALY**