

# MyTaxiService

Authors: Alessandro Comodi  
Davide Conficconi  
Stefano Longari



## MyTaxiService Project:

- Requirements Analysis & Specification
- Design
- Integration Test Plan
- Project Plan

## Code Inspection



## Functionalities of the final product:

- Guest:
  - Register and login
- User:
  - Request or reserve a taxi w/ or w/o sharing option
  - Manage taxi requests and reservations
  - Manage profile
- Taxi Driver:
  - Manage availability
  - Confirm or decline requests



## User characteristics:


- Basic web knowledge
- Internet enabled devices
  - (taxi drivers only) GPS service on smartphone

## General assumptions

- Cover most of the mobile operating systems (iOS, Android, ect.)
- The target city population is around 2-3 millions
- Taxi-Driver side application is not available on marketplaces.




## Use Case Diagram






## Class Diagram






## Sequence Diagram (1)





## Sequence Diagram (2)









The design section deals with the technical point of view of the project:


- Overall architecture
- Relevant Components
- Main Algorithms
- Mockups



## Software


### Architecture:

- Multi-tier





## Component view






## Relevant Components:

- Mobile/Web client
- Connection Handler
- Application Controller
- Queue Manager



## Shared ride sequence diagram







## Description of the Queue Manager

### Algorithms:

- Positioning
  - To distribute taxis to avoid overpopulation/lack of drivers
  - Check drivers GPS/requests per hour in zones
  - Eventually redirects drivers
- Distribution prevision
  - Register rides and analyze distribution




## Mockups







## Mockups





## Entry criteria:


- Unit tests
- Fulfilled requirements of RASD and DD

## Integration Strategy:

- Bottom Up
- Functional grouping




## Module integration sequence





## Sybsystem integration sequence





## Individual Step example

### 3.4.6 Application Subsystem → Communication Subsystem

Test case identifier	G_I5T1
Components involved	Application Subsystem → Communication Subsystem
Input specifications	Notification from the Application subsystem directed to a client
Purposes	Check if the Communication Subsystem receives the right informations from the Application Subsystem
Output specifications	Notification received correctly
Environment needed	Application Subsystem and Communication Subsystem tests succeeded



## Project size estimation:

- Attribution of function points

Function Types	Weight		
	Simple	Medium	Complex
Internal Logic Files	7	10	15
External Interface Files	5	7	10
External Inputs	3	4	6
External Inquiries	3	4	6
External Outputs	4	5	7



## Result of size estimation

- $SLOC = FP * CR = 5671$
- $CR = 53$

Function Type	Value
Internal Logic Files	29
External Logic Files	15
External Inputs	50
External Inquiries	13
External Outputs	-
Total	107



## COCOMO II: Project effort and cost estimation

### Results

#### Software Development (Elaboration and Construction)

Effort = 18.5 Person-months

Schedule = 9.6 Months

Cost = \$33312

Total Equivalent Size = 5700 SLOC

#### Acquisition Phase Distribution

Phase	Effort (Person- months)	Schedule (Months)	Average Staff	Cost (Dollars)
Inception	1.1	1.2	0.9	\$1999
Elaboration	4.4	3.6	1.2	\$7995
Construction	14.1	6.0	2.3	\$25317
Transition	2.2	1.2	1.8	\$3997





## Project schedule

Month	Tasks	Developer
February	Queue Manager	Alessandro, Davide, Stefano
	Ride Manager	Alessandro
	Web Client	Davide
	Mobile Client	Davide
	DBMS	Stefano
March	Application Controller Driver	Alessandro
	Lower level components testing	Alessandro, Davide, Stefano
	Application Controller	Alessandro
	Data Access Manager	Stefano
	Web Server & Connection Handler	Davide
April	Application Controller	Alessandro
	Data Access Manager	Stefano
	Web Server & Connection Handler	Davide
May	Security Manager	Stefano
	Subsystem Linking	Alessandro, Davide
June	Testing Subsystems	Alessandro, Davide, Stefano
	Integration of all subsystems	Alessandro, Davide, Stefano
	Deployment	Alessandro, Davide, Stefano



## Project risks

- Change in requirements
- No proper subject training



Assigned Class:

WebDavServlet.java

Assigned Methods:

- copyResource
- doUnlock
- isLocked



## Relevant Issues:

25. *The class or interface declarations shall be in the following order:*

- *class/interface documentation comment:* No issues found.
- *class or interface statement:* No issues found.
- *class/interface implementation comment, if necessary:* No issues found.
- *class (static) variables (in the order: public class variables/ protected class variables/ package level/ private class variables):*
  - In class WebdavServlet this point is not respected. At line 239, 248, 262 and 277 there are protected static variables that should come before the private ones.
  - In private class WebdavStatus this point is not respected. At line 2889 we can find a private static variable followed at line 2898 by the public static variables.
- *instance variables (in the order: public instance variables/ protected instance variables/ package level/ private instance variables):* In private class LockInfo the 25.e/f points are not respected. At line 2731 we find the constructor, after which we find at line 2736 Instance variables.
- *constructors:* see above.
- *methods:* No issues found.



## Relevant issues:

*27. Check that the code is free of duplicates, long methods, big classes, breaking encapsulation, as well as if coupling and cohesion are adequate:*

- From what we can see WebdavServlet class is actually pretty big, with almost 3000 lines of code.
- At line 475 there is a method, doPropfind, that is about 250 lines.
- At line 923 there is a method, doLock, that is about 500 lines.
- At line 2080 there is a method, parseProperties, that is about 300 lines and has a giant elseif structure.
- At line 2366 there is a method, parseLockNullProperties, that is about 250 lines.



End

30

