

# Alma Mater Studiorum University of Bologna

Artificial Intelligence - Deep Learning  
Deep Deblurring project

Alessandro Dicosola [Matr. 935563]

# Introduction

## Problem

Remove blurring artifact from images

- ▶ CIFAR10[1]
- ▶ REDS[2]

# Introduction

## Hardware

- ▶ CPU: i7-8750H@2.20GHz
- ▶ GPU: Nvidia GTX 1060 (6 GB)


# Autoencoders

Networks implemented:

- ▶ ResUNet
- ▶ EDDenseNet
- ▶ CAESSC
- ▶ SRNDeblur

# Autoencoders - ResUNet[3][4]

## Architecture



- ▶ The backbone is a UNet architecture
- ▶ Use of ResBlock at each level improves the flow of the information
- ▶  $\text{Conv} \rightarrow \text{BN} \rightarrow \text{ReLU}$
- ▶ Conv2DTranspose at the end for learning additional information

# Autoencoders - ResUNet[3][4]

## Results




Figure: ResUNet1 - Run test for ResUNet1





Figure: ResUNet3 - Run test for ResUNet3

number of ResBlock	MSE	PSNR	SSIM
1	0.0018	28.49	0.930
3	0.0016	29.03	0.935

# Autoencoders - EDDenseNet[5]

## Architecture



- ▶ Growth rate: 16
- ▶ Encoder: [6,6,3]
- ▶ Decoder: [3,6]
- ▶ Use of DenseBlock
- ▶ Conv  $\rightarrow$  BN  $\rightarrow$  ReLU
- ▶ Conv2DTranspose at the end

# Autoencoders - EDDenseNet[5]

## Results





Figure: EDDenseNet - Run test for EDDenseNet

kernel type	MSE	PSNR	SSIM
gaussian	0.0021	27.62	0.90



# Autoencoders - CAESSC[6]

## Architecture



- ▶ Simple structure
- ▶ Use of symmetric skip connections between with a fixed interval
- ▶ Use of highway skip connection improve the outcome
- ▶ Use of Sigmoid/ReLU in the last layer

# Autoencoders - CAESSC[6]




Figure: Run test for CAESSC\_d22\_f128\_half\_no\_sigmoid




Figure: Run test for CAESSC\_d22\_f128\_half





Figure: Run test for CAESSC\_d30\_f64

network	MSE	PSNR	SSIM
RED30 <sup>1</sup>	-	34.49	-
CAESSC_d22_f128_half_no_sigmoid	0.00389	24.85	0.839
CAESSC_d22_f128_half	0.0020	28.12	0.916
CAESSC_d30_f64	0.0018	28.95	0.919

<sup>1</sup>RED30 is composed by 30 layers with skip connections every 2 layers, 128 filters, kernel size equal to 3 and no downsampling. Taken from [https://github.com/ved27/RED-net/blob/master/model/REDNet\\_ch3.prototxt](https://github.com/ved27/RED-net/blob/master/model/REDNet_ch3.prototxt) and [/model/deblurring/gaussian.caffemodel](https://github.com/ved27/RED-net/blob/master/model/deblurring/gaussian.caffemodel)

# Autoencoders - SRNDeblur[7]




## Architecture



- ▶ FCNN
- ▶ Use of Blocks
- ▶ Encoder-Decoder architecture
- ▶ ResBlocks and skip connections
- ▶ Multi-Scale network
- ▶ Recurrent layer

# Autoencoders - SRNDDeblur[7]

## Training



# Autoencoders - SRNDeblur[7]

## Results

- ▶ ● Run test for SRNDe-blur\_cifar\_no\_lstm
- ▶ ● Run test for SRNDe-blur\_cifar\_lstm

Figure: Test image generated by SRNDeblur\_cifar network

CIFAR10 network	MSE	PSNR	SSIM
Without LSTM	0.00175	29.23	0.9225
With LSTM	0.00174	29.38	0.9188

# Autoencoders - SRNDeblur[7]

## Results



Figure: High resolution test image generated by SRNDeblur\_reds network.

Run test for SRNDeblur\_reds with high resolution images

dataset	SRNDeblur_reds			SRN-DeblurNet	
	MSE	PSNR	SSIM	PSNR	SSIM
REDS	0.002	27.23	0.8105	-	-
GOPro	-	-	-	30.26	0.9342

# Autoencoders - SRNDeblur[7]

## Results



Figure: Low resolution test image generated by SRNDeblur\_reds network.

Run test for SRNDeblur\_reds with low resolution images

# Bibliography



A. Krizhevsky, "Learning multiple layers of features from tiny images," 2009.



S. Nah, S. Baik, S. Hong, G. Moon, S. Son, R. Timofte, and K. M. Lee, "Ntire 2019 challenge on video deblurring and super-resolution: Dataset and study," in *The IEEE Conference on Computer Vision and Pattern Recognition (CVPR) Workshops*, June 2019.



O. Ronneberger, P. Fischer, and T. Brox, "U-net: Convolutional networks for biomedical image segmentation," *CoRR*, vol. abs/1505.04597, 2015.



K. He, X. Zhang, S. Ren, and J. Sun, "Deep residual learning for image recognition," *CoRR*, vol. abs/1512.03385, 2015.



G. Huang, Z. Liu, and K. Q. Weinberger, "Densely connected convolutional networks," *CoRR*, vol. abs/1608.06993, 2016.



X. Mao, C. Shen, and Y. Yang, "Image restoration using convolutional auto-encoders with symmetric skip connections," *CoRR*, vol. abs/1606.08921, 2016.



X. Tao, H. Gao, Y. Wang, X. Shen, J. Wang, and J. Jia, "Scale-recurrent network for deep image deblurring," *CoRR*, vol. abs/1802.01770, 2018.