

Dynamic Array



- Create a list, *seqList*, of N empty sequences, where each sequence is indexed from 0 to $N - 1$. The elements within each of the N sequences also use 0 -indexing.
- Create an integer, *lastAnswer*, and initialize it to 0 .
- The **2** types of queries that can be performed on your list of sequences (*seqList*) are described below:
 1. Query: **1** x y
 1. Find the sequence, *seq*, at index $((x \oplus \text{lastAnswer}) \% N)$ in *seqList*.
 2. Append integer y to sequence *seq*.
 2. Query: **2** x y
 1. Find the sequence, *seq*, at index $((x \oplus \text{lastAnswer}) \% N)$ in *seqList*.
 2. Find the value of element $y \% \text{size}$ in *seq* (where *size* is the size of *seq*) and assign it to *lastAnswer*.
 3. Print the new value of *lastAnswer* on a new line

Task

Given N , Q , and Q queries, execute each query.

Note: \oplus is the *bitwise XOR* operation, which corresponds to the `^` operator in most languages. Learn more about it on [Wikipedia](#).

Input Format

The first line contains two space-separated integers, N (the number of sequences) and Q (the number of queries), respectively.

Each of the Q subsequent lines contains a query in the format defined above.

Constraints

- $1 \leq N, Q \leq 10^5$
- $0 \leq x \leq 10^9$
- $0 \leq y \leq 10^9$
- It is guaranteed that query type **2** will never query an empty sequence or index.

Output Format

For each type **2** query, print the updated value of *lastAnswer* on a new line.

Sample Input

```
2 5
1 0 5
1 1 7
1 0 3
2 1 0
2 1 1
```

Sample Output

```
7
```

Explanation*Initial Values:*

$$N = 2$$

$$lastAnswer = 0$$

$$S_0 = []$$

$$S_1 = []$$

Query 0: Append **5** to sequence $((0 \oplus 0) \% 2) = 0$.

$$lastAnswer = 0$$

$$S_0 = [5]$$

$$S_1 = []$$

Query 1: Append **7** to sequence $((1 \oplus 0) \% 2) = 1$.

$$S_0 = [5]$$

$$S_1 = [7]$$

Query 2: Append **3** to sequence $((0 \oplus 0) \% 2) = 0$.

$$lastAnswer = 0$$

$$S_0 = [5, 3]$$

$$S_1 = [7]$$

Query 3: Assign the value at index **0** of sequence $((1 \oplus 0) \% 2) = 1$ to *lastAnswer*, print *lastAnswer*.

$$lastAnswer = 7$$

$$S_0 = [5, 3]$$

$$S_1 = [7]$$

Query 4: Assign the value at index **1** of sequence $((1 \oplus 7) \% 2) = 0$ to *lastAnswer*, print *lastAnswer*.

$$lastAnswer = 3$$

$$S_0 = [5, 3]$$

$$S_1 = [7]$$