

Abbreviation



You can perform the following operations on the string, *a*:

1. Capitalize zero or more of *a*'s lowercase letters.
2. Delete all of the remaining lowercase letters in *a*.

Given two strings, *a* and *b*, determine if it's possible to make *a* equal to *b* as described. If so, print **YES** on a new line. Otherwise, print **NO**.

For example, given *a* = **AbcDE** and *b* = **ABDE**, in *a* we can convert **b** and delete **c** to match *b*. If *a* = **AbcDE** and *b* = **AFDE**, matching is not possible because letters may only be capitalized or discarded, not changed.

Function Description

Complete the function *abbreviation* in the editor below. It must return either **YES** or **NO**.

abbreviation has the following parameter(s):

- *a*: the string to modify
- *b*: the string to match

Input Format

The first line contains a single integer *q*, the number of queries.

Each of the next *q* pairs of lines is as follows:

- The first line of each query contains a single string, *a*.
- The second line of each query contains a single string, *b*.

Constraints

- $1 \leq q \leq 10$
- $1 \leq |a|, |b| \leq 1000$
- String *a* consists only of uppercase and lowercase English letters, `ascii[A-Za-z]`.
- String *b* consists only of uppercase English letters, `ascii[A-Z]`.

Output Format

For each query, print **YES** on a new line if it's possible to make string *a* equal to string *b*. Otherwise, print **NO**.

Sample Input

```
1
daBcd
ABC
```

Sample Output

```
YES
```

Explanation

`daBcd` \longrightarrow `dABcd` \longrightarrow `ABC`

We have $a = daBcd$ and $b = ABC$. We perform the following operation:

1. Capitalize the letters `a` and `c` in a so that $a = dABcd$.
2. Delete all the remaining lowercase letters in a so that $a = ABC$.

Because we were able to successfully convert a to b , we print `YES` on a new line.