Reverse Shuffle Merge



Given a string, A, we define some operations on the string as follows:

a. reverse(A) denotes the string obtained by reversing string A. Example: reverse("abc") = "cba"

```
b. shuffle(A) denotes any string that's a permutation of string A. Example: shuffle("god") \in ['god', 'gdo', 'ogd', 'odg', 'dgo', 'dgo']
```

c. merge(A1,A2) denotes any string that's obtained by interspersing the two strings A1 & A2, maintaining the order of characters in both. For example, A1 = "abc" & A2 = "def", one possible result of merge(A1,A2) could be "abcdef", another could be "abdecf", another could be "adbecf" and so on.

Given a string s such that $s \in merge(reverse(A), shuffle(A))$ for some string A, find the lexicographically smallest A.

For example, s = abab. We can split it into two strings of ab. The reverse is ba and we need to find a string to shuffle in to get abab. The middle two characters match our reverse string, leaving the a and b at the ends. Our shuffle string needs to be ab. Lexicographically ab < ba, so our answer is ab.

Function Description

Complete the *reverseShuffleMerge* function in the editor below. It must return the lexicographically smallest string fitting the criteria.

reverseShuffleMerge has the following parameter(s):

• s: a string

Input Format

A single line containing the string s.

Constraints

- s contains only lower-case English letters, ascii[a-z]
- $1 \le |s| \le 10000$

Output Format

Find and return the string which is the lexicographically smallest valid A.

Sample Input 0

eggegg

Sample Output 0

egg

Explanation 0

Split "eggegg" into strings of like character counts: "egg", "egg"

```
reverse("egg") = "gge"
shuffle("egg") can be "egg"
"eggegg" belongs to the merge of ("gge", "egg")
```

The merge is: eggegg.

'egg' < 'gge'

Sample Input 1

abcdefgabcdefg

Sample Output 1

agfedcb

Explanation 1

Split the string into two strings with like characters: abcdefg and abcdefg. Reverse abcdefg = gfedcba Shuffle agfedcb can be bcdefga Merge to abcdefgabcdefg

Sample Input 2

aeiouuoiea

Sample Output 2

eaid

Explanation 2

Split the string into groups of like characters: aeiou

Reverse aeiou = uoieaThese merge to aeiouuoiea