

How Many Substrings?

Consider a string of n characters, s , of where each character is indexed from 0 to $n - 1$.

You are given q queries in the form of two integer indices: *left* and *right*. For each query, count and print the number of different substrings of s in the inclusive range between *left* and *right*.

Note: Two substrings are *different* if their sequence of characters differs by at least one. For example, given the string $s = \text{aab}$, substrings $s_{[0,0]} = \text{a}$ and $s_{[1,1]} = \text{a}$ are the same but substrings $s_{[0,1]} = \text{aa}$ and $s_{[1,2]} = \text{ab}$ are different.

Input Format

The first line contains two space-separated integers describing the respective values of n and q .

The second line contains a single string denoting s .

Each of the q subsequent lines contains two space-separated integers describing the respective values of *left* and *right* for a query.

Constraints

- $0 \leq \textit{left} \leq \textit{right} \leq n - 1$
- String s consists of lowercase English alphabetic letters (i.e., **a** to **z**) only.

Subtasks

- For 30% of the test cases, $1 \leq n, q \leq 100$
- For 50% of the test cases, $1 \leq n, q \leq 3000$
- For 100% of the test cases, $1 \leq n, q \leq 10^5$

Output Format

For each query, print the number of different substrings in the inclusive range between index *left* and index *right* on a new line.

Sample Input 0

```
5 5
aabaa
1 1
1 4
1 1
1 4
0 2
```

Sample Output 0

```
1
8
1
8
5
```

Explanation 0

Given $s = \text{aabaa}$, we perform the following $q = 5$ queries:

1. 1 1: The only substring of a is itself, so we print 1 on a new line.
2. 1 4: The substrings of abaa are a, b, ab, ba, aa, aba, baa, and abaa, so we print 8 on a new line.
3. 1 1: The only substring of a is itself, so we print 1 on a new line.
4. 1 4: The substrings of abaa are a, b, ab, ba, aa, aba, baa, and abaa, so we print 8 on a new line.
5. 0 2: The substrings of aab are a, b, aa, ab, and aab, so we print 5 on a new line.