

The Full Counting Sort



In this challenge you need to print the string that accompanies each integer in a list sorted by the integers. If two strings are associated with the same integer, they must be printed in their original order so your sorting algorithm should be *stable*. There is one other twist. The first half of the strings encountered in the inputs are to be replaced with the character "-" (**dash**).

Insertion Sort and the simple version of Quicksort are stable, but the faster in-place version of Quicksort is not since it scrambles around elements while sorting.

In this challenge, you will use counting sort to sort a list while keeping the order of the strings preserved.

For example, if your inputs are $[[0, a], [1, b], [0, c], [1, d]]$ you could set up a helper array with three empty arrays as elements. The following shows the insertions:

```
i string converted list
0  [[],[],[]]
1  a - [[-],[],[]]
2  b - [[-],[-],[],[]]
3  c  [[-,-,c],[-],[],[]]
4  d  [[-,-,c],[-,-,d],[],[]]
```

The result is then printed: **- c - d** .

Input Format

The first line contains n , the number of integer/string pairs in the array ar .

Each of the next n contains $x[i]$ and $s[i]$, the integers with their associated strings.

Constraints

$$1 \leq n \leq 1000000$$

n is even

$$1 \leq |s| \leq 10$$

$$0 \leq x < 100, x \in ar$$

$s[i]$ consists of characters in the range `ascii[a-z]`

Output Format

Print the strings in their correct order, space-separated on one line.

Sample Input

```
20
0 ab
6 cd
0 ef
6 gh
4 ij
0 ab
6 cd
0 ef
6 gh
0 ij
4 that
3 be
0 to
1 be
5 question
1 or
2 not
4 is
2 to
4 the
```

Sample Output

- - - - to be or not to be - that is the question - - - -

Explanation

Below is the list in the correct order. In the array at the bottom, strings from the first half of the original array were replaced with dashes.

```
0 ab
0 ef
0 ab
0 ef
0 ij
0 to
1 be
1 or
2 not
2 to
3 be
4 ij
4 that
4 is
4 the
5 question
6 cd
6 gh
6 cd
6 gh
```

```
sorted = [['-', '-', '-', '-', 'to'], ['be', 'or'], ['not', 'to'], ['be'], ['-', 'that', 'is', 'the'], ['question'], ['-', '-', '-', '-'], [], [], [], []]
```