

Starting with Erlang

Sequential Programming in Erlang (Overview)

Walter Cazzola

Dipartimento di Informatica
Università degli Studi di Milano
e-mail: cazzola@di.unimi.it
twitter: @w_cazzola



Erlang Overview

Erlang is concurrency oriented, i.e., the process is the basic of every computation.

Erlang adopts the actor's model for concurrency with

- asynchronous message exchange;
- non shared memory

Erlang is a dynamically typed functional language.

Erlang supports distribution, fault tolerance and hot-swapping (dynamic SW updating).



Erlang

A Few of History

1981 — the Ericsson CS Lab has been founded.

1981-1986

- a lot of work to decide which paradigm would be better to use in the telecommunication domain;
- conclusions: doesn't exist the perfect paradigm but several characteristics should be mixed.

1987 Erlang is BORN

- the name is after the Danish mathematician Agner Krarup Erlang but could also mean **Ericsson language**.

1987-1991

- the JAM ("Joe's Abstract Machine") virtual machine (inspired by the Prolog WAM) has been implemented (in C);
- in 1998 it has been replaced by BEAM ("Bogdan/Björn's Erlang Abstract Machine").

1996 — Open Telecom Platform (OTP) has been released.

1998

- Ericsson stops to develop Erlang but not to use it
- Erlang becomes open source
 - since 2006 the BEAM supports multi-core processors.

30+ years



My First Erlang Program

Again a Factorial!!!

```
-module(fact).  
-export([fact/1]).  
  
fact(0) -> 1;  
fact(N) -> N*fact(N-1).
```

The program must be run through the BEAM shell

```
[12:56]cazzola@surtur:~/P/erlang-erl
Erlang/OTP 17 [erts-6.3] [source] [64-bit] [smp:8:8] [async-threads:10] [hipe]
[kernel-poll:false]
```

```
Eshell V6.3 (abort with ^G)
1> c(fact).
{ok,fact}
2> fact:fact(7).
5040
3> fact:fact(100).
```

```
9332621544394415268169923885626670049071596826438162146859296389521759999322991560894146
3976156518286253697920827223758251185210916864000000000000000000000000
```

Alternatively it could be run as a script via escript or through native compilation via HiPE.





Sequential Erlang Overview

Numbers and Atoms

Starting with Erlang
Walter Cazzola

Erlang
a few of history
characteristics
Sequential Erlang
BEAM
datatypes
pattern matching
functions
guards
comprehensions
References

```
1> 10.
10
2> 16#FF.
255
3> $A.
65
4> -12.35e-2.
-0.1235
```

- B#val is used to store numbers in Base "B";
- \$char is used for ascii values.

```
1> cazzola@di.unimi.it.
'cazzola@di.unimi.it'
2> 'Walter Cazzola'.
'Walter Cazzola'
3> 'Walter'M
3> Cazzola'.
'Walter\nCazzola'
```

- atoms start with lowercase letter but can contain any character.
- if quoted they can start by uppercase letters.



Slide 5 of 12



Sequential Erlang Overview

Tuples and Lists

Starting with Erlang
Walter Cazzola

Erlang
a few of history
characteristics
Sequential Erlang
BEAM
datatypes
pattern matching
functions
guards
comprehensions
References

```
1> {123, "walter", cazzola}.
{123,"walter",cazzola}
2> {}.
{}
3> {abc, {'Walter', 'Cazzola'}, 3.14}.
{abc,{'Walter','Cazzola'},3.14}
4> {(1,2),3}={1,{2,3}}.
false
```

- used to store a fixed number of items;
- tuples of any size, type and complexity are allowed.

```
1> [].
[]
2> [1][].
[1]
3> [1][2].
[1,2]
4> [{1,2},ok,[]].
[{1,2},ok,[]]
5> length([{1,2},ok,[]]).
3
6> [{1,2},ok,[]]={[1,2],ok,[]}.
true
7> A=[W,$a,$l,$t,$e,$r], B=[$C,$a,$z,$o,$o,$l,$a].
"Cazzola"
8> A++" "++B.
"Walter Cazzola"
9> A--B.
"Wter"
```

- used to store a variable number of items;
- lists are dynamically sized.



Slide 6 of 12



Sequential Erlang Overview

Assignments & Pattern Matching

Starting with Erlang
Walter Cazzola

Erlang
a few of history
characteristics
Sequential Erlang
BEAM
datatypes
pattern matching
functions
guards
comprehensions
References

```
1> A = 1.
1
2> A = 2.
** exception error: no match of right hand side value 2
```

- are just name bindings to values and **cannot** be modified;
- start with an uppercase letter and _ is an anonymous variable.
- the bindings are created via pattern matching.

```
3> [B|L]=[a,b,c].
[a,b,c]
4> {A,B,L}.
{1,a,[b,c]}
5> {X,X}={B,B}.
{a,a}
6> {Y,Y}={X,b}.
** exception error: no match of right hand side value a,b
7> 1=A.
1
8> 1=Z.
* 1: variable 'Z' is unbound
9> {A1,_,_, [B1|_], {B1}} = {abc, 23, [22,x], {22}}.
{abc,23,[22,x],[22]}
10> A1.
abc
11> B1.
22
```



Slide 7 of 12



Sequential Erlang Overview

Functions & Modules

Starting with Erlang
Walter Cazzola

Erlang
a few of history
characteristics
Sequential Erlang
BEAM
datatypes
pattern matching
functions
guards
comprehensions
References

```
name(pattern11, pattern12, ..., pattern1n) [when guard1] -> body1 ;
name(pattern21, pattern22, ..., pattern2n) [when guard2] -> body2 ;
...
name(patternk1, patternk2, ..., patternkn) [when guardk] -> bodyk .
```

- clauses are scanned sequentially until a match is found;
- when a match is found all the variables in the head become bound;

```
-module(ex_module).
-export([double/1]).

double(X) -> times(X, 2).
times(X, N) -> X * N.
```

- double can be called from outside the module, times is local to the module;
- double/1 means the function double with one argument (note that double/1 and double/2 are two different functions).



Slide 8 of 12



Sequential Erlang Overview

Guard Sequences

Starting with Erlang
Walter Cazzola

Erlang
a few of history
characteristics
Sequential Erlang
BEAM
datatypes
pattern matching
functions
guards
comprehensions
References

Each clause in function definition can be guarded by a **guard sequence**.


- a guard is a sequence G_1, G_2, \dots, G_n of **guard expressions**;
- a guard expression is a subset of Erlang expressions to guarantee to be free of side-effects;
- a guard sequence is true when all the guard expressions evaluate to true.

Valid guard expression are:

- the atom true and other constants;
- calls to some built-in functions (BIFs);
- arithmetic and Boolean expressions; and
- short-circuit expressions (andalso/orelse).

Permitted BIFs are:

is_atom/1	is_binary/1	is_bitstring/1	is_float/1	is_function/2
is_function/1	is_integer/1	is_list/1	is_number/1	is_pid/1
is_port/1	is_record/2	is_record/3	is_reference/1	is_tuple/1
abs/1	bit_size/1	byte_size	element/2	float/1
hd/1	length/1	node/0	round/1	tuple_size/1
self/1	size/1	tl/1	trunc/1	



Slide 9 of 12



Sequential Erlang Overview

Map, Filter ≠ Reduce

Starting with Erlang
Walter Cazzola

Erlang
a few of history
characteristics
Sequential Erlang
BEAM
datatypes
pattern matching
functions
guards
comprehensions
References

```
-module(mfr).
-export([map/2,filter/2,reduce/2]).

map(_, []) -> [];
map(F, [H|TL]) -> [F(H)|map(F,TL)].

filter(_, []) -> [];
filter(P, [H|TL]) -> filter(P(H), P, H, TL).

filter(true, P, H, L) -> [H|filter(P, L)];
filter(false, P, _, L) -> filter(P, L).

reduce(F, [H|TL]) -> reduce(F, H, TL).

reduce(_, Q, []) -> Q;
reduce(F, Q, [H|TL]) -> reduce(F, F(Q,H), TL).
```

```
1> mfr:map(fun(X) -> X*X end, [1,2,3,4,5,6,7]).
[1,4,9,16,25,36,49]
2> mfr:filter(fun(X) -> (X rem 2)==0 end, [1,2,3,4,5,6,7]).
[2,4,6]
3> mfr:reduce(fun(X,Y) -> X+Y end, [1,2,3,4,5,6,7]).
28
```

They are available in the module lists.



Slide 10 of 12



Sequential Erlang Overview

List Comprehensions

Starting with Erlang
Walter Cazzola

Erlang
a few of history
characteristics
Sequential Erlang
BEAM
datatypes
pattern matching
functions
guards
comprehensions
References

`[X||Qualifier1, ..., Qualifiern]`

X is an expression, each qualifier is a generator or a filter

- generators are in the form Pattern <- ListExpr where ListExpr evaluates to a list;
- filters are either predicates or Boolean expressions.

```
-module(sort).
-export([qsort/2]).

qsort(_, []) -> [];
qsort(P, [Pivot|TL]) ->
  qsort(P, [X||X<-TL, P(X,Pivot)]) ++ [Pivot] ++ qsort(P, [X||X>=TL, not P(X,Pivot)]).
```

```
-module(prime).
-export([primes/1]).

primes(N) when N>1 -> [X|| X <- lists:seq(2,N),
  (length([Y || Y <- lists:seq(2, trunc(math:sqrt(X))), (X rem Y) == 0])) == 0];
primes(_) -> [].
```

```
1> sort:qsort(fun(X,Y) -> X<Y end, [13,1,-1,8,9,0,3,14]).
[-1,0,1,3,14,8,9,13]
2> sort:qsort(fun(X,Y) -> X>Y end, [13,1,-1,8,9,0,3,14]).
[13,9,8,3,14,1,0,-1]
3> prime:primes(100).
[2,3,5,7,11,13,17,19,23,29,31,37,41,43,47,53,59,61,67,71,73,79,83,89,97]
```



Slide 11 of 12



References

Starting with Erlang
Walter Cazzola

Erlang
a few of history
characteristics
Sequential Erlang
BEAM
datatypes
pattern matching
functions
guards
comprehensions
References

► Gul Agha.

Actors: A Model of Concurrent Computation in Distributed Systems.
MIT Press, Cambridge, 1986.

► Joe Armstrong.

Programming Erlang: Software for a Concurrent World.
The Pragmatic Bookshelf, fifth edition, 2007.

► Francesco Cesarini and Simon Thompson.

Erlang Programming: A Concurrent Approach to Software Development.
O'Reilly, June 2009.



Slide 12 of 12