2. XV

A: DIMENSION

Model			5 door	
Overall length mm (in)		mm (in)	4,450 (175.2)	
Overall width mm (in)		mm (in)	1,780 (70.1)	
Overall height (at C.W.)		mm (in)	n) 1,615 (63.6)	
	Length	mm (in)	2,005 (78.9)	
Compartment	Width	mm (in)	1,490 (58.7)	
Comparanent	Height	mm (in)	Model without sunroof: 1,205 (47.4) Model with sunroof: 1,180 (46.5)	
Wheelbase	•	mm (in)	2,635 (103.7)	
Tread	Front	mm (in)	1,525 (60)	
Ileau	Rear	mm (in)	1,525 (60)	
Minimum road clea	arance	mm (in)	220 (8.7)	

B: ENGINE

Model		2.0 L	2.0 L HEV			
Engine type		Horizontally opposed, liquid cooled, 4-cylinder, 4-stroke gasoline engine				
Valve arrangement		DOHC				
Bore × stroke	mm (in)	84.0 × 90.0 (3.31 × 3.54)				
Displacement	cm ³ (cu in)	1,995 (121.73)				
Compression ratio		10.5	10.8			
Ignition order		1 — 3 -	-2 4			
Idle speed at parking or neutral position	r/min	650:	±100			
Maximum output	kW (HP)/[r/min]	110 (147)/6,200	110 (147)/6,000			
Maximum torque	N·m (kgf-m, ft-lb)/[r/min]	196 (20.0,	145)/4,200			

C: ELECTRICAL

Model		2.0 L	2.0 L HEV		
Ignition timing (at idling) BTDC		MT: 12°±10° CVT: 16°±10°	10°±10°		
Spark plug	Type and manufacturer	NGK: SILZKAR7B11	NGK: DILZKAR7B11		
Generator		12 V — 130 A	_		
Integrated star	ter generator (ISG)	-	12 V — 200 A		
DC/DC conver	ter	_	12 V — 130 A		
Battery	Type and capacity (5HR)	12 V — 48 AH (55D23L)	12 V — 48 AH (55D23L) (12 volt auxiliary battery) 12 V — 41 AH (N55-R) (12 volt engine restart battery)		
	CCA	390 A	390 A (12 volt auxiliary battery) 450 A (12 volt engine restart battery)		
High voltage battery	Type and capacity (1HR)	_	100.8 V — 5.5 AH Ni-MH (nickel metal hydride) battery		
	kind	_	Three-phase AC synchronous motor		
Drive meter	Rated voltage	_	100 V		
Drive motor	Maximum output	_	10 kW [13.4 HP]		
	Maximum torque	_	65 N⋅m [6.6 kgf-m]		

D: TRANSMISSION

1. MT

Model			2.0 L DOHC non-turbo		
Transmission type	Transmission type		5MT		
Clutch type	Clutch type		DSPD		
		1st	3.545		
		2nd	1.888		
Gear ratio	3rd	1.296			
Gear railo		4th	0.972		
		5th	0.780		
		Rev.	3.333		
Deduction goor (front)		Type of gear	Hypoid		
Reduction gear (front)		Gear ratio	4.444		
Transfer reduction		Type of gear	Helical		
Transfer reduction	Transfer reduction		1.000		
Reduction gear (rear)	Final raduation	Type of gear	Hypoid		
neduction gear (rear)	Final reduction	Gear ratio	4.444		

5MT: 5-forward speeds and 1-reverse with synchromesh

DSPD: Dry Single Plate Diaphragm

2. CVT

Model			2.0 L DOHC non-turbo	2.0 L DOHC motor hybrid		
Transmission type			CVT CVT (HEV)			
Clutch type			TCC			
Gear ratio		Forward	3.581 — 0.570	3.420 — 0.544		
		Rev.	3.667	3.502		
Reduction gear	Final	Type of gear	Hypoid			
(front)	reduction	Gear ratio	3.700			
Transfer reduction ratio	0		1.000			
Type of gear		Type of gear	Hypoid			
Reduction gear (rear)		Gear ratio	3.700			

TCC: Torque Converter Clutch

CVT: Forward continuously variable speed change, 1-reverse

E: STEERING

Model	2.0 L	2.0 L HEV	
Туре	Rack and pinion		
Turns, lock to lock	2.8		
Minimum turning diameter m (ft)	5.3 (1	7.39)	

F: SUSPENSION

Front	Macpherson strut type suspension
Rear	Double-wishbone type suspension

G: BRAKE

Service brake system	Dual circuit hydraulic with vacuum suspended power unit
Front	Ventilated disc brake
Rear	Solid disc brake
Parking brake	Mechanical on rear brakes

H: TIRE

Model	2.0 L	2.0 L HEV			
Rim size	17 >	× 7J			
Tire size	P225/55R17 95H				
The Size	225/55R17 97V	_			
Туре	Tubeless, steel belted radial				

I: CAPACITY

Model				2.0 L	2.0 L HEV		
wodei			5MT	CVT	CVT		
Fuel tank	Fuel tank L (US gal, Imp gal)		6	60 (15.9, 13.2)	52 (13.7, 11.4)		
Total capacity (at overhaul)		L (US qt, Imp qt)					
Engine oil	When replacing engine oil and oil L filter		4.8 (5.1, 4.2)				
	When replacing engine oil only	L (US qt, Imp qt)		4.6 (4.9, 4.0)			
Transmission	gear oil	L (US qt, Imp qt)	3.5 (3.7, 3.1)		_		
CVTF		L (US qt, Imp qt)	_ 11.68 — 12.18 (12.3 — 12.9, 10.3 — 10.7)		13.67 — 14.17 (14.4 — 15.0, 12.0 — 12.5)		
Front differential gear oil		L (US qt, Imp qt)	_ 1.14 — 1.24 (1.2 — 1.3, 1.0 — 1.1)		1.3 — 1.4 (1.4 — 1.5, 1.1 — 1.2)		
Rear differential gear oil L (US qt, Imp		L (US qt, Imp qt)	0.8 (0.8, 0.7)				
Engine coola	ınt	L (US qt, Imp qt)	8.0 (8.5, 7.0) 8.4 (8.9, 7.4)		8.2 (8.7, 7.2)		

J: WEIGHT

Model					5 d	oor			
Model			2.0 i-Premium						
Transmission			5MT						
OB code		U5	U5	C5	C5	C5	C4		
OP code			3A	3E	3A	PE	RU	RB	
Curb weight (C.W.)	Total	kg	1,410	1,410	1,410	1,410	1,410	1,410	
		(lb)	(3,108) 825	(3,108) 825	(3,108) 825	(3,108) 825	(3,108) 825	(3,108) 820	
	Front	kg (lb)	(1,819)	o≥5 (1,819)	625 (1,819)	625 (1,819)	625 (1,819)	(1,808)	
	Rear	kg (lb)	585 (1,290)	585 (1,290)	585 (1,290)	585 (1,290)	585 (1,290)	590 (1,301)	
Gross vehicle	weight (G.V.W.)	kg (lb)	1,970 (4,343)	1,970 (4,343)	1,970 (4,343)	1,970 (4,343)	1,970 (4,343)	1,970 (4,343)	
Gross axle weight	Front	kg (lb)	1,010 (2,227)	1,010 (2,227)	1,010 (2,227)	1,010 (2,227)	1,010 (2,227)	1,010 (2,227)	
(G.A.W.)	Rear	kg (lb)	1,000 (2,205)	1,000 (2,205)	1,000 (2,205)	1,000 (2,205)	1,000 (2,205)	1,000 (2,205)	
	Aluminum wheel		\circ	\circ	\circ	\circ	\circ	\circ	
	Keyless access with push button start		_	_	_	_	_	_	
	Auto A/C		_	_	_	0	0	0	
	Manual A/C		0	0	0	_	_	_	
	Leather package		_	_	_	_	0	\circ	
	Genuine leather se	eat	_	_	_	_	_	_	
0 11	Standard audio		0	0	0	0	0	\circ	
Option	Premium audio		_	_	_	_	_	_	
	Navigation		_	_	_	_	_	_	
	Side airbag		0	0	0	0	0	\circ	
	Curtain airbag		0	0	0	0	0	\circ	
	HID headlight		_	_	_	_	0	_	
	Cold weather pack	age	_	0	_	0	0	_	
	Privacy glass		0	0	0	0	0		
	Sunroof		_	_	_	_	\circ	_	

Model							oor			
Wodel			2.0 i-Premium							
Transmission						C)	V T			
OP code			U5	U5	U5	U5	C5	C5	C5	C4
01 0000	1		3A	3E	3S	VS	3A	PE	RU	RB
	Total	kg (lb)	1,445 (3,186)	1,450 (3,197)						
Curb weight (C.W.)	Front	kg (lb)	865 (1,907)							
	Rear	kg (lb)	580 (1,279)	585 (1,290)						
Gross vehicle	Gross vehicle weight (G.V.W.) kg (lb)		1,970 (4,343)							
Gross axle	Front	kg (lb)	1,010 (2,227)							
weight (G.A.W.)	Rear	kg (lb)	1,000 (2,205)							
	Aluminum wheel		0	0	0	0	0	0	0	0
	Keyless access w push button start	ith	_	_	_	_	_	_	_	_
	Auto A/C		_	_	_	_	_	0	0	0
	Manual A/C		0	0	0	0	0	_	_	_
	Leather package		_	_	_	_	_	_	0	0
	Genuine leather s	eat		_	_	_	_		_	
Ontina	Standard audio		\circ	\circ	0	_	\circ	\circ	0	\circ
Option	Premium audio			_	_	_	_		_	
	Navigation		_	_	_	0	_	_	_	_
	Side airbag		0	0	0	0	0	0	0	0
	Curtain airbag		0	0	0	0	0	0	0	0
	HID headlight		_	_	_	_	_	_	0	_
	Cold weather pack	kage	_	0	0	0	_	0	0	_
	Privacy glass		0	0	0	0	0	0	0	_
	Sunroof		_	_	0	0	_	_	0	_

Model			5 door			5 door							
			2.0 i-Premium EyeSight			2.0 i-Limited					2.0 i-Limited EyeSight		
Transmission			CVT			5MT	CVT					-	
OD sada			U5	U5	C5	C5	U5	U5	C5	C4	U5	C5	
OP code			VE	3E	TU	HU	QE	ES	HU	SR	ES	EU	
Curb weight (C.W.)	Total	kg (lb)	1,445 (3,186)	1,445 (3,186)	1,445 (3,186)	1,410 (3,108)	1,455 (3,208)	1,455 (3,208)	1,455 (3,208)	1,460 (3,219)	1,455 (3,208)	1,455 (3,208)	
	Front	kg (lb)	865 (1,907)	865 (1,907)	865 (1,907)	825 (1,819)	875 (1,929)	875 (1,929)	875 (1,929)	875 (1,929)	875 (1,929)	875 (1,929)	
	Rear	kg (lb)	580 (1,279)	580 (1,279)	580 (1,279)	585 (1,290)	580 (1,279)	580 (1,279)	580 (1,279)	585 (1,290)	580 (1,279)	580 (1,279)	
Gross vehicle weight (G.V.W.) kg (lb)		1,970 (4,343)	1,970 (4,343)	1,970 (4,343)	1,970 (4,343)	1,970 (4,343)	1,970 (4,343)	1,970 (4,343)	1,970 (4,343)	1,970 (4,343)	1,970 (4,343)		
Gross axle weight (G.A.W.)	Front	kg (lb)	1,010 (2,227)	1,010 (2,227)	1,010 (2,227)	1,010 (2,227)	1,010 (2,227)	1,010 (2,227)	1,010 (2,227)	1,010 (2,227)	1,010 (2,227)	1,010 (2,227)	
	Rear	kg (lb)	1,000 (2,205)	1,000 (2,205)	1,000 (2,205)	1,000 (2,205)	1,000 (2,205)	1,000 (2,205)	1,000 (2,205)	1,000 (2,205)	1,000 (2,205)	1,000 (2,205)	
Option	Aluminum wheel		0	0	0	0	0	0	0	0	0	0	
	Keyless access w push button start	ith		_	0		_	0		0	0	0	
	Auto A/C		1	_	0	0	0	0	0	0	0	0	
	Manual A/C		0	\circ			_			_		_	
	Leather package		_	_	\circ	\circ	0	\circ	\circ	0	\circ	0	
	Genuine leather seat		_	_	_	0	0	0	0	0	\circ	0	
	Standard audio		_	_	0	_	_	_	_	_	_	_	
	Premium audio		_	0	_	_	0	_	_	0	_	_	
	Navigation		0	_	_	\circ	_	\circ	\circ	_	\circ	0	
	Side airbag		0	0	0	0	0	0	0	0	0	0	
	Curtain airbag		0	0	0	0	0	0	0	0	0	0	
	HID headlight		_	_	0	0	_	_	0	0	_	0	
	Cold weather pac	kage	0	0	0	0	0	0	0	0	\circ	0	
	Privacy glass		0	0	\circ	\circ	0	0	\circ	_	\circ	0	
	Sunroof		_	_	0	0	_	\circ	0	\circ	0	\circ	

	5 door HEV							
Model		2.0 i-Pı	2.0 i-Limited					
Transmission	CVT							
OP code	U5	C5	C5	C5	U5	C5		
OP code			TE	PS	TS	TU	ES	EU
	Total	kg (lb)	1,565 (3,450)	1,560 (3,439)	1,565 (3,450)	1,565 (3,450)	1,570 (3,461)	1,570 (3,461)
Curb weight (C.W.)	Front	kg (lb)	935 (2,061)	930 (2,050)	935 (2,061)	935 (2,061)	940 (2,072)	940 (2,072)
	Rear	kg (lb)	630 (1,389)	630 (1,389)	630 (1,389)	630 (1,389)	630 (1,389)	630 (1,389)
Gross venicle weldni (G. V. W.)		kg (lb)	2,120 (4,674)	2,120 (4,674)	2,120 (4,674)	2,120 (4,674)	2,120 (4,674)	2,120 (4,674)
Gross axle weight (G.A.W.)	Front	kg (lb)	1,110 (2,447)	1,110 (2,447)	1,110 (2,447)	1,110 (2,447)	1,110 (2,447)	1,110 (2,447)
	Rear	kg (lb)	1,050 (2,315)	1,050 (2,315)	1,050 (2,315)	1,050 (2,315)	1,050 (2,315)	1,050 (2,315)
	Aluminum wheel		\circ	0	0	0	0	0
	Keyless access with push button start		0	_	\circ	\circ	\circ	\circ
	Auto A/C		0	0	0	0	0	0
	Manual A/C		_	_	_	_	_	_
Option	Leather package		\circ		0	0	0	0
	Genuine leather se	_		_	_	0	0	
	Standard audio		\circ	\circ	\circ	\circ	_	_
	Premium audio		_	_	_	_	_	_
	Navigation		_				0	0
	Side airbag		0	\circ	0	\circ	\circ	0
	Curtain airbag		0	\circ	\circ	\circ	\circ	\circ
	HID headlight		_	_	_	\circ	_	\circ
	Cold weather package		0	0	\circ	\circ	\circ	0
	Privacy glass		0	\circ	\circ	\circ	\circ	\circ
	Sunroof		_	\circ	\circ	\circ	\circ	\circ

PRECAUTION

	J

		Page
1.	Precaution	2